CS202 Quiz 1 File by Tanveer Online Academy

Which of the option(s) given below is correct if we apply CSS property "display: none;" to an element?	It hides an element and it will not be taking the same space as before on the web page.
In HTML tables, rowspan attribute is used _____.	To make a cell span more than one row.
Which of the following tags is used to define HTML paragraph?	<p>
Which of the following list-style-type is supported by in HTML?	Circle
Which element can be used to show the italic text?	<i>
The Advantage(s) of CSS is/are :	All of the given options
Which of the following is correct attribute to add border to an HTML table?	Border
Which of the following CSS property is used to change the text color?	Color
Which of the option(s) given below is correct if we apply CSS property "visibility: hidden;" to an element?	It hides an element and it will be taking the same space as before on the web page.
Which of the following is correct property to define the text size for an HTML element?	font-size
In HTML, the document language can be declared in the _____ tag in _____ attribute.	<language>, lang
_____ property is used to set the border spacing for an HTML table.	border-spacing
_____ does not allow a user to change the text size in all browsers.	Absolute size
Choose the correct HTML tag for the smallest size heading?	H6
_____ element is used to highlight the text in HTML.	<mark>
Which of the following list-style-type is supported by in HTML?	Disc
With CSS, a color is most often specified by_____.	All of the given

In HTML, headings are defined with _____tag(s).	<h1> to <h6>
CSS stands for_____.	Cascading Style Sheets

CS202 Quiz 2 File by Tanveer Online Academy

Creating a variable in JavaScript is called_____.	Declaring Variable
Which of the following is not a valid JavaScript variable?	2number
In JavaScript, = sign is used to_____.	Assign values to variables
What value will be returned by the following JavaScript function? Math.round(8.4);	8
What value will be returned by the following JavaScript function? parseInt("13.2");	13
In CSS3, there are _____ different combinators.	Four
Which of the following statement is true in context of JavaScript?	All of the above.
What value will be returned by the following JavaScript expression? isNaN("100");	False
What value will be returned by the following JavaScript function? Math.SQRT2_3	Returns square root of 2/3
What is the default position of the elements in HTML?	Static
Which of the following value will JavaScript return if we calculate a number outside the largest possible number?	Infinity
What will be the sequence of elements in the array "colour" after using sort function on it? var colour = ["Blue", "Pink", "Purple", "Black"];	["Black", "Blue ", "Pink ", "Purple "];

colour.sort();	
A _____ explains the relationship between the selectors.	**Combinator**
Which of the following CSS3 property can be used to add transparency in image?	**Opacity**
Which of the following is NOT a way to join multiple words into one variable name in JavaScript?	**Semicolon**
Which of the following value cannot return by Math.random() function?	**1.7**
What value will be in variable "z" after execution of the following code? **var z= 3 + "3";**	**33**
JavaScript is _____ side scripting language.	**Client Side**