CS402 - Quiz No.04

Date: 06 January 2026

Q.1 The length of output string in case of _____ is one more than the length of corresponding input string.

A. Adding Machine

B. Moore machine

C. Incremental machine

D. Mealy machine

Q.2 The language L defined over Σ, not belonging to L, is called _____ of the language L.

A. intersection

B. closure

C. union

D. complement

Q.3 For a given Moore Machine, the input string is '101010', thus the output string would be of length:

A. Length of input string - 2

B. Length of input string + 2

C. Length of input string + 1

D. Length of input string - 1

Q.4 Which of the following is a non-regular language?

A. Prime

B. Even-Even

C. Language of strings ending in abba

D. Odd-Odd

Q.5 If a language generates finite number of distinct classes then it must be _____.

A. both regular and context free

B. non-regular

C. context free

D. regular

Q.6 In pref(Q in R), Q is _____ to/than R.

A. Greater

B. Smaller

C. Equal

D. Not equal

Q.7 If new A =1 NAND (1 AND 1), then what will be the value of new A?

A. 1

B. 0

C. 10

D. 01

Q.8 In Moore machine, output is produced over the change of:

A. None of the mentioned

B. Transitions and states

C. States

D. Transitions

Q.9 The operators like (* , +) in the parse tree are considered as _____.

A. terminals

B. productions

C. non-terminals

D. intermediates

Q.10 In polish notation, (o-o-o) is the abbreviation of _____.

A. Operator - Operand – Operand

B. Operand - Operator – Operand

C. Operand - Operand - Operator

D. Operand - Operand – Operand
