Q.1 Which reference modifier is used to define reference variable?

A. #

B. &

C. ref

D. def

Q.2 Tasks that proceed independently of one another are said to execute_____

A. Synchronously

B. Simultaneously

C. Asynchronously

D. Intensively

Q.3 In C#, when a value type is converted to object type, it is called _____

A. Abstraction

B. Polymorphism

C. Data Conversion

D. Boxing

Q.4 On successful compilation of a Java source code ___ is generated.

A. Bytecode

B. Output

C. Hexadecimal code

D. Octal code

Q.5 C# is a _____ and .NET is a _____.

A. Language, Platform

B. Platform, Language

C. Package, Language

D. Language, Package

Q.6 The initial name for C# was _____.

A. COOL

B. COAP

C. COOP

D. COAL

Q.7 Which symbol is used to declare the preprocessor directives?

A. ^

B. #

C. $

D. *

Q.8 COOL stands for _____.

A. C-like Object Oriented Language

B. Class Oriented Object Language

C. Consumer Oriented Object Language

D. C++-like Object Oriented Language

Q.9 In C++,_____ function is used to return the next character in the input sequence,without extracting it.

A. fstream

B. peek()

C. good()

D. putback()

Q.10 Which of the following is built from request-response?

A. Event-processing Architecture (EDA)

B. Service-oriented architecture (SOA)

C. Event-based Architecture (EBA)

D. Service-driven Architecture (SDA)
