Q.1 _____ handles the occurrence of event.

A. Event routines

B. Event order

C. Event queue

D. Event cycle

Q.2 MTBSO is abbreviated from _____

A. Mean time between service outage

B. Mean time between server outlets

C. Minimum time between service outage

D. Main time between service outage

Q.3 The value of a typical MTBF is once per_____

A. 4000 sec

B. 4000 min

C. 4000 hrs

D. 400 hrs

Q.4 _____ is not a network simulator.

A. Optimized Network Engineering Tool (OPNET)

B. TinyOS Simulator (TOSSIM)

C. Team viewer

D. Network Simulator-2 (NS-2)

Q.5 _____ is a measurement of cost that the system is able to pay for services that it received.

A. Availability

B. Performance

C. Manageability

D. Affordability

Q.6 _____ is the degree to which a system, subsystem or equipment is in a specified operable and committable state

A. Scalability

B. Usability

C. Reliability

D. Availability

Q.7 The "Compute Scalars" can be computed from other scalar in the _____

A. Dataset

B. Library

C. Vectors

D. Scalars

Q.8 MTBF with MTTR helps to assess frequency and _____

A. length of service output

B. life of service outage

C. life of server output

D. length of service outage

Q.9 _____ has an ordered list of events as input.

A. Monte Carlo

B. Trace driven

C. Discrete events

D. Continuous events

Q.10 MTTSO is abbreviated for_____

A. Mean time to recover from service outage

B. Maximum time to recover from service outage

C. Mean time to recover from server outage

D. Minimum time to recover from service outage

VU TOOLKIT