Q.1 Every time you press a key, an interrupt is generated.

This is an example of

A. Hardware interrupt

B. None of the given

C. All of the given

D. Software interrupt

Q.2 A software routine performed when an interrupt is received by the computer is called as ---------

A. Exception

B. Interrupt handler

C. Interrupt

D. Trap

Q.3 The Pentium does allow the use of some part of its ____ accumulator register EAX

A. 16 bits

B. 32 bits

C. 8 bits

D. 64 bits

Q.4 ----------the device usually means reading its status register every so often until the device's status changes to indicate that it has completed the request.

A. Masking

B. Executing

C. Polling

D. Interrupting

Q.5 ____ form the branch control field in the micro instruction.

A. B Bits

B. A Bits

C. M Bits

D. C Bits

Q.6 Which of the following control signals is NOT activated during instruction fetch operation?

A. Cout

B. PCout

C. LMAR

D. LC

Q.7 The directive _____ is used to define variables.

A. .org

B. .equ

C. .sw

D. .db

Q.8 The source file of FALSIM should contain _____ text only.

A. ASCII

B. Unicode

C. ANSI

D. UTF

Q.9 Connection to a CPU that provides a data path between the CPU and external devices, such as a keyboard, display, or reader is called----------

A. I/O port

B. Processor

C. Memory mapping

D. Buffer

Q.10 What is the status of the ACKNLG# signal when a character is completely received by the printer?

A. It goes from high to low

B. It remains unaffected

C. It toggles its state

D. It goes from low to high
