**Q.1 A component connected to the system bus and having control of it during a particular bus cycle is called_____.**

A. System bus

B. Buffer component

**C. Master component**

D. Slave component

---

**Q.2 A component connected to the _____ and with which the master component can communicate during a particular bus cycle. Normally the CPU with its bus control logic is the master component.**

A. System bus

B. Master component

C. Bus component

**D. Slave component**

---

**Q.3 In _____ adder circuit we feed carry out from the previous stage to the next stage and so on.**

A. Carry Look Ahead Adder

**B. Ripple Carry Adder**

C. Complement Adder

D. 2's Complement Adder

---

**Q.4 _____ is a combination of arithmetic, logic and shifter unit along with some multiplexers and control unit.**

A. Flip Flop

B. Barrel Rotator

C. Control Unit

**D. ALU**

---

**Q.5 In Single-Precision Binary Floating Point Representation the exponent is _____**

A. 11 bits

B. 1 bit

C. 23 bits

**D. 8 bits**

---

**Q.6 Raid level _____ distributes the parity strips across all disks.**

A. 2

B. 3

C. 4

**D. 5**

---

**Q.7 For _____ of an error we just need to know that there exists an error.**

A. None of the given

B. Detection

**C. Both Correction and Detection**

D. Correction

---

**Q.8 Along with the information bits, we add up another bit, which is called?**

A. Stop bit

**B. Parity bit**

C. Header bit

D. Start bit

---

**Q.9 human works with base 10 and computers work with base _____.**

A. 10

B. 8

**C. 2**

D. 16

---

**Q.10 The average latency to the desired data is halfway round the disk so, what will be the average rotational latency if the disk rotates at 20,000 rpm.**

A. 1.0ms

**B. 1.5ms**

C. 2.0ms

D. 1.25ms

---