Q.1 If we associate (x, y) integers pair to cars where x is the speed of the car and y is the negation of the price. High y value for a car means a _____ car.

A. Fast

B. Expensive

C. Cheap

D. Slow

Q.2 In Random Access Machine, Instructions are executed

A. one by one

B. in the form of bytes

C. in the form of bits

D. in parallel

Q.3 In 3-Dimensional space, a point P has _____ coordinate(s).

A. (X, Y, Z)

B. (0, Y)

C. (X, Y)

D. (X, 0)

Q.4 Approach of solving geometric problems by sweeping a line across the plane is called _____sweep.

A. Line

B. Cube

C. Box

D. Plane

Q.5 Number of _____of the pseudo code are counted to measure the running time.

A. Steps

B. Outputs

C. Pages

D. Inputs

Q.6 In 2d-maxima problem, a point is said to be _____if it is not dominated by any other point in that space.

A. Joint

B. Minimal

C. Member

D. Maximal

Q.7 An algorithm is a mathematical entity, which is independent of _____.

A. Programming language

B. Programming language, Compiler and Machine

C. Compiler and Programming language

D. Machine and Programming language

Q.8 In the statement "if (P[i].x < P[j].x) & (P[i].y < P[j].y)", the number of times elements of P are accessed is _____

A. 3

B. 2

C. 4

D. 1

Q.9 A Random Access Machine (RAM)is an idealized machine with _____ random access memory.

A. Infinite large

B. 512 MB

C. 256 MB

D. 2 GBs

Q.10 If the time complexity of an algorithm is O(n), then it is called _____ time complexity.

A. Average

B. Constant

C. Linear

D. Exponential

VU TOOLKIT