Q.1 PROLOG supports the _____ programming paradigm.

A. Declarative

B. Object Oriented

C. Functional

D. Aspect Oriented

Q.2 Which of the following are the types of constants in PROLOG?

A. single and decimal

B. float and numbers

C. atoms and numbers

D. short and char

Q.3 All the variables in PROLOG clauses/predicates are:

A. Global

B. Generic

C. Strongly typed

D. Local

Q.4 The function that is used to remove all properties of a symbol in LISP is:

A. NULLP

B. remprop

C. REMOVE

D. terminate-all

Q.5 While eliminating repeated elements of list in PROLOG, each element should be replaced with:

A. Previous element

B. Next element

C. Single copy of the same element

D. Blank space

Q.6 Which of the following function is used in LISP to see all properties of a symbol?

A. get

B. symbol-plist

C. enlist

D. defun

Q.7 In a PROLOG program, the names of all relationships and objects must begin with:

A. Dollar sign ($)

B. Uppercase letter

C. Lowercase letter

D. Underscore

Q.8 How many times the value of a PROLOG variable can be changed after first assignment?

A. Many times

B. Once

C. Twice

D. Zero (Can not be changed)

Q.9 Which of the following statement of LISP creates an array of size 5?

A. (setf (make-array '(5)))

B. (setf linear-array (make-array '(5)))

C. (make linear-array (5))

D. (setq linear-array (array '(5)))

Q.10 Following statement in PROLOG is considered as _____. "relieves(penicilline, pneumonia)"

A. Fact

B. Constant

C. Variable

D. Rule
