Q.1 In transmission impairments _____noise occurs from other sources like motors and appliances etc.

A. Impulse

B. Induced

C. Cross talk

D. Thermal

Q.2 To calculate the data rate for noiseless channel _____ formula is used.

A. Shannon

B. reedy

C. Propagation

D. Nyquist

Q.3 _____ is the Nyquist bit rate formula for noiseless channel.

A. BitRate =2*Bandwidth* L

B. BitRate =2*Bandwidth*log2 L

C. BitRate =3*Bandwidth*log2 L

D. BitRate =2*Bandwidth*log2

Q.4 For a noiseless channel, theoretical formula to calculate the data rate was developed by _____.

A. Shannon

B. Nyquist

C. Hamming

D. Rivest

Q.5 Set of rules to be followed for effective network communication is called _____.

A. Protocol

B. Encryption

C. Switching

D. Topology

Q.6 _____is the data format used at Transport layer of TCP/IP Protocol suite.

A. Frame

B. Bit

C. Segment

D. Packet

Q.7 Two PCs and one printer are connected in a network within a room; it is an example of _____.

A. WAN

B. MAN

C. LAN

D. SONET

Q.8 During transmission, _____ is the effect of one wire on the other.

A. Induced noise

B. Impulse noise

C. Crosstalk

D. Thermal noise

Q.9 A frequency is called ------, if sine wave does not change with time.

A. Zero frequency

B. Frequency hertz

C. Infinite frequency

D. Bandwidth

Q.10 The bandwidth-delay product defines the number of bits that can fill the_____.

A. Hub

B. Link

C. Network

D. Switch

VU TOOLKIT