Q.1 The _____ is the number of signal elements sent per unit time.

A. Bit rate

B. Period

C. Signal rate

D. Data rate

Q.2 The message 110 sent by a source is received by a destination as 111. This is _____type of error.

A. Burst

B. Multi-Bit

C. Single-Bit

D. Byte

Q.3 _____are used to exchange session management and control information between connected devices.

A. N-frames

B. I-frames

C. S-frames

D. U-frames

Q.4 _____ is the process of converting digital data to digital signals.

A. Line coding

B. CSMA/CD

C. CSMA/CA

D. Segmentation

Q.5 _____ is the purpose of the Cyclic Redundancy Check (CRC) method

A. Counting the number of bits in a frame

B. Regulating data flow

C. Detecting and correcting errors

D. Adding redundancy for encryption

Q.6 The _____ protocol uses both flow and error control.

A. HDLC

B. Stop-and-Wait

C. ICMP

D. TCP/IP

Q.7 The term "single-bit error" refer to _____

A. interfering with the flow control process

B. changing 1 bit of a data unit

C. changing multiple bits in a data unit

D. changing the shape of the signal

Q.8 Payload field of the PPP frame is of variable size and it can carry maximum data up to _____.

A. 10 bytes

B. 500 bytes

C. 1500 bytes

D. 100 bytes

Q.9 If the Hamming distance between sent and received code word is _____, then it shows that received data is corrupted.

A. ≠ 0

B. =1

C. = 0

D. ≠ 1

Q.10 The purpose of block coding is _____

A. removing errors from transmitted data

B. creating relationships between bits

C. adding redundancy to data in fixed-size blocks

D. regulating data flow
