Q.1 Signed integer color components, when specified, are linearly mapped to floating-point values such that the most positive representable value maps to 1.0, and the most negative representable value maps to ----------. Floating-point values are mapped directly.

A. 0.0

B. -1.0

C. 2.0

D. 1.0

Q.2 Imagine a curve in three-dimensional space, each point on the curve has a unique set of coordinates: a specific x value, y value, and z value. Each coordinate is controlled by a ---------- parametric equation.

A. Similar

B. None of the given

C. Opposite

D. Separate

Q.3 The value returned is a unique small integer identifier for the window. The range of allocated identifiers starts at ----------. This window identifier can be used when calling glutSetWindow.

A. Zero

B. Two

C. Three

D. One

Q.4 End points and an intermediate point on the curve, then we now ---------- quantities that we can express in terms of these coefficients (3 points x 3 coordinates each), and we can use these three points to define a unique curve.

A. Three

B. Nine

C. Six

D. Two

Q.5 Silhouette edges occur when dot product of surface normal vector and the view vector is _____.

A. Zero

B. One

C. None of the given

D. Both zero and one

Q.6 If we assign a different value to the parametric variable for the intermediate point, then we obtain different values for the coefficients. This, in turn, means that a different curve is produced, although it passes through the ---------- three points.

A. Same

B. None of the given

C. Different

D. Isolate

Q.7 In order to get a more realistic representation of lighting, we'll need to understand how light passes through a medium and how hitting the boundary layer at the ---------- of two media can affect light's properties.

A. Endpoints

B. Union

C. Intersection

D. Edges

Q.8 glutReshapeWindow requests a change in the size of the current window. The width and height parameters are size extents in pixels. The width and height must be ---------- values.

A. Neutral

B. Negative

C. Non of the given

D. Positive

Q.9 To ensure a smooth transition from one section of a piecewise _____ to the next, we can impose various continuity conditions at the connection points

A. Non of the these

B. non parametric curve

C. polygon vector

D. parametric curve

Q.10 If the current matrix (according to glMatrixMode) is multiplied by the translation matrix, with the product replacing the current matrix. That is, if M is the current matrix and T is the translation matrix, then M is replaced with ----------.

A. M-T

B. M+T

C. M/T

D. M*T
