Q.1 In YACC, what does the notation $2 refer to?

A. The second symbol on the right-hand side of a production

B. The first symbol on the left-hand side of a production

C. The first symbol on the right-hand side of a production

D. The second symbol on the left-hand side of a production

Q.2 What is the purpose of analyzing attribute rules in the rule-based methodology of attribute grammar evaluation?

A. To optimize the attribute computation process

B. To generate the parse tree

C. To establish a fixed ordering of attribute evaluation

D. To determine the syntax of the source code

Q.3 What is the purpose of the $3 notation in YACC?

A. To refer to the first symbol on the right-hand side of a production

B. To refer to the third symbol on the right-hand side of a production

C. To refer to the second symbol on the right-hand side of a production

D. To refer to the fourth symbol on the right-hand side of a production

---

Q.4 What is the purpose of using an intermediate representation (IR) in a compiler?

A. To directly translate high-level code into machine code.

B. To simplify the debugging process for the compiled code.

C. To provide a structured and uniform representation for code analysis and transformation.

D. To eliminate the need for multiple passes in the compilation process.

Q.5 What consideration might influence the choice of the attribute evaluation order in the oblivious methodology?

A. Dynamic attribute dependencies

B. Syntax tree generation algorithms

C. Attribute propagation rules

D. Optimization goals

Q.6 Which two linear intermediate representations (IRs) are commonly used in modern compilers?

A. Assembly code and bytecode

B. High-level language and low-level language

C. Stack-machine code and three-address code

D. Register-transfer language and SSA form

Q.7 Stack-machine code and three-address code are mutually exclusive and cannot be used together in modern compilers.

A. True

B. False

Q.8 S --> A B A --> □ | aA B --> □ | bB. FIRST(S) contains ___ elements.

A. 3

B. 4

C. 5

D. 6

Q.9 In YACC specification file, different sections are separated by _____ symbol.

A. @@

B. %%

C. &&

D. ##

Q.10 The size of an LR(1) parsing table can be calculated by multiplying the number of _____ with the number of symbols.

A. Terminals

B. Actions

C. States

D. Rules
