Q.1 In comparison of DLL, executable library files are linked at _____ time.

A. Load

B. Link

C. Compile

D. Run

Q.2 Parent process usually creates a _____ handle if parent and child process may require _____ access rights.

A. New, different

B. Duplicate, different

C. New, Same

D. Duplicate, same

Q.3 How is the linking of functions in DLLs different from monolithic programs?

A. Functions are linked at build time

B. Functions are not linked at all

C. Functions are linked at runtime only

D. Functions are linked at program load time or run time

Q.4 A file mapping handle returns _____ on failure.

A. FALSE

B. UNDEFINED

C. NULL

D. TRUE

Q.5 In order to deallocate a block of heap, _____ is used.

A. HeapFree()

B. HeapTruncate()

C. HeapDelete()

D. HeapDestroy()

Q.6 Console control handlers are similar to _____.

A. Interrupts

B. Exception handlers

C. Parameters

D. Functions

Q.7 IF the system is a _____then windows scheduler can run process threads on separate processors.

A. Bio processor

B. Linear processor

C. Multiprocessor

D. Uni processor

Q.8 While using CreateFileMapping(), setting IpMapName to _____ disables the map sharing.

A. 0

B. 1

C. Null

D. -1

Q.9 It's not a good idea to use _____ within the program as it will not give it chance to release resources.

A. FinishProcess()

B. CreateProcess()

C. TerminateProcess()

D. ExitProcess()

Q.10 Which structure contains the child process handle and id, as well as the primary thread handle and id?

A. PROCESS_INFORMATION

B. SYSTEM_INFO

C. PROCESS_INFO

D. THREAD_INFO
