



DANISH

HANIF

HELP BY DANISH



Paid Services Available 10/10 Marks Guarantee

WhatsApp Contact: 0323-1731413

CS201 Quiz File For Final term

7/28/2023 1:33:32 PM

_____ is the pointer which determines the position in a file from where the next read operation occurs.

Select the correct option

- Put
- Get
- Set
- **Tell**

A pointer with value NULL is defined in the header files _____ and _____.

Select the correct option

- conio.h , iostream.h
- process.h, stdi.h
- **stdlib.h , stddef.h**
- conio.c , getche()

An integer uses four bytes and the integer calculations occur in _____ bytes.

Select the correct option

- 3
- 2
- 4
- 8

Which of the following is not a file opening mode_____?

Select the correct option

- ios::truncate
- ios::out
- ios::ate
- ios::in

NULL has been defined in _____ header file.

Select the correct option

- String.h
- Iostream.h
- Stdio.h
- Stdlib.h

Which is not true regarding structures?

Select the correct option

- (We can declare arrays of structurec)
- We can't declare pointers to structureb)
- We can take the size of structured)
- Both b & c

All the preprocessors directives starts with _____.

Select the correct option

- \$
- #
- _
- &

How many bits form a byte?

Select the correct option

- 4
- 6

- 2
- 8

the sizeof operator is used to determine the size of _____.

Select the correct option

- None of the given
- variable
- data
- data type

_____ allow us to have a memory location and use it as int or char interchangeably

Select the correct option

- struct
- structures
- None of the given
- Union

For accessing data members we use _____ operator

Select the correct option

- plus +
- dot .
- multiplication *
- Division /

#undef is used for _____.

Select the correct option

- defining a header file
- making a symbol undefined
- defining a symbol
- defining a macro

When we include the header file in the angle brackets the compiler searches for it in _____.

Select the correct option

- current directory

- current folder
- **specific directory**
- all the drives

_____ is used for input file or for reading from the file.

Select the correct option

- tellg()
- seekp()
- **seekg()**
- tellp()

Public member functions of the class _____ main program.

Select the correct option

- are defined within the
- are private to
- are not accessible in
- **are accessible in**

In C++, a variable can be declared anywhere in the program, this will increase _____.

Select the correct option

- efficiency
- writability
- portability
- **readability**

With the use of dynamic allocation of memory, the system resources can be _____.

Select the correct option

- used carelessly
- all of the given options
- **used efficiently**
- wasted

The data members of the class are initialized _____.

Select the correct option

- outside the function
- **at runtime**
- within main program

- at compile time

Constructor is itself a _____ of C++ and _____.

Select the correct option

- **function, can be overloaded**
- object, can not be initialized
- function , cannot be overloaded
- class , can be overloaded

An instance of a class is called _____. Select the correct option

- **object**
- structure
- member function
- data type

To access the data members of structure, _____ is used.

Select the correct option

- Dereference operator
- Logical operator
- **Dot operator**
- Address operator

Multiplicative, Additive and assignment operators are _____ operators.

Select the correct option

- Relational
- **Binary**
- Conditional
- Unary

What is the other name for a variable?

Select the correct option

- Constant
- **Identifier**
- Static
- Visual

The object code of our program is combined with the _____.

Select the correct option

- object code of the library functions
- source program
- machine code of the operating system
- with header files

Constructor is itself a _____ of C++ and _____.

Select the correct option

- class , can be overloaded
- object, can not be initialized
- function, can be overloaded
- function , cannot be overloaded

$a = a \& b;$ can be written as _____.

Select the correct option

- $a \&= b;$
- $a = b;$
- $a=a \& b;$
- $a=\& b;$

Which of the following permits function overloading in C++.

Select the correct option

- Both type and arguments
- Type only
- Number of function names
- Number of arguments only

Structures use _____ for memory allocation.

Select the correct option

- Stack
- Heap
- Cache
- Queue

What can the resultant number when you AND two numbers 12 & 8 bit-wise using & operator? Select the correct option

- 8

- 4
- 12
- 6

Which one of the following is used to perform bit-wise OR operation?

Select the correct option

- ||
- ~
- |
- ^

The dynamic memory allocation uses _____ whereas static memory allocation uses _____.

Select the correct option

- heap , stack
- classes , array
- stack , lists
- array , stack

Default constructor takes _____.

Select the correct option

- one parameter
- two parameters
- character type parameter
- no parameters

Which header file is required to use file I/O operations?

Select the correct option

- <fstream>
- <ostream>
- <ifstream>
- <iostream>

_____ function is used to determine the next position to write a character while writing into a file.

Select the correct option

- tellp()
- seekp()
- tellg()

- seekg()

Structures use _____ for memory allocation.

Select the correct option

- Cache
- Heap
- Queue
- Stack

We use dot operator to access the data members of both _____ and _____.

Select the correct option

- unions, structures
- none of them
- unions, arrays
- arrays, structures

Which of the following code segment represents a left shift operator?

Select the correct option

- result = number >> 1 ;
- cin >> number ;
- cout<<1;
- result = number << 1 ;

Name the function whose definition can be substituted at a place where its function call is made _____.

Select the correct option

- friend function
- static function
- inline function
- volatile function

NULL has been defined in _____ header file.

Select the correct option

- Stdio.h
- Iostream.h
- String.h
- Stdlib.h

getche() is a _____ function and defined in _____ header file.

Select the correct option

- built -in function, iostream.h
- built-in function , conio.h
- built-in function, stlib.h
- **user-define function , conio.h**

Windows operating system may itself takes memory from _____.

Select the correct option

- stack
- array
- lists
- **heap**

For accessing data members we use _____ operator

Select the correct option

- multiplication *
- **dot .**
- Division /
- plus +

the sizeof operator is used to determine the size of _____.

Select the correct option

- data
- variable
- **data type**
- None of the given

Constructor is special type of function :

Select the correct option

- **which has no return type**
- which returns integer type data
- which returns zero
- which returns NULL pointer

The function calloc takes two arguments, first argument is the _____ and the second argument is the _____.

Select the correct option

- size of space, number of bytes
- required space in terms of numbers , size of space
- space in terms of string character, size of list
- size of array , number of bytes

Structures use _____ for memory allocation.

Select the correct option

- Heap
- Stack
- Cache
- Queue

Constructor is itself a _____ of C++ and _____.

Select the correct option

- object, can not be initialized
- class , can be overloaded
- function, can be overloaded
- function , cannot be overloaded

Once we have defined a symbolic constant value using #define, that value _____ during program execution.

Select the correct option

- can be changed
- becomes zero
- varies
- cannot be changed