



FINAL

EXAM

Grow Your life



0. In C++ combination of ----- and ----- functions are used to determine the actual data length of a file.

Seekg(), tellg()

1. What will be the output of the following code?

```
Int num=2;
```

```
Int count=0;
```

```
While(num!=0)
```

```
{
```

```
If(num&01)
```

```
Count ++;
```

```
Num>>=1;
```

```
}
```

```
Cout<<count;
```

1

2. In bit manipulation of binary system , if we shift a bit towards right then it means we are ----- that binary value with "2"

Dividing

3. The bit manipulation operator ----- is used to set a specific bit.

|

4. In C++ default visibility of structure is-----

Private

5. In C++ when accessing files randomly, which function is used to get current pointer position inside a file.

Tellg()

6. Which of the following statement is true regarding structures?

Variables which are part of a structure are called data members.

7. In C++ ----- function is used to write a character into a file while ----- is used to get a character from a file.

Putc(), getc()

8. What will be the output of the following code?

```
Struct student{  
    Int age;  
    Float cgpa;  
    Char name[20];  
};  
Int main()  
{  
    Student s={21,3.56,"zaman"};  
    Cout<<sizeof(s);  
}
```

28

9. The bit manipulation operation ----- is used to check whether a specific bit is set or not.

&

10. Functions `seekg()` and `seekp()` require an argument of type `-----` to let them know bytes to move forward or backward.

Long

11. In C++ which operator is used while accessing through the pointer to structure.

->

1. Variables defined in the main function are_____to the function main()

- Static
- Global
- **Local**
- Private

2. Which of the following statement is not true about overloading stream extraction operator(>>)?

- Returns an object of type 'istream &'
- First parameter is of type 'istream &'
- **It can be member operator**
- Second parameter is passed by reference

3. When we call a function and pass an argument, an object or variable to the function , it is called?

- Reference
- Pointer
- **Call by value**
- Call by reference

4. 'endl' is a type of _____ manipulator,

- Class
- **Parameter – less**
- User- defined
- Parameterized

5. Stream insertion (<<) and extraction operator (>>) are always implemented as _____ function:

- User- defined
- Non – member
- Member
- **Friend**

6. In class, if we have to use dynamic memory allocation, we must define a _____ for it.

- Destructor
- **Constructor**
- Reference
- Pointer

7. Automatic variables are created constantly and destroyed_____.

- Often
- **All the time**
- Never
- Sometime

8. Which statement about manipulator is not true?

- Stream insertion operator is on the right-hand side
- They return a reference to insertion operator
- **The left-hand side is ostream operator**
- It automatically gets that object as parameter passed into the function

9. We cannot declare a function as a friend of _____ class.

- Doublestream
- ostream only
- istream
- **istream or ostream**

10. which of the following header file deals with stream extraction?

- String.h
- Iostream
- **Fstream.h**
- manipio.h

11. In function calling, by which method you can call the copy construction?

- Value
- **Call by value**
- Pointer
- Reference

12. Which statement about pointer is not true?

- Pointer can be 'void'
- Points to an area in memory
- **Pointer contains a value**
- Pointer contains a memory address

CS201P

Quiz File

Q.1 We cannot declare a function as a friend of ----- classes

Ans: istream or ostream

Q.2 Automatic variable are created constantly and destroyed

Ans: All the time

Q.3:-----are a conditional compilation process that is used to replace a piece of code by its definition in a programe

Ans: function

Q.4: calloc () functions allocates multiple blocks of memory and each block have-----?

Ans: same size

Q.5: in C++ sizeof operator is used to determine-----

Ans: not confirm

Q.6:which of the following header file deals with stream extraction?

Ans: iostream.h

Q.7: Type to use getch() function without including #include<conio.h> header file in the program is a ----- error

Ans: compilation

Q.8: in C++ the default constructor takes-----

Ans: Only one argument

Q.9: in C++ the name of the ----- is the same as that of a class with a preceding tild (~) sign.

Ans: Destructor

Q10: which of the following option returns the state of end file?

Ans: cin.eof()

Q.11: If the memory in the free store is not sufficient enough to fulfill the request , malloc () function return-----

Ans; Null

**Q.12: in C/C++ language . memory at runtime is allocated from -
-----**

Ans: Stack

Q.13: When overloading assignment (=) operator, which of the following syntax is correct?

Ans: void operator(=) const string &other:

Q.14: which of the following code:

Ans :*7**

Q.15: For overloading minus (-) operator, which member operator function will be correct?

Ans: complex operator-(complex c)

Q:16: In C++ which operator is used for memory allocated ?

Ans: New

Q.17: The Statement `char array [10];` is an example of a type of ----- memory allocation

Ans: static

Q.18: which of the following option not a source of the output stream?

Ans: file

Q.19: A square matrix has-----

Ans: Equal number of rows and columns

Q.20: The statement `*double** elements;` * says that `*elements*` is a / an ----- to double.

Ans: Array of pointers

Q.21: A matrix is nothing but a ----- of numbers.

Ans: Two- dimensional array

Q.22: A programmer can ----- the simple matrix class to handle the integer, float, or double data type as elements of the given matrix.

Ans: Hide

Q.23: in C and C++ language, every expression has a ----- of its own?

Ans: Value

Q.24: The cycle of testing and ----- continues until the program is working perfectly without any problem.

Ans: Bug fixing

Q.25: Default scope for members of structures is ----- and default visibility for class members is ----

Ans: Public, Private

Q.26: If A and B are two matrices of order $M \times N$ to be added then their resultant matrix will have an order of

Ans: $M \times N$

Q.27: if *m* is a matrix object, then self-assignment can be avoided by using following code statement

Ans: If (&m!=this);

Q.28: Which of the following is correct format of template function?

Ans: Template <class T>

Q.29: In template class, compiler makes a copy of ---- and convert in to -----

Ans: Source code , Object code

Q.30: For a matrix, the variables of Rows and Columns should always be a -----

Ans: Whole Number

Q.31: After implementation of code is completed, we do its ----- to verify that it is behaving properly in all scenarios.

Ans: Testing

Q.32: which three constructs do we need to solve any problem?

Ans: Classes, structures, functions

Q.33: Declaration and definition of a template function should be in the ----- file

Ans: same

Q.34: For template function, we must have at least ----- generic argument.

Ans: One

Q.35: In C++ , which of the following option has the correct meaning of the expression "a<=b"?

Ans: a is less than or equal to b

Q.36: which of the following code?

Ans: 2 4 6 8

Q.37: What will be the output of the following code?

Int x=15;

Iny y=10;

Int z= 5;

Cout<< x*x-4*y*z;

Ans: 25

Q.38: Which of the following expression is correct in C/C ++ language?

Ans: X=X+3

Q.39: Which of the following C++ statements I used take input from the user?

Ans: cin

Q.40: Which of the following is an example of logical operator?

Ans: &&,||

Q.41: in C/C++ , which of the following data type is used to store real numbers?

Ans: Float

Q.42: C/C++ has many libraries which contain variables and function names normally starting with -----

Ans: Underscore

Q.42: The coding of a program is translated into machine language by -----

Ans: Compiler

Q.43: Learning "How to program" is important, because it develops----- and problem solving abilities.

Ans: Analytical

Q.44: in C/C++ , the algebraic expression $(b^2-4ac)/2a$ can be written as:

Ans: $(b*b-4*a*c)/(2*a)$

Q.45: In C/C++ , which of the following data type is used to store real member?

Ans: Float

Q.46: To understand programming concepts,----- programming language being used as a vehicle in cs201 "Introduction to programming" course.

Ans: C/C++

Q.47: The bit manipulators operator----- is used to check weather a specific bit is set or not.

Ans: &

Q48.: in C++, which operator is used while accessing through the pointer to structure?

Ans: ->

Q.49: Function seekg() and seekp() require an argument of type----- to let them know how many bytes to move forward backward.

Ans: Long

Q:50: Macro is defined by ----- preprocessor directive.

Ans: #define

Q.51: In C++ , when accessing files randomly, which function is used at get current pointer position inside a file?

Ans: tellg()

Q.52:Which is not a preprocessor directive of C-Language?

Ans: # Startif

**Q.53:The statement char arr [10]; is an example of a type of -----
-- memory allocation**

Ans: Built-in

Q.54: What would be the output of the following statement?

C=13%2;

Ans= 1

Q.55: Which of the following two array are copy-able?

Ans: int a[5],int b[5]

Q.56: A variable declared inside a code block becomes the ----- variable for that block.

Ans: Local

Q.57: Which type of arrays are used while dealing with sentences?

Ans: Character arrays

Q.58: In the call by reference method, which operator is used to get the address of a variable?

Ans: &

Q.59: Which of the following is the correct method to declare an array?

Ans: data-type array-name[size];

Q.60: char name []= "Hello World";

In the above statement, a memory of ----- characters will be allocated to the array name.

Ans: 12

Q.61 In C++ , what is the correct syntax for accessing the fifth element of an array?

Ans: a(4)

Q.62: Which of the following shows the memory address of the first element in an array?

Ans: array[0]

Q.63 In C++ , the precise way to declare a pointer is ,

Ans: int*ptr;

Q.64: Identify the invalid option.

Ans: int *pi=0;

Q.65: ----- character is used to terminate a string.

Ans: Null

Q.66: which of the following is an example of repetition structure?

Ans: while

Q.67: Function declaration is a one-line statement in which we write the return type,----- of the function and the----- of arguments

Ans: Name, Data type

Q.68: If the condition is not made false in while loop, what will happen?

Ans: Program will terminate only

Q.69: Which of the following option gives the [value] stored at the address pointed to by the pointer "ptr"?

Ans: *ptr

Q.70: in C++ , cout is known as -----

Ans: output stream

Q.71: Which of the following is not a file opening mode?

Ans: ios:: trunk

Q.72: In C++ , the precise way to declare a pointer is.

Ans: int*ptr;

Q.73: -----statement is necessary in switch structure.

Ans: Break

Q.74: Normally, the float data type is half of the size of -----

Ans: Double

Q.75: which of the following option is used when working with completed expression in c++?

Ans: {}

Q.76: A binary operator has ----- operands.

Ans: Two

Q.77: which of the following is the default function calling mechanism of C/C++?

Ans: Call by value

Q.78: which function is automatically called when an object of a class is initialed?

Ans: constructor

Q.79: in C++, the default constructor takes-----

Ans: No arguments

Q.80: In C++, which of the following option is used to declare a class?

Ans: class

Q.81:in C++ which of the following function causes the full definition of the function to be inserted in each place when it gots called?

Ans: Inline function

Q.82:Bool data type takes -----values.

Ans: 2

Q.83: In the syntax of the overloaded operator function given below

Complex operator + (Complex &);

What is operator?

Ans: keyword

Q.84:which operator can be overloaded?

Ans: not confirm

Q.85:Complex codd (complex c1, complex c2);

Which statement is true far above code?

Ans: Creating object of class complex with name codd with parameters.

Q.86: Which of the following operator can be overloaded?

Ans: ?

Q.87: Which of the following is assignment operator?

Ans: =

Q.88: which option will be correct in order to free the space of memory allocated to a buffer (but)?

Ans: Delete but

Q.89: When overloading assignment (=) operator, which of the following syntax is correct?

Ans: void operator=(const String &s);

Q.90: Complex codd (Complex c1, Complex c2);

Which of statement is true for above code?

Ans: It accepts two complex numbers as parameters and returns back the resultant complex number.

Q.91: What is correct example of binary operator?

Ans: -

Q.92: Which of the following options not a source of the output stream?

Ans: region in the memory

Q.93: How many option are initialized for the class?

Date my Dates[10];

Ans: 10

Q.94:which statement about pointer is not true?

Ans: pointer can be void

Q.95:Representing logical depiction of the solution to the problem is known as a -----

Ans: Structure

Q.96: Which statement about manipulators is not true?

Ans: it automatically gets that object as parameter passed in to the function

Q.97:which of the following structure is correct for WHILE loop?

Ans: While (condition)

Q.98:which of the following is true about the switch statement?

Ans: It cannot handle the compound conditions which use logical operators

Q.99: If the condition is not made false in while loop, what will happen?

Ans: Loop will become infinite

Q.100: If a function does not return anything, its return type will be -----

Ans: void

Q.101: which of the following is the first step in FOR loop?

Ans: Initialization condition

Q.102: When we call a function and pass an argument, an object or variable to the function, it is called ?

Ans: call by value

Q.103: Stream insertion(<<) and extraction operators (>>) are always implemented as ----- function.

Ans: Non-member

Q104: which of the following statement is not true about overloading stream extraction operator(>>)?

Ans: it can be a member operator.

Q.105: endl is a type of -----manipulator.

Ans: Parameterized less

1. Identify the invalid option

Int* pi = 0;

2. Word processor is

Application software

3. Each pass through a loop is called a/an

Iteration

4. What is the correct syntax to declare an array of size 10 of int data type?

Int name[10];

5. Which of the following operator is used to access the value of variable pointer to by a pointer

& operator

6. Analysis is the ____ step in designing a program

First

7. Paying attention to detail in designing a program is _____.

Necessary

8. Statement in curly braces is

Must

9. The while loop becomes infinite.

When the condition is always true

10. Which of the following function(s) is/are included in stdlib.h header file?

Double atof(const char*nptr), int atol(const char*nptr) 1 and 2 only both

11. If we want to store a string abc in an array str then the size of this array must be at least

2

12. Char name[] = "Hello world";

In the above statement a memory of _____ characters will be allocated to the array name

11

13. Suppose we have declared a two dimensional array multi. To access elements using pointer we should use referencing like _____.

***multi**

14. Which of the following is the correct method to declare an array?

Data,type,array,name,[size]

15. What will be the output of the following code?

```
Int main(){  
Int a(4)={1,2,3,4};  
Cout<<a{2};  
}
```


16. Which of the following two arrays are copy able?

`Int a[5]. Int b[5]`

17. What will be the output of the following code?

```
Int main (){  
Char str1{} = "Hello";  
Char str2{}="World!";  
Cout<<strcat (str1,str2);  
}
```

HelloWorld!

18. In C++ using if statement if we want to execute more than one statement then we have to enclose all statement in _____

{ }

19. What is the output of the following statement?

```
Int I = 2.5;  
Do (cout i*2;)  
While (I > 3 && I < 10);
```

Error

20. Searching is easier when an array is already sorted.

True

21. If an array has 100 elements what is allowable range of subscripts?

0 – 99

22. What will be the value of a and b after executing the following statements?

```
A = 3; b = a++;
```

4 , 3

23. Which of the following function returns the size of a string variable?

Strlen ()

24. Computer can understand only machine language code.

True

25. If the file is not properly closed in the program, the program _____.

Terminate normally

26. Which of the following header file include string conversion functions?

String.h

27. The function of cin is

To read data from keyboard

28. IN C/C++ language the header file which is used to perform useful task and manipulation

Ctype.h

29. The coding of a program is translated into machine language by _____.

Compiler

30. In C/C++ the algebraic expression $(b^2-4ac)/2a$ can be written as;

$(b*b-4*a*c)/(2*a)$

31. The coding of a program is translated into machine language by

Compiler

32. Which of the following expression is correct in C/C++ language?

X=X+3

33. _____ character is used to terminate a string

Null

34. In C++ atoi () function is used to convert _____.

Character string to integer

35. Which of the following is an example of repetition structure?

While

36. Function declaration is a one-line statement in which we write the return type, _____ of the function and the _____ of arguments.

Name, Data type

37. What will be the output of the following code?

```
Int main (){  
Int a[4]={1,2,3,4};  
Cout<<a[2];}
```

3

38. If the condition is not mode false in while loop, what will happen?

Local will become infinte

39. In C++ cout is known as _____.

Output stream

40. What will be the output of the following piece of code?

```
int square(int number){  
int result = 0;  
result = number *number;  
return result;}  
int main()  
{  
Cout<<square(9);  
}
```

81

41. What will be the output of the following code?

```
Int main(){  
Int number[5] = {10,20,30,40,50};  
Cout<<(number+3)}
```

40

42. Which of the following is not a file opening mode?

Ios::trune

43. Function declaration is a one-line statement in which we write the return type ____ of the function and the ____ of argument

Name, Data type

44. In C++, the precise way to declare a pointer is.

Int*ptr;

45. In C++, what is the correct syntax for accessing the fifth element of an array?

A[4]

46. ____ statement is necessary in switch structure.

Break

47. Normally the float data type is half of the size of ____.

Double

48. A variable declared inside a code block becomes the ____ variable for that block.

Local

49. In C++, all the string manipulation function are defined inside ____ header file.

String.h

50. The size variable in the following program is a ____ variable

```
#include<iostream>
```

```
-
```

```
Int size
```

```
-
```

```
Int main()
```

```
{
```

```
-
```

```
}
```

Global

51. What will be the output of the following code?

```
Int I = 0;
```

```
While(i!= 15){
```



```
Cout<<i<<"";  
I=i+5;  
}
```

0 5 10

52. Which of the following C++ statements is used take input from the user?

Cin

53. _____ statement is necessary in switch structure

Break

54. Learning how to program is important because it develops _____ and problem solving abilities.

Analytical

55. Which of the following option is used when working with complicated expressions in C++?

()

56. A binary operator has _____ operands

Two

57. Which of the following is the default function calling mechanism of C/C++?

Call by value

58. In C++ which of the following option has the correct meaning of the expression $a \leq b$?

A is less than or equal to b

59. What will be the output of the following code?

```
Int i=1;  
While(i<10){  
If(i%2==0)
```



```
Cout<<i<<" ";
```

```
I++;}
```

2,4,6,8

60. What will be the output of the following code

```
Int x=15;
```

```
Int y=10;
```

```
Int z=5;
```

```
Cout<<x*x - 4*y*z;
```

25

61. Which of the following expression is correct C/C++ language?

X=x+3

62. Which of the following is an example of logical operator

&&,||

63. In C/C++, which of the following data type is used to store real numbers?

Float

64. C/C++ has many libraries which contain variables and function names normally starting with _____.

Underscore

65. The coding of a program is translated into machine language by _____.

Compiler

66. Which of the following option gives the value stored at the address pointed to by the pointer "ptr"?

*ptr

67. We cannot declare a function as a friend of _____ class

Istream or ostream

68. What will be the output of this given code

```
#include <iostream>
#include<iomanip>
Using namespace std;
Main( )
{float num = 15.9999;
Cout<<setprecision (2)<<num;}
```

16

69. Automatic variables are created constantly and destroyed _____.

All the time

70. _____ are a conditional compilation process that is used to replace a piece of code by its definition in a program

Macros

71. Calloc() functions allocates multiple blocks of memory and each block have _____?

Same size

72. Which of the following header file deals with stream extraction?

Iostream.h

73. Trying to use getch() function without including #include<conio.h> header file in the program is a _____ error

Compilation

74. In C++ the default constructor takes _____.

No arguments

75. In C++ the name of the _____ is the same as that of a class with a preceding tilde (~) sign

Destructor

76. Which of the following option returns the state of end of file?

`Cin.eof();`

77. If the memory in the free store is not sufficient enough to fulfill the request, `malloc()` function returns _____.

NULL

78. In C/C++ language memory at runtime is allocated from _____.

Free store(heap)

79. When overloading assignment (=) operator which of the following syntax is correct?

`Void operator = (const string &s);`

80. What will be output of the following code

```
#include<iostream>
#include<iomanip>
Using namespace std;
Main()
{
Int num = 7
Cout<<setfil(" ") <<setw(4)<<num<<endl;}
```

***7

81. For overloading minus (.) operator which member operator function will be correct?

`Complex operator – (Complex c)`

82. In C++ which operator is used for memory allocation?

`new`

83. The statement `char arr[10]` is an example of a type of _____ memory allocation

Static

84. Which of the following options not a source of the output stream?

Region in the memory

85. Which is not a preprocessor directive of C language?

#startif

86. In the syntax of the overloaded operator function given below

Complex operator + (Complex &);

What is operator

Keyboard

87. If(day==daysofMonth(*this))

{ }

In above code *this refers to;

Current class

88. How many objects are initialized for the class data? Date mydates[10];

10

89. What would be the output of the following statement? C=13%2

1

90. Which statement about pointer is not true?

Pointer can be void

91. Representing logical depiction of the solution to the problem is known as a _____.

Structure

92. Which statement about manipulator is not true?

It automatically gets that object as parameter passed in to the function

93. Which of the following options not a source of the output stream

screen

Correct syntax of the prototype of the overloaded operator function is _____

return-type operator operator-symbol (parameter-list);

in the syntax of the overloaded operator function given below:

Complex operator + (Complex &);

What is 'operator'?

Keyword

What will be out put of following code?

```
#include <iostream>
#include <iomanip>
using namespace std;
main()
{
    int num=7;
    cout<<setfill('*')<<setw(4)<<num<<endl;
}
***7
```


What will be out put of following code?

```
#include <iostream>
#include <iomanip>
using namespace std;
main()
{
    float num=15.9999;
    cout<<setprecision (2) << num;
}
15.99
```

Consider the code below:

```
Class class1
{
    Private int l;
};
Class class2 : protected class1
{};
Then int member l of class1 is ____ in class2.
Protected
```

Consider the code below:

```
Class class1
{
    Private : void func1();
};
Class class2 : protected class1
{};
Then int member l of class1 is ____ in class2.
```

Protected

If (day == daysOfMonth (*this))

{

In the above code, *this refers to:

Current object

The correct syntax of stream insertion operator is:

ostream& ostream::operator << (char *text);

which one is not the member function of input stream?

Get();

Complex cadd (Complex c1, Complex c2) ;

Which statement is true for above code?

It accepts two complex numbers as parameters and returns back the resultant complex number.

which option will be correct in order to free the space of memory allocated to a buffer (buf)?

Delete buf

Which header file is used for file manipulation?

io manip.h

What will be out put of following code?

```
#include <iostream>
using namespace std;
main()
{
    int num;
    cout<<" ";
    cin >> num + 4;
}
```

Add number + 4

Which one is the correct syntax for declaration of a function which can return a reference:

datatype& function_name (parameter list)

where can we declare a friend function in the class:

Anywhere

An entry in an online encyclopedia that refers to another entry whose title has been changed is an example of _____

Reference pointer

In the following code what will be the output of it?

```
#include <iostream>
using namespace std;
main()
{
int i;
int &j=i;
i = 123;
cout<<"\n the value of i ="<<i;
}
```

The value of i = 123

The data members that are visible only from inside the class and hidden from the outside know as:

Private

Which one is the correct syntax to declare a friend function?

friend return_type friend_function_name(int,char);

----- is a user-defined data type.

Class

A constructor with arguments is known as:

Parameterized constructor

We cannot declare a function as a friend of ----- classes

istream or ostream

Automatic variable are created constantly and destroyed

All the time

_____are a conditional compilation process that is used to replace a piece of code by its definition in a programme

function

calloc () functions allocates multiple blocks of memory and each block have-----
----?

same size

in C++ sizeof operator is used to determine-----

the size that a data type represents

which of the following header file deals with stream extraction?

iostream.h

Type to use getch() function without including #include header file in the program is a ----- error

compilation

in C++ the name of the ----- is the same as that of a class with a preceding tild (~) sign.

Destructor

which of the following option returns the state of end file?

cin.eof()

If the memory in the free store is not sufficient enough to fulfill the request , malloc () function return-----

Null

in C/C++ language . memory at runtime is allocated from - -----

Free Store(heap)

When overloading assignment (=) operator, which of the following syntax is correct?

void operator(=) const string &other:

which of the following code:

*****7**

For overloading minus (-) operator, which member operator function will be correct?

complex operator-(complex c)

In C++ which operator is used for memory allocated ?

New

The Statement `char array [10];` is an example of a type of ----- memory allocation

static

which of the following option not a source of the output stream?

Screen

A square matrix has-----

Equal number of rows and columns

The statement `*double** elements;` * says that `*elements*` is a / an ----- to double.

Array of pointers

A matrix is nothing but a ----- of numbers

Two- dimensional array

A programmer can ----- the simple matrix class to handle the integer, float, or double data type as elements of the given matrix.

Hide

in C and C++ language, every expression has a ----- of its own?

Value

The cycle of testing and ----- continues until the program is working perfectly without any problem.

Bug fixing

Default scope for members of structures is ----- and default visibility for class members is ----

Public, Private

If A and B are two matrices of order $M \times N$ to be added then their resultant matrix will have an order of

$M \times N$

if *m* is a matrix object, then self-assignment can be avoided by using following code statement

If (&m!=this);

Which of the following is correct format of template function?

Template

In template class, compiler makes a copy of ---- and convert it to ----

Source code , Object code

For a matrix, the variables of Rows and Columns should always be a -----

Whole Number

After implementation of code is completed, we do its ----- to verify that it is behaving properly in all scenarios.

Testing

which three constructs do we need to solve any problem?

Classes, structures, functions

Declaration and definition of a template function should be in the ----- file

same

For template function, we must have at least ----- generic argument.

One

In C++ , which of the following option has the correct meaning of the expression "a<=b"?

a is less than or equal to b

which of the following code?

2 4 6 8

What will be the output of the following code? `Int x=15; Iny y=10; Int z= 5; Cout<< x*x-4*y*z;`

25

Which of the following expression is correct in C/C ++ language?

X=X+3

Which of the following C++ statements I used take input from the user?

cin

Which of the following is an example of logical operator?

&&,||

in C/C++ , which of the following data type is used to store real numbers?

Float

C/C++ has many libraries which contain variables and function names normally starting with -----

Underscore

The coding of a program is translated into machine language by -----

Compiler

Learning "How to program" is important, because it develops----- and problem solving abilities.

Analytical

in C/C++ , the algebraic expression $(b^2-4ac)/2a$ can be written as:

$(b*b-4*a*c)/(2*a)$

In C/C++, which of the following data type is used to store real member?

Float

To understand programming concepts,----- programming language being used as a vehicle in cs201 "Introduction to programming" course

C/C++

The bit manipulators operator----- is used to check whether a specific bit is set or not.

&

in C++, which operator is used while accessing through the pointer to structure?

->

Function seekg() and seekp() require an argument of type----- to let them know how many bytes to move forward backward.

Long

Macro is defined by ----- preprocessor directive.

#define

In C++ , when accessing files randomly, which function is used at get current pointer position inside a file?

tellg()

Which is not a preprocessor directive of C-Language?

Startif

The statement char arr [10]; is an example of a type of ----- memory allocation

Built-in

What would be the output of the following statement? C=13%2;

1

Which of the following two array are copy-able?

int a[5],int b[5]

A variable declared inside a code block becomes the ----- variable for that block.

Local

Which type of arrays are used while dealing with sentences?

Character arrays

In the call by reference method, which operator is used to get the address of a variable

&

Which of the following is the correct method to declare an array?

data-type array-name[size];

char name []= "Hello World"; In the above statement, a memory of ----- characters will be allocated to the array name.

12

In C++ , what is the correct syntax for accessing the fifth element of an array?

a(4)

Which of the following shows the memory address of the first element in an array?

array[0]

In C++ , the precise way to declare a pointer is , int*ptr; Q.64: Identify the invalid option.

int *pi=0;

----- character is used to terminate a string.

Null

which of the following is an example of repetition structure?

while

Function declaration is a one-line statement in which we write the return type,---- of the function and the----- of arguments .

Name, Data type

If the condition is not made false in while loop, what will happen?

Program will terminate only

Which of the following option gives the [value] stored at the address pointed to by the pointer "ptr"?

***ptr**

in C++ , cout is known as -----

output stream

Which of the following is not a file opening mode?

ios:: trunk

In C++ , the precise way to declared a pointer is.

int*ptr;

-----statement is necessary in switch structure.

Break

Normally, the float data type is half of the size of -----

Double

which of the following option is used when working with completed expression in c++?

()

A binary operator has ----- operands.

Two

which of the following is the default function calling mechanism of C/C++?

Call by value

which function is automatically called when an object of a class is initialed?

constructor

in C++, the default constructor takes-----

No arguments

In C++, which of the following option is used to declare a class?

class

in C++ which of the following function causes the full definition of the function to be inserted in each place when it gets called?

Inline function

Bool data type takes -----values.

2

In the syntax of the overloaded operator function given below Complex operator + (Complex &); What is operator?

keyword

which operator can be overloaded?

delete[]

Complex codd (complex c1, complex c2); Which statement is true far above code?

Creating object of class complex with name codd with parameters.

Which of the following operator can be overloaded?

?

Which of the following is assignment operator?

=

which option will be correct in order to free the space of memory allocated to a buffer (but)?

Delete but

When overloading assignment (=) operator, which of the following syntax is correct?

void operator=(const String &s);

Complex codd (Complex c1, Complex c2); Which of statement is true for above code?

It accepts two complex numbers as parameters and returns back the resultant complex number.

What is correct example of binary operator?

-

Which of the following options not a source of the output stream?

region in the memory

How many option are initialized for the class? Date my Dates[10];

10

which statement about pointer is not true?

pointer can be void

Representing logical depiction of the solution to the problem is known as a -----
--

Structure

Which statement about manipulators is not true?

it automatically gets that object as parameter passed in to the function

which of the following structure is correct for WHILE loop?

While (condition)

which of the following is true about the switch statement?

It cannot handle the compound conditions which use logical operators

If the condition is not made false in while loop, what will happen?

Loop will become infinite

If a function does not return anything, its return type will be -----

void

which of the following is the first step in FOR loop?

Initialization condition

When we call a function and pass an argument, an object or variable to the function, it is called ?

call by value

Stream insertion(<>) are always implemented as ----- function.

Non-member

Which of the following is true about the switch statement? Select the correct option

It is valid for the large programs only.

It cannot handle the compound conditions which use logical operators

.It is valid for the small programs only.

It works efficiently on compound conditions which use logical operators.

The correct option is:

It works efficiently on compound conditions which use logical operators.

Which of the following is the first step in FOR loop? Select the correct option

Continuation condition

Incrementing condition

Termination condition

Initialization condition

The correct option is: **Initialization condition.**

If the condition is not made false in while loop, what will happen? Select the correct option

Program will not run at all.

Program will terminate early.

Loop will become infinite

.Syntax errors occur.

correct option is: Loop will become infinite.

The loop, given below, will iterate_____ times.For (int counter = 1; counter < 10; counter = counter +1)Select the correct option

01

10

9

10

correct option is 9.

The operators ++ and -- are used to increment or decrement the variable value by _____.Select the correct option

3

4

1

2

1. The coding of a program is translated into machine language by _____.
Compiler
2. Normally, the float data type is half of the size of _____.
Double
3. What will be the output of the following code? `int x = 15;int y = 10;int z = 5;cout << x * x - 4 * y * z;`
25
4. Which data type from the following will take lesser space in memory?
Char
5. In C/C++, which of the following data type is used to store real numbers?
float

1: In C++, all the string manipulation function are defined inside _____ header file. Select the correct option

string.h

stdio.h

iostream

conio.h

2: What will be the output of the following code? int main(){ int number[5] = {10,20,30,40,50}; cout << *(number+3);} Select the correct option

30

40

10

50

3: In C++, atof () function is used to convert _____. Select the correct option

Character string to float

Character string to integer

Character string to short

Character string to long integer

4: What will be the output of the following code? int main (int argc, char **argv) {cout<<argc;} Select the correct option

Null

1

2

0

5: From the following code, what will be the size of the array "name"? char name [] = "My full name"; Select the correct option

13

14

15

12

6: What will be the output of the following code?
`int main(){ char str1[] = "Hello "; char str2[] = "World!"; cout << strcat(str1,str2);}`
Select the correct option

World!

HelloWorld!

HelloHello

World!

7: In C++, atoi () function is used to convert _____.Select the correct option

Character string to long integer

Character string to integer

Character string to float

Character string to double

8: To perform I/O operations on file, we must use _____ header file.Select the correct option

Fstream

Istream

Cstream

hstream

1) Which of the following is the first step in FOR loop?

Select the correct option

- A. Termination condition
- B. Incrementing condition
- C. Continuation condition
- D. Initialization condition

2) Which of the following expression is correct in C/C++ language?

Select the correct option

- A. $Y + X = 7$
- B. $3 = X + 3$
- C. $X = X + 3$
- D. $X + 5 = Y + 7$

3) What will be the output of the following piece of code?

```
int square(int number)
```

```
{
```

```
int result = 0;
```

```
result = number * number;
```

```
return result;
```

```
}
```

```
int main()
```

```
{
```

```
cout<<square(9);
```

Select the correct option

- A. 99
- B. 99
- C. 49
- D. 81

4) In C++, cout is known as _____.

Select the correct option

- A. input stream
- B. output stream
- C. file stream
- D. error stream

5) Which of the following is an example of logical operator?

Select the correct option

- A. /,%
- B. +,*
- C. &&,||
- D. <,>

6) While programming in C++, the statement if (x = 3), will result into a _

Select the correct option

- A. Linker Error
- B. Syntax Error
- C. Runtime Error
- D. Logical Error

7) Learning “how to program” is important, because it develops _____ abilities.

Select the correct option

- A. Listening
- B. Reading
- C. Writing
- D. Analytical

Question # 10 of 10 (**Start time: 10:36:04 PM, 28 June 2024**)

Which function is automatically called in C++ if we do not define it in a class?

Select the correct option

☐	Inline function
☒	Default Constructor
☐	Default and Parametrized Constructor
☐	Parametrized Constructor

**Question # 9 of 10 (Start time: 10:35:29 PM, 28 June 2024)**

What will be the output of the following code?

```
void sampleFunction(int = 5,float = 4.1, char = 'A');  
int main(){  
    sampleFunction(50,3.2);  
}  
  
void sampleFunction(int one,float two ,char three) {  
    cout << one << " , " << two << " , " << three;  
}
```

Select the correct option

☐	5, 4.1, A
☐	50, 4.1, A
☐	5, 3.2, A
☒	50, 3.2, A

[Click](#)



CS201P - Introduction to Programming (Practical) (Regular Quiz 3)

Quiz Start Time: 10:31

Question # 8 of 10 (Start time: 10:34:54 PM, 28 June 2024)

In C++, the name of the _____ is the same as that of a class with a preceding tilde (~) sign.

Select the correct option

Reload

- | | |
|----------------------------------|------------------|
| ☐ | Friend function |
| ☒ | Destructor |
| ☐ | Utility function |
| ☐ | Constructor |

Click to Save Answer & Move to

Question # 7 of 10 (Start time: 10:34:23 PM, 28 June 2024)

In C++, when accessing files randomly, which function is used to get current pointer position inside a file?

Select the correct option

☒	tellg()
☐	tellp()
☐	seekg()
☐	seekp()

Click to Save

Question # 6 of 10 (Start time: 10:33:59 PM, 28 June 2024)

Total Marks: 1

Functions **seekg ()** and **seekp ()** require an argument of type ____ to let them know how many bytes to move forward or backward.

Select the correct option

 Reload Math Equations

☐	float
☐	int
☐	double
☒	long

Click to Save Answer & Move to Next Question

**Question # 5 of 10 (Start time: 10:33:15 PM, 28 June 2024)**

In C++, which operator is used while accessing through the pointer to structure?

Select the correct option

☒	->
☐	&
☐	-
☐	=



CS201P - Introduction to Programming (Practical) (Regular Quiz 3)

Question # 4 of 10 (Start time: 10:32:45 PM, 28 June 2024)

Dynamic memory allocation uses memory from the _____.

Select the correct option

☐	Stack
☒	Heap
☐	Multidimensional Array
☐	Array

**CS201P - Introduction to Programming (Practical) (Regular Quiz 3)****Question # 3 of 10 (Start time: 10:32:16 PM, 28 June 2024)**

What would be the output of the following statement?

`c = 13 % 2;`

Select the correct option

☐	0
☒	1
☐	3
☐	2



Question # 2 of 10 (Start time: 10:31:48 PM, 28 June 2024)

Which of the following is not true about Destructor?

Select the correct option

☐	Destructors cannot be overloaded.
☒	Destructors cannot be used for memory manipulation.
☐	Destructors don't return a value.
☐	Destructors take no arguments



CS201P - Introduction to Programming (Practical) (Regular Quiz 3)

Question # 1 of 10 (Start time: 10:31:11 PM, 28 June 2024)

In C++, which operator is used to access the data members of the class?

Select the correct option

- | | |
|----------------------------------|------|
| ☐ | Not |
| ☐ | Plus |
| ☒ | Dot |
| ☐ | And |

Question # 2 of 10 (Start time: 06:13:43 PM, 07 July 2023)

Total Marks: 1

In C++, which operator is used for memory allocation?

Select the correct option

 Reload Math Equations

☐	Allocate
☒	New
☐	Allocate_memory
☐	Calloc

[Click to Save Answer & Move to Next Question](#)

Question # 3 of 10 (Start time: 06:15:07 PM, 07 July 2023)

Total Marks: 1

A constructor with arguments is known as.

Select the correct option

 Reload Math Equations

☐	Virtual Constructor
☐	Default Constructor
☒	Paramterized Constructor
☐	Destructor

Question # 4 of 10 (Start time: 06:15:29 PM, 07 July 2023)

Total Marks: 1

In C++, which of the following function causes the full definition of the function to be inserted in each place when it gets called?

Select the correct option



☐	Recursive function
☒	Inline function
☐	Built-in function
☐	Library function

Question # 5 of 10 (Start time: 06:16:38 PM, 07 July 2023)

Total Marks: 1

An entry in an online encyclopedia that refers to another entry whose title has been changed is an example of -----.

Select the correct option



☒	Dangling pointer
☐	This pointer
☐	Reference pointer
☐	NULL Pointer

Question # 6 of 10 (Start time: 06:17:37 PM, 07 July 2023)

Total Marks: 1

Which one is correct syntax for declaration of a function which can return a reference?

Select the correct option

[Reload Math Equations](#)

- | | |
|----------------------------------|---|
| ☒ | <code>datatype& function_name (parameter list)</code> |
| ☐ | <code>&function_name datatype (parameter list)</code> |
| ☐ | <code>datatype (parameter list) &function_name</code> |
| ☐ | <code>&datatype function_name (parameter list)</code> |

Question # 7 of 10 (Start time: 06:18:51 PM, 07 July 2023)

Total Marks: 1

Which function is automatically called when an object of a class is initiated?

Select the correct option

[Reload Math Equations](#)

- | | |
|----------------------------------|------------------|
| ☐ | Friend function |
| ☐ | Destructor |
| ☒ | Constructor |
| ☐ | Utility function |

Question # 8 of 10 (Start time: 06:19:10 PM, 07 July 2023)

Total Marks: 1

In C++, the default constructor takes _____.

Select the correct option

 Reload Math Equations

- | | |
|----------------------------------|-------------------------|
| ☐ | Only one argument |
| ☒ | No arguments |
| ☐ | More than two arguments |
| ☐ | Only two arguments |

Question # 9 of 10 (Start time: 06:19:59 PM, 07 July 2023)

Total Marks: 1

In C++, **sizeof** operator is used to determine _____.

Select the correct option

 Reload Math Equations

- | | |
|----------------------------------|-------------------|
| ☐ | Length of string |
| ☐ | Length of words |
| ☒ | Size of data type |
| ☐ | Number of words |

[Click to Save Answer & Move to Next Question](#)

Question # 10 of 10 (Start time: 06:20:58 PM, 07 July 2023)

Total Marks: 1

Which one is the correct syntax to declare the *friend* function?

Select the correct option

 Reload Math Equations

- | | |
|----------------------------------|--|
| ☐ | <code>FRIEND return_type friend_function_name(int, char);</code> |
| ☐ | <code>FRIEND friend_function_name(int, char);</code> |
| ☐ | <code>Friend return_type (int, char);</code> |
| ☒ | <code>friend return_type friend_function_name(int, char);</code> |

[Click to Save Answer & Move to Next Question](#)

Question # 1 of 10 (Start time: 08:03:33 AM, 08 July 2023)

An entry in an online encyclopedia that refers to another entry whose title has been changed is an example of _____

Select the correct option



- | | |
|----------------------------------|-------------------|
| ☐ | Dangling pointer |
| ☒ | Reference pointer |
| ☐ | NULL Pointer |
| ☐ | This pointer |

Click to Save Answer & Move t

Question # 2 of 10 (Start time: 08:04:00 AM, 08 July 2023)

Data encapsulation can be achieved through _____.

Select the correct option

☐	Pointers
☒	Classes
☐	Structures
☐	Arrays

Question # 3 of 10 (Start time: 08:04:31 AM, 08 July 2023)

In C++, which operator is used for memory allocation?

Select the correct option

☐	Allocate
☐	Calloc
☒	New
☐	Allocate_memory

Click to See

CS201P - Introduction to Programming (Practical) (Lab 9&10 Quiz)

Question # 4 of 10 (Start time: 08:05:03 AM, 08 July 2023)

In C++, which of the following option is used to declare a class?

Select the correct option

☐	Class
☒	class
☐	cLass
☐	CLASS

Click

Question # 5 of 10 (Start time: 08:05:38 AM, 08 July 2023)

In the following code, what will be the output of i?

```
#include<iostream>

using namespace std;

main()
{
    int i;
    int &j = i;
    i = 123;
    cout<< "\n The value of i =" << i;
}
```

Select the correct option

☐	321
☐	x012345
☐	012345x
☒	123

CS201P - Introduction to Programming (Practical) (Lab 9&10 Quiz)

Question # 6 of 10 (**Start time: 08:06:43 AM, 08 July 2023**)

A constructor with arguments is known as.

Select the correct option

☐	Destructor
☒	Paramterized Constructor
☐	Default Constructor
☐	Virtual Constructor

CS201P - Introduction to Programming (Practical) (Lab 9&10 Quiz)

Question # 7 of 10 (**Start time: 08:07:13 AM, 08 July 2023**)

In C++, **sizeof** operator is used to determine _____.

Select the correct option

☐	Length of words
☒	Size of data type
☐	Length of string
☐	Number of words

Question # 9 of 10 (Start time: 08:09:13 AM, 08 July 2023)

Which function is automatically called when an object of a class is initiated?

Select the correct option

Reload

☒	Constructor
☐	Utility function
☐	Friend function
☐	Destructor

Click to Save Answer & Move to Next

Question # 10 of 10 (Start time: 08:09:35 AM, 08 July 2023)

In C++, the name of the _____ is the same as that of a class with a preceding tilde (~)

Select the correct option

☐	Utility function
☐	Friend function
☒	Destructor
☐	Constructor

[Click to Save Answer](#)

Finalterm File



GrowYourlife

ARE
YOU
READY
FOR
EXAMS?

