

Paid Services Available 10/10 Marks Guarantee

WhatsApp Contact: 0323-1731413

CS604p Lab # 8 Quiz File

1/5/2024 4:28:12 PM

Question #1: In the Banker's algorithm, the Need data structure is used. If_____, then process Pi may need k more instances of resource type Rj to complete the task.

A) Need[j,i] = k
B) Need[k,j] = k
C) Need[i,j] = k
D) Need[i,k] = j

Answer: A) Need[j,i] = k

Question #2: In the Banker's algorithm, we can say that a system is in a _____ if all of the processes in the system can be executed to termination in some order.

A) Halt state
B) Reverse state
C) Stop state
D) Safe state

Answer: D) Safe state

Question #3: The address generated by the CPU is commonly referred to as the _____.

A) Complex address
B) Physical address

C) Logical address
D) Sample address

Answer: C) Logical address

Question #4: In the Banker's algorithm, the Max data structure is used. If_____, then process Pi can request a maximum of k instances of resource type Rj.

A) Max[j,i] = k
B) Max[i,j] = k
C) Max[i,k] = j
D) Max[k,j] = i

Answer: B) Max[i,j] = k

Question #5: We need the following data structures in the Banker’s algorithm:

A) Available, Min, Allocation, and Find.
B) Available, Min, Allocation, and First.
C) Available, Max, Allocation, and Need.
D) Available, Max, Allocation, and Next.

Answer: C) Available, Max, Allocation, and Need.

WHATSAPP CONTACT 03231731413
HELP BY DANISH