Professional Online Academy Vu Topper RM

CS606-Compiler Construction Update MCQ'S Final Term By Vu Topper RM

Follow Us on YouTube: @vutopperrm

For More Help Contact What's app Me!!!
Number's = # 0322-4021365, 0316-4980094

Rizwan Manzoor
Vu Topper RM



بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:1 **(Marks:1)** **Vu-Topper RM**

The canonical collection is used to generate which of the following parsing tables?

A. Production and symbol tables
B. First and follow tables
C. Closure and reduction tables
D. Action and goto tables

Question No:2 **(Marks:1)** **Vu-Topper RM**

What does the term "canonical collection" refer to in LR parsing?

A. A set of LR items representing the states of the parser during parsing.
B. A table used for storing parsing actions.
C. The final output of the parsing process.
D. A list of production rules in a grammar.

Question No:3 **(Marks:1)** **Vu-Topper RM**

In LR grammar, the R stands for _____.

A. Right shift
B. Right to left scan
C. Right most derivation
D. Right hand side of grammar

Question No:4 **(Marks:1)** **Vu-Topper RM**

The NFA of LR(0) items represents transitions between:

A. LR(1) items.
B. LR(0) items without considering lookahead symbols.
C. Grammar symbols and their derivations.
D. Non-terminal symbols and their productions.

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:5 **(Marks:1)** **Vu-Topper RM**

In the grammar "T → a b c d | a b d c", the _____ is a common prefix for non-terminal 'T'.

A. c d
B. a b
C. b d
D. a c

Question No:6 **(Marks:1)** **Vu-Topper RM**

In the LR table, how are the entries other than the state containing [S' → •S, $] initialized?

A. Marked as "accept"
B. Assigned with reduce actions
C. Marked as "error"
D. Assigned with shift actions

Question No:7 **(Marks:1)** **Vu-Topper RM**

Left factoring is primarily used in which type of parsing?

A. Predictive parsing
B. Bottom-up parsing
C. Shift-Reduce parsing
D. LR parsing

Question No:8 **(Marks:1)** **Vu-Topper RM**

In the handle representation <A → α, k>, what does A represent?

A. The non-terminal on the left-hand side of the production rule.
B. The last symbol in the input string.
C. The position of the handle within the input string.
D. The lookahead symbol.

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:9 **(Marks:1)** **Vu-Topper RM**

The output from the algorithm for the construction of collection of canonical sets of LR(1) items is _____.

A. CC sets of LR(1)
B. Original Grammar G
C. CC sets of LR(0)
D. Augmented Grammar G'

Question No:10 **(Marks:1)** **Vu-Topper RM**

Which of the following is NOT a step in the closure procedure for an LR item?

A. Add the item to the closure set.
B. Identify the symbols immediately following the dot in the item.
C. Compute the FIRST set for the nonterminal symbol following the dot.
D. Determine the lookahead symbols for the item.

Question No:11 **(Marks:1)** **Vu-Topper RM**

The augmented grammar has its own start symbol, while original grammar includes an additional production rule, called the augmented start production.

True
False

Question No:12 **(Marks:1)** **Vu-Topper RM**

In Shift-Reduce parser, the handle-recognizing DFA is basically represented as a 2-dimensional table, where _____ correspond to DFA states.

A. Cells
B. Rows
C. Captions
D. Columns

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:13 **(Marks:1)** **Vu-Topper RM**

The Upper Frontier is associated with which type of parsing algorithm?

A. Top-Down
B. Bottom-Down
C. Top-Up
D. Bottom-Up

Question No:14 **(Marks:1)** **Vu-Topper RM**

The upper frontier in a shift-reduce parser is the set of symbols at the top of the parser's stack that have not been reduced yet.

True
False

Question No:15 **(Marks:1)** **Vu-Topper RM**

The input to the algorithm for the construction of collection of canonical sets of LR(1) items is _____.

A. Original Grammar G
B. CC sets of LR(1)
C. CC sets of LR(0)
D. Augmented Grammar G'

Question No:16 **(Marks:1)** **Vu-Topper RM**

What is the upper frontier in a partially constructed parse tree?

A. The bottommost part of the tree.
B. The leftmost part of the tree.
C. The topmost part of the tree.
D. The rightmost part of the tree.

Question No:17 **(Marks:1)** **Vu-Topper RM**

In the context of LR(1) parser, which of the following forms the GoTo table in the DFA representation table?

A. Columns with non-terminals
B. Columns with terminals

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

C. Rows with non-terminals
D. Rows with terminals

Question No:18 **(Marks:1)** **Vu-Topper RM**
LR(0) parsing is a more powerful parsing technique than LR(1) parsing.
True
False

Question No:19 **(Marks:1)** **Vu-Topper RM**
LR parsers are commonly used for:
A. Syntax analysis
B. Register Allocation
C. Code generation
D. Lexical analysis

Question No:20 **(Marks:1)** **Vu-Topper RM**
If closure(I) is "I0 = [S' → ·S, S → ·s]" for a typical grammar, then goto(I0, s) would be _____.
A. S' → S·
B. S → S·
C. S' → s·
D. S → s·

Question No:21 **(Marks:1)** **Vu-Topper RM**
In the context of canonical collection of LR(1) items, if a terminal appears after the placeholder "·" then no further closure is possible.
True
False

Question No:22 **(Marks:1)** **Vu-Topper RM**
The purpose of the added ε-transitions in the NFA is to:
A. Resolve conflicts in the parsing process.
B. Recognize the symbols β before a reduction by X → β.

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

C. Push the non-terminal X onto the parse stack.
D. Identify the start state of the grammar.

Question No:23 **(Marks:1)** **Vu-Topper RM**
In the context of canonical collection of LR(1) items, if a non-terminal appears after the placeholder "·" then no further closure is possible.
True
False

Question No:24 **(Marks:1)** **Vu-Topper RM**
The canonical collection is constructed by repeatedly applying which operations?
A. Closure and shift
B. Shift and reduce
C. Reduce and goto
D. Closure and goto

Question No:25 **(Marks:1)** **Vu-Topper RM**
The augmented grammar is particularly important in which parsing algorithm?
A. Top-down parsing.
B. Recursive descent parsing.
C. LR(1) parsing.
D. LL(1) parsing.

Question No:26 **(Marks:1)** **Vu-Topper RM**
What does the GoTo table in the DFA representation table represent?
A. Transitioning to terminals
B. Accepting the input
C. Applying production rules
D. Transitioning to non-terminals

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

Question No:27 **(Marks:1)** **Vu-Topper RM**

A top-bottom parser operates by repeatedly locating handles on the frontier of the partial parse tree and performing reductions that they specify.

True

False

Question No:28 **(Marks:1)** **Vu-Topper RM**

In the context of canonical collection of LR(1) items, compute the state I0 for the grammar " S → E, E → E + (E) | int".

A. s = { [S → •E,],[E→·E+(E),] , [E → •int, $] }

B. s = { [E → •S,],[E→·E+(E),] , [E → •int, $] }

C. s = { [E → •S,],[S→·S+(S),] , [E → •int, $] }

D. s = { [S → •E,],[S→·S+(S),] , [E → •int, $] }

Question No:29 **(Marks:1)** **Vu-Topper RM**

In Shift-Reduce parsing, every legal input eventually reduces the entire frontier to grammar's goal symbol.

True

False

Question No:30 **(Marks:1)** **Vu-Topper RM**

One of the rationales behind the Closure procedure is to:

A. Handle conflicts arising from ambiguous grammar rules.

B. Optimize the performance of the parsing algorithm.

C. Determine potential reductions and expansions in the grammar.

D. Identify grammar errors in the production rules.

Question No:31 **(Marks:1)** **Vu-Topper RM**

In the handle representation <A → α, k>, what does k represent?

A. The index of the first symbol in the handle.

B. The number of non-terminal symbols in the handle.

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

C. The position of the handle within the input string.
D. The length of the handle.

Question No:32 **(Marks:1)** **Vu-Topper RM**
If [X → α • β, c] is an LR(1) item, then "c" is a/an _____.
A. Production
B. Look-ahead symbol
C. Non-terminal
D. Terminal

Question No:33 **(Marks:1)** **Vu-Topper RM**
In LR(1) parser, the Action table specifies the next state, while the GoTo table determines the particular action (i.e., shift / reduce).
True
False

Question No:34 **(Marks:1)** **Vu-Topper RM**
In the reduce action, the shift-reduce parser applies an inverse production at the right end of the _____ string.
A. Bottom
B. Top
C. Right
D. left

Question No:35 **(Marks:1)** **Vu-Topper RM**
LR parsers CAN NOT handle left-recursive grammars.
True
False

Question No:36 **(Marks:1)** **Vu-Topper RM**
In the context of LR(1) parser, the construction of _____ begins by building a model of parser's initial state.
A. Closure Procedure

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

B. Upper Frontier
C. Handle
D. Canonical Collection **Page 80**

Question No:37 **(Marks:1)** **Vu-Topper RM**
Which direction does a bottom-up parser use to build the parse tree?
A. From the root to the leaves.
B. From the right to the left.
C. From the leaves to the root.
D. From the left to the right.

Question No:38 **(Marks:1)** **Vu-Topper RM**
The identification of a handle in shift-reduce parsing is an indication that:
A. The parsing process is complete.
B. A syntax error has occurred.
C. A reduction can be performed.
D. The next token needs to be shifted.

Question No:39 **(Marks:1)** **Vu-Topper RM**
When transitioning from "A → α•Xη" to "A → αX•η" in the NFA of LR(0) items, the symbol X is a/an _____ symbol.
A. Terminal
B. Lookahead
C. Start
D. Non-terminal

Question No:40 **(Marks:1)** **Vu-Topper RM**
The pair <A → β, k> is called the handle of the _____ parse.
A. Top-Up
B. Bottom-Up **Page 73**
C. Top-Down
D. Bottom-Down

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

Question No:41 **(Marks:1)** **Vu-Topper RM**

In the context of Shift-Reduce parser, the number of complete handles is equal to the number of _____.

A. Productions

B. Terminals

C. Non-terminals

D. Symbols

Question No:42 **(Marks:1)** **Vu-Topper RM**

In the context of Shift-Reduce parser, the number of potential handles for a grammar is equal to the _____ of the lengths of the right-hand side of all the productions.

A. Multiplication

B. Sum **Page 77**

C. Division

D. Subtraction

Question No:43 **(Marks:1)** **Vu-Topper RM**

In the handle representation <A → α, k>, where A is the left-hand side non-terminal and α is the right-hand side, what does α represent?

A. The entire input string.

B. The handle itself.

C. The stack symbols of the parser.

D. The input symbols matched by the handle.

Question No:44 **(Marks:1)** **Vu-Topper RM**

The Closure procedure inserts a dot ('•') before the production γ to:

A. Track the position of the dot in the grammar rules.

B. Mark the completion of the left context.

C. Indicate the start of a reduction.

D. Identify the non-terminal symbols in the production.

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

Question No:45 **(Marks:1)** **Vu-Topper RM**

The recognition of potential handles is crucial for the parser to:

A. Determine the next state in the parsing table.

B. Decide when to perform a reduce operation.

C. Determine the previous state in the parsing table.

D. Decide when to perform a shift operation.

Question No:46 **(Marks:1)** **Vu-Topper RM**

For every LR(0) item "A → α•Xη", the ε-transitions are added for:

A. The terminal symbols in the input sequence.

B. The lookahead symbols of X.

C. The non-terminal symbols in the grammar.

D. The production rules containing X as a non-terminal.

Question No:47 **(Marks:1)** **Vu-Topper RM**

The action table in the DFA representation table is used for:

A. Transitioning to non-terminals

B. Shifting terminals

C. Accepting the input

D. Reducing using production rules

Question No:48 **(Marks:1)** **Vu-Topper RM**

In the context of LR(1) parser, each set in _____ represents a state in the eventual parser DFA.

A. Handle

B. Upper Frontier

C. Closure Procedure

D. Canonical Collection **Page 80**

Question No:49 **(Marks:1)** **Vu-Topper RM**

What would be the potential handle for the grammar "T → Ua, U → vw" at the start of Shift-Reduce parsing?

A. <T → Ua, 1>

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

B. <U → vw,1>
C. <U → wv,1>
D. <T → aU, 1>

Question No:50 (Marks:1) Vu-Topper RM
Which of the following production contains a placeholder at its end of right-hand side?
A. Expr → Expr – Term •
B. Expr → Expr – •Term
C. Expr → Expr • – Term
D. Expr → • Expr –Term

Question No:51 (Marks:1) Vu-Topper RM
In a shift-reduce parser, a placeholder is used to represent an incomplete or partial structure during the parsing process.
True
False

Question No:52 (Marks:1) Vu-Topper RM
Shift-Reduce parser uses a/an _____ to hold grammar symbols.
A. Array
B. Stack
C. Queue
D. Tree

Question No:53 (Marks:1) Vu-Topper RM
In Shift-Reduce parsing, the process of identifying and reducing handles is essential for determining the validity of a given input string according to the given grammar.
True
False

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:54 **(Marks:1)** **Vu-Topper RM**

In Shift-Reduce parser, the handle-recognizing DFA is basically represented as a 2-dimensional table, where _____ correspond to terminals and non-terminals.

A. Cells
B. Rows
C. Columns
D. Captions

Question No:55 **(Marks:1)** **Vu-Topper RM**

If X is a non-terminal symbol, the transition on symbol X in the NFA of LR(0) items corresponds to:

A. Performing a reduction based on the production rule X → γ.
B. Determining the valid lookahead symbols.
C. Applying the closure operation to the LR(0) items.
D. Shifting X from the parse stack to the input.

Question No:56 **(Marks:1)** **Vu-Topper RM**

If [X → α • β, a] is an LR(1) item, then symbol "•" (between α and β) represents a/an _____.

A. Terminal
B. Placeholder
C. Non-terminal
D. Production

Question No:57 **(Marks:1)** **Vu-Topper RM**

The LR(1) items are used as the states of a finite automaton (FA) that maintains information about the parsing stack and progress of a/an _____ parser.

A. RR(1)
B. LL(1)
C. Shift-reduce
D. Top-down

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

Question No:58 **(Marks:1)** **Vu-Topper RM**

In LR parsing, the error action indicates that the input has been successfully parsed, and the parsing process can be completed.

True

False

Question No:59 **(Marks:1)** **Vu-Topper RM**

In YACC specification file, different sections are separated by _____ symbol.

A. ##

B. %%

C. &&

D. @@

Question No:60 **(Marks:1)** **Vu-Topper RM**

In shift-reduce parsing, what does a handle represent?

A. The non-terminal symbol on the left-hand side of a production rule.

B. The terminal symbol at the top of the parser's stack.

C. The current state of the parser's stack.

D. The right-hand side of a production rule that matches a portion of the input string

Question No:61 **(Marks:1)** **Vu-Topper RM**

In LR table construction, for each non-terminal A Î G; if goto (Ii, A) = Ij , then _____.

A. Goto [i, A] ← j

B. Goto [i, G] ← i

C. Goto [i, G] ← j

D. Goto [i, A] ← i

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:62 **(Marks:1)** **Vu-Topper RM**

In attribute grammars, each symbol in the derivation has a set of values or attributes.

True

False

Question No:63 **(Marks:1)** **Vu-Topper RM**

What is the first step performed by the compiler application when using the dynamic method in attribute grammar evaluation?

A. Evaluating attributes in topological order

B. Building the dependence graph

C. Constructing the parse tree

D. Performing a topological sort

Question No:64 **(Marks:1)** **Vu-Topper RM**

Stack-machine code and three-address code are mutually exclusive and cannot be used together in modern compilers.

True

False

Question No:65 **(Marks:1)** **Vu-Topper RM**

In attribute grammars, an attribute (e.g., val) of a symbol (e.g., B) can be written as _____.

A. val@B

B. B@val

C. val.B

D. B.val

Question No:66 **(Marks:1)** **Vu-Topper RM**

What is the purpose of analyzing attribute rules in the rule-based methodology of attribute grammar evaluation?

A. To generate the parse tree

B. To determine the syntax of the source code

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

C. To optimize the attribute computation process

D. To establish a fixed ordering of attribute evaluation

Question No:67 **(Marks:1)** **Vu-Topper RM**

S --> A B

A --> ∈ | aA

B --> ∈ | bB.

FIRST(S) contains ___ elements.

A. 4

B. 5

C. 6

D. 3

Question No:68 **(Marks:1)** **Vu-Topper RM**

In syntax-directed translation, every time the parser encounters an identifier, it stores it in the _____.

A. Symbol table

B. Parsing Stack

C. Priority Queue

D. Linear Array

Question No:69 **(Marks:1)** **Vu-Topper RM**

How does the symbol table help in detecting undefined symbols?

A. By performing lexical analysis of the source code

B. By associating symbols with their memory locations

C. By identifying symbols with missing type information

D. By checking if symbols are declared before they are used

Question No:70 **(Marks:1)** **Vu-Topper RM**

In attribute grammars, a CFG is augmented with a set of _____.

A. Non-terminals

B. Rules

C. Terminals

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

D. Symbol

Question No:71 **(Marks:1)** **Vu-Topper RM**
It is mandatory to deliver efficient target code by lowering the number of instructions in a program.
True
False

Question No:72 **(Marks:1)** **Vu-Topper RM**
If find ε in FIRST(α), add production rule "A → α" to LL(1) parsing table entry M[A, b] for each _____ in FOLLOW(A).
A. Non-Terminal B
B. Terminal a
C. Terminal b
D. Non-Terminal A

Question No:73 **(Marks:1)** **Vu-Topper RM**
The main advantage of non-recursive predictive parsing is:
A. Reduced memory usage
B. Faster parsing speed
C. Simpler implementation
D. Avoidance of stack overflow errors

Question No:74 **(Marks:1)** **Vu-Topper RM**
The parsing completion criteria in non-recursive predictive parsing include:
A. Empty stack and consumed input tokens
B. Non-empty stack and remaining input tokens
C. Empty stack and remaining input tokens
D. Non-empty stack and consumed input tokens

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:75 **(Marks:1)** **Vu-Topper RM**

In the context of recursive descent parser in C++, what does the "s → nextToken() != RPAREN" condition check?

A. If the next token is an identifier or number.
B. If the next token is a left parenthesis.
C. If the next token is an arithmetic operator.
D. If the next token is not a right parenthesis.

Question No:76 **(Marks:1)** **Vu-Topper RM**

The formal definition of FIRST set is:

A. FIRST(X) = {b | X →* ba} ⊂ {ε | X →* ε}
B. FIRST(X) = {b | X →* ba} ∪ {ε | X →* ε}
C. FIRST(X) = {b | X →* ba} ∩ {ε | X →* ε}
D. FIRST(X) = {b | X →* ba} ⊃ {ε | X →* ε}

Question No:77 **(Marks:1)** **Vu-Topper RM**

In LR grammar, the L stands for _____.

A. Left most derivation
B. Left to right scan
C. Left Shift
D. Left hand side of grammar

Question No:78 **(Marks:1)** **Vu-Topper RM**

In the grammar "A → a d c b | a d b c", the _____ is a common prefix for non-terminal 'A'.

A. a d
B. b
C. d c b
D. a b c d

Question No:79 **(Marks:1)** **Vu-Topper RM**

If find ε in FIRST(α), the production rule "A → α" should be added to the LL(1) parsing table entry M[A, b] for each terminal 'b' in:

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

A. FOLLOW(B)
B. FOLLOW(A)
C. FIRST(B)
D. FIRST(A)

Question No:80 **(Marks:1)** **Vu-Topper RM**
The LL(1) parsing table is typically represented as a/an _____ array.
A. Four-dimensional
B. One-dimensional
C. Two-dimensional
D. Three-dimensional

Question No:81 **(Marks:1)** **Vu-Topper RM**
At each step, the _____ parser looks for a section of the upper frontier that matches right-hand side of some production.
A. Shift-Reduce
B. LL(1)
C. Predictive
D. Top-down

Question No:82 **(Marks:1)** **Vu-Topper RM**
For each _____, add production rule "A → α" to LL(1) parsing table entry M[A, a].
A. Terminal 'a' in FIRST(α).
B. Non-terminal 'A' in FOLLOW(α).
C. Non-terminal 'A' in FIRST(α).
D. Terminal 'a' in FOLLOW(α).

Question No:83 **(Marks:1)** **Vu-Topper RM**
What is the purpose of the FOLLOW set in LL(1) parsing?
A. To determine the first symbol of a production rule

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

B. To determine the set of terminals that can follow a non-terminal

C. To determine the last symbol of a production rule

D. To determine the set of non-terminals that can follow a terminal

Question No:84 **(Marks:1)** **Vu-Topper RM**

The construction of an LL(1) parsing table also involves computing the first and follow sets for each _____.

A. Node

B. Terminal

C. Non-terminal

D. Token

Question No:85 **(Marks:1)** **Vu-Topper RM**

If S → S a, then FOLLOW (S) = ?

A. { ε, a }

B. { $, a }

C. { $, S }

D. { ε, S }

Question No:86 **(Marks:1)** **Vu-Topper RM**

Non-recursive predictive parsing is a technique used for:

A. Optimizing the performance of recursive functions.

B. Debugging software applications.

C. Analyzing the syntax of a programming language.

D. Analyzing runtime behavior of programs.

Question No:87 **(Marks:1)** **Vu-Topper RM**

What should be added to the LL(1) parsing table entry M[A, a] during the construction process?

A. The FOLLOW set of A.

B. The FIRST set of A.

C. The non-terminal A.

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

D. The production rule A → α

Question No:88 **(Marks:1)** **Vu-Topper RM**

If E → T and T → a, then FOLLOW (T) = ?

A. { E }
B. { a }
C. { $ }
D. { T }

Question No:89 **(Marks:1)** **Vu-Topper RM**

Non-recursive predictive parsing is a type of:

A. Top-down parsing
B. Bottom-up parsing
C. Recursive descent parsing
D. Shift-reduce parsing

Question No:90 **(Marks:1)** **Vu-Topper RM**

In the context of recursive descent parser in C++, how does the isPresent() function contribute to the construction of an abstract syntax tree?

A. It checks for the presence of factors in the expression.
B. It validates the syntax of the expression.
C. It performs arithmetic operations on the parsed tokens.
D. It constructs the leaf nodes of the abstract syntax tree.

VuTopper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Visit My YouTube Channel
For Subjective and More
Important Files
Channel Name = #VuTopperRM

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365