

Question # 2 of 5 (Start time: 04:01:51 PM, 16 June 2025)

The bit manipulation operator _____ is used to set a specific bit.

Select the correct option

☐	$\wedge$
☐	$*$
☐	$\&$
☒	$ $

Question # 4 of 5 (Start time: 04:05:01 PM, 16 June 2025)

In C++, default visibility of structure is _____.

Select the correct option

☐	Private
☐	Pass
☐	Protected
☒	Public

Question # 5 of 5 (Start time: 04:05:17 PM, 16 June 2025)

The bit manipulation operator _____ is used to set a specific bit.

Select the correct option

☐	$\&$
☐	$*$
☒	$ $
☐	$\wedge$

```
using namespace std;
```

```
struct Student {  
    char name[10];  
    char grade[2];  
    int age;  
    int id;  
};
```

```
int main() {  
    Student s1;  
    cout << sizeof(s1);  
    return 0;  
}
```

Select the correct option

☐	24
☐	16
☒	20
☐	18



Type here to search



Question # 2 of 5 (Start time: 04:04:05 PM, 16 June 2025)

In C++, which operator is used while accessing through the pointer to structure?

Select the correct option

☐	-
☒	->
☐	&
☐	=

Question # 1 of 5 (Start time: 04:01:37 PM, 16 June 2025)

Functions **seekg ()** and **seekp ()** require an argument of type ____ to let them know how many bytes to move forward or backward.

Select the correct option

☐	float
☐	int
☐	double
☒	long

Question # 3 of 5 (Start time: 04:02:03 PM, 16 June 2025)

In C++, _____ function is used to write a character into a file while _____ is used to get a character from a file.

Select the correct option

☒	putc(), getc()
☐	getc(), putc()
☐	tellg(), seekg()
☐	seekg(), tellg()

Question # 5 of 5 (Start time: 04:02:40 PM, 16 June 2025)

Which of the following is a correct way to declare structure variables immediately after the structure definition?

```
struct student {  
    char name[60];  
    char address[100];  
    float GPA;  
} _____;
```

Select the correct option

☒	std1, std2
☐	struct std1, std2;
☐	student std1, std2;
☐	struct student std1, std2;

Question # 1 of 5 (Start time: 04:03:51 PM, 16 June 2025)

Which of the following is a correct way to declare structure variables immediately after the structure definition?

```
struct student {  
    char name[60];  
    char address[100];  
    float GPA;  
} _____;
```

Select the correct option

☐	struct std1, std2;
☐	struct student std1, std2;
☐	student std1, std2;
☒	std1, std2

Question # 4 of 5 (Start time: 04:02:27 PM, 16 June 2025)

In bit manipulation of binary systems, if we shift a bit towards right then it means we are _____ that binary value with '2'

Select the correct option

[Reload](#)

☐	Subtracting
☒	Dividing
☐	Adding
☐	Multiplying

[Click to Save Answer & Move](#)

Question # 3 of 5 (Start time: 04:04:23 PM, 16 June 2025)

What will be the output of the following code?

```
#include <iostream>

using namespace std;

struct Student {
    char name[10];
    char grade[2];
    int age;
    int id;
};

int main() {
    Student s1;
    cout << sizeof(s1);
    return 0;
}
```

Select the correct option

- | | |
|-----------------------|----|
| ☐ | 24 |
| ☐ | 16 |



Type here to search



35