Q.1 Choose the correct option.

A. < input type="reset" >

B. < input type="submitted" >

C. < input type="radiobutton" >

D. < input type="checked" >

Q.2 Size, width, align and no-shade are attributes of _____.

A.

B.

C. <hr>

D. <table>

Q.3 The Domain Name System (DNS) is primarily used to _____.

A. remove the need for a user to indicate a host they wish to communicate with by means of an IP address expressed in binary form.

B. determine the symbolic name of a host, given its IP address.

C. determine the MAC address of a host, given its IP address.

D. determine the IP address of a host, given its MAC address.

Q.4 Which of following is not an attribute of checkbox?

A. Value

B. Checked

C. Name

D. Select

Q.5 If first octet of an IP address is between 128 to 191 then it is a class __ IP address.

A. C

B. D

C. B

D. A

Q.6 The number of addresses in a class C block is _____ .

A. 65534

B. 16777216

C. 256

D. 128

Q.7 _____ attribute indicates the unique field name for a checkbox.

A. Input

B. Value

C. Name

D. Type

Q.8 <MARQUEE BEHAVIOR=ALTERNATE> makes the content _____.

A. Visible all the time

B. Scroll off the edge of area

C. Bounce back and forth and visible

D. Bounce back and forth and invisible

Q.9 Which HTML tag is used to define an internal (embedded) style sheet?

A. Script

B. Text / Style

C. CSS

D. Style

Q.10 In HTML, how many different types of lists are there?

A. 5

B. 3

C. 4

D. 2

VU TOOLKIT