Q.1 "/dev/null" is an example of _____ in linux system.

A. User-defined-device
B. Default-device
C. Physical-device
D. Pseudo-device

Q.2 The simplest way to delete an empty directory is _____.

A. del <DirectoryPath>
B. rmdir <DirectoryPath>
C. rmdir -r <DirectoryPath>
D. rm <DirectoryPath>

Q.3 To delete a non-empty directory following command can be used.

A. rmdir <DirectoryName>
B. rmdir -r <DirectoryName>
C. rm <DirectoryName>
D. rm -r <DirectoryName>

Q.4 The key used by a server for authenticating a client with password-less configuration of SSH is _____.

A. Private Key of Client
B. Private Key of Client
C. Public Key of Client
D. Private Key of Server

Q.5 A system administrator has found that a Ubuntu server has /selinux in its root path, What could be the reasons of the existence of above directory?

A. OS may have security risk
B. It exists because of the first boot after the installation
C. It is normal to have this directory
D. Root path may have been corrupted

Q.6 With SSH, files _____.

A. Can be exchanged with additional tool
B. Can be exchanged
C. Cannot be exchanged
D. Can be exchanged with TFTP

Q.7 Authorized keys are stored in _____.

A. /etc/ssh
B. ~/.ssh
C. /usr/keys
D. /etc/ssh/sshd_config

Q.8 The following command will _____. mkdir ~/d1 d2 d3

A. Create a directory d1 in home directory and directories d2 and d3 in current working directory
B. Create directories d1, d2 and d3 in the home directory
C. Create directories d1, d2 and d3 in current working directory
D. Fail to execute

Q.9 The linux directory /lib contains _____.

A. Data for services
B. Dependencies of programs in /etc
C. Dependencies of programs in /usr/bin
D. Dependencies of programs in /bin and /sbin
