Q.1 What does ans refer to in MATLAB?

A. A reserved keyword

B. The output of the last executed command

C. Any assigned variable

D. An answer function

Q.2 Which of the following MATLAB command clears all data and variables stored in memory?

A. clear

B. clc

C. delete

D. None of these

Q.3 In MATLAB, : operator in a vector creation, such as 2:5, indicates:

A. A range from 2 to 5

B. A loop

C. A multiplication factor

D. None of these

Q.4 Which operator is used to check if two elements are equal in MATLAB?

A. !=

B. Isequal

C. ==

D. =

Q.5 The output of the code syms x y ; (x-y)*(x-y)^2 in MATLAB is _____.

A. (x-y)^3

B. (x-y)^2

C. (x-y)*(x-y)*(x-y)

D. X^3-3*x^2*y+3*x*y^2-y^3

Q.6 Which of the following will be the output of the command a = [1 0 2]; b = [3 0 7]; c=a*b

A. [4 0 9]

B. this command will give the error message

C. None of these

D. [3 0 14]

Q.7 MATLAB stands for _____.

A. Multiplication, Addition, Table, Linear Algebra, Basis

B. Matrix Laboratory

C. Matrix Linear Algebra

D. Master Laboratory

Q.8 What does a line starting with % signify in a script file?

A. A function

B. An error

C. A command

D. A comment

Q.9 What is the function of format long in MATLAB?

A. Rounds off numbers

B. Formats text output

C. Displays results to 15 decimal places

D. Clears the Workspace

Q.10 How can you extract the third entry from a vector Y?

A. get(Y,3)

B. extract(Y,3)

C. Y(3)

D. Y{3}

VU TOOLKIT