Q.1 If we use [P, D] = eig(B), P determines _____ and D determines _____.

A. eigen vectors, eigen values

B. eigen values, eigen vectors

C. square matrix, rectangular matrix

D. rectangular matrix, square matrix

Q.2 To solve the system of equations 2x+3y=4, 3x-4y=8, we will write _____ into MATLAB.

A. rref([2 3 4; 3 -4 8])

B. A=[2 3; 3 -4]; b=[4; 8]; Ab=[A b]; rref(Ab)

C. b=[4; 8]; Ab=[[2 3; 3 -4] b]; rref(Ab)

D. All of these

Q.3 The _____ command calculates the eigen value of a _____ matrix.

A. value, rectangular

B. eig, square

C. eig, rectangular

D. eigen, square

Q.4 What MATLAB function is used to find the inverse of a matrix?

A. eye()

B. eig()

C. inv()

D. inverse()

Q.5 _____ command calculates the eigen value of the square matrix M.

A. sym(M)

B. eig(M)

C. inv(M)

D. none of these

Q.6 What MATLAB function is used to find the determinant of a matrix?

A. determinant()

B. trace()

C. det()

D. rank()

Q.7 _____ command calculates the inverse of the matrix A.

A. sym(A)

B. inv(A)

C. eig(A)

D. none of these

Q.8 To calculate the reduced echelon form of a matrix E=[0 1 3 4; 2 4 1 5; 6 1 8 6], we will write _____ in MATLAB.

A. eig(E)

B. rref(E)

C. eig

D. rref

Q.9 To enter system of equations 2x+3y=4, 3x-4y=8 into MATLAB as an (augmented) matrix we will write _____ .

A. A=[2 3; 3 -4]; b=[4; 8]; Ab=[A b]

B. b=[4; 8]; Ab=[[2 3; 3 -4] b]

C. Ab=[2 3 4; 3 -4 8]

D. All of these

Q.10 Using MATLAB, solution of system of linear equations is obtained by _____ command .

A. solve

B. sym

C. eig

D. inv
