

Question # 10 of 10 (**Start time: 04:06:38 PM, 23 June 2025**)

Which is not a preprocessor directive of C-language?

Select the correct option

☒	#startif
☐	#if
☐	#else
☐	#endif

Question # 9 of 10 (Start time: 04:06:24 PM, 23 June 2025)

In C++, which of the following option is used to declare a class?

Select the correct option

☐	CLASS
☐	cLASS
☒	class
☐	Class

Question # 3 of 10 (Start time: 04:04:49 PM, 23 June 2025)

What will be the output of the following code?

```
int num = 2;  
int count=0;  
while(num!= 0)  
{  
    if ( num & 01)  
        count ++;  
    num >>=1;  
}  
  
cout<< count;  
return 0;
```

Select the correct option

☐	2
☒	1
☐	3
☐	4

Question # 8 of 10 (Start time: 04:06:09 PM, 23 June 2025)

The statement `char arr [10];` is an example of a type of _____ memory allocation.

Select the correct option

☒	Static
☐	Built-in
☐	Dynamic
☐	Null Value

Question # 2 of 10 (Start time: 04:04:34 PM, 23 June 2025)

Which function is automatically called in C++ if we do not define it in a class?

Select the correct option

☐	Inline function
☐	Parametrized Constructor
☒	Default Constructor
☐	Default and Parametrized Constructor

Question # 7 of 10 (Start time: 04:05:55 PM, 23 June 2025)

In C++, the name of the _____ is the same as that of a class with a preceding tilde (~) sign.

Select the correct option

☒	Destructor
☐	Utility function
☐	Constructor
☐	Friend function

Question # 4 of 10 (Start time: 04:05:04 PM, 23 June 2025)

In C++, _____ function is used to write a character into a file while _____ is used to get a character from a file.

Select the correct option

☒	putc(), getc()
☐	tellg(), seekg()
☐	seekg(), tellg()
☐	getc(), putc()

Question # 1 of 10 (Start time: 04:03:55 PM, 23 June 2025)

Which of the following is a correct example of function overloading in C++?

Select the correct option

☒	<code>int sqrt(int i); double sqrt(double i);</code>
☐	<code>int sqrt(int i); double sqrt(int i);</code>
☐	<code>double sqrt(int i); float sqrt(int i);</code>
☐	<code>int sqrt(int i); int sqrt(double i);</code>

Question # 6 of 10 (Start time: 04:05:37 PM, 23 June 2025)

Total Marks: 1

Functions `seekg()` and `seekp()` require an argument of type `_____` to let them know how many bytes to move forward or backward.

Select the correct option

 Reload Math Equations

☐	<code>int</code>
☐	<code>double</code>
☐	<code>float</code>
☒	<code>long</code>

Click to Save Answer & Move to Next Question

Question # 5 of 10 (Start time: 04:05:20 PM, 23 June 2025)

Total Marks: 1

In C++, which of the following function causes the full definition of the function to be inserted in each place when it gets called?

Select the correct option

 Reload Math Equations

- | | |
|----------------------------------|--------------------|
| ☒ | Inline function |
| ☐ | Library function |
| ☐ | Built-in function |
| ☐ | Recursive function |

Click to Save Answer & Move to Next Question