Question: 1 (Marks: 1) Attempted Questions: 0 Total Questions: 50

_____ generates readable code which is easy to maintain.

CS508 - Modern Programming Langauges Final
By BLACK VIGO



Beware Coming to Pick you up at anytime!

Choices:

- Clauses
- Backtracking
- Inference mechanism
- Facts

Question: 3 (Marks: 1) Attempted Questions: 2 Total Questions: 50

Which of the following is used in LISP to forbid the evaluation of a symbol?

Choices:

- Space
- Quote
- Hyphen
- Double quote

Question: 4 (Marks: 1) Attempted Questions: 5 Total Questions: 50

float* a, b;

In context of C#, the above given statement is equivalent to which set of statements?

Choices:

- float a; float *b;
- float a; float b;
- float * a; float b;
- float * a; float * b;

Question: 10 (Marks: 1) Attempted Questions: 9 Total Questions: 50

In Prolog, a "member(X, T)" predicate is used to check the membership of X in _____.

Choices:

- Symbol
- Class
- List
- Stack

Question: 16 (Marks: 1) Attempted Questions: 16 Total Questions: 50

The concept of package in Java is similar to _____.

Choices:

- Global Class in C++
- Assembly in C# (selected)
- Global class in C#
- Assembly in C++

Question: 20 (Marks: 1) Attempted Questions: 20 Total Questions: 50

COBOL uses _____ to show nested records.

Choices:

- Level numbers
- Recursive definitions
- Pointers
- Arrays

Question: 23 (Marks: 1) Attempted Questions: 23 Total Questions: 50

In LISP, there is no concept of _____ .

Choices:

- Functions
- Sequential statements
- Strings
- Symbols

Question: 31 (Marks: 1) Attempted Questions: 31 Total Questions: 50

Which of the following programming language allows functions to be defined inside functions?

Choices:

C#

C

JAVA

PHP

Question: 33 (Marks: 1) Attempted Questions: 33 Total Questions: 50

The resultant value of variable 'x' in JavaScript statement `var x = "5" - "2";` will be_____.

Choices:

- 5-2
- 52
- "5"-"2"
- 3

Question: 35 (Marks: 1) Attempted Questions: 34 Total Questions: 50

In Ada language, all pointers are initialized to _____.

Choices:

- Garbage value
- One
- Null
- Zero

Question: 36 (Marks: 1) Attempted Questions: 35 Total Questions: 50

Which of the following special word in used in Modula-2 as a closing word for all control structures?

Choices:

- END
- CLOSE
- THEN
- ENDIF

Question: 37 (Marks: 1) Attempted Questions: 37 Total Questions: 50

In which of the following programming language, type checking of parameters is not required?

Choices:

- Java
- Ada
- Pascal
- FORTRAN 77

Question: 38 (Marks: 1) Attempted Questions: 38 Total Questions: 50

All variables in SNOBOL are _____.

Choices:

Explicit Heap Dynamic variables

Implicit Heap Dynamic variables

Stack Dynamic variables

Static variables

Question: 39 (Marks: 1) Attempted Questions: 40 Total Questions: 50

Which of the following statement is true if variable **$a** is not identical to variable **$b** in PHP?

Choices:

- $a !== $b
- $a != $b
- $a =! $b
- $a ==! $b

Question: 40 (Marks: 1) Attempted Questions: 40 Total Questions: 50

A/an _____is a special word that cannot be used as a user defined name.

Choices:

- Dynamic word
- Reserved word
- Flag word
- Dummy word

Question: 41 (Marks: 3) Attempted Questions: 41 Total Questions: 50

Convert the followings into Prolog rules,

1. Socrates is a mortal if he is human
2. X is an animal if X eats grass
3. X is a sportsperson if X plays football

Answer:

Question: 42 (Marks: 3) Attempted Questions: 41 Total Questions: 50

Name any three browser objects in JavaScript.

Answer:

Question: 41 (Marks: 3) Attempted Questions: 41 Total Questions: 50

Convert the followings into Prolog rules,

1. Socrates is a mortal if he is human
2. X is an animal if X eats grass
3. X is a sportsperson if X plays football

Answer:

Question: 43 (Marks: 3) Attempted Questions: 41 Total Questions: 50

Write the name of function in LISP that returns the difference of the two lists. Now, use this function to return the difference of two lists L3 and L4.

Answer:

Question: 44 (Marks: 3) Attempted Questions: 44 Total Questions: 50

List down at least three design issues of user-located loop control mechanisms.

Answer:

Question: 47 (Marks: 5) Attempted Questions: 45 Total Questions: 50

Can a dangling reference be created in Java? Justify your answer with reasons.

Answer:

Question: 50 (Marks: 5) Attempted Questions: 47 Total Questions: 50

Just like all programming languages, PHP also supports user-defined functions. A function is a block of statements that can be used repeatedly in a program.

Write a simple function in PHP that displays "Programming is Fun" on screen. Name of function should be **DisplayMsg**. This function does not accept any arguments. After definition, call this function to show the output.

Answer:

Question: 48 (Marks: 5) Attempted Questions: 47 Total Questions: 50

Prolog has several syntactic elements, ten (10) of them are as follows;

nl, cut, write, not, +, -, <, <=, readint(var), readchar(var)

You are required to categorized them according to the type as shown in the table given below.

Answer:

below.

Special Predicates	Predefined Predicates	Arithmetic Operators	Relational Operators

Answer:

Question: 50 (Marks: 5) Attempted Questions: 49 Total Questions: 50

Just like all programming languages, PHP also supports user-defined functions. A function is a block of statements that can be used repeatedly in a program.

Write a simple function in PHP that displays "Programming is Fun" on screen. Name of function should be **DisplayMsg**. This function does not accept any arguments. After definition, call this function to show the output.

Answer:

Question: 45 (Marks: 3) Attempted Questions: 50 Total Questions: 50

```
public class Test {
    // write your code here…
}
```

Answer:

Question: 45 (Marks: 3) Attempted Questions: 50 Total Questions: 50

Suppose, there is a class named "**ThreadExample**" in a typical Java program, which implements **runnable** interface to create a thread. You are required to write a simple program to start a thread by creating an object of **ThreadExample** class.

Note: You are required to write Java code for main method, to create an object of ThreadExample class and a statement to start thread.

```
public class Test {
```

Answer:

Question: 44 (Marks: 3) Attempted Questions: 50 Total Questions: 50

List down at least three design issues of user-located loop control mechanisms.

Answer:

Question: 1 (Marks: 1) Attempted Questions: 50 Total Questions: 50

_____ generates readable code which is easy to maintain.

.....

Choices:

- (•) Clauses
- ( ) Backtracking
- ( ) Inference mechanism
- ( ) Facts

Question: 2 (Marks: 1) Attempted Questions: 50 Total Questions: 50

The _____model in JavaScript provides access to the contents of the browser window.

Choices:

- DOM
- BOM
- ROM
- COM

Question: 4 (Marks: 1) Attempted Questions: 50 Total Questions: 50

float* a, b;

In context of C#, the above given statement is equivalent to which set of statements?

Choices:

- float a; float *b;
- float a; float b;
- float * a; float b;
- float * a; float * b;

Modern Programming Languages (CS508)

Question: 5 (Marks: 1) Attempted Questions: 50 Total Questions: 50

"with" statement in JavaScript is an alternative of _____.

Choices:

- While statement
- Union statement
- Single document.write statement
- Multiple document.write statements

Question: 6 (Marks: 1) Attempted Questions: 50 Total Questions: 50

In a PROLOG program, the definitions of predicate sentences or phrases are known as:

Choices:

- Declarations
- Clauses
- Facts
- Inferences

Question: 7 (Marks: 1) Attempted Questions: 50 Total Questions: 50

The variables in PROLOG are actually:

Choices:

- Structures
- Objects
- Constant Placeholders
- Reserved Words

Question: 8 (Marks: 1) Attempted Questions: 50 Total Questions: 50

Each class in a Java program can have:

Choices:

- Only one constructor function
- Many constructor functions
- Maximum two constructor functions
- Five constructor functions

Question: 9 (Marks: 1) Attempted Questions: 50 Total Questions: 50

Restricted use of pointers is permitted in C# within the code marked as:

Choices:

- safe
- unsafe
- static
- void

Question: 10 (Marks: 1) Attempted Questions: 50 Total Questions: 50

In Prolog, a "member(X, T)" predicate is used to check the membership of X in _____.

Choices:

- Symbol
- Class
- List
- Stack

Modern Programming Languages (CS508)

Question: 11 (Marks: 1) Attempted Questions: 50 Total Questions: 50

Each source file in _____ has a public class.

Choices:

- C++
- C#
- Java
- Prolog

Question: 12 (Marks: 1) Attempted Questions: 50 Total Questions: 50

There is no concept of global variable and function in _____ .

Choices:

- Java
- C++
- ADA
- Lisp

Question: 13 (Marks: 1) Attempted Questions: 50 Total Questions: 50

Each Thread in Java has its own set of _____and _____.

Choices:

- Code , Data
- Register , Code
- Stack , Register
- Stack , Data

Question: 14 (Marks: 1) Attempted Questions: 50 Total Questions: 50

In PHP 'switch' structure, the _____ starts or implements an implicit loop.

Choices:

- Break statement
- For loop
- Continue statement
- Return statement

Question: 17 (Marks: 1) Attempted Questions: 50 Total Questions: 50

Delegates in C# are used for_____.

Choices:

- Web Application
- Event Driven Application
- Parallel Programming
- Multi Threading

Question: 18 (Marks: 1) Attempted Questions: 50 Total Questions: 50

PHP syntax looks like _____.

Choices:

- ASP syntax
- VB Script syntax
- C/C++ syntax
- Snobol

Question: 19 (Marks: 1) Attempted Questions: 50 Total Questions: 50

C++ and Java does not support _____ data type.

Choices:

- Int
- Float
- Decimal
- Char

Question: 20 (Marks: 1) Attempted Questions: 50 Total Questions: 50

COBOL uses _____ to show nested records.

Choices:

- Level numbers
- Recursive definitions
- Pointers
- Arrays

Question: 21 (Marks: 1) Attempted Questions: 50 Total Questions: 50

_____ has a pre-test version, but no post-test version of logically controlled loop.

Choices:

- Java
- C++
- C
- Ada

Question: 22 (Marks: 1) Attempted Questions: 50 Total Questions: 50

ALGOL 60 and most of its descendants use the _____ for parameter passing.

Choices:

- Run-time Stack
- ROM
- Secondary Memory
- Heap

Question: 23 (Marks: 1) Attempted Questions: 50 Total Questions: 50

In LISP, there is no concept of _____ .

Choices:

- Functions
- Sequential statements
- Strings
- Symbols

Question: 28 (Marks: 1) Attempted Questions: 50 Total Questions: 50

The size of integers in PHP is _____ .

Choices:

- Fixed on all operating systems
- Assigned by programmer
- Platform dependent
- 128 bits

Question: 29 (Marks: 1) Attempted Questions: 50 Total Questions: 50

In C#, the value type and reference type variables are interconvertible through _____ concept.

Choices:

- Tagged type
- Boxing
- Interfaces
- Indexing

Question: 31 (Marks: 1) Attempted Questions: 50 Total Questions: 50

Which of the following programming language allows functions to be defined inside functions?

Choices:

- C#
- C
- JAVA
- PHP

Question: 32 (Marks: 1) Attempted Questions: 50 Total Questions: 50

In JavaScript, _____operator is used for concatenation.

Choices:

- Dot (.)
- Plus (+)
- Vertical bar (|)
- Exponent (^)

Question: 33 (Marks: 1) Attempted Questions: 50 Total Questions: 50

The resultant value of variable 'x' in JavaScript statement `var x = "5" - "2";` will be_____.

Choices:

- 5-2
- 52
- "5"-"2"
- 3

Question: 34 (Marks: 1) Attempted Questions: 50 Total Questions: 50

In the context of programming language, if type-binding is dynamic then _____must be dynamic.

Choices:

- Type matching
- Type checking
- Type security
- Type sequence

Question: 36 (Marks: 1) Attempted Questions: 50 Total Questions: 50

Which of the following special word in used in Modula-2 as a closing word for all control structures?

Choices:

- END
- CLOSE
- THEN
- ENDIF

Question: 38 (Marks: 1) Attempted Questions: 50 Total Questions: 50

All variables in SNOBOL are _____.

Choices:

- Explicit Heap Dynamic variables
- Implicit Heap Dynamic variables
- Stack Dynamic variables
- Static variables

Question: 40 (Marks: 1) Attempted Questions: 50 Total Questions: 50

A/an _____is a special word that cannot be used as a user defined name.

Choices:

- Dynamic word
- Reserved word
- Flag word
- Dummy word