CS411-Visual Programming

Solved MCQS for MID terms papers

Current MCQs and Subjective

Solved by JUNAID MALIK and Team



AL-Junaid Institude

Contact no: 03041659294

VU LMS HELP vulmshelp.com

LMS Handling

Subject Enrollment

1) Online classes available
HTML, CSS, Javascript
Phyton..etc
2) Solved Graded Activities
- Assignment's
- Quizze's
- GDB's

3) Sloved Quiz File's
4) Short Note's
5) Past paper's &
Current paper's

Final project CS619

1) SRS
(Software Requirement's Specification)
2) DD
(Design Document)
3) Test phase + viva
4) Viva preparation
5) Final Deliverable

Website Link
vulmshelp.com

Gmail
junaidfazal08@gmail.com

AL-JUNAID INSTITUTE OF GRPUP

Current MCQS CS411 (10 to 16 Date 2022)

1. Every _____ is represented by an event-object.

- Information
- Entity
- Object
- Event page10

2. Which statement is True about interfaces?

- An interface can contain only methods, variables, events, and indexers.
- An interface can contain only variables, properties, events, and indexers.
- An interface can contain only methods, properties, variables, and indexers.
- An interface can contain only methods, properties, events, and indexers. Page 40

3. Which one is the correct syntax for declaring attribute?

- [Obsolete] page 48
- {Obsolete}
- (Obsolete)
- *Obsolete

4. An "object" element can have ___ type/s of children.

- Four
- Three Page 73
- Two
- One

5_____ allows to keep the user interface description and implementation separate.

- GDI

For More Visit: vulmshelp.com

- ❖ WPF (Page#61)
- ❖ Avalon
- ❖ Altia

6. There is/are ___ type(s) of padding in WPF element.

- ❖ One
- ❖ Two
- ❖ Three page 91
- ❖ Four

7. Which of the following is not a feature of "C#"?

- ❖ Operator overloading is not allowed. Page 17
- ❖ Multiple Inheritances is not supported but interfaces are supported.
- ❖ Enumeration members are scoped.
- ❖ Global variables or functions are not allowed.

8. Stylus can behave like a ____ but has _____resolution.

- ❖ Keyboard, lower
- ❖ Mouse, lower
- ❖ Mouse, higher page 122
- ❖ Keyboard, higher

9. Attributes are declared ____ the class/function.

- ❖ Within
- ❖ After
- ❖ Above
- ❖ Outside

10. If we want that "Stretch" property of child element takes the available "height or

width of parent" and shape of child element doesn't change, then we should write

- ❖ "Stretch = ____".

For More Visit: vulmshelp.com

- Fill page 109
- UniformToFill
- Uniform

11.The code given below is equivalent to ___.

- <SolidColorBrush>White</SolidColorBrush>
- <WhiteBrush >MyWhiteBrush </ WhiteBrush>
- <SolidColorBrush Color="White"/> (Page#65)
- <Brush Style= “SolidWhite”>

12.Visual Studio has a snippet called ____ that automatically expands into a definition of a

dependency property, which makes defining one much faster than doing all the typing yourself!

- Propdp (Page#77)
- Property extension
- Dpprop
- Dependency property

13.Multiple ____ are conventionally stored in multiple files.

- Functions
- Values
- Variables
- Classes (Page#22)

14. "Situation" is an event occurrence that requires a (n) ____.

- Reaction page 10
- Class
- Object
- Action

15. We have two buttons "b1" and "b2". If we want to place "b1" on "b2" then value of

For More Visit: vulmshelp.com

- "ZIndex" of "b1" should be __ the value of "ZIndex" of "b2".
- Less than
- Greater than
- Equal to
- No need to give value of ZIndex of b1 page99

16. Events can be _____.

- Specialized
- Composed
- Generalized
- All of the given options page 15

17. Wpf 3.5 released in

- 2005
- 2006
- 2008 Page No 61 In AUGUST
- 2009

18.The corresponding type converter class for “Brush” class will be ___.

- BrushConverter
- CastBrush
- BrushCast
- None of the given options

19.Extension methods _____ access the private data members of the class in which they are extended.

- may
- **cannot**
- may not
- can

20. Which "transform" property can help us to flip the element from its center?

- ScaleY

More Visit: vulmshelp.com

- None of given options
- ScaleX
- RenderTransformOrigin page 126

21. CLI stands for _____.

- Compact Language Infrastructure
- Common Language Infrastructure page18
- Console Language Infrastructure
- Control Language Infrastructure

22. The elements in a/an ___ are always stored in a contiguous block of memory.

- Tree
- Array
- Variable
- Struct

23. The ____ statement iterates over each element in an "enumerable" object.

- Foreach page 191
- Dowhile
- While
- For

24. We are checking that whether an element is eligible for focus or not, which property

will help us in this testing?

- Focus
- IsFocus
- IsFocusable
- Focusable page 121

25. Directory is the class of _____.

- System.Collections.Generic

For More Visit. vulmshelp.com

- ❖ System.Reflection
- ❖ System.Text
- ❖ System.IO MPOV and GOOGLE

25. WCF stands for
- ❖ Windows Communication Foundation
- ❖ Windows Class Foundation
- ❖ Windows Classic Foundation
- ❖ None

26. C# is a ___ and .NET is a ___.
- ❖ Platform, Language
- ❖ Package, Language
- ❖ Language, Package
- ❖ Language, Platform

27. The ___, ___ and ___ of applications that use events, either directly or indirectly is called event-based programming.
- ❖ Model, Code, Operation
- ❖ Analyze, Design, Operation
- ❖ Code, Operation, Maintain
- ❖ Design, Coding, Operation

28. Suppose we want to restrict the user to don't decrease the height of a WPF element from a specific amount, then which property will be used?
- ❖ MinHeight
- ❖ None
- ❖ HeightMinimum
- ❖ MinimumHeight

29. Types not defined in any namespace are said to reside in the ___ namespace.
- ❖ Local
- ❖ Static
- ❖ Virtual
- ❖ Global

30. Overloaded operators must be ___
- ❖ Referenced
- ❖ Static

- Objective
- Delegates

31. If we want to scale an object in the 2-D x-y coordinate system then which transform class will be used?

- Rotate Transform
- Matrix Transform
- Translate Transform
- Skew Transform

32. Polymorphism works on the basis that child class should have ___ feature/s of its parent class.

- Only one
- No
- Few
- All

33.The root object element in XAML must specify at least _____ XML namespace that is usedto qualify itself and any child elements.

- **one(Page#63)**
- two
- three
- five

34. In event-driven architecture (EDA), _____ sends event to _____.

- Event Consumer, Event Producer
- **Event Producer, Event Consumer(Page#10)**
- Event Handler, Event Producer
- Event Generator, Event Producer

35. Auto-implemented properties do not allow simplified syntax.

- True
- **False(Page#30)**

36.Clean room design is useful as a defense against _____.

- Copyright
- Trade secret infringement
- **Copyright and trade secret infringement(Page#13)**
- None of the given options

37._____ is an occurrence within a particular system or domain.

- Function
- **Event (Page#7)**
- Information
- Transaction

38.BAML stands for:

- binary application map language
- binary application markup linkage
- **binary application markup language(Page#69)**
- binary application map linkage

39. If we want to place a component at top in "dockpanel" then which one is correct syntax?

- PanelDock="Top"
- Dock="Top"
- **DockPanel.Dock="Top"(Page#93)**
- DockPanel="Top

40. Dock panel allows easy docking of elements to an entire side.

- **True(Page#91)**
- False

41. _____ processing operations include reading, creating, transforming, and deleting events.

- Observed Events
- **Common event(Page#8)**
- Deducted Events
- Probabilistic Events

42.The _____ in the namespace indicate a hierarchy of nested namespaces.

- Arrows
- Dots
- Semicolon
- **Brackets(Page#22)**

43. The interface forces each component to expose specific _____ members that will be used ina certain way.

- **Public(Page#35)**
- Private
- Both of above

For More visit: vulmshelp.com

- None of the given

44.Static ctor exists to initialize class static members and called only ___.

- **Once(Page#23)**
- Twice
- Anytime
- All of the given

45. Interfaces define a contract.

- **True(Page#35)**
- False

46. Additional XML namespaces (on the root or on children) must be _____ to be used on anyidentifiers from that namespace.

- Given a common prefix
- Qualified with "Pre" keyword
- **Given a distinct prefix(Page#63)**
- Qualified with "Ext" keyword

47. We want the width of button should cover the whole width of StackPanel in WPF then whatshould be value of HorizontalAlignment property of button?

- Parent
- Whole
- Fill
- **Stretch(Page#97)**

48. _____ decouple producers and consumers.

- Requests
- **Events(Page#10)**
- Functions
- All of these

49. To declare an anonymous method, you just use keyword "_____".

- handler
- event
- **delegate (Page#47)**

- none of the given

50. A (n) _____is a subscription mechanism for events.

- Raw Event
- Event Stream
- **Event Channel (Page#10)**
- Event Producer

51. "Situation" is an event occurrence that requires a (n) _____.

- Class
- Object
- **Reaction**
- Action

52. XML is a stricter version of _____.

- CSS
- C#
- Java
- **HTML**

53._____ contacts the service provider or the server.

- Event-driven
- **Service Requester (Page#10)**
- Both of the above
- None of the given options

54.Any class, including the same class that the event is declared in, may register one of its methods with the _____.

- **Event (Page 39)**
- Delegate
- Function
- Class

55.There are _____ methods to read XML document.

- **Two (1.xmldocument 2.xmlreader) Page#47**

- Three
- Four
- Five

56.releasing resources or doing some other type of cleanup.

- Functions
- **Exception (Page#41)**
- Abstraction
- All of these

57._____ are called by garbage collector.

- Constructors
- **Destructors (Page#23)**
- Both of above
- None of the given

58. Attributes are generally applied _____ in front of type and type member declarations.

- Logically
- **Physically (Page#42)**
- Both of above
- None of given

59.Multiple _____ are conventionally stored in multiple files.

- **Classes (Page#22)**
- Values
- Variables
- Functions

60.The _____, _____ and _____of applications that use events, either directly or indirectly is called event-based programming.

- Model, Code, Operation

- Analyze, Design, Operation
- **Design, Coding, Operation (Page#8)**
- Code, Operation, Maintain

61. C# is a _____ and .NET is a _____.

- Platform, Language
- **Language, platform (Page#13)**
- Package, Language
- Language, Package

62. Windows Presentation Foundations (WPF) was publicly announced in _____.

- 2000
- 2001
- 2002
- **2003 (Page#61)**

63. WPF stands for:

- Windows Powerful Foundations
- Windows Presentation Formations
- Windows Presentation Functions
- **Windows Presentation Foundations (Page#61)**

64.Value-types hold their value in _____ where they are declared.

- Variable
- **Memory (Page#33)**
- Object
- Reference

65.Indexers can take any number of _____.

- Arrays
- Variables
- **Parameters (Page#31)**

- All of these

66. Attributes add declarative_____ to your programs.

- Clearance
- **information (Page#41)**
- Meta Data
- Ambiguity

67.Cast back to base type to call a/an _____ method of base.

- Instance
- Base Class
- **Overridden (Page#24)**
- Derived Class

68._____ is said to be stateless if the way it processes one event does not influence the way it processes any subsequent events.

- Event Producer
- Raw Event
- **Event Processing (Page#11)**
- Event Stream

69._____ is built from request-response and it moves away from monolithic applications.

- Event-driven architecture (EDA)
- **Service-oriented architecture (SOA)(Page#10)**
- Both of above
- None of the given option

70.Object variables are references to the _____ object not the object themselves.

- **Original (Page#20)**
- Alternative
- Primary

- None of the given

71.An indexer enables your class to be treated like a/an _____.

- Class
- Function
- **Array (Page#30)**
- Pointer

72. Polymorphism needs the signatures to be the _____.

- Different
- **Same (Page#25)**
- Alternative
- None of the given

73.Types of class members in C# are _____ and _____.

- static, instance
- **instance, static (Page#22)**
- public, private
- static, private

74. Events may live _____ events like in event logs.

- Inside
- **Outside (Page#10)**
- Both of above
- None of the given

75. Additional XML namespaces (on the root or on children) must be _____ to be used on any identifiers from that namespace.

- Given a common prefix
- Qualified with “Pre” keyword
- **Given a distinct prefix (Page#63)**
- Qualified with “Ext” keyword

76. The interface forces each component to expose specific _____ members that will be used in a certain way.

- **Public (Page#35)**
- Private
- Both of above
- None of the given

77._____ allows to keep the user interface description and implementation separate.

- GDI
- **WPF (Page#61)**
- Avalon
- Altia

79. Dependency properties are represented by _____.

- **System.Windows.DependencyProperty (Page#75)**
- System.Windows.Dependency.Property
- System.Windows.Dependency
- System.Windows.Property.Dependency

80. Suppose we want to restrict the user to don‟t decrease the height of a WPF element from a specific amount then which property will be used?

- HeightMinimum
- MinimumHeight
- **MinHeight**
- None of the given

81. If we want to scale an object in the 2-D x-y coordinate system then which transform class will be used?

- Rotate Transform
- Matrix Transform
- **Translate Transform**
- Skew Transform

82. Which of the following is/are not derived from “Control” class?

- ListBox
- StatusBar
- Button
- **None of the given**

83. Wait for a single event is _____operation.

- Waiting
- Waste
- **Blocking (Page#8)**
- Idle

84. **_____ method reads the whole document in memory.**

- XPath
- **XmlDocument (Page#49)**
- XmlReader
- XmlLine

85.Which of the following events may or may not relate to an actual occurrence?

- **Probabilistic Events (Page#7)**
- Actual Events
- Real Events
- Expected Events

86. The System.Console is a _____ which enables us to do Console Input and Output.

- Structure
- **Class**
- Namespace
- Library

88. Clean room design is useful as a defense against _____.

- Copyright
- Trade secret infringement
- **Copyright and trade secret infringement (Page#13)**

- None of the given options

89. Clean room design is also called_____.

- Clear Room Design
- Wall Technique Design
- **Chinese Wall Technique (Page#13)**
- French Wall Technique

90.Which of the following is an occurrence within a particular system or domain?

- Object
- **Event (Page#7)**
- Result
- Message

91.During the program execution, program can be stopped with the help of _____.

- Attributes
- Compiler
- **Breakpoints (Page#48)**
- Exception Handling

92.Which of the following does NOT include in event processing operations?

- Deleting Events
- Reading Events
- **Terminating Events (Page#8)**
- Transforming Events

93.The result of Exception can bring _____ in the program.

- Reliability
- Stability
- **Inconsistency**
- Consistency

95.Graphical user interfaces and the event-driven model is not applied on which of the following?

- Web Application

- **Console Application (Page#4)**
- Mobile Application
- Desktop Application

96.Events are based on the principle of _____.

- Request
- Response
- Coupling
- **Decoupling (Page#10)**

97._____methods do not have names.

- Attribute
- Non-Anonymous
- **Anonymous (Page#47)**
- None of give

98.Which of the following is an entity that introduces event into the system?

- Event Channel
- **Event Producer (Page#11)**
- Event Stream
- Event Consumer

99.Anonymous methods _____ the code size.

- Double
- Expand
- **Reduce (Page#47)**
- Extend

100._____ events may or may not relate to an actual occurrence

- Layer
- Properties
- Event properties
- **Probabilistic (Page#7)**

101.Task Parallel _____exploit multicore for real parallel tasks.

- Structure
- **Library (Page#175)**

- Class
- Namespace

102.The Main method returns a non-zero value which indicates the_____.

- Source of Program
- **Error in Program**
- Termination of Program
- Exception in Program

103. WPF4 was released in _____.

- 2012
- **2010 (Page#61)**
- 2005
- 2003

104.Extension methods can only be defined in _____ class.

- **Static class**
- Dynamic class
- Normal class
- String class

105.BAML is compressed representation of _____.

- CAML:NS
- **XAML (Page#69)**
- XAML:NS
- CAML

106._____ processing operations include reading, creating, transforming,

- **and deleting events.**
- Observed Events
- **Common event (Page#8)**
- Deducted Events
- Probabilistic Events

107.Static ctor exists to initialize class static members and called only _____.

- **Once (Page#23)**
- Twice
- Anytime
- All of the given

108._____ in the namespace indicate a hierarchy of nested namespaces.

- Arrows
- **Dots**
- Semicolon
- Brackets

109._____ Interact with web page layout.

- Java script
- **HTML**
- XML
- DOM

110._____ supports the creation of applications that run directly in a web browser.

- C#
- **WPF**
- HTML
- C/C++

111.Which one of the following panels is most powerful, versatile and customizable?

- Doc panel
- Stack panel
- **Grid Panel (Page#92)**
- Canvas panel

112. With the help of WPF, an ugly looking application can be _____ by the designers.

- Rearranged
- Re-created
- Rejected

- **Re-themed (Page#61)**

113.Graphical user interfaces and the event-driven model are not applied on which of the following?

- Web Applications
- Mobile applications
- Desktop Applications
- **Console Applications (Page#4)**

114.C# is most often used with some implementation of the _____.

- Compact Language Interface
- **Common Language Infrastructure (Page#14)**
- Control Language Infrastructure
- Control Language Interface

115.In C#, comments are written using _____.

- # and */ /*
- **// and /* */**
- # and /*
- // and */ /*

116. XML document is readable by _____.

- Human only
- Machine only
- No one
- **Machine and Human both (Page#48)**

117."Console" is a/an _____ class in the "System" namespace.

- Input
- Dynamic
- **Static (Page#15)**
- Virtual

118.The only _____ .Net language has an intrinsic understanding of dependency Properties.

- Vb.net

- **Xaml (Page#74)**
- C#
- J#

119.Which of the following grabs the "OK" button by only knowing its name?

- Button okButton = (Button)window.GetName("okButton")
- Button okButton = (Button)window.getElementByName("okButton")
- Button okButton = (Button)window.FindName("okButton")
- **Button okButton = (Button)window.GetButton("okButton")**

120.Unlike type converters, however, markup extensions are invoked from XAML with _____.

- Bridge assemblies
- **Explicit and consistent syntax (Page#65)**
- Wrapper code
- None of the given options

121.Which statement is True about interfaces?

- An interface can contain only methods, variables, events, and indexers.
- An interface can contain only variables, properties, events, and indexers.
- An interface can contain only methods, properties, variables, and indexers.
- **An interface can contain only methods, properties, events, indexers.**

122.Events can be _____.

- Specialized
- Composed
- Generalized
- **All of the given options**

123. g++ is a command of _____.

- Dev C++

- **Unix based system**
- Windows based system
- None of the given options

124._____ reads entire document in memory.

- **Xmldocuments (Page#49)**
- Xmlreader
- Both of above
- None of the given

125._____ may contain events.

- Requests
- Service
- **Messages (Page#10)**
- Applications

126.A customer order can be represented as _____.

- Event
- Request
- **Event or Request (Page#10)**
- All of the given

127.Markup extensions are invoked from _____ with explicit and consistent syntax.

- C#
- HTML
- **XAML (Page#65)**
- None of the given

128.All the members of interfaces are implicitly_____.

- Private
- Static
- **Public**
- Abstract

129.A compiled C# file is called _____.

- Complied File

- Source File
- **Assembly File**
- EXE File

130._____ add declarative information to your programs.

- **Attributes (Page#41)**
- Functions
- Exception
- Objects

131.Anonymous method is a method without a name.

- **True (Page#47)**
- False

132."out" parameters which are not used for return values or the "params" argument for variable arguments.

- True
- **False (Page#20)**

133._____types have the notion of referential identity.

- Value
- **Reference (Page#14)**
- Both of above
- None of the given

134._____let any classes behave like an array.

- Properties
- Fields
- **Indexers**
- Finalizers

135._____ are algorithms that operate on data.

- Variables
- Functions
- **Methods (Page#37)**
- Classes

136._____ is an event that is introduced into an event processing system by an event producer.

- Event Producer
- Event Consumer
- **Raw Event (Page#11)**
- Event Stream

137.Events and _____ work hand in hand.

- Parameters
- **Delegates (Page#39)**
- Functions
- Data Members

138.C# event is a class member that is _____ whenever the event it was designed for occurs (fires).

- **Activated (Page#38)**
- Deactivated
- Transformed
- Associated

139._____ is a static class in the System namespace.

- **Console (Page#15)**
- Pointer
- Variable
- Function

140.Default value of first member is _____.

- **(Page#44)**
- 1
- 2
- 3

141._____ are inherited by classes which provide the real implementation.

- Functions
- Variables
- **Interfaces (Page#35)**

- Objects

142._____ is basically array of arrays.

- Stack
- Pointer
- **Jagged (Page#18)**
- Function

143.The initial name for C# was _____.

- COAL
- COOP
- COAP
- **COOL (Page#13)**

144.BAML is compressed representation of _____.

- CAML:NS
- **XAML (Page#69)**
- XAML:NS
- CAML

145.Extension methods _____ access the private data members of the class in which they are extended.

- May
- **Cannot**
- May not
- Can

146.Which of the following is/are not derived from "Control" class?

- ListBox
- StatusBar
- Both of above
- **None of the given**

147._____ events may or may not relate to an actual occurrence.

- Observed Events
- Deducted Events
- **Probabilistic Events (Page#7)**
- None of the above

148._____ is an entity that receives events from the system.

- ❖ Event Producer
- ❖ **Event Consumer (Page#11)**
- ❖ Event Channel
- ❖ Event Generator

149.The easiest way to declare an event is to put the event keyword in front of a _____ member.

- ❖ Interface
- ❖ **Delegate**
- ❖ Class
- ❖ Struct

Current SUBJECTIVE: (LONG+SHORT)

1: What are delegates?

A delegate is a reference to a method. It is like function pointers in some other languages. Delegates are used **to define callback methods and implement event handling**, and they are declared using the "delegate" keyword.

Allow you to develop libraries and classes that are easily extensible, through delegation, a **manager is able to divide the work and allocate it to the subordinates**. This helps in reducing his work load so that he can work on important areas such as - planning, business analysis etc.

2: Types of constructor:

In C#, constructors can be divided into 5 types

- Default Constructor.
- Parameterized Constructor.
- Copy Constructor.
- Static Constructor.

- Private Constructor.

3: Explain delegates declare and call delegate:

delegates declare

A delegate is a type that represents references to methods with a particular parameter list and return type. When you instantiate a delegate, you can associate its instance with any method with a compatible signature and return type. You can invoke (or call) the method through the delegate instance.

// this is the delegate declaration

public delegate int Comparer(object obj1, object obj2);

call delegate:

Delegates can be invoke like a normal function or Invoke() method. Multiple methods can be assigned to the delegate using "+" or **"+=" operator** and removed using "-" or "-=" operator. It is called multicast delegate. If a multicast delegate returns a value then it returns the value from the last assigned target method.

4: purpose of event driven architecture:

An event-driven architecture uses **events to trigger and communicate between decoupled services** and is common in modern applications built with microservices. An event is a change in state, or an update, like an item being placed in a shopping cart on an e-commerce website.

5: Attached property in WPF:

An attached property is a Extensible Application Markup Language (XAML) concept. Attached properties enable **extra property/value pairs to be set on any XAML element**, even though the element doesn't define those extra properties in its object model. The extra properties are globally accessible.

6: Keyboard event:

KeyboardEvent objects describe **a user interaction with the keyboard**; each event describes a single interaction between the user and a key (or combination of a key with modifier keys) on the keyboard.

keyboard events include, keyup, and preview versions of them. KeyEventArgs contains Key, ImeProcessedKey, DeadCharProsessedKey, SystemKey, IsUp, IsDown, IsToggled, KeyStates, IsRepeat, and KeyboardDevice. System.Windows.Input.Keyboard and its PrimaryDevice property are accessible everywhere.

7 :What is the return type of destructor?

Destructors do not have any return type not even void.

8: Why you use "iostream", write the syntax:

iostream **provides basic input and output services for C++ programs**. iostream uses the objects cin , cout , cerr , and clog for sending data to and from the standard streams input, output, error (unbuffered), and log (buffered) respectively.

#include<iostream.h>

9: What is debugging and its two ways:

Debugging is **the process of finding errors during application execution**. It does not mean syntax errors, with which the application cannot be compiled, but on logic errors. Logic errors can only be noticed during application execution.

Ways of debugging:

- **Evaluate an expression with or without side effect**
- Enable and Disable Just My Code
- Edit and Continue in XAML
- **Use OzCode**

Visit: ...help.com

10: What is bytecode in Java?

Java bytecode is the instruction set for the Java Virtual Machine. It acts similar to an assembler which is an alias representation of a C++ code. As soon as a java program is compiled, java bytecode is generated. In more apt terms, java bytecode is the machine code in the form of a . class file.

11: Why most WPF classes are inherently thread-unsafe?

Answer: Most WPF classes derive from dispatcher object and are therefore inherently thread-unsafe. The Dispatcher part of the name refers to wpfs version of a Win32-like

message loop,

12: Name the properties supported by the Scale Transform also write its default values of each of Them?

Answer:

Scale Transform:

Scale Transform enlarges or shrinks an element horizontally, vertically,

or in both directions. This transform has four straightforward double properties:

. ScaleX—Multiplier for the element's width (default value = 1)

. ScaleY—Multiplier for the element's height (default value = 1)

. CenterX—Origin for horizontal scaling (default value = 0)

. CenterY—Origin for vertical scaling (default value = 0)

<Button.RenderTransform>

<ScaleTransform ScaleX="2" ScaleY="2"/>

</Button.RenderTransform>

For More Visit: vulmshelp.com

13:Consider the following code snippet and write the output:

XmlDocument xmlDoc = new XmlDocument();

xmlDoc.LoadXml("<uni name=\'Virtual\"> university Node</uni.");

console.writeLine(xmldoc.DocumentElement.Name);

console.writeLine(xmldoc.DocumentElement.InnerText);

console.readline();

ANS: Element Name: Virtual Inner Text: University Node

14: What we achieve from ZIndex codes?

ZIndex is an integer with a default value of 0 that you can set to any number (positive or negative). Elements with larger ZIndex values are rendered on top of elements with smaller ZIndex values, so the element with the smallest value is in the back, and the element with the largest value is in the front.

15: Difference b/w Margin and padding???

Answer:

Margin and Padding

Margin and Padding are two very similar properties that are also related to an element's size. All Framework Elements have a Margin property, and all Controls (plus Border) have a Padding property. Their only difference is that Margin controls how much extra space gets placed around the outside edges of the element, whereas Padding controls how much extra space gets placed around the inside edges of the element. Both Margin and Padding are of type System. Windows. Thickness, an interesting class that can represent one, two, or four double values. The meaning of these values is demonstrated in Listing 4.1, which applies various Padding and Margin settings to Label controls. The second set of Labels is wrapped in Borders because the margin settings would not be noticeable otherwise. Although not shown in this figure, Margin permits negative values. Padding does not.

For More Visit: vulmshelp.com

16: Which Option to be Used to Fill the Dock Panels?

Answer:

Dock panel allows easy docking of elements to an entire side.

Dock attached property has left, right, top, bottom values.

Last child fills space unless lastchildfill=false.**in**

We can also do this by setting Background = —Red‖

17: How many children an object can have, name them?

ANS: An object element can have three types of children

1. A value for a content property,
2. Collection items
3. A Value that can be type-converted to the object element.

17: which functionality is actually a super set of stack panel functionality.

ANS: Stack Panel is popular, simple, useful, stacks sequentially. It is one of the few panels that don't even define an attached property. Orientation can be horizontal or vertical (which is default). Default horizontal direction is based on flow direction

18: What is Default of "Max height ""Min Height ""Max width" and "Min Width" ?

Max height = 1 because The height of an element does not include padding, borders, or margins

Min Height = 0

Max width= **Positive Infinity**.

Min Width = AUTO

19: Write the C# code line to take any string as input from user and the write that string to a file named "Student.txt"?

Answer:

For More Visit: vumshelp.com

```
using System;


class Program
{
static void Main()
{
while (true) // Loop
indefinitely
{
Console.WriteLine("Ente
r input:"); // Prompt
string line =
Console.ReadLine();
 // Get string from user


if (line == "exit") //
Check string
{
break;


}
// Write the string to a
file.
{
System.IO.StreamWriter
file = new
```

For More Visit: vulmshelp.com

```
System.IO.StreamWriter(
"c:\\student.txt");

file.WriteLine(lines);

}

file.Close();
```

20: **Which panel functionality is actually a superset of "stack panel" functionality?**

Answer:

Dock panel is a superset of stack panel, Dock attached property has left, right, top, bottom Values.

21: **For what purpose XAML is used in WF and WCF?**

Answer:

XAML is primarily used to describe interfaces in WPF and Silverlight. It is also used to express activities and configurations in workflow foundation (WF) and windows communication foundation (WCF). It's a common language for programmers and other experts e.g. UI design experts. Field specific development tools can be made. Field experts are graphic designers. They can use a design tool such as expression blend. Other than coordinating with designers, XAML is good for a concise way to represent UI or hierarchies of objects, encourages separation of front-end and back-end, tool support with copy and paste, used by all WPF tools.

22: WPF Panels Are Derived from Which Class?

Answer:

Panels are parents supporting layout of multiple children. They derive from the abstract

System.Windows.Controls.Panel class.

23: **How matrix transform is work like translate transform and give example?**

Answer:

For More Visit: vulmshelp.com

Translate Transform has X — Amount to move horizontally (default value = 0), Y.Amount to move vertically (default value = 0). It has no effect as a layout transform. Matrix Transform has a single Matrix property (of type System.Windows.Media.Matrix). representing a 3x3 affine transformation matrix.

19 Write xml code of given C# code?

```
StakPanelstackpanel = new StakePanel

Button button = new
system.window.control Button;
button.widh = 50;

button.Hight = 70
button.HOrizontelAlligenemtn
=right;
stakepanel.child.add(button);
```

Answer:

```
<?xml version="1.0" encoding="UTF-8" ?>

    <root>

    <0>

    <StakPanelstackpanel = new StakePanel>

    Button button = new system.window.control Button;

    </StakPanelstackpanel = new StakePanel>

    </0>

    <1>

    <StakPanelstackpanel = new StakePanel>

    button.widh = 50;</StakPanelstackpanel = new StakePanel>
```

For More Visit: vulmshelp.com

```
</1>
<2>
<StakPanelstackpanel = new StakePanel>
button.Hight = 70
</StakPanelstackpanel = new StakePanel>
</2>
<3>
<StakPanelstackpanel = new StakePanel>
button.HOrizontelAlligenemtn = right;
</StakPanelstackpanel = new StakePanel>
</3>
<4>
 <StakPanelstackpanel = new StakePanel>
 stakepanel.child.add(button);
 </StakPanelstackpanel = new StakePanel>
 </4>
```

20: Name the Properties Supported by Scale Transform, write their default values?

Answer:

Scale Transform has

scalex, scaley = 1; by default.

centerx, centery = 0; by default.

21: Write names of 3 children of an object?

Ans. An object element can have three types of children:

- ❖ A value for a content property

For More Visit: vulmshelp.com

- ❖ Collection items
- ❖ A value that can be type-converted to the object element

22: When Context Overflow in Built-in Panel Arise, How to Fix That?

Answer:

Content overflow is when parents and children can't agree on the use of available space. Content overflow can be dealt with Clipping, Scrolling, Scaling, Wrapping and Trimming.

23: Logical Tree of the Code?

Answer:

Logical tree exists even if there is no XAML. Properties, events, resources are tied to logical

trees. Properties propagated down and events can be routed up or down the tree. It's a

simplification of what's actually going on when rendered. Visual tree can be thought of as an

extension of the logical tree though some things can be dropped as well. Visual tree exposes

visual implementation details e.g. A list box is a border, two scrollbars and more. Only things

from visual or visual3d appear in a visual tree. Avoid depending on visual tree in your code.

24: **Syntax of CDATA Section?**

Answer:

<x:Code>

<![CDATA[

Void button_Click(object sender, routedeventargs e)

{

This.Close();

For More Visit: vulmshelp.com

```
}
]]>
```

25: Explain Routed Events?

Answer:

Routed events are like dependency properties on top of .net properties.

Similarly routed events are a layer on top of .net events.

They can travel up or down a visual or logical tree.

Helps apps remain oblivious to the visual tree. E.g. Button exposes Click based on

mouseleftbuttondown and key down but actually button chrome or text block visual child fires

it. Event travels up the tree and Button eventually sees it. Or like in a previous example

rectangle on top of button. So arbitrary complex content but Click still raised. Otherwise

would require custom code on inner content or consumers. Very similar to dependency

property concept.

26: **WPF Read-Only?**

Answer:

Read only properties

- Desiredsize
- Rendersize
- Actualheight
- Actualwidth.

They are useful to act programmatically on final size

For More Visit: vulmshelp.com

27: **What We Achieve from ZIndex Codes?**

Answer:

ZIndex is an integer with a default value of 0 that you can set to any number (positive or negative). Elements with larger ZIndex values are rendered on top of elements with smaller ZIndex values, so the element with the smallest value is in the back, and the element with the largest value is in the front.

28: **Why Most WPF Classes Are Inherently Thread-Unsafe?**

Answer:

Since WPF classes derive from dispatcher object therefore they are inherently thread-unsafe. Reason: Dispatcher object is the base class meant for any object that wishes to be accessed only on the thread that created it.

29: **Which transforms all framework elements have?**

Answer:

- Layout Transform
- Render Transform

30: **What will be the easiest way if someone wants to know whether a certain string is a number or not? Elaborate your answer with an example?**

Answer:

- IsNumeric (String s)
- This method is used to find if the string is numeric or not.

31: **Write the XAML code to create a "DockPanel" having four buttons with dock settings i.e. Top, Bottom, Right and Left.**

Answer:

Dock panel allows easy docking of elements to an entire side. Dock attached property has left, right, top, bottom values. Last child fills space unless lastchildfill=false.

```
<dockpanel>
  <Button dockpanel.Dock="Top" Background="Red">1(Top)</Button>
  <Button dockpanel.Dock="Left" Background="Orange">2 (Left)</Button>
  <Button dockpanel.Dock="Right" Background="Yellow">3 (Right)</Button>
  <Button dockpanel.Dock="Bottom" Background="Lime">4 (Bottom)</Button>
  <Button  Background="Aqua">5</Button>
</dockpanel >
```

32: Write two differences between WPF and DirectX?

Answer:

More visit: vulmshelp.com

WPF is made for designers to create vector-based applications using XML and managed code. It uses DirectX as the rendering engine under the covers. DirectX is a set of APIs that abstracts access to modern graphics rendering hardware, as well as other technologies such as sound or input devices. WPF is not designed for any significant game programming, other than, say, a simple card came. DirectX is designed with the intention of allowing you to create a 3D user interface into your game.

33: **When two or more independent grids need to be synchronized, then how can we synchronize them?**

Answer:

we can synchronize two or more independent grids by using Sharedsizegroup

34: What is the biggest feature of dependency property?

Answer:

Its built-in-ability to provide change notification.

35: **What is the purpose of using XAML extensions?**

Answer:

XAML is the **language to build user interfaces for Windows and Mobile applications** that use Windows Presentation Foundation (WPF), UWP, and Xamarin Forms. The purpose of XAML is simple, to create user interfaces using a markup language that looks like XML.

36: **WPF combines the best attribute of some systems. write the names of three?**

Answer:

WPF aims to combine the best attributes of systems such as:

- DirectX (3D and hardware acceleration),
- Windows Forms (developer productivity),
- Adobe Flash (powerful animation support)
- HTML (declarative markup)

For More : vumshelp.com

37: **What is the purpose of WPF 2D transform classes?**

Answer:

To rotate, scale, move (translate), and skew FrameworkElement objects.

39: **For which class WPF are derived?**

Answer:

using System.Windows;

WPF is used to

build Windows client applications that run on Windows operating system.

40: Why C# let us Develop devices resolution independent graphics?

Answer:

C# enable us to develop device independent graphics so that same application/ GUI have same aspect ratio and appearance on all kind of displays. e.g. Windows phone, Windows PC etc

41: **Which term is used to refer to an object that derives from "UIElement" or "FrameworkElement"?**

Answer:

Uielement is the base class for all 2D visual objects.
System.Windows.UIElement. Frameworkelement is the base class that adds support for styles, data binding, resources etc.
System.Windows.FrameworkElement

42: **Name the three routed strategies?**

- T**unneling**: The event is first raised on the root, then on each element down the tree until the source element is reached (or until event is marked as handled).
- **Bubbling**: The event is first raised on the source element, then on each element up the tree until the root is reached (or until the event is marked as handled).

For More Visit: vulmshelp.com

- **Direct**: The event is only raised on the source element. Only source element is given the chance to invoke handlers in response.

43: **Name the three parameters of Handlers for routed events?**

Answer:

Two are known - third is unknown.

1. Sender

Type: System.Object - The source of the event.

2. E

Type: System.EventArgs - An object that contains no event data.

44: **Why "Grid" panel is the best choice for most complex layout scenarios?**

Answer:

The grid is a layout panel that arranges its child controls in a tabular structure of rows and columns. Its functionality is similar to the HTML table but more flexible. A cell can contain multiple controls, they can span over multiple cells and even overlap themselves.

45: **Why C# let us Develop devices resolution independent graphics?**

Answer:

Fortunately for us, C# makes it very easy. The File class, from the Syste.IO namespace comes with pretty much everything we could possibly want, making it very easy to do simple

reading and writing of a file.

File.ReadAllText

File.WriteAllText

Also

AppendAllText

46: What happens when an event is moved up?

Answer:

For More Visit: vulmshelp.com

- **Bubbling**: The event is first raised on the source element, then on each element up the tree until the root is reached (or until the event is marked as handled).

47: **Why events are used in pairs? explain with example?**

Answer:

In VPL, a program is created by assembling pairs of one event and one or more action blocks. For example, a pair composed of a *button* event and a *motors* action tells the robot to move when a button is touched on the robot.

48: **Name the Built-in Transforms Their Default Values?**

Name 5 built in 2D transform which are supported by "System.Windows.Media" namespace.

Answer:

- Translate Transform
- Skew Transform - AngleX, AngleY, CenterX & CenterY (default value = 0)
- Scale Transform
- Rotate Transform – Angle, Centrex, Centery = 0;
- Matrix Transform

49: Using Dock panel in WPF which attributes will be used if we don't want out center to be filled and what will be its value?

Answer:

We can prevent and Turn off the Last Child element to fill the remaining Space the attributes Last Child fill and gives its property False

Syntax:

<Dockpanel lastchildfill="False">

50: What are the type of Constructor in C#?

Answer:

For More Visit: vulmshelp.com

A special method of the class that is automatically invoked when an instance of the class is created is called a constructor.

It Has 5 Types:

- Default Constructor.
- Parameterized Constructor.
- Copy Constructor.
- Static Constructor.
- Private Constructor.

IN:

Details You Can Search by Yourself

51: What are main Benefits of Event Driven Architecture?

Answer:

These are Following:

- Impure competitive advantage
- Create operational Efficacies
- More Robust Information
- Better Scalability and Fault Tolerance
- Increase Versatility
- Casting Functionality

52: Name Any Three types of Mouse Event WPF Supports.

Answer:

These are Following.

- MouseDown − it occurs when a mouse button is pressed.
- MouseEnter − it occurs when the mouse pointer enters the control.
- MouseHover − it occurs when the mouse pointer hovers over the control.
- MouseLeave − it occurs when the mouse pointer leaves the control.

53: How x: Asynchronous and x: Synchronous attributes are XAML 2006?

Answer:

More Visit: vulmshelp.c

X: Asynchronous: It controls the Size of asynchronous XAML Loading Chunk.

x: Synchronous: 'x:SynchronousMode="Async"' on the root element of the xaml file.

54: Purpose of Event Driven.

Answer:

Event-driven architecture (EDA) is **a software design pattern that enables an organization to detect "events" or important business moments**

55: Different Between Event consumer and Event Procedure.

Answer:

EVENT CONSUMER: An event consumer is an entity at the edge of an event processing system that receives events from the system.

EVENT PRODUCER: An event producer is an entity at the edge of an event processing system that introduces events into the system.

55: Different Between STATELESS EVENT and Derived EVENT:

Answer:

RAW EVENT: A raw event is an event that is introduced into an event processing system by an event producer.

DERIVED EVENT: A derived event is an event that is generated as a result of event processing that takes place inside an event processing system.

56: What is the meaning of word abstraction?

Answer:

It is a process the Hide the Internal details and Show only the functionality

57: How can we make a C# program when we can the same number of Columns in 2.3 column?

Answer:

For More Visit: vulmshelp.com

```
using System;


public class Program
{
    public static void Main()
    {
        int[,] arr2d = new int[3,2]{
                {1, 2},
                {3, 4},
                {5, 6}
            };
        Console.WriteLine(arr2d[0, 0]);
        Console.WriteLine(arr2d[0, 1]);
        Console.WriteLine(arr2d[1, 0]);
        Console.WriteLine(arr2d[1, 1]);
        Console.WriteLine(arr2d[2, 0]);
        Console.WriteLine(arr2d[2, 1]);
    }
}
```

58: Anonymous in C#? Declear and use in Anonymous in C#?

Answer:

without any name that can contain public read-only properties only. It cannot contain other members, such as fields, methods, events, etc. You create an anonymous type using the new operator with an object initializer syntax.

Code:

Sir Mobeen Ulmshelp.com

```
using System;


public class Program
{
	public static void Main()
	{
		var student = new { Id = 190202640, FirstName = "JUNAID ", LastName = "Malik" };


		Console.WriteLine(student.Id);
		Console.WriteLine(student.FirstName);
		Console.WriteLine(student.LastName);


	}
}
```

59: write xaml code to create a button in a canvas with attributes left=0 right =0left =0 bottom =0

Answer:

```
<Button Canvas.Right="0" Canvas.Bottom="0"
	Canvas.Right="0" Canvas.Top="0" Canvas.Bottom="0">Damo
```

60: What is the different type of properties are available in c#?

Answer:

There are the following 4 types of Properties:

for more visit: vulmshelp.com

1. Read-Write Property
2. Read-Only Property
3. Static Property
4. Indexer Property

61: **Lets supposed we have create a button in c# now you need to set minimum width=75 and margin=10 in c# .**

Answer:

We have three Method these are following

- ❖ First Drag
- ❖ Then go to the Property an Increase or Decrease the Size of button
- ❖ Same as it in Programming Code

```
private void CreateButton()
{
   // Create a Button object
   Button Button = new Button();

   // Set Button properties
   Button.Height = 10;
   Button.Width = 75;
       }
```

62. Uses of delegates

Answer:

Delegates are used to define callback methods and implement event handling, and they are declared using the “delegate” keyword. You can declare a delegate that can appear on its own or even nested inside a class.

63. What is the return type of destructor in C#? Also In C++

For More Visit: vulmshelp.com

Answer:

A Destructor **has no return type** and has exactly the same name as the class name (Including the same case).

C++

Do not return a value (or void). Cannot be declared as const, volatile, or static

64. What is include iostream for C#? Also in C++

Answer:

iostream stands for standard input-output stream

iostream is the header file which contains all the functions of program like cout, cin etc. and #include tells the preprocessor to include these header file in the program.

65. What is a keyboard event?

Answer:

Keyboard Event objects describe **a user interaction with the keyboard** The event type (keydown , keypress , or keyup) identifies what kind of keyboard activity occurred.

66. **Write XML code Grid splitters 3 columns to apply in seconds?**

Answer:

<Grid>

<Grid.colmundefinitions >

<Columndefinition width = “auto”/>

<Colmundefinitions />

</Grid. columndefinition>

<Label Grid.column = “0” Backgrid =” red”

HorizontalContentAlignment = “Centre” verticalContentAlignment = “centre” >1

</Lable>

For More Visit.

<Gridsplitter Grid-colmn = “0” Width = “5”/>

<Lable Grid.culmn = “1” Background = “orange”

HorizontalContentAlignment = “Centre” verticalContentAlignment = “centre” >2

</Lable>

<Lable Grid.culmn = “2” Background = “yellow”

HorizontalContentAlignment = “Centre” verticalContentAlignment = “centre” >3

</Lable>

</Grid>

67: **Qno.1 How can I use the CopyTo method of the Windows Forms controls collection to copy controls into an array?**

Answer:

The CopyTo method will take the current controls collection and copy all the controls into an array. In order to use it, you must specify the array and the starting point. For instance, the following code copies the controls to the MyArrayOfControls array starting at the first element

68: How Windows keep track of the files?

Answer:

The system requires instance handles to keep track of all modules. The system assigns a handle to each copy of a running executable or .dll.

69: Can you write a class without specifying namespace? Which namespace does it belong to by default?

Answer:

Yes, you can, and then the class belongs to global namespace which has no name. For commercial products, naturally, you wouldn’t want global

For More Visit: vulmshelp.com

namespace.

70: "In the GDI environment there are two working spaces", Name these two.

Answer:

In the GDI environment there are two working spaces

1. Logical
2. Physical

71: how many kinds of macros are there?

Answer:

There are two kinds of macros.

1. Object-like macros resemble data objects when used,
2. Function-like macros resemble function calls.

72: What are the GDI environment working space names?

Answer:

In the GDI environment there are two working spaces

1. Logical
2. Physical

73: what are macros and its types? Explain it with example.

Answer:

There are two kinds of macros.

1 Object-like macros resemble data objects when used,
2 Function-like macros resemble function calls.

Example:

Here's a macro that computes the maximum of two numeric values:

#define min(X, Y) ((X)>(Y) ? (X) Y))

Explain

To define a macro that takes arguments, you use the #define command with a list of parameters in parentheses after the name of the macro. The parameters may be any valid C identifiers separated by commas at the top level (that is, commas that aren't within parentheses) and, optionally, by

For More Visit: vulmshelp.com

white-space characters. The left parenthesis must follow the macro name immediately, with no space in between

74: what is a process?

Answer:

A series of actions or steps taken to achieve an end, a process is a collection of interrelated work tasks initiated in response to an event that achieves a specific result for the customer of the process.

75: **Explain Pointer to Constant, and constant to Painter?**

Answer:

char * const ptr = buff. **// constant pointer to variable data**

*ptr = 'a';

ptr = buff2; **// it will be an error**

since we have declared ptr as a "constant pointer to variable data", so we can change the contents of the place where ptr is pointing at, i.e. data but being a constant variable, the ptr value i.e. the address it contains cannot be modified.

ariable pointer to Constant data:

const char * ptr = buff. **//variable pointer to constant data**

*ptr = 'a'; // it will be an errorptr = buf2;

76: Types of assertion and name them?

Answer:

There are three types of assertion:

1. **Preconditions**
   - Specify conditions at the start of a function.
2. **Post conditions**
   - Specify conditions at the end of a function.
3. **Invariants**

For More Visit vulmshelp.com

- Specify conditions over a defined region of a program

77: Define Client area?

Answer:

The client area is the part of a window where the application displays output, such as text or graphics. For example, a desktop publishing application displays the current page of a document in the client area. The application must provide a function, called a window procedure, to process input to the window and display output in the client area.

78: WIN MAIN describe with detail

Answer:

WinMain is the starting point in Every Win32 GUI programs. WinMain has four Parameters these are,

1. First is instance of the current application.
2. Second parameter is also an instance of this application which is used for the previous application of the same type that is already running. It is used only in Window 16bit editions or Windows 3.1. Windows 32bit editions do not support this parameter. It is here just for compatibility.
3. Third parameter is a command line argument of string type which is a type defined as char *.
4. Fourth parameter is windows style.

79: Message queues of each application (2)

Answer:

An application must remove and process messages posted to the message queues of its threads

80: **Differentiate Desktop Window and Application Window**

Answer:

Desktop Windows	Application Windows
When you start the system, it automatically creates the desktop window. The desktop window is a system-defined window	When you start an application, the system also associates a taskbar button with the application. The taskbar button contains the program icon and title

For More Visit vulmshelp.com

uses a bitmap to paint the background of the screen	Most applications also create other windows, either directly or indirectly, to perform tasks related to the main window
A system configuration application, such as a Control Panel item, changes the desktop wallpaper by using the System Parameters Info function	An application window includes elements such as a title bar, a menu bar, the window menu (formerly known as the system menu),

81: show the implementation of _cdecl calling convolution with respect to

Answer:

1: Argument passing order.
2: stack maintenance responsibility.
3: name decoration convention.

82: A window may have more than one windows inside it explain the line(2)

Answer:

A Window may further contain more windows inside it. For example let's take a calculator; A calculator contains more windows in forms of buttons, radio buttons and check boxes.

- Every Window has its parent and zero or more siblings.
- Top level window has desktop as its parent.

83: What is the function of was paint in Windows class

Answer:

DispatchMessage function to a window procedure when the application obtains a WM_PAINT message from message Queue by using the GetMessage or PeekMessage functions.

84: **Kernel tasks**

Answer:

Kernel is a main module of the operating system. This provides system services for managing threads, memory, and resources.

For More Visit: vulmshelp.com

Kernel has to perform very important responsibilities e.g.

1. Process Management
2. File Management
3. Memory Management (System and Virtual Memory)

85: Difference between __stdcall and __cdecl calling convention

Answer:

cdecl and __stdcall just tells the compiler whether the called function or the calling function cleans up the stack. In __stdcall calling convention, the called function cleans up the stack when it is about to return. So if it is called in a bunch of different places, all of those calls do not need to extra code to clean up the stack after the function call. In __cdecl calling convention, it is the caller function that is responsible for cleaning the stack, so every function call must also need to include extra code to clean up the stack after the function call.

86: Erase window function explanation

Answer:

Erase windows uses the GetClipBox function to retrieve the logical coordinates of the area to erase and passes these coordinates to the FillRect function. Applications that process these messages can use similar techniques. The system supplies a window device context with the WM_ICONERASEBKGND message regardless of whether the corresponding window has a private device context.

87: Clipboard Working

Answer:

In Windows, data is shareable among applications. We can use it for copying the data from one file to the other in same format.e.g from notepad to MS Word.. All the text or image data you have previously copied can now be pasted in other application.

88: Infinite recursion

Answer:

Infinite recursion, a special case of an infinite loop that is caused by recursion. This revised function will only run out of stack space if n is less than 1 or n is too large; error checking would remove the first case. For

For More Visit: vulmshelp.com

information on recursive functions which never run out of stack

86: what is stack?

Answer:

In computer science, a stack is an area of memory that holds all local variables and parameter used by any function, and remembers the order in which functions are called so that function returns occur correctly.

87: what is extern storage class?

Answer:

Extern defines a global variable that is visible to all object modules. When you use 'extern' the variable cannot be initialized as all it does is to point the variable name at a storage location that has been previously defined

88: An application can set up for itself any logical coordinates system, using API. Write down any two.

Answer:

There are two types of brushes: logical and physical. A logical brush is one that you define in code as the ideal combination of colors and/or pattern that an application should use to paint shapes. A physical brush is one that a device driver creates, which is based on your logical-brush definition.

89: Differentiate between Super Classing and Sub Classing.

Answer:

SuperClassing	SubClassing
Super-classing defines a class that adds new functionality to a predefined window class,	*Subclassing is allowed only within a process.*
Button or list box controls.	Win32 processes have separate address spaces
Superclassing involves creating a new class that uses the window procedure of an existing class for basic functionality.	*An application cannot subclass a window or class that belongs to another process.*

90: why the entries in the parent process table and child table?

Answer:

It means that the handle value that identifies a kernel object is identical in

For More Visit: vulmshelp.com

both the parent and the child processes

91: **Define instance Handle? Briefly explain**

Answer:

This member is Application instance handle.

91: Write two macros that perform the same tasks as these functions perform?

Answer:

A *macro* is a fragment of code which has been given a name. Whenever the name is used, it is replaced by the contents of the macro. There are two kinds of macros. They differ mostly in what they look like when they are used. *Object-like* macros resemble data objects when used, *function-like* macros resemble function calls.

You may define any valid identifier as a macro, even if it is a C keyword. The preprocessor does not know anything about keywords. This can be useful if you wish to hide a keyword such as const from an older compiler that does not understand it. However, the preprocessor operator defined can never be defined as a macro, and C++'s named operators cannot be macros when you are compiling C++.

To define a macro that takes arguments, you use the #define command with a list of parameters in parentheses after the name of the macro. The parameters may be any valid C identifiers separated by commas at the top level (that is, commas that aren't within parentheses) and, optionally, by white-space characters. The left parenthesis must follow the macro name immediately, with no space in between.

For example, here's a macro that computes the maximum of two numeric values:

```
#define min(X, Y) ((X)>(Y) ? (X):(Y))
```

92: about _cdecl calling convention?

Answer:

The __cdecl is the default calling convention for C programs. In this calling convention, the stack is cleaned up by the caller. The__cdecl calling

For More Visit: vumshelp.com

convention creates larger executables than_stdcall, because it requires each function call to include stack cleanup code.


93: Different Between homogeneous and heterogeneous event stream

Answer:

A stream in which all the events must be of the same type is called a homogeneous event stream while a stream in which the events may be of different types is referred to as a heterogeneous event stream.

94: Types of event agents.

Answer:



93: Feature of C#.

Answer:

- No global variables or functions.
- Locals cannot shadow global variables.
- There is a strict boolean type.
- Memory address pointers can only be used in specifically marked "unsafe" blocks and require permissions
- No instruction to "free" memory. Only garbage collection.
- Try-finally block.
- No "multiple inheritance" but interfaces supported.
- Operator overloading allowed.
- More type-safe (only integer widening allowed).
- Enumeration members are scoped.
- Property syntax for getters and setters.
- No checked exceptions.
- some functional programming features like function objects and lambda expressions.

94: Why Breaks Points Are Used?

Answer:

It Allows the Stopping Program during Execution

95: Why XML is used?

Answer:

It is Used to EXCHANGED the DATA. And It is a Stricter version of HTML.

96: What are the Method of XML Documents?

Answer:

It has TWO method.

- XMLDOCUMENT
- XMLREADER

For More Details, See HO Page No 49:

97: How to represent the XML code in C#? or Convert the XML code in C#.

For More Visit: vulh

Answer:

```
<Button xmlns="http://schemas.microsoft.com/winfx/2006/xaml/presentation" Content="OK"/>
```

And the corresponding C# code is

```
System.Windows.Controls.Button b= new System.Windows.Controls.Button();
B.Content= "OK";
```

98: Difference Between x:classmodifier and x:filedmodiefier.

Answer:

x:classmodifier= visibility, public by default,

x:filedmodiefier= - field visibility (internal def)

99: Syntax of XML in Attached Property.

Answer:

```
<Window xmlns="http://schemas.microsoft.com/winfx/2006/xaml/presentation"
```

100:Write XMAL code to create a "stackpanel" having four Buttons with dock setting i.e. Top,center,Bottom and Stretch

Answer:

```
<stackpanel>
<Button  horizontalalignment="Left" Background="Red">Left</Button>
<Button  horizontalalignment="Center" Background="Orange">Center</Button>
<Button  horizontalalignment="Right" Background="Yellow">Right</Button>
<Button  horizontalalignment="Stretch" Background="Lime">Stretch</Button>
</stackpanel >
```

101: Write XMAL code to create a "stackpanel" having four Buttons with dock setting i.e.left and top except button which overrides it. Textblock doesnt strech like a control.

Answer:

```
<stackpanel>
<Button  horizontalcontentalignment="Left" Background="Red">Left</Button>
<Button  horizontalcontentalignment="Center" Background="Orange">Center</Button>
<Button  horizontalcontentalignment="Right" Background="Yellow">Right</Button>
<Button  horizontalcontentalignment="Stretch" Background="Lime">Stretch</Button>
</stackpanel >
```

For More visit.vuhelp.com