Question No : 30 of 50

In the context of asynchronous functions in C#, the **await** operator tells the compiler that the **async** method can't continue past that point until the awaited _____ is complete.

100% Correct Confirm File, All new Mcqs
Solved by Faisal (Jc FIA)

Answer

- Terminated process
- Running process
- Asynchronous process ✓ Correct Answer
- Waiting process

CS411 (Visual Programming)

Question No : 10 of 50

XBAP stands for_____.

Answer

- XAML Based Application
- XAML Browser Application ✓ Correct
- Extensible Based Application
- Extensible Browser Application

Finish Exam

CS411 (Visual Programming)

29

Question No : 11 of 50

The translation of application resources into localized versions for the specific culture is called_____

Answer

- Globalization
- Localization
- Localized
- Globlauzed

CS411 (Visual Programming)

Question No : 13 of 50

Threadpool is a collection of thread which can be used _____

Answer

- To perform number of task in background — Correct
- To make easy debugging process
- To avoid complexity
- To make easy the process of thread creation

Finish Exam

24

Question No : 15 of 50

Mo

The command source can query the current status of the RoutedCommand by using the _____ method.

Answer

- canexecute Correct
- execute
- executedChange
- canexecutechange

Question No : 22 of 50

Which Tag is used in XAML to define Columns inside a grid?

Answer

- Grid.Columns
- Grid.ColumnDefinitions ✓ Correct Answer
- Column.Definitions
- Grid.Column.Definitions

Question No : 24 of 50

In JQuery, _____ is an easing value while using SlideUp.

Answer

- Circular
- Swing ✓ Correct Answer
- Non-Linear
- Transparent

Question No : 27 of 50

Input Events usually come from _____.

Input events usually come from input devices such as a keyboard, mouse, touch screen, or stylus.

Answer

- Keyboard
- Mouse
- Software
- Keyboard,Mouse Correct Answer

Question No : 26 of 50

Grid acts as a canvas if it has _____.

Grid can act as a canvas if it has multiple rows and a single column with alignment.

Answer

- AutoSize Rows and 1 column with margin
- Single row & multiple columns
- Single row and single column with alignment and margin
- Multiple rows and single column with alignment

Correct by Jc FIA

Question No : 28 of 50

In C# WPF, Each finger press is associated with its own _____.

Answer

- TouchDevice Correct Answer
- Touchevent
- TouchUp
- TouchDown

Question No : 7 of 50

JavaScript was introduced in the year _____

JavaScript was first introduced in 1995 by Brendan Eich

Answer

- 1995 Correct Ans
- 1996
- 1997
- 1998

Question No : 12 of 50

_____thread can lock that target object at a time.

only one thread can lock a target object at a time using the synchronized keyword.

Answer

- Two
- Three
- Five
- One Correct Answer

Question No : 25 of 50

In Objective C,if you pass "nil" as an argument in setPossessionName:, the possession releases its current possessionName and sets its possessionName to _____.

In Objective-C, if you pass nil as an argument in setPossessionName:, the possession releases its current possessionName and sets its possessionName to nil.

Answer

- As new instance
- Initialized
- Zero
- Nil

Correct Answer by Jc FIA

Question No : 23 of 50

You can use_____ to check if left or right alt is down.

Answer

- Keyboard.IsAltKeyDown Correct Answer
- KeyBoard.AltKey
- KeyBoard.WhichKeyDown
- KeyboardDevice.IsKeyDown

Question No : 19 of 50

_____functions are used to handle responses from the server in Ajax.

Callback functions are used to handle responses from the server in Ajax.
These functions are executed when the server returns a response to the Ajax request.

Answer

- Callback — Correct Answer by Jc FIA
- Send
- Asynchronous
- Synchronous

Question No : 46 of 50

Write the name of three functions of Grand Central Dispatch.

dispatch_async: This function is used to asynchronously execute a block of code on a dispatch queue.

dispatch_sync: This function is used to synchronously execute a block of code on a dispatch queue.

dispatch_barrier_async: This function is used to asynchronously execute a block of code on a dispatch queue, but ensures that any other blocks enqueued after it do not begin executing until it has completed. This is useful for operations that require exclusive access to a shared resource.

Question No : 41 of 50

Name and explain the two categories of an application's binary resources?

Binary resources are what rest of .net framework considers a resource. To define a binary resource, add a file and set the build action resource or content (loose file).
Binary resource has two categories
Binary resource can be embedded to assembly
Binary resource can be loose file that may or may not be known at compile time. It can be localizable or not.

CS411 (Visual Programming)

Login Time 8:34 AM

BC18
RUB

84

Question No : 45 of 50

Marks: 3 (Time 6 Min)

Write a post method using JQuery that will post a rating for certain restaurant using object literal.

87

Question No : 47 of 50

Marks: 5 (Time 10

What is the purpose of the following Objective C code?

```
NSData*imagedata = [NSURLConnection sendSynchronousRequest:urlRequest  returningResponse:nil
Error:\&downloadError];
```

The given code is used to download data. Sendsynchronousrequest is used as a function of Nsurlconnection to download data.
As there could come an error in downloading data so we have make a variable name downloadError.
If ReturningResponse is nil than data will be downloaded otherwise error message will display on screen.

Answer

Login Time 8:34 AM

88

Question No : 48 of 50

Marks: 5 (Time 10 Min)

Write the difference between one way and Two Way Data Binding? Also give example of both ways in XAML.

One way
The target is updated whenever the source changes.
Two way
A change to either the target or source updates the other.

Question No

Create a grid in XAML(WPF) which has 5 rows and 3 Columns.

```
<Grid>
   <Grid.RowDefinitions>
      <RowDefinition/>
      <RowDefinition/>
      <RowDefinition/>
      <RowDefinition/>
      <RowDefinition/>
   </Grid.RowDefinitions>
   <Grid.ColumnDefinitions>
      <ColumnDefinition/>
      <ColumnDefinition/>
      <ColumnDefinition/>
   </Grid.ColumnDefinitions>
</Grid>
```

Question No : 44 of 50

Mark

How can we create and start a new thread? Also write C# code to create and start a thread.

```
Class threadtest
{
Static void Main()
{
Thread t = new Thread(writey);
T.Start();
For (int i = 0; i < 1000; i++) Console.Write("x");
}
Static void writey()
{
For (int i = 0; i < 1000; i++) Console.Write("y");
}
}
```

Answer

Question No : 42 of 50

Which type of information is provided in following Window's properties in WPF?

1. Owner
2. OwnedWindows

Whenever an application makes a window then the concept of parent window and child window arises.
The key difference between child window and parent window is that if we close the child window then there will be no effect on parent window but if we close the parent window than child window will also closed.
The owner property contains the information of parent window while OwnedWindows contains the information about the list of child window.

In Jquery, what does the following mean?

1. $('body > p') Child selectors $('body ¿ p')
2. $('img[alt]') form element selector
3. $('h2 + div') Adjacent sibling $('h2 + div')
4. $('a[href ="mailto:"]') form element selector
5. $('input[type="text"]') form element selector

Login Tim

88

Question No : 48 of 50

Marks: 5 (Time

Write the difference between one way and Two Way Data Binding? Also give example of both ways in XAML.