

Mid

Quiz by Attiq Kundi

SUBSCRIBE "[Knowledge For Us](#)" ON YOU TUBE

100 % CORRECT MCSQ

AND Many MoRe

CS-610

QUIZ FILE

FALL 2021

Mapping between a protocol address and a hardware address is called

- .

- a) Segmentation
- b) Hashing
- c) Address Resolution**
- d) Fragmentation

2. _ protocols of TCP/IP layering model specify how to organize data into frame and how a computer transmits frames over a network.

- a) Session
- b) Network interface layer**
- c) Internet Layer
- d) Transport Layer

3. In Closed-form computation, the protocol address assigned to a computer is chosen carefully so that computer's hardware address can be computed from the protocol address using basic Boolean and _ operations.

- a) Arithmetic**

- b) XOR
- c) Shift
- d) XNOR

4. As the Internet grew, the original Classful addressing scheme became a limitation. The IP address space was being exhausted because all networks had to choose one of possible sizes.

a) Three

- b) two
- c) four
- d) five

5. Dotted decimal notation is a syntactic form the IP software uses to express binary values when interacting with humans.

- a) 8-bit
- b) 16-bit

c) 32-bit

- d) 64-bit

6. protocols of TCP/IP layering model specify how to ensure reliable transfer.

- a) Physical Layer
- b) Network Interface Layer
- c) Internet Layer

d) Transport Layer

7. In the IP address identifies an individual computer on the network.

- a) Prefix

b) Suffix

- c) Mux
- d) Demux

8. Internet protocol (IP) address version 4 is comprised of bits.

- a) 48

b) 32

- c) 24
- d) 128

9. A separate table is used for each physical network.

- a) bit-binding
- b) Checksum

c) address-binding

- d) CRC

10. Inside a computer, each address mask is stored as a bit value.

- a) 48
- b) 64
- c) 16

d) 32

11. Dotted decimal represents each octet in and uses a dot to separate octets.

- a) binary

b) decimal

c) hexadecimal

d) Octal

12. _ of TCP/IP Protocol Suit specifies the format of packets sent across Internet as well as the mechanisms used to forward packets.

a) Physical Layer

b) Data Link Layer

c) Internet Layer

d) Transport Layer

13. The IP class scheme does not divide the address space into equal size class and the classes do not contain the same number of networks.

a) 16-bit

b) 32-bit

c. 48-bit

d. 64-bit

14. _ of TCP/IP protocol suit defines the basic characteristics of network hardware.

a) Physical Layer

b) Data Link Layer

c) Internet Layer

d) Transport Layer

15. The protocol address of the next hop must be to an equivalent hardware address before a packet can be sent.

a) Encrypted

b) Decrypted

c) Translated

d) Segmented

16. Address Resolution Protocol is mostly used to bind a 32-bit IP address to an _ Ethernet address.

a) 16-bit

b) 48-bit

c) 64-bit

d) 128-bit

17. TCP/IP defines the term _ to refer any computer system that connects to a network and runs applications for users.

a) Router

b) Host computer

c) Bridge

d) Switch

18. _ are two standard implementations to improve computational efficiency.

a) Hashing and Direct indexing

b) Segmentation and Fragmentation

c) Queuing and Packetizing

d) Indexing and Framing

19. In the IP address _ identifies the physical network to which the computer is attached.

a) Prefix

b) Suffix

- c) Mux
- d) Demux

----- have advantages arisen from the size and ease of computation.

- ▶ CRC
- ▶ Parity (Page 19)
- ▶ Checksums
- ▶ None of given

In Cyclic Redundancy Checking, CRC is_____.

- a. Divisor
- b. Quotient
- c. Remainder page 20
- d. Dividend

The satellite or radio topology in which all computers are connected to each other via satellite or radio wave is a kind of

- a. Broadcast network page 5
- b. Point-to-Point network

Which of the following two operations are performed by Ethernet CD?

- I. It monitors outgoing signals.
- II. Grabbled signal is interpreted as a collision.
- III. Signals are sent back to the sender.

- a. I and III
- b. II and IV
- c. II and III
- d. I and II page 28

While transmitting data from source A to destination B, 4 bits are changed during the transmission then the error is a

_____.

- a. Burst error page 22
- b. Single error
- c. Double error
- d. Logic error
- d. TDMA

Missing_____in a frame format indicates receiving computer missed beginning of the message.

a. eot

b. soh page 16

c. sot

d. eoh

The_____of errors is easier than the _____of errors.

a. correction; detection

b. detection; correction cs601 handouts

c. correction; creation

d. detection; manipulation

The_____of errors is difficult than the _____of errors.

a. correction; detection google

b. detection; correction

c. correction; creation

d. detection; manipulation

The___layer of the OSI model takes the data from the physical layer and perform error checking.

a. Transport

b. Data link google

c. Application

d. Presentation

CBR stands for _____.

a. Constant Byte Rate

b. Constant Bit Rate

c. Connection break Recovery

d. Constant Borrow Rate

A network that uses _____usually consist of a single long cable to which

computer attach.

a. Star Topology

b. Ring Topology

c. Bus Topology page 26

d. Bus and Ring Topology

If simultaneous transmission occurs, the frames interfere with each other and this phenomenon is called _____.

a. packet loss

b. collision page 28

c. delayed transmission

d. coordination

In _____ all computers are attached to a central hub
a. Ring topology

b. Star topology page 31

c. Hub topology

d. Bus topology

For adding a new computer in a point to point network _____ new connection

will be required

a. N

b. N-1 page 23

c. N-2

d. 2n

The fastest Ethernet hardware operates at a rate of _____

a. 1000 bps

b. 100 Mbps page 27

c. 10 Mbps

d. 1000 Mbps

Which of the following the benefit to point to point communication? a. Quick to configure

b. Security implementation page 23

c. Cost

Thick Ethernet is known as _____

a. 10 Base 2

b. 10 Base 5 google

c. 10 Base T

d. 10 Base 10

In a ping command, small –sized information packets of _____ are sent.

a. TCP

b. UDP

c. ICMP page 11

d. IGMP

Which of the following is not a function of ping commands?

a. Local computer network issue

b. Congestion in the network

c. Relay nodes page 11

d. Remote host availability

Fixed network is a type of network which is classified with respect to the _____ factor

- a. Size
- b. Connectivity
- c. Medium

d. Mobility page 6

Parity bit can detect _____ error(s)

- a. 4
- b. 3
- c. 2 page 19 (even or odd)
- d. 1

How many computers are mandatory to form a network?

- a. 1
- b. 2 google
- c. 4
- d. 8

_____ is standard wireless LAN that uses radio signals at 2.4GHz.

- a. IEEE 803.16
- b. IEEE 802.15
- c. IEEE 802.3
- d. IEEE 802.11 page 29

LAN interface hardware obeys _____ access rule.

- a. CSMA/CD page 34
- b. Round robin
- c. First come first served
- d. High priority

Which multiplexing technique transmits digital signals?

- a. WDM
- b. FDM
- c. TDM page 15
- d. GSM

_____ and _____ are the two frame types.

- a. Internal and external
- b. Single and dual
- c. Implicit and explicit
- d. Multicast and broadcast page 35

Bluetooth uses shared medium and _____ instead of coaxial cable.

- a. Radio waves page 29

- b. Infrared waves
- c. Micro waves
- d. Low frequency waves

Which of the following is not a guided medium?

- a. Twisted-pair cable
- b. Fiber-optic cable
- c. Atmosphere [google](#)
- d. Coaxial cable

As a result of ARPA research, the first network was established which was named as _____.

- a. INTERNETWORKING
- b. ARPNET
- c. ARPANET [page 9](#)
- d. PACKET NETWORK

LAN interface uses _____ to copy frame data directly from main memory

- a. DMA [page 34](#)
- b. FDDI
- c. Hard disk
- d. Flash

The Gigabit Ethernet hardware operates at a rate of _____.

- a. 10 Mbps
- b. 100 Mbps
- c. 1000 Mbps [reference book page 263](#)
- d. 1000 Gbps

In the early resource sharing era, which resources were shared among users?

- a. Computation [page 9](#)
- b. Floppy Drives
- c. Hard Disk
- d. Printers

Which type of network consists of wireless connection of laptops in a university classroom?

- a. WAN
- b. MAN
- c. Fog
- d. LAN [google](#)

There are _____ types of data stuffing.

- a. 1
- b. 2 page 17
- c. 0
- d. 5

_____ masks your IP address.

- a. Firewall
- b. Antivirus
- c. VPN
- d. Incognito mode

In which type of error detection, the arithmetic sum is calculated before and after the transmission of data at both communication ends?

- a. CRC
- b. Parity
- c. Checksum page 19
- d. Hash Function

Ethernet uses a _____ bit static addressing scheme in which each device is

assigned a unique address by the manufacturer.

- a. 64
- b. 48
- c. 32
- d. 16

A _____ relies on the hardware manufacturer to assign a unique physical

address to each network interface.

- a. Static addressing scheme page 34
- b. Configurable addressing scheme
- c. Dynamic addressing scheme
- d. None of the given

In _____ topology, if the switch goes down all the computers will be disconnected.

- a. Star
- b. Ring
- c. Bus
- d. Mesh

Which type of network consists of wired computers in a university classroom?

- a. MAN
- b. PAN
- c. WAN
- d. LAN

If you as a network administrator want to know the traffic flow of your data while communicating with a remote computer which of the following will be used to know about intermediate routers?

- a. Ipconfig
- b. Ping page 11
- c. Traceroute
- d. Arp

Hardware address is also called _____.

- a. Physical address
- b. Logical address
- c. IP address
- d. Port address

Which of the following network is using the TCP/IP model globally?

- a. PAN
- b. SAN
- c. LAN
- d. The Internet

The length of hardware address is _____.

- a. One to ten bytes
- b. One to five bytes
- c. One to six bytes page 34
- d. One to seven bytes

A network analyzer is also called _____.

- a. Network manager
- b. Network administrator
- c. Network monitor page 37
- d. Network

No any error detection scheme is perfect because transmission errors can affect

_____.

- a. Data
- b. Additional Information
- c. Additional information & data [google](#)
- d. Transmission medium

Which layer of the OSI Model directly communicates and controls the transmission medium:

- a. Transmission
- b. Physical
- c. Application
- d. Network

In _____ technique data is treated as a sequence of integers and their

arithmetic sum is computed and the carry bits are added to the final sum.

- a. CRC
- b. Bit stuffing
- c. Checksum [page 19](#)
- d. 2D Parity

A network uses _____ to arrange computers in a single closed loop.

- a. Star Topology
- b. Mesh Topology
- c. Ring Topology [page 25](#)
- d. Bus Topology

Which of the following tasks is not done by the second layer of the OSI model?

- a. Flow control
- b. Framing
- c. Channel coding [google](#)
- d. Error control

LAN and WAN are classified according to their _____.

a. Size page 4

b. Connectivity

c. Medium

d. Mobility

The identifier that is used for data transfer in the virtual circuit network is called _____.

a. Virtual circuit identifier

b. Global address

c. Network identifier

d. IP identifier

In Direct point to point communication adding the Nth computer requires

_____ new connections

e. N^2

f. $N-1$

c. $(N^2 - N)/2$ page 23

d. $N(N-1)$

Point to point topology is

a. Size based

b. Mobility based

c. Connectivity based page 5

d. Medium based

108. IEEE LLC / SNAP header is _____ which is used to specify the type of data.

a. 8 octets google

b. 16 octets

c. 32 octets

d. 64 octets

IEEE LLC / SNAP header is _____ which is used to specify the type of data.

a. CRC

b. Bit stuffing

c. Checksum

d. 2D Parity

What is the largest network in existence?

- a. The internet google
- b. A PAN
- c. A Fog
- d. Edge Network

The frame format of any LAN technology must consists of _____ and ____-

- a. Payload and CRC
- b. Frame header and CRC
- c. Payload and Frame type
- d. Frame header and payload page 36

Which of the following cannot be used to extend a LAN?

- a. Repeaters
- b. Switches
- c. Routers
- d. Fiber modems

According to size, there are ____ classifications of networks

- a. 2 page 2
- b. 3
- c. 4
- d. 5

In which topology terminators are used at the end of the cable?

- a. Star
- b. Bus
- c. Ring
- d. Mesh
- d. Plastic virtual circuit

If a sender with a 1 Gigabit NIC and receiver with 100 Megabit NIC wants to communicate with each other than at which speed they can communicate

- a. 11 Megabit
- b. 100 Megabit
- c. 1 Gigabit
- d. 1.1 Gigabit

_____ is used as an alternative of packet for a specific computer network technology

- e. Datum

f. Token

g. Ether

d. Frame page 14

The sharing of a medium and its link by two or more devices is called

a. Modulation

b. Encoding

c. Multiplexing

d. Line discipline

The topology each computer is connected to a central hub is called

e. Ring topology

b. Star topology page 5

c. Tree topology

d. Mesh topology

The basic responsibility of NIC is _____

a. To access medium network

b. To resource allocation

c. To access memory

d. All of the given option

In Token Ring, if all computers are ready to transmit it enforces

access

a. First come first served

b. Round Robin page 30

c. Shorter delay

d. Last come first served

The Ethernet standard specifies that frames are sent using the

scheme.

a. Differential Manchester

b. Not Return to Zero (NR2)

c. Manchester Encoding page 27

d. Return to Zero (RZ)

Which of the following is a benefit of point to point communication?

a. Quick to configure

b. Security implementation

c. Cost

d. Less availability

_____ is not used to extend LAN.

- Hub
- **Fiber modem**
- Repeater
- Bridge

Which types of VPNs are used for corporate connectivity across companies residing in different geographical locations?

- Remote access VPNs
- Peer-to-peer VPNs
- Country-to-country VPNs
- **d. Site-to-site VPNs**

google Star topology is the kind of a.

Tree topology

- b. **Point-to-point topology** page 05
- c. Broadcast topology
- d. Ring topology

In a _____ state, a bridge allows simultaneous use of each segment.

- a. Ready
- b. **Steady**
- c. Final
- d. Startup

The network occupies larger areas like cities & countries is called

- LAN
- **WAN**
- MAN
- All of the above

In link state routing _____ send link-state information about local connections.

- Bridges
- **Switches**
- Routers
- Hubs

Transmission media are usually categorized as _____.

- a. **Guided or unguided**
- b. Fixed or unfixed

- c. Determinate or indeterminate
- d. Metallic or nonmetallic

Even parity can be used to check for _____ bit/ bits of errors.

- a. 1 page 18
- b. 2
- c. 3
- d. 0

Routing table entries can be _____ with a default route.

- a. Collapsed
- b. Redirected
- c. Emerged
- d. Guaranteed

The system administrator must coordinate to avoid the conflict in _____ hardware addressing scheme.

- Static
- Dynamic
- Configurable
- Fixed

_____ network does not depend on CSMA/CD.

- Ethernet
- Fast Ethernet
- Gigabit Ethernet
- Wireless

Which of the following technologies can extend the diameter of LAN medium?

- Fiber optic
- Repeater
- Diameter of LAN medium is not extendable
- Both. Fiber optic and Repeaters

The _____ scheme must be reliable to prevent conflicts.

- a. Static
- b. Dynamic page 34
- Configurable
- Fixed

Which addressing can be only used in the local area networks?

- a. IP google

- Physical
- Port
- Protocol

The sharing of a _____ among the workers in an office is a goal of resource sharing.

- Mouse
- **b. Printer** page 9
- Keyboard
- Motherboard

Which of the followings is not an advantage of framing?

- Missing eot indicates sending computer crashed
- Missing soh indicates receiving computer missed beginning of message
- **c. Delimiters do not contain any user data** page 16
- Bad frame is discarded

The _____ field of Ethernet frame has the purpose of receiver synchronization.

- **a. Preamble** page 36
- Frame Type
- Data
- CRC

_____ was the first internet available for the first time.

- ARPANAT
- The ARPNET
- The NET
- **. ARPANET** page 9

We need packets rather than bits because _____

- To compress the data
- Packets move faster
- Sender and receiver need to coordinate to detect
- **transmission errors. Page 14**

Mid

Quiz by Attiq Kundi

SUBSCRIBE "[Knowledge For Us](#)" ON YOU TUBE

100 % CORRECT MCSQ

AND Many MoRe

CS-610

QUIZ FILE

FALL 2021