CS611 – Modelling and Simulation

Final Term Papers 2025

Prepared By: Usama Farooq

Short Questions

1. What does Imminent Event mean?
2. Define Agent, Observer, Environment, and Interaction.
3. What is verification role in correctness of model?
4. Operational Analysis as Simulation Tool
5. What are the major disadvantages of simulation?
6. Define Activity
7. Define Clock
8. Explain Binomial equation
9. Verification and validation replication
10. Operational analysis as modelling tool
11. Phases of modeling and simulation
12. Give the examples of distribution which were created on the physical basis?
13. Why multiple runs are needed in the modeling
14. Formal modeling
15. Why for agent-based modeling no special training is required?
16. Explain complex adaptive systems with its properties?
17. IEEESC and HWC stand for?

Long Questions

1. What is Common Random Number (CRN)?
2. Explain imperfect debugging modeling?
3. Write down a detail note on when simulation is appropriate tool and when it's not an appropriate tool?
4. Explain different types of measurements in an agent-based modeling?
5. Explain chaos theory?
6. Explain performance evaluation of a model?
7. Explain Bernoulli distribution in detail?
8. Write down a detail note on when simulation is appropriate tool and when it's not an appropriate tool?
9. Macro-validation of Agent-Based Modelling
10. How does the BehaviorSpace tool in NetLogo streamline the process of collecting data from multiple runs in agent-based modeling experiments?
11. Disadvantage of agent base representative?
12. What are the properties in agent-based modeling? What were
13. Functions of Sheep and Wolves (ABM Example)
14. Given reason why analytical module choose as modeling?
15. Discuss the simulation and modeling how many types of models we can study?
16. Brief note on Game of Life

Usama Farooq

Answers:

Short Questions

1. **What does Imminent Event mean?**
   An imminent event is something that is about to happen in a simulation. It's the next event scheduled to occur based on the simulation's timeline or clock.
2. **Define Agent, Observer, Environment, and Interaction.**
   - **Agent**: An individual entity (like a person, animal, or object) in a simulation that can make decisions or act independently.
   - **Observer**: Something or someone that watches or collects information about the simulation without directly affecting it.
   - **Environment**: The setting or world where agents act, like a virtual city or forest in the simulation.
   - **Interaction**: The way agents communicate or affect each other or the environment, like animals moving or people talking.
3. **What is verification role in correctness of model?**
   Verification checks if the model is built correctly, meaning the computer code or logic matches the design of the model. It ensures there are no errors in how the model is programmed.

4. **Operational Analysis as Simulation Tool**
   Operational analysis uses simulation to study how a system (like a factory or traffic flow) works by testing different scenarios. It helps understand system behavior and improve decisions.
5. **What are the major disadvantages of simulation?**
   - Takes a lot of time and effort to build and run.
   - Can be expensive due to software and computing needs.
   - Results may not always be accurate if the model is too simple or data is poor.
   - Hard to understand complex simulations without expertise.
6. **Define Activity**
   An activity is a specific task or action in a simulation that takes time and involves agents or objects, like a car moving or a machine working.
7. **Define Clock**
   A clock in a simulation keeps track of time. It helps schedule events and moves the simulation forward, like a timer in a game.
8. **Explain Binomial Equation**
   The binomial equation is used to calculate the probability of getting a certain number of successes in a fixed number of trials, where each trial has two outcomes (like success or failure). For example, flipping a coin 10 times and calculating the chance of getting 5 heads. The formula is:
   P(x) = (n choose x) * p^x * (1-p)^(n-x)
   where:
   - n = number of trials
   - x = number of successes
   - p = probability of success
   - (n choose x) = combination formula.
9. **Verification and Validation Replication**
   Verification checks if the model is coded correctly, while validation checks if the model represents the real world accurately. Replication means running the simulation multiple times to ensure results are consistent and reliable.
10. **Operational Analysis as Modelling Tool**
    Operational analysis as a modeling tool involves creating models to study real-world systems (like businesses or traffic) by analyzing how they work under different conditions. It helps predict outcomes and improve efficiency.
11. **Phases of Modeling and Simulation**
    - **Problem Definition**: Identify what you want to study.
    - **Model Design**: Create a simplified version of the system.
    - **Data Collection**: Gather data to feed into the model.
    - **Model Implementation**: Build the model in software.
    - **Verification**: Check if the model is coded correctly.
    - **Validation**: Ensure the model matches real-world behavior.
    - **Experimentation**: Run simulations to test scenarios.
    - **Analysis**: Study results to make decisions.
12. **Give the examples of distribution which were created on the physical basis?**
    - **Normal Distribution**: Models things like heights or weights in nature.
    - **Exponential Distribution**: Models time between events, like machine breakdowns.
    - **Poisson Distribution**: Models random events in a fixed time, like customer arrivals.
13. **Why multiple runs are needed in the modeling?**
    Multiple runs help account for randomness in simulations. By running the model many times, you get average results, which are more reliable and show how the system behaves over time.
14. **Formal Modeling**
    Formal modeling uses strict mathematical or logical rules to represent a system. It ensures the model is precise and can be analyzed systematically, like using equations to model traffic flow.
15. **Why for agent-based modeling no special training is required?**
    Agent-based modeling is often designed to be user-friendly, with tools like NetLogo that have simple interfaces. Users can create models by defining basic rules for agents without needing advanced math or programming skills.
16. **Explain Complex Adaptive Systems with its Properties?**
    A complex adaptive system is a system where many parts (like agents) interact, adapt, and learn, creating complex behavior. Examples include ant colonies or stock markets.
    Properties:
    - **Adaptation**: Parts change based on experience.
    - **Emergence**: Simple rules lead to complex outcomes.
    - **Non-linearity**: Small changes can cause big effects.
    - **Interconnectedness**: Parts influence each other.

Usama Farooq

17. IEEESC and HWC stand for?

- **IEEESC**: Institute of Electrical and Electronics Engineers Computer Society.
- **HWC**: Likely refers to Hardware Component (context-specific, but often used in modeling for hardware parts in simulations).

Long Questions

1. **What is Common Random Number (CRN)?**
   Common Random Number (CRN) is a technique used in simulations to compare different scenarios fairly. It uses the same random numbers for all scenarios, so differences in results come from the model's changes, not random variations. For example, if you're testing two factory layouts, CRN ensures both use the same random events (like machine failures) to make the comparison more accurate.
2. **Explain Imperfect Debugging Modeling?**
   Imperfect debugging modeling is used in software development to simulate how fixing bugs can sometimes introduce new ones. It assumes that when a bug is fixed, there's a chance the fix isn't perfect, and new errors might appear. This model helps predict how reliable software will be over time and how much effort is needed for testing and fixing.
3. **When Simulation is an Appropriate Tool and When It's Not?**
   Appropriate:
   - When studying complex systems (like traffic or ecosystems) where real-world testing is hard.
   - To test "what-if" scenarios safely, like predicting factory output.
   - When real-world experiments are too costly or risky.

   Not Appropriate:
   - When the system is simple and can be solved with math (e.g., basic calculations).
   - If data is missing or unreliable, leading to inaccurate results.
   - When time or resources are limited, as simulations can be slow and expensive.
4. **Explain Different Types of Measurements in Agent-Based Modeling?**
   In agent-based modeling, measurements help analyze how agents and systems behave. Types include:
   - **Individual Metrics**: Track single agent behaviors, like how far an agent moves or its energy level.
   - **Aggregate Metrics**: Look at group behavior, like the total population or average wealth.
   - **Spatial Metrics**: Measure patterns in space, like how agents cluster or spread out.
   - **Network Metrics**: Analyze connections between agents, like how many friends an agent has.
   - **Temporal Metrics**: Track changes over time, like how fast a disease spreads.
5. **Explain Chaos Theory?**
   Chaos theory studies systems where small changes in starting conditions can lead to big differences in outcomes. For example, in weather forecasting, a tiny change in temperature can drastically change the prediction. These systems are unpredictable but follow rules. Key ideas include:
   - **Sensitivity to Initial Conditions**: Small differences grow over time.
   - **Non-linearity**: Simple rules create complex behavior.
   - **Deterministic Chaos**: The system follows rules but seems random.
6. **Explain Performance Evaluation of a Model?**
   Performance evaluation checks how well a model works. It involves:
   - **Accuracy**: Comparing model results to real-world data (validation).
   - **Efficiency**: Checking if the model runs quickly and uses reasonable resources.
   - **Reliability**: Running the model multiple times to ensure consistent results.
   - **Usefulness**: Ensuring the model answers the questions it was designed for.
     This helps decide if the model is trustworthy for decision-making.
7. **Explain Bernoulli Distribution in Detail?**
   The Bernoulli distribution models a single trial with two outcomes: success (1) or failure (0). For example, flipping a coin (heads = success, tails = failure).
   - **Parameters**: Probability of success (p) and failure (1-p).
   - **Formula**: P(X=1) = p, P(X=0) = 1-p.
   - **Mean**: p (average outcome).
   - **Variance**: p * (1-p) (spread of outcomes).
   - **Use**: Common in simulations for binary events, like whether a customer buys a product.
8. **Macro-Validation of Agent-Based Modelling**
   Macro-validation checks if the overall behavior of an agent-based model matches real-world patterns. Instead of focusing on individual agents, it looks at big-picture results, like total population trends or market behavior. For example, in a model of a city, macro-validation checks if traffic patterns or population growth match real data. It ensures the model captures system-level behavior accurately.
9. **How does the BehaviorSpace tool in NetLogo streamline the process of collecting data from multiple runs in agent-based modeling experiments?**
   BehaviorSpace in NetLogo is a tool that automates running a model multiple times with different settings. It helps by:

Usama Farooq

- Allowing users to set up experiments with varied parameters (e.g., different agent speeds).
- Running simulations automatically and collecting data from each run.
- Saving results in files (like spreadsheets) for easy analysis.
- Reducing manual work and errors, making it faster to study how changes affect outcomes.

10. Disadvantage of Agent-Based Representative?

- **Complexity**: Models can be hard to design and understand.
- **Computationally Intensive**: Needs powerful computers for many agents.
- **Data Requirements**: Needs detailed data about agents and their behaviors.
- **Hard to Validate**: Real-world data may not match agent-based results.
- **Time-Consuming**: Building and running models takes a lot of time.

11. What are the Properties in Agent-Based Modeling?

Properties in agent-based modeling describe characteristics of agents and their environment. Examples include:

- **Agent Properties**: Speed, energy, location, or decision-making rules.
- **Environment Properties**: Size, resources, or obstacles.
- **Interaction Rules**: How agents communicate or compete.

These properties define how the system behaves and evolves.

12. Functions of Sheep and Wolves (ABM Example)

In the Sheep and Wolves model (a classic NetLogo example):

- **Sheep**: Move, eat grass, reproduce, and die if energy runs out.
- **Wolves**: Move, hunt sheep, reproduce, and die if they don't eat enough.
- **Grass**: Grows back over time and is eaten by sheep.

The model shows predator-prey dynamics, like how populations balance or collapse.

13. Given Reason Why Analytical Model Chosen as Modeling?

Analytical models are chosen when:

- The system is simple enough to describe with equations (e.g., calculating profit).
- They provide exact solutions without randomness.
- They are faster and cheaper than simulations.
- They work well for systems with predictable patterns, like physical laws.

14. Discuss the Simulation and Modeling: How Many Types of Models We Can Study?

Modeling and simulation involve different types of models:

- **Physical Models**: Miniature versions of real objects (e.g., model airplanes).
- **Mathematical Models**: Use equations to describe systems (e.g., economic models).
- **Agent-Based Models**: Focus on individual agents and their interactions.
- **Discrete Event Models**: Track events that happen at specific times (e.g., queue systems).
- **Continuous Models**: Track systems that change smoothly (e.g., fluid flow).
- **Stochastic Models**: Include randomness (e.g., weather models).
- **Deterministic Models**: No randomness, predictable outcomes (e.g., planetary motion).

15. Brief Note on Game of Life

The Game of Life is a simulation created by John Conway. It's a grid where each cell is either "alive" or "dead." Simple rules decide what happens next:

- A live cell with 2 or 3 live neighbors stays alive.
- A live cell with fewer than 2 live neighbors dies (loneliness).
- A live cell with more than 3 live neighbors dies (overcrowding).
- A dead cell with exactly 3 live neighbors becomes alive (birth).

It shows how simple rules can create complex patterns, like moving shapes or stable structures, and is used to study emergence in complex systems.

Usama Farooq