

Virtual University

4-Year Experience



Cell No : 0342-7193822

All Services Available Very Reasonable Prices 100 % Correct
Solutions Assignments, GDBs, PDF Handouts, PDF Notes, Past
paper Files , Current Paper Officials
Special Guidelines (Sir Muhammad Usman) Owner YouTube
Channel Learn For Success
Cell No : 0342-7193822 (Only WhatsApp)

Introduction to Programming (Practical) (CS201P)

Question: 4 (Marks: 1)

In operator overloading, ^ is _____ operator.

Choices:

Unary



Choices:

Unary



Binary



solved by math zone for vu

Tinary



2 of 33 1 Word

Question: 22 (Marks: 1)

Attempted Qu

In C++, the default visibility of the class is _____

Choices:

Public



Private



Protected



solved by math zone for vu



Question: 11 (Marks: 1)

The operations used within template functions should be present in the _____ part of the class.

Attempted Questions: 0

Choices:

☐ Private

☐ Body

☐ Main()



Body

Main()

Public

solved by math zone for vu

TIME LEFT

85



Type here to search



Q.12 (Marks: 1)
If we do not define the assignment operator for a class, the default assignment operator will do the member-wise copy which is known as _____

Choices:

☐ Hard copy

☐ Deep copy

☐ Shallow copy

solved by math zone for vu

☐ Soft copy

04:01

X



Identify which option is valid.

Choices:

☐ `int i, int * dp = &i;`

☐ `int x = 0, int *ip = &x;`

☐ `char s, *sp = &0;`

☐ `int *pi = *0;`

solved by math zone for vu



Question: 23 (Marks: 1)

Attempt

Which of the following have same functionalities?

Choices:

☐ Structures and Classes

☒ Functions and Pointers

☐ If-else and Loops

☐ Arrays and Functions

solved by math zone for vu

What will be the output of the following code?

```
int main () {  
    int lineno = 5;  
    int count = 0;  
    for (int lineno = 0; lineno < 1; lineno++, count++){  
        cout << lineno << ", " << count;  
    }
```

Choices:

5,0

☐

1,0

☐

0,0

☐

1,1

☐

solved by math zone for vu

_____ is a header file for console input/output in a program.

Choices:

☐ `#include<conio.h>`

☐ `#include<string.h>`

☐ `#include<stdlib.h>`

☐ `#include<math.h>`

solved by math zone for vu



Question: 19 (Marks: 1)

Attempted Question

Array indexing starts from _____ in C/C++ language.

Choices:

0



solved by math zone for vu

1



2

**SUBSCRIBE!**

TIME LEFT

84



Type here to search



Question: 18 (Marks: 1)

Attempted Questions

In bit manipulation of binary systems, if we shift a bit towards left then it means we are _____ that binary value with '2'.

Choices:

☐ Adding

☐ Subtracting

☐ Multiplying

☐ Dividing

solved by math zone for vu

Suppose we have an integer variable named "num" with 5678 as its value then what will be the resulting value for the expression "num%100"?

Choices:

9

☐

78

☐

solved by math zone for vu

56

☐

678

☐

Whenever a programmer writes $a += b$, now 'a' itself is being _____.

Choices:

☐ Changed

☐ Copied to b

☐ Returned to class constructor

☐ Destroyed

solved by math zone for vu

Question: 10 (Marks: 1)

Attempted Question

```
void sample() {  
    Surround::SecondWithin a;  
    Surround::FirstWithin b;  
    Surround c;  
    c.myFirstWithin.getVar();  
}
```

In the above code, the access specifier (::) used in function sample (), is used to access the member of _____

Choices:

☐ Inner class

solved by math zone for vu

☐ Variable

☐ Pointer

☐ Main function

```
    cout << "Constructor is called" << endl;
}
~Date() {
    cout << "Destructor is called" << endl;
}
};

int main() {
```

Answer:



Out put
Constructor is called
Dlstructor is called

```
cin >> students[i].name ;  
cout << "Enter the Student's Age : " ;  
cin >> students[i].age ;  
cout << "Enter the Student's GPA : " ;  
cin >> students[i].GPA ;  
}
```

Answer:



Output

Enter data for student #:

Enter the student's Name:

Enter student's Age:

Enter Student CGPA

TIME LEFT

88

Type here to search

Which is correct prototype of overloading of *new* operator?

Choices:

☐ `new * operator (size_t size);`

☐ `size * operator new (size_t, size);`

☐ `void * operator new (size_t size);`

☐ `void * operator new (size_t size);`

solved by math zone for vu

TIME LEFT

85



Type here to search



In the following statement:

Date operator ++(int),

Which operator is being overloaded for the Date class?

Choices:

☐ Pre-increment operator

solved by math zone for vu

☐ Addition operator

☐ Unary plus operator

☐ Post-increment operator

TIME LEFT

86



Type here to search



Question: 6 (Marks: 1)

Attempted

Keeping in mind the following code segment, which of the following options should not be input for the variable *i*?

```
int i;  
cin >> i;
```

Choices:

1

☐

10

☐

a

☐

0

☐

solved by math zone for vu

TIME LEFT

86

Question: 16 (Marks: 1)

Atten

What will be the output of the following code?

```
int i = 1;
while(i < 10) {
    if (i % 2 == 1)
        cout << i << " ";
}
```

Choices:

1 3 5 7 9

☒ solved by math zone for vu

2 4 6 8 10

1 5 9

1 7

Write the C++ code to overload stream extraction operator for class `Date` which have the following data members: `day`, `month` and `year`.

Q30

```
#include <iostream>
```

```
class Date {
```

```
private:
```

```
    int day;
```

```
    int month;
```

```
    int year;
```

```
public:
```

```
    Date(int d, int m, int y) : day(d), month(m), year(y) {}
```

```
    friend std::ostream& operator<<(std::ostream& os, const Date& date);  
};
```

```
std::ostream& operator<<(std::ostream& os, const Date& date) {  
    os << date.day << "/" << date.month << "/" << date.year;  
    return os;  
}
```

```
Date(int d, int m, int y) : day(d), month(m), year(y) {}  
  
friend std::ostream& operator<<(std::ostream& os, const Date& date);  
};  
  
std::ostream& operator<<(std::ostream& os, const Date& date) {  
    os << date.day << "/" << date.month << "/" << date.year;  
    return os;  
}  
  
int main() {  
    Date myDate(18, 8, 2023);  
    std::cout << "Date: " << myDate << std::endl;  
  
    return 0;  
}
```

Question 27 (Marks: 5)

```
#include <string.h>
using namespace std;
main()
{
    char string1[15]="String1";
    char string2[15]="String2";
    strcpy0;
    cout<<"After copy: "<<endl;
```

```
    cout<<"String 1:"<<string1<<endl;
    cout<<"String 2:"<<string2<<endl;
    strcpy(string3, string1, 3);
    cout << "strcpy (string3, string1, 3) = " << string3 ;
}
```

Output

After copy:

String 1: String1

String 2: String2

String 3: String1

87

```
cout<<"The sorted array is"<<endl;
```

Question: 28 (Marks: 5)

Attempt

```
cin >> students[i].name;  
cout << "Enter the Student's Age: ";  
cin >> students[i].age;  
cout << "Enter the Student's GPA: ";  
cin >> students[i].GPA;
```

Answer:



Output

Enter data for student #:

Enter the student's Name:

Enter student's Age:

Matrix (Matrix &);

In above statement '&' sign shows that a _____ of the object of type Matrix will be passed.

Choices:

☐ Function

☐ Reference

☐ Class

☐ Value

solved by math zone for vu

In C++, when accessing files randomly, which function is used to take the pointer to the position from where we want to start reading?

Choices:

☐ tellp()

☐ tellg()

☐ seekp()

☐ seekg()

c or D

TIME LEFT

84



Type here to search



What will the output of the following program?

```
#include <iostream>
using namespace std;
int main()
{
    int a, digit=78563412;
    a=digit%100;
    digit=digit/100;
```

Answer:



Virtual University

4-Year Experience



Cell No : 0342-7193822

All Services Available Very Reasonable Prices 100 % Correct
Solutions Assignments, GDBs, PDF Handouts, PDF Notes, Past
paper Files , Current Paper Officials
Special Guidelines (Sir Muhammad Usman) Owner YouTube
Channel Learn For Success
Cell No : 0342-7193822 (Only WhatsApp)