CS-602 Quiz-4 By Vu Topper RM
For Help = 03224021365 , 03164980094



بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

CS-602 Quiz-4 By Vu Topper RM
For Help = 03224021365 , 03164980094

Normalized cross product of two vectors on that surface provides real number.

No

Yes

The matrix generated by gluPerspective is multiplied by the current matrix, just as if glMultMatrix were called with the generated matrix. To load the perspective matrix onto the current matrix stack instead, precede the call to gluPerspective with a call to ----------.

A. gluPerspective
B. glRotated
C. glTranslated
D. glLoadIdentity

A parametric curve is one whose defining equations are given in terms of a ----------, common, independent variable called the parametric variable.

A. Double
B. Single
C. Triple
D. None of the given

To ensure a smooth transition from one section of a piecewise _____ to the next, we can impose various continuity conditions at the connection points

A. Non of the these
B. parametric curve
C. non parametric curve
D. polygon vector

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

CS-602 Quiz-4 By Vu Topper RM
For Help = 03224021365 , 03164980094

_____ sets the global idle call back to be 'func' so a GLUT program can perform background processing tasks or continuous animation when window system events are not being received.

A. glutDisplayFunc
B. glutIdleFunc
C. glutMainLoop
D. glutReshapeFunc

While building polygonal model of surfaces, we should use T-intersections.

Yes
No

If the current matrix (according to glMatrixMode) is multiplied by the translation matrix, with the product replacing the current matrix. That is, if M is the current matrix and T is the translation matrix, then M is replaced with ----------.

A. M+T
B. M*T
C. M/T
D. M-T

NURBS stands for ----------.

A. Non Universal Rational Binary Spline
B. Non Uniform Rational Beta Splines
C. Non Uniform Rational Binary Splines
D. Non Universal Rational Beta Splines

Another way to define a space curve by using intermediate points and the tangents at each end for making the curve

Yes
No

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

CS-602 Quiz-4 By Vu Topper RM
For Help = 03224021365 , 03164980094

If we assign a different value to the parametric variable for the intermediate point, then we obtain different values for the coefficients. This, in turn, means that a different curve is produced, although it passes through the ---------- three points.

A. Isolate
B. Same
C. None of the given
D. Different

Every point on a curve has a straight line associated with it called the _____

A. tangent line
B. None of the given
C. State line
D. curved line

A tangent vector certainly defines the slope at one end of the curve, but a vector has characteristics of.....

A. direction
B. magnitude
C. None of the given
D. both direction and magnitude

The mathematics of parametric equation is the basis for ---------- curves.

A. Hercules
B. Hermite
C. Tangent
D. Bresenham

Imagine a curve in three-dimensional space, each point on the curve has a unique set of coordinates: a specific x value, y value, and z value. Each

Vu Topper RM

coordinate is controlled by a ---------- parametric equation.

A. Separate
B. Opposite
C. None of the given
D. Similar

A space curve can be confined to a plane.
True
False

To convert the information in the A matrix into that required for the P matrix, we do some simple matrix algebra, First we have UA=UNP then Simply A = ----------

A. UN
B. None of the given
C. UP
D. N

Curve and surface equations can be expressed in either a parametric or a nonparamehic form.
True
False

The curve is always contained within the _____ of the control points

A. Convex Hull
B. Subdivision
C. Tangents
D. None of Above

Brenstien polynomial functions are the basic functions of _____ curves.

A. Both NURBS and Bazier

Vu Topper RM

B. Bezier
C. NURBS
D. None of the given

Bezier curve is tangent to the lines connecting _____.
A. Last two points
B. Fist two points and last two point
C. First two points
D. None of the given

_____ can cause cracks to appear intermittently in the surface
A. Rong Measurements
B. T-Intersection
C. None of above
D. Icosahedron

The value returned is a unique small integer identifier for the window. The range of allocated identifiers starts at ----------. This window identifier can be used when calling glutSetWindow.
A. Two
B. Zero
C. One
D. Three

glutReshapeWindow requests a change in the size of the current window. The width and height parameters are size extents in pixels. The width and height must be ---------- values.
A. Negative
B. Neutral
C. Positive
D. Non of the given

Vu Topper RM

CS-602 Quiz-4 By Vu Topper RM
For Help = 03224021365 , 03164980094

Silhouette edges occur when dot product of surface normal vector and the view vector is _____.

A. None of the given
B. Both zero and one
C. One
D. Zero

End points and an intermediate point on the curve, then we now ---------- quantities that we can express in terms of these coefficients (3 points x 3 coordinates each), and we can use these three points to define a unique curve.

A. Nine
B. Three
C. Two
D. Six

The basis functions fi(u) in Bezier curve must be symmetric with respect to u and (u-2)
Rue
False

the French mathematician who made significant contributions to our understanding of cubic and quadratic polynomials.

A. None of above
B. Hermit
C. Leonhard Euler
D. Bezier

Geometric patterns that is repeated at ever smaller scales to produce irregular shapes and surfaces are called _____

A. Segments
B. Geometric patterns

VuTopper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

C. Animated components
D. Fractals

The glClearColor function specifies the red, green, blue, and alpha values used by glClear to clear the color buffers. Values specified by glClearColor are clamped to the range ----------.

A. [0,1]
B. [0,-1]
C. [-1,1]
D. [.5,1]

_____ sets the reshape callback for the current window. The reshape callback is triggered when a window is reshaped.

A. glutIdleFunc
B. glutDisplayFunc
C. glutMainLoop
D. glutReshapeFunc

Bezier curve can represent the more complex piecewise _____ curve.

A. Cubic
B. Polynomial
C. None of above
D. Exponential

The degree of a Bezier curve is equal to n-1, where n is the number of control points

No
Yes

Calculating the normalized cross product of two vectors on that surface provides ---------- vector.

Vu Topper RM

A. Unit
B. Space curve
C. Plane
D. Normal

A mathematical fractal is based on an equation that undergoes iteration, a form of feedback based on recursion
Yes
No

End points and an intermediate point on the curve, then we now ---------- ---------- quantities that we can express in terms of these coefficients (3 points x 3 coordinates each), and we can use these three points to define a unique curve.
A. Nine
B. Six
C. Three
D. Two

To convert the information in the A matrix into that required for the P matrix, we do some simple matrix algebra. First we have GP = ---------- ----------
A. NU
B. UNP
C. UP
D. NP

_____ is based on characteristic size or scale
A. Euclidean Geometry
B. Traditional Geometry
C. Fractal Geometry
D. None of Above

Vu Topper RM

CS-602 Quiz-4 By Vu Topper RM
For Help = 03224021365 , 03164980094

Fractals are normally the result of an iterative or ---------- construction.

A. Decremental
B. Recursive
C. Productive
D. Multiplicative

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

CS-602 Quiz-4 By Vu Topper RM
For Help = 03224021365 , 03164980094

Vu Topper RM

Visit My YouTube Channel
For Subjective and More
Important Files
Channel Name = #VuTopperRM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے