Professional Online Academy Vu Topper RM

CS604-P Operating System Practical

Update MCQ'S Quiz-1 File

Follow Us on YouTube:
@vutopperrm

For More Help Contact What's app Me!!!
Number's = # 0322-4021365, 0316-4980094

Rizwan Manzoor
Vu Topper RM



بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

VirtualBox is developed by the _____.
Reload Math Equations
Oracle Corporation
Microsoft Corporation
DELL
IBM Corporation

_____ is the file descriptor for the write end of the pipe.
Reload Math Equations
fd[3]
fd[1]
fd[0]
fd[2]

In Linux _____ command is used to create the new directory.
Reload Math Equations
mkdir
maked
make
dir

Which of the following is Linux distribution.
Reload Math Equations
DOS
WinNT
Ubuntu
MYSQL

In Unix/Linux, a Pipe uses _____ buffering.
Bounded
Zero
Unbounded
Multiple

VuTopper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

In Linux environment, command line window is called the _____.
Reload Math Equations
bell
tell
well
shelI

In Unix/Linux environment _____ system call is used for writing to the pipe.
Reload Math Equations
written()
through()
write()
read()

In Unix/Linux environment _____system call is used for creating pipe between two related processes.
Reload Math Equations
system()
connection()
communicate()
pipe()

_____ is the file descriptor for the read end of the pipe.
Reload Math Equations
fd[1]
fd[2]
fd[3]
fd[0]

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:1 **(Marks:1)** **Vu-Topper RM**

In Disk Free Space Management by using bit map and bit vector each block is represented by _____.

A. 1 bit
B. 2 bit
C. 3 bit
D. 4 bit

Question No:2 **(Marks:1)** **Vu-Topper RM**

Two-dimensional array can be traversed in column major order if is traversed _____wise.

A. hash
B. diagonal
C. column
D. row

Question No:3 **(Marks:1)** **Vu-Topper RM**

In the following declaration of two dimensional integer array:int A[1024][1024];Integer array A has _____number of rows.

A. 512
B. 256
C. 1024
D. 1024x 1024

Question No:4 **(Marks:1)** **Vu-Topper RM**

In _____the pager brings only those necessary pages into memory that are needed.

A. Demand paging
B. Self paging
C. hash paging
D. push paging

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:5 **(Marks:1)** **Vu-Topper RM**

Overhead of Bit-Map in Free-Space Management is calculated as:

A. overhead = (diskSize / freespaceSize)

B. overhead = (diskSize / bit-vactorSize)

C. overhead = (fileSize / blockSize)

D. overhead = (diskSize / blockSize)

Question No:6 **(Marks:1)** **Vu-Topper RM**

Page Replacement Algorithm LRU is called:

A. Low Reset UP

B. Low Resolution Used

C. Least Recently Used

D. Low Reset Used

Question No:7 **(Marks:1)** **Vu-Topper RM**

In _____Page Replacement algorithm. If we use the recent past as an approximation of the near future, then we will replace the page that has not been used for the longest period of time.

A. Low Resolution Used (LRU)

B. Least Recently Used (LRU)

C. Low Reset Used (LRU)

D. Low Reset UP (LRU)

Question No:8 **(Marks:1)** **Vu-Topper RM**

Least Recently Used (LRU) page replacement algorithm basically works on the concept that the pages that are heavily used in _____instructions are likely to be used heavily in next instructions.

A. previous

B. push

C. hash

D. pop

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:9 **(Marks:1)** **Vu-Topper RM**

Two-dimensional array can be traversed in row major order if it is traversed _____wise.

A. column
B. row
C. hash
D. diagonal

Question No:10 **(Marks:1)** **Vu-Topper RM**

In Disk Free Space management free space list is implemented as a _____.

A. Bit Sap or Bit Wap
B. Bit Nap or Bit Tap
C. Bit Cap or Bit Tap
D. Bit Map or Bit Vector

Question No:11 **(Marks:1)** **Vu-Topper RM**

In Banker algorithm Need data structure is used. If_____, then process Pi may need k more instances of resource type Rj to complete the task.

A. Need[i,k] = j
B. Need[i,j] = k
C. Need[j,i] = k
D. Need[k,j] = k

Question No:12 **(Marks:1)** **Vu-Topper RM**

In dining philosopher problem all the five philosophers sitting around the round circular table have _____ chopsticks.

A. 3
B. 4
C. 5
D. 10

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Vu Topper RM

Question No:13 **(Marks:1)** **Vu-Topper RM**

In dining philosopher problem all the five philosophers can do two things _____.

A. thinking and eating
B. playing and eating
C. laughing and eating
D. sleeping and eating

Question No:14 **(Marks:1)** **Vu-Topper RM**

Logical data refers to the instruction or data stored in the _____.

A. Physical memory location
B. Hash table space
C. Process address space
D. Secondary memory location

Question No:15 **(Marks:1)** **Vu-Topper RM**

The address seen by memory unit i.e. the address loaded into the memory address register is commonly referred to as the _____.

A. Logical address
B. Simple address
C. Physical address
D. Complex address

Question No:16 **(Marks:1)** **Vu-Topper RM**

In Banker's algorithm we can say that a system is in a _____if all of the processes in the system can be executed to termination in some order.

A. reverse state
B. safe state
C. stop state
D. halt state

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:17 **(Marks:1)** **Vu-Topper RM**

The address generated by CPU is commonly referred to as the _____.

A. Complex address
B. Logical address
C. Sample address
D. Physical address

Question No:18 **(Marks:1)** **Vu-Topper RM**

The Solution of Dining Philosopher Problem is used to avoid _____.

A. Isolation condition
B. Deadlock condition
C. Separation condition
D. Multitasking condition

Question No:19 **(Marks:1)** **Vu-Topper RM**

In First-Come-First-Served (FCFS) scheduling algorithm waiting times of P1 and P2 are 8 and 9 seconds respectively, their average waiting time will be.

A. 8 seconds
B. 10 seconds
C. 8.5 seconds
D. 9 seconds

Question No:20 **(Marks:1)** **Vu-Topper RM**

In Linux _____command is used to show the listing of all the files in current working directory.

A. is
B. bs
C. ms
D. ds

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:21 **(Marks:1)** **Vu-Topper RM**

In Unix/Linux environment _____ system call is used for reading from the pipe

A. written()

B. read()

C. communicate()

D. write()

Question No:22 **(Marks:1)** **Vu-Topper RM**

To install the Linux on Virtual Machine we need to install the _____software on our system.

A. Python

B. MYSQL

C. PHP

D. Virtual Box

Question No:23 **(Marks:1)** **Vu-Topper RM**

_____command is used to show the current working directory.

A. pss

B. pwd

C. mms

D. ps

Question No:24 **(Marks:1)** **Vu-Topper RM**

In First-Come-First-Served (FCFS) scheduling algorithm turnaround times of P1 and P2 are 10 and 11 seconds respectively, their average turnaround time will be.

A. 10.5 seconds

B. 10 seconds

C. 9 seconds

D. 11 seconds

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:25 **(Marks:1)** **Vu-Topper RM**

In Linux environment we can create the thread by using the _____ system call.

A. exce()

B. pthread_create()

C. fork()

D. execlp()

Question No:26 **(Marks:1)** **Vu-Topper RM**

In Unix/Linux environment for inter-process communication for related processes we used _____.

A. connection

B. pipe

C. linklist

D. symbol

Question No:27 **(Marks:1)** **Vu-Topper RM**

Suppose there are 16 number of pages so number of bits needed for p is:

A. 1

B. 4

C. 3

D. 2

Question No:28 **(Marks:1)** **Vu-Topper RM**

Logical Address generated by the CPU is divided into two parts: a page number (p) and a page offset (d) and is calculated by following formula:

A. p + d

B. p / d

C. p % d

D. p * d

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:29 **(Marks:1)** **Vu-Topper RM**

Suppose there are 32 number of frames so number of bits needed for f is:

A. 5
B. 4
C. 3
D. 2

Question No:30 **(Marks:1)** **Vu-Topper RM**

_____has the significant effect on computer performance.

A. Queue paging
B. Demand paging
C. Stack paging
D. Self paging

Question No:31 **(Marks:1)** **Vu-Topper RM**

First-Come-First-Served (FCFS) Scheduling algorithm used the _____data structure.

A. Link List
B. Stack
C. Last in Last Out (LIFO)
D. First in First Out (FIFO)

Question No:32 **(Marks:1)** **Vu-Topper RM**

In Linux environment _____function returns the ID of the calling thread.

A. bthread()
B. Xthread()
C. mthread()
D. pthread_self()

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:33 **(Marks:1)** **Vu-Topper RM**

In Linux _____command is used for changing your current working directory.

Cd

Question No:34 **(Marks:1)** **Vu-Topper RM**

As long as there is no_____, the effective access time is equal to the memory access time.

A. queue faults
B. demand faults
C. stack faults
D. page faults

Question No:35 **(Marks:1)** **Vu-Topper RM**

In case producer process has not yet produced any item and consumer process want to consume an item from the buffer than there will be buffer_____ message.

A. full
B. empty
C. busy
D. lock

Question No:36 **(Marks:1)** **Vu-Topper RM**

We have to implement the Producer-Consumer problem by using _____.

A. Programmable Read-Only Memory (PROM)
B. Unshared Memory
C. Read-Only Memory (ROM)
D. Shared Memory

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:37 **(Marks:1)** **Vu-Topper RM**

Producer-Consumer problem is considered as the process _____ problem.

A. receiving
B. limitation
C. blocking
D. synchronization

Question No:38 **(Marks:1)** **Vu-Topper RM**

In Banker algorithm Max data structure is used. If_____, then process Pi can request maximum k instances of resource type Rj.

A. Max[i,j] = k
B. Max[k,j] = i
C. Max[j,i] = k
D. Max[i,k] = j

Question No:39 **(Marks:1)** **Vu-Topper RM**

In _____a process must enter the maximum number of instances that he may need in the future.

A. Banker algorithm
B. College algorithm
C. University algorithm
D. Lotus algorithm

Question No:40 **(Marks:1)** **Vu-Topper RM**

In Unix/Linux environment pipe() system call return the _____descriptors.

A. Two
B. four
C. six
D. five

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:41 **(Marks:1)** **Vu-Topper RM**
In order to add the Linux distribution in VirtualBox/VMWare software, Linux distribution file should have _____extension.

A. .iso
B. .exe
C. .doc
D. .pdf

Question No:42 **(Marks:1)** **Vu-Topper RM**
In Linux environment executable files have the _____extension.

A. .pdf
B. .doc
C. .mms
D. .out

Question No:43 **(Marks:1)** **Vu-Topper RM**
In the following declaration of two dimensional integer array:
int A[1024][1024];
Integer array A has _____number of rows.

A. 1024x 1024
B. 1024
C. 256
D. 512

Question No:44 **(Marks:1)** **Vu-Topper RM**
In _____the pager brings only those necessary pages into memory that are needed.

A. Demand paging
B. Hash paging
C. Push paging
D. Self paging

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Question No:45 **(Marks:1)** **Vu-Topper RM**

In Disk Free Space Management by using bit map and bit vector each block is represented by _____.

A. 3 bits
B. 4 bits
C. 2 bits
D. 1 bit

Question No:46 **(Marks:1)** **Vu-Topper RM**

Overhead of Bit-Map in Free-Space Management is calculated as:

A. overhead = (diskSize / freespaceSize)
B. overhead = (diskSize / blockSize)
C. overhead = (fileSize / blockSize)
D. overhead = (diskSize / bit-vactorSize)

Question No:47 **(Marks:1)** **Vu-Topper RM**

Two-dimensional array can be traversed in column major order if is traversed _____wise.

A. row
B. column
C. diagonal
D. hash

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

Visit My YouTube Channel
For Subjective and More
Important Files
Channel Name = #VuTopperRM

Vu Topper RM

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365