Cs201 quiz today made by Abdullah

1.which software testing refers to tests that do not rely on knowledge of software's interior composition

(white-box testing)

2.The language understood by a computer without translation is known as:

(Machine language)

3.which one is a unary operator?

(NOT)

4.In the case of highly standardized language, compiler designers often provide feature ,sometimes called

(Language extension)

5.Under_____paradigm a program is viewed as an entity that accept inputs and produces outputs

(functional)

6.in c++,symbolic representation of "Assignment" operator is _____

(=)

7. A translator which takes assembly language program as input & produce machine language code as output is know as:

(Assembler)

8.Which of the following statement is used in c++.

(cout<<)

9.We used_____ to reduce unnecessary dependencies or effects on other module

(information hiding)

10.The memory allocation functions return a chunk of memory with a pointer of type_____

(void)

Abdullah

11.default constructor takes_____

(no parameters)

12. In a class we have_____constructor(s).

(many)

13.which one of the following in mandatory preprocessor directive for c++?

(#include <iostream>)

14.Header files provide_____so the program running on the operating system can run without an error on the other system

(accessibility)

15.With the use of dynamic allocation of memory,the system resources can be_____

(Used efficiently)

16._____for parameters is also done for inline functions.

(automatic type checking)

17.We should not use such variable names that are starting with_____because in c++. There are lots of internal constants and symbolic names that start with it

(double underscore)

18.Which of the following code segment represents a left a left shift operator?

(Cout<<1)

19. c++ was developed by _____

(bejama stoustrup)

20. special name which is substituted in code by its definition and as a result we get an expanded code is called

(macro)

21. a= a+1; can be written as____

(a + = 1;)

22. The compilar generates_____automatically

(constuctors)

23.The data numbers of the class are initialized_____

(At runtime)

24._____for parameters is also done for infine functions

(automatic type checking)

25.AN instance of a class is called_____

(object)

26. with the use of dynamic allocation of memory. The system resources can be _____

(used efficiently)

27.When we include header file in the angle brackets the compiler search for it in_____

(specific directory)

28._____ is a special type of pointer we have to castit before we use it.

(void)

29.Multiplicative, additive and assignment operators are _____ operators.

(binary)

30.a =a+1; can be written as_____

(a + = 1;)

31.The compiler generates_____automatically

(constructors)

32.The data members of the class are initialized_____

(at runtime)

33._____for parameters is also done for inline functions

(automatic type checking)

34.AN instance of class of a class is called_____

(object)

35.with the use of dynamic allocation of memory , the system resources can be_____

(used efficiently)

36.for converting a void type pointer ptr, the correct syntax is:

(Int* ptr)

37.header files provide____so the program running on one operating system can run without an error on the other system

(reliability)

38.a pointer with value null is defined in the header files____and____

(stdlib.h,stdef.h)

39.molic function returns____to the ____from the available memory

(void pointer,starting of chunk of memory…from the array)

40.constructor is a special function, called whenever we_____

(Instantiate an object of a class)

41.we should not use such variable names that are starting with_____because in c++there are lots of internal constant….with it

(double underscope)

42.CONStructor is itself a_____of c++ and_____

(function can be overloaded)

43what is the other name of variable

(Identifier)

44.what will be the output of the following c++ code?

#include<iostream.h>

#define max 100

Main()

{#ifdef max

Cout<"hello world"

(error)

45. In shifting operations if zero is inserted at the left most bit,the negative number will become a___number

(positive)

46.The compilar generates ____automatically

(constructors

47.A class is____

(a member function)

48.bugs can occur due to_____

(uninitialized data)

49.the heap memory structure_____

(constantly change in size

50 how many bits form a byte

(8)

51.the function calloc takes two arguments. First argument is the_____ and the second argument is the_____

(require space in terms of number ,size of space)

52the main advantage of function overloading is that___

(the program become more redable)

53.A pointer with value null is defined in the header files_____and_____

(stdlib.h…..)

54.the_____is the increment operator in c++

(++)

55.what will be the output of the given code)

X=32; y=45;

(x=24 y=46)

56.the constructor constains_____

(no returntype)

57.multiplicative,additive and assignment operators are_____ operators

(Binary)

58 for accessing data members we use____operator

(dot)

59.in a class we can have_____constructor

(Only one)

60.object code is machine code but it is not____and _____

(relocatable ,executable)

61.shifting the binary number Is similar to shifting the __number

(decimal)

62.The____is called automatically when an object destroys

(destructor)

63.an integer uses four bytes and the integer calculation occur in___bytes

(2byte)

64.which of the following code segment represents a left shift operator?

(cout<<1)

65. Raid stand for__

(redundant array of inexperience device)

66. windows operating system may itself takes memory from____

(list)

67what is the storage space of double data type

(8)

68. dynamic memory allocation uses____Whereas static memory allocation uses_____

(Heap , stack)

69.which one is the correct example of a unary operator

(-)

70.which is the output of following code

(b correct answr)

71. array indexes start from_____

0

72.which one of the following is used to perform bit-wise exclusive or operation

(^)

73.getche() is a_____function and defined in_____header file

(build-in function,iostream.h)

74.In c++, a variable can be declared anywhere in the program, this will increase_____

(Portability)

75the compilar use a name mangling technique to_____

Compile the function

76.macros are categorized into type(s)

Two

77constructor is a special function called whenever we____

Instantiate an object of a clas

Abdullah