Q.1 The coding of a program is translated into machine language by _____.

A. Loader
B. Debugger
C. Linker
D. Compiler

Q.2 Short data type store _____ bytes of memory.

A. 1
B. 3
C. 2
D. 4

Q.3 Normally, the float data type is half of the size of _____.

A. int
B. double
C. char
D. short

Q.4 Which of the following expression is correct in C/C++ language?

A. Y + X = 7
B. X + 5 = Y + 7
C. 3 = X + 3
D. X = X + 3

Q.5 C/C++ has many libraries which contain variables and function names normally starting with ___.

A. Semi-Colon
B. Hyphen
C. Underscore
D. Hash

Q.6 Which data type from the following will take lesser space in memory?

A. short
B. char
C. int
D. float

VU TOOLKIT

Q.7 A binary operator has ____ operands.

A. Four

B. Two

C. Three

D. One

Q.8 What will be the output of the following code? int x = 15; int y = 10; int z = 5; cout << x * x - 4 * y * z;

A. -25

B. 5

C. 25

D. -5

Q.9 Suppose we have an integer variable named “num” with 4567 as its value, then what will be the resulting value for the expression “num/100”?

A. 45

B. 456.7

C. 4

D. 456

Q.10 What will be the output of following C++ program? #include <iostream> using namespace std; int main() { int num1 = 10; int num2 = 20/3; int sum; sum = num1 + num2; cout << "The sum is: " << sum << endl; return 0; }

A. The sum is: 19

B. The sum is: 20

C. The sum is: 16

D. The sum is: 18

VU TOOLKIT