Q.1 What will be the output of the following code? int i = 0; while(i!=15){ cout << i << " "; i = i + 5; }

A. 0 5

B. 1 5 10

C. 0 5 10

D. 5 10

Q.2 Which of the following C++ statements is used to show output on the screen?

A. cout

B. cget

C. cerr

D. cin

Q.3 In C++, which of the following option has the correct meaning of the expression “a <= b” ?

A. a is less than or equal to b

B. a is less than b

C. a is greater than or equal to b

D. a is greater than b

Q.4 What will be the output of following program? #include <iostream> using namespace std; int main() { int x = 5; while (x > 0) { x--; } cout << "Final value of x: " << x << endl; return 0; }

A. Final value of x: 5

B. Final value of x: 0

C. Final value of x: 2

D. Final value of x: 6

Q.5 In C/C++, the algebraic expression (b2-4ac) / 2a can be written as:

A. (b*b – 4*a*c) / (2*a)

B. b*b – 4*a* c/ 2*a

C. b*b – (4*a*c) / 2*a

D. b*b – 4* a*c / (2*a)

Q.6 What will be the output of the following code? int i = 1; while(i<10){ if (i % 2 == 0) cout << i << “ ”; i++; }

A. 2 4 8 10

B. 2 4 6 10

C. 2 4 6 8

D. 1 3 5 7

Q.7 Which of the following is an example of logical operator?

A. &&,||

B. <,>

C. /,%

D. +,*

Q.8 Which of the following option is used when working with complicated expressions in C++ ?

A. []

B. /

C. ()

D. {}

Q.9 Which of the following is an example of repetition structure?

A. cond

B. while

C. if-else

D. if

Q.10 Which of the following C++ statements is used take input from the user?

A. cget

B. cerr

C. cin

D. cout

VU TOOLKIT