Q.1 If we pass more than one arguments to a function then they are separated by _____.

A. Colon :

B. Double quotes "

C. Semicolon ;

D. Comma ,

Q.2 _____ will be used for clarity and to force the order of evaluation in an expression.

A. ' '

B. " "

C. ()

D. []

Q.3 Which of the following is not a valid variable name in C++?

A. @studentName

B. nameOfStudent

C. _studentName

D. NameOfStudent

Q.4 While loop becomes infinite in which scenario _____.

A. Condition contains arithmetic operators

B. When the condition is always False

C. When the condition is always True

D. Condition contains logical operators

Q.5 _____ is a substitute of multiple if statement.

A. If..elseif statement

B. Break statement

C. Continue statement

D. Default statement

Q.6 Which of the following is the right syntax to declare a variable in C++?

A. DataType = VariableName;

B. DataType VariableName;

C. (DataType) VariableName;

D. VariableName Datatype;

Q.7 _____ Loop executes atleast one times.

A. While

B. Inner

C. For

D. Do while

Q.8 We use _____ to include all those functions in our program which are located in different files.

A. Compiler

B. Debugger

C. Linker

D. Loader

Q.9 Which of the following is the correct operator to compare the values of two variables?

A. ==

B. =

C. *=

D. :=

Q.10 Telling a computer what to do, is called _____.

A. Compiling

B. Implementing

C. Programming

D. Designing

VU TOOLKIT