Q.1 Which operator has the highest precedence? (*, -, /, +)

A. - has the highest precedence

B. + has the highest precedence

C. + and - both have the same highest precedence

D. * and / both have the same highest precedence

Q.2 How many times the following loop will execute? int j = 3; while(j > 0) { cout << "Statements" << endl; j -= 2; }

A. 0

B. 2

C. 3

D. 1

Q.3 _____ Loop executes atleast one times.

A. Inner

B. Do while

C. While

D. For

Q.4 Identify the logical error in the following if condition If ((i < 5) && (i > 15))

A. & will be used instead of &&

B. && cannot be used with if condition

C. Condition is always true

D. Condition is always false

Q.5 What will be the values of variables x and y after executing the following code if x = 33 and y = 19? if(x % y != 0) { x++; y--; }

A. x = 34, y = 18

B. x = 22, y = 14

C. x = 30, y = 36

D. x = 14, y = 36

Q.6 < , <= , > , >= are called _____ operators.

A. Arithmetic

B. Relational

C. Conational

D. Logical

Q.7 If x = 11, and x %= 3, then value of x will be _____.

A. 11

B. 3

C. 0

D. 2

Q.8 In the following nested For Loop, which loop will run most number of times? for(int i = 0; i < 5; i++) { for(int k = 0; k < 5; k++) { ..... } }

A. Inner loop

B. Both loops run equal number of times

C. Outer loop

D. Depends upon the statements in the inner loop's body

Q.9 Find the syntax error in the following piece of code? if (x > y); cout<<" x is greater than y "; else cout<<"y is greater than x";

A. Condition in the if statement is wrong

B. Semicolon should not be after the if statement

C. Braces not given for if and else blocks

D. No error in the code

Q.10 Which of the following is not the subcategory of the system software?

A. Application software

B. Operating system

C. Utilities

D. Device drivers

VU TOOLKIT