Q.1 Stack and Queue can be implemented using _____,

A. Binary Search Tree

B. AVL Tree

C. Singly Link List

D. Binary Tree

Q.2 Consider the following expression: P= A*B+C-D In the above expression "-" is a _____ operator.

A. Technical

B. Unary

C. Logical

D. Binary

Q.3 Stack.push(15) will push 15 on _____.

A. Bottom of Stack

B. Top of the Stack

C. Middle of the Stack

D. Anywhere in the Stack

Q.4 An efficient program executes faster and helps in _____ the usage of resources like memory and disk.

A. Minimizing

B. Increase

C. Maximizing

D. Equalizing

Q.5 Whenever we call a function, the compiler makes a stack, the top element of the stack is _____ of the function.

A. Return address

B. First argument

C. Last argument

D. Variable name only

Q.6 int * i = new int [10]; Above given code will:

A. Create 10 pointers of integer type

B. Allocate memory for 10 integers

C. Create an integer having value 10

D. Allocate memory for 9 integers

Q.7 A template is a function or class that is written with a _____data type.

A. Generic

B. Specific

C. Definite

D. Logical

Q.8 Which operation of queue data structure is used to get front element from the queue and then remove it from the queue?

A. remove()

B. dequeue()

C. front()

D. enqueue()

Q.9 Before using the push method of stack, the user must call the _____ method.

A. isEmpty();

B. push();

C. isFull();

D. pop();

Q.10 If we use singly linked list to implement list, then there is an issue that it gives difficulty when we:

A. Move backward in the list

B. We will increase its size

C. We will decrease its size

D. Move forward in the list

VU TOOLKIT