Q.1 Consider the following expression: P= A*B+C-D In the above expression "-" is a _____ operator.

A. Binary

B. Logical

C. Technical

D. Unary

Q.2 Consider the linked list having data [6, 72, 35, 65, 25] stored in it. While current pointer is pointing to memory location having 35 stored in it. What will be the resultant linked list after calling add(18) function on the given linked list.

A. 6, 72, 18, 35, 65, 25

B. 6, 72, 35, 18, 65, 25

C. 6, 18 ,72, 35, 65, 25

D. 6, 72, 35, 65, 25, 18

Q.3 Consider the linked list implementation of a stack. Which of the following node is considered as Top of the stack?

A. Any node

B. First node

C. Middle node

D. Last node

Q.4 In singly linked list a node consists of two parts:

A. Two objects

B. Two pointers

C. Object and pointer

D. Object and structure

Q.5 Which of the following function don't belongs to the stack class?

A. crash()

B. top()

C. push()

D. pop()

Q.6 A software solution is said to be efficient if it solves the problem _____ .

A. by consuming more hardware resources.

B. by using some extra resources.

C. within its resource constraints.

D. within no time.

Q.7 Consider we have performed the following operations on a stack of size 5. Push(10); Push(20); Push(30); Pop(); Pop(); Push(40); Push(50); Pop(); After the completion of all operations, the number of element present on stack are ____.

A. 3

B. 2

C. 4

D. 1

Q.8 The usage of the class of a data structure causes the code of the program

A. Lengthy

B. Complicated

C. Simplifies

D. Difficult

Q.9 _____ is a collection of elements arranged in a linear order.

A. Binary Search Tree

B. AVL Tree

C. Stack

D. Heap

Q.10 In singly linked list a node comprises of _____ field/s.

A. One

B. Four

C. Three

D. Two
