Q.1 isEmpty() method of stack class will return true when:

A. Stack is full

B. Stack is partially empty

C. Stack is not empty nor full

D. Stack is empty

Q.2 Consider we have performed the following operations on a stack of size 5. Push(10); Push(20); Push(30); Pop(); Pop(); Push(40); Push(50); Pop(); After the completion of all operations, the number of element present on stack are ____.

A. 4

B. 2

C. 3

D. 1

Q.3 The _____ method of list will position the currentNode and lastCurrentNode at the start of the list.

A. Back

B. Start

C. Next

D. Remove

Q.4 The expression DE+H* is called_____

A. Infix expression

B. Hybrid expression

C. Postfix expression

D. Prefix expression

Q.5 Head node pointer always points to the _____ of the linked list?

A. newly added node

B. current node

C. first node

D. last node

Q.6 "set()" method of list class is used to:

A. Set the value of pointer

B. Set the value of Null Nodes

C. Set the value of lvalue

D. Set the value of object

Q.7 Which operation of queue data structure is used to get front element from the queue and then remove it from the queue?

A. enqueue()

B. dequeue()

C. remove()

D. front()

Q.8 Consider the linked list implementation of a stack. Which of the following node is considered as Top of the stack?

A. Middle node

B. Any node

C. Last node

D. First node

Q.9 In the calling function, after the execution of the function called, the program continues its execution from the _____after the function call.

A. Previous line

B. Beginning

C. Next line

D. End

Q.10 The next field in the last node in a singly-linked list is set to_____.

A. 1

B. false

C. NULL

D. 0

VU TOOLKIT