Q.1 Stack can be implemented by which of the following data structure?

A. AVL
B. BST
C. Skip list
D. Array

Q.2 Stack.push(15) will push 15 on _____.

A. Anywhere in the Stack
B. Middle of the Stack
C. Top of the Stack
D. Bottom of Stack

Q.3 What will be the postfix expression of following infix expression? A*B/C+D-E

A. A B + C D/ + E –
B. A B * C / D + E –
C. A B * C + D E/ –
D. A B / C * D + E –

Q.4 When add() operation of a linked list is called the following action is done

A. last node is removed to add new
B. Set the next pointer of last current node
C. A new node is made
D. Current node is removed to add new

Q.5 In singly linked list "next" field of node contains:

A. Address of next node
B. Object of current node
C. Address of head node
D. Object of next node

Q.6 add(12) method of linked list class will:

A. Add 12 pointers in linked list
B. Add 12 values in the linked list
C. Add 12 as value in linked list
D. Add 12 nodes in linked list

Q.7 In the linked list implementation of the stack class, where does the push member function places the new entry on the linked list?

A. After all other entries that are greater than the new entry.

B. At the head

C. After all other entries that are smaller than the new entry.

D. At the tail

Q.8 Which one of the following operations returns and removes top value of the stack?

A. First

B. Top

C. Push

D. Pop

Q.9 Consider the following expression: P= A*B+C-D In the above expression "-" is a _____ operator.

A. Logical

B. Technical

C. Binary

D. Unary

Q.10 What will be postfix expression of following infix expression? 4*1↑7+2

A. ↑ * + 4 1 7 2

B. 4 1 7 ↑ * 2 +

C. 4 1 ↑ 7*2+

D. 4 1 7 2 ↑ * +
