Virtual University

بسم الله الرحمن الرحيم

Mickey ch

CS301-(Data Structures)

Mid Term Important Solved Mcqs

By Mickey Ch

80 to 100% Marks

We offers:

- LMS Handling
- Assignments
- Quizes
- GDB
- Mid&Final Term important Notes

We also offers:

- CS 619 Projects

Follow us on youtube:

@mickeych8525

Whatsapp

#0333-6166150

Email:

mickeych96@gmail.com

Learning With Mickey ch

Q NO 01:

Inarraylisttheworstcaseofremovinganelementis

A. Toremoveanelementfromtheendofthelist
B. Toremoveanelementfromthemiddleofthelist
C. Toremoveanelementfromthestartofthelist
D. Wecannotremoveelementfromanarraylist

Q NO 02:

Whenanexecutableprogramrun,itisloadedinthememoryand becomesa_____.

A. Thread
B. .hfile
C. Process
D. Noneoftheabove

Q NO 03:

"+"isa_____operator.

A. Unary
B. Binary
C. Ternary
D. Noneoftheabove

Q NO 04:

The first statement in the given code is called as:

A. Binary Declaration
B. Pre Class Declaration
C. Forward Declaration
D. Post Class Declaration

Q NO 05:

In level-order traversal for Binary Search Tree,_____data structure is used.

A. Queue
B. Stack
C. Tree
D. Heap

Q NO 06:

When a function calls another function, the parameters and return address of the calling function are put in_____.

A. Stack
B. Tree
C. Heap
D. Pointer

Q NO 07:

In the perspective of memory organization each process is divided into___sections.

A. 2
B. 4
C. 6
D. 8

Q NO 08:

To create a reference variable we need to use__sign.

A. Ampersand
B. Dollar
C. Asterisk
D. sigma

Q NO 09:

Mickey ch

Whatsapp#0333-6166150

Learning With Mickey ch

Whenever a node is deleted from a binary search tree,___has to be maintained.

A. In Order Traversal
B. Any Traversal can be maintained
C. Post order Traversal
D. Pre order Traversal

Q NO 10:

The_____sign before the name of the variable meansthat the address of the variable is beingpassed :

A. ||
B. ::
C. &
D. #

Q NO 11:

If we return the reference of a local variable from a function itwill cause :

A. Refrence Overloading
B. Duplication of local variables
C. Deletion of local variables from memory
D. Dangling refrence

Q NO 13:

In Preorder traversal of a binary tree the second step is____.

A. Traverse the right subtree
B. Traverse the root
C. Traverse the leaf nodes
D. Traverse the left subtree

Q NO 14:

parameter passing (by value or by reference) is similar toPASCAL.

A. C++
B. COBOL
C. JAVA
D. FORTRAN

Q NO 15:

Function signatures are also called :

A. Function Prototype
B. Function Overloading
C. Function Defination
D. Function Overriding

Q NO 16:

In a complete binary tree the number of nodes at level 5 are

A. 32
B. 30
C. 23
D. 40

Q NO 17:

The abstract data type refers to the basic mathematical concept that defines the

A. Variable
B. Functions
C. Pointer
D. Data type

Q NO 18:

If we return the reference of a local variable from a function it will cause:

A. Dangling reference

Mickey.ch

Whatsapp#0333-6166150

B. reference overloading
C. duplication of local variable
D. deletion of local variable from memory

Q NO 19:

Which data structure is needed to convert infix expression to postfix expression?

A. Tree
B. Stack
C. Heap
D. Pointer

Q NO 20:

For making Binary Search Tree for Strings we need,_____data type.

A. Int
B. Char
C. Float
D. Double

Q NO 21:

Consider the following push operations of a Stack:

A. Stack.push(4);
B. Stack.push(6);
C. Stack.push(5);
D. Stack.push(8);

Q NO 22:

If there is a strictly complete binary tree of depth 3, the total number of nodes in it will be?

A. 2K
B. 0k
C. 1k
D. 3k

Q NO 23:

Suppose we have a value for Queue: 2 1 4 6 3Where front is at 2 and rear is at 3, after dequeue one element from that Queue, what will be theresultant Queue?

A. 2146
B. 2141
C. 4621
D. 2147

Q NO 24:

Each operator in a postfix expression refers to the previous _____ operand(s).

A. Two
B. Three
C. Four
D. Five

Q NO 25:

If numbers 5, 222, 4, 48 are inserted in a queue, which one will be removed first?

A. 5
B. 6
C. 7
D. 8

Q NO 26:

The_____symbol is used when we want to get the value of a variable using pointer.

A. *
B. @
C. &

Mickey ch

D. #

Q NO 27:

A node in AVL tree can become imbalanced due to

A. insertion operation
B. deletion operation
C. both insertion and deletion operations
D. node does not imbalance due to insertion and deletion

Q NO 28:

When a node to be deleted from a BST has both left and right child, afterdeletion its node will replace this node.

A. Successor
B. Predecessor
C. inorder Successor
D. Preorder successor

Q NO 29:

What will be output of the given C++ code?Char lhs[]= "Army"; Char rhs[]= "Army"; cout<<strcmp(lhs,rhs);

A. 0
B. Syntax Eroor
C. Negative number
D. Positive number

Q NO 30:

In Binary Search Tree, deleting a node is easy if it is a _____node.

A. Left
B. Leaf
C. Root
D. Right

Q NO 31:

In which traversal method root node is visited at last step

A. Postorder
B. Level order
C. Inorder
D. Preorder

Q NO 32:

The _____symbol is used when we want to get the value of a variable using pointer.

A. *
B. ||
C. #
D. ::

Q NO 33:

At a particular node, the difference in heights of its left andright subtree gives the __of thenode.

A. Right Subtree
B. Balance
C. Left Subtree
D. Height

Q NO 34:

In the perspective of memory organization each process isdivided into ___sections.

A. 2
B. 5
C. 4

Mickey ch

D. 3

Q NO 35:

The_of every node should be 1, 0 or -1 otherwise, itwill not be an AVL tree.

A. Length
B. Balance
C. Width
D. Size

Q NO 36:

From Operating System point of view, the recursive functioncalls are made with the help of ____.

A. Binary Search Tree
B. Stack
C. Query
D. Linked List

Q NO 37:

Consider the linked list having data [6, 72, 35, 65,25] stored in it. While current pointer is pointing memory location having 72 storedin it. After calling add(4) function on the following linked list current point will point to memory location having value?

A. 36
B. 4
C. 72
D. 25

Q NO 38:

Convert the Given infix from 12+60-23 of expression in postfixform.

A. 12+60 23-
B. 12 60+ -23
C. -12 60 -23
D. None

Q NO 39:

Stack and Queue can be implemented using_____

A. Binary Tree
B. Singly Linked List
C. AVL Tree
D. Binary Search Tree

Q NO 40:

_____Method returns the top element of the stack without removingit.

A. Pop()
B. Front()
C. Push()
D. Top()

Q NO 41:

The Computer memory can be thought of as a/an.

A. List
B. Queue
C. Stack
D. Array

Q NO 42:

Suppose there is an image segmented into pixels. Each pixel has____neighbor(s).

A. 0
B. 4
C. 8
D. 16

Mickey ch

Learning With Mickey ch

Q NO 43:

If ahmad is boss of ehsan and ehsan is boss of umer then ahmadis also boss of umer. The above mentioned relation is_____.

A. Reflexive
B. Symmetry
C. Transitive
D. None of the given

Q NO 44:

A binary tree of N nodes has_____.

A. Log10 N levels
B. Log2 N levels
C. N / 2 levels
D. N x 2 levels

Q NO 45:

The worst case of searching in binary search tree (BST) is:

A. When the data inserted in BST is sorted
B. When the height of left sub-tree is greater than right sub-tree
C. When the height of right sub-tree is greater than left sub-tree
D. When the tree is balanced

Q NO 46:

While implementing non-recusive traversal for BinarySearchTree, we need to implement _ .

A. Queue
B. Stack
C. Min heap
D. Max heap

Q NO 47:

Doubly Linked List always has_____NULL pointer/s in anode.

A. One
B. Two
C. Three
D. Four

Q NO 48:

Which of the following is correct about AVL Tree?

A. It is identical to BST except height of the left and right subtrees candiffer by at least 1.
B. It is identical to BST except height of the left and right subtrees mustdiffer by at least 1.
C. It is not identical to BST, it is totally different kind of tree.
D. It is identical to BST except height of the left and right subtrees candiffer by at most 1.

Q NO 49:

_____in AVL is logarithmic.

A. Updating
B. Searching
C. Deletion
D. Insertion

Q NO 50:

In C++, we place the class interface in _____file.

A. .cpp
B. .cppp
C. .h
D. .hh

Q NO 51:

Mickey.ch

Whatsapp#0333-6166150

Learning With Mickey ch

The_____of a node in a binary tree is defined as the heightof its left subtree minus height of its right subtree.

A. Height
B. Balance
C. Width
D. None of the above

Q NO 52:

Stack and Queue can be implemented using_____.

A. Singly Link List
B. Binary Tree
C. Binary Search Tree
D. AVL Tree

Q NO 53:

Which one of the following statement is correct?

A. Array size is fixed once it is created
B. Link List size is fixed once it is created
C. Binary Search Tree size is fixed once it is created
D. AVL Tree size is fixed once it is created

Q NO 54:

The difference between a "Binary Tree (BT)" and a "BinarySearch Tree (BST)" is that,

A. A BST has two children per node whereas a BT can have none,one or two children per node
B. In BST nodes are inserted based on the values they contain
C. In BT nodes are inserted based on the values they contain
D. There is no difference

Q NO 55:

In singly linked list which node will keep track of startingposition of the list.

A. Next Node
B. Previous Node
C. Head Node
D. Last Node

Q NO 56:

Circular Linked List Solve the problem of_____pointer/method ofthe doubly link list.

A. Remove
B. Null
C. Add
D. Find

Q NO 57:

If a tree has a 50 Node then the total linked in the tree will be

A. 55
B. 51
C. 50
D. 49

Q NO 58:

For every Process execute the last part of the Memory isfor_____of the Program

A. Data
B. Code
C. Stack
D. Heap

Q NO 59:

A binary tree is said to be a _____binary tree if every non-leaf node in a binary tree has non-empty left and right sub trees.

A. Complete

Mickey.ch

Whatsapp#0333-6166150

B. Strictly
C. AVL
D. Perfect

Q NO 60:

A tree is an AVL tree if

A. Any one node ful fills tha AVL condition
B. At least half of the nodes fulfill the AVL condition
C. All the nodes fulfill the AVL condition
D. None of the given options

Q NO 61:

The_of a binary tree is the maximum level of its leaves(also called the depth).

A. Level
B. Width
C. Height
D. None of the above

Q NO 62:

what will be postfix expression of the following infix expression? Infix expression a+b*c-d

A. ab+c*d-
B. abc*+d-
C. abcd+*-
D. abc+*d-

Q NO 63:

The main use of AVL tree is:

A. Searching of data
B. Storing of data
C. Insertion of data
D. Security of data

Q NO 64:

A zigzag rotation is performed. In Left-Left case of rotation inAVL tree.

A. True
B. False
C. In some cases
D. None of the above

Q NO 65:

Elements in a queue data structure are added from_____ andremove from___.

A. Rear end. front end
B. Front end. Rear end
C. Front end
D. rear end

Q NO 66:

The lifetime of a transient object can exceed that of applicationwhich is accessing it.

A. True
B. False
C. In some cases
D. None of the given

Q NO 67:

A stack carries _____behavior.

A. FIFO
B. LIFO
C. AVCO
D. FEFO

Mickey ch

Learning With Mickey ch

Q NO 68:

Deleting a _node in BST is a _____case.

A. Root, simplest
B. Left child, simplest
C. Right child, simplest
D. Leaf, simplest

Q NO 69:

Doubly linked list always has_____NULL pointers in a node.

A. One
B. Two
C. Three
D. Four

Q NO 70:

Consider the linked list having data [6, 72, 35, 65,25] stored in it. While current pointer is pointing memory location having 72 storedin it. After calling remove() function on the following linked list current point will point to memory location having value?

A. 6
B. 35
C. 65
D. 25

Q NO 71:

Which one of the following method does not change the originalvalue of the argument in the calling function?

A. Call by passing reference of the argument
B. Call by passing the address of the argument
C. Call by passing the value of the argument
D. None of the given options

Q NO 72:

The_____of a node in a binary tree is defined as the heightof its _ __sub tree minus height of its right sub tree.

A. Height
B. Balance
C. Width
D. None

Q NO 73:

For a complete binary tree, the depth is calculated as_____.

A. log2(number of nodes+1)-1
B. log2(number of nodes*1)+1
C. log2(number of nodes-1)-1
D. log2(number of nodes-1)+1

Q NO 74:

Every ____tree is a binary search tree.

A. AVL
B. binary
C. big
D. small

Q NO 75:

Generalized code written for a class is called:

A. Function
B. Template
C. Structure

Mickey ch

Whatsapp#0333-6166150

D. Stack

Q NO 76:

New items are added at the _____of the stack.

A. Bottom
B. Middle
C. Center
D. Top

Q NO 77:

Consider the following infixexpression. 7/8+9 If one converts the above expression into postfix, what would be theresultant expression?

A. 789/+
B. 78/+9
C. /78+9
D. 78/9+

Q NO 78:

Suppose there are 100 elements in an equivalence classes so initiallythere will be 100 tree.The collection of tree is called_

A. Cluster
B. Class
C. Forest
D. Bunch

Q NO 79:

For a perfect binary tree of height h, having N nodes the sum of heightof nodes is

A. N-h-1
B. N-1
C. N-1+h
D. -(h-1)

Q NO 80:

Sorting procedure normally takes_____time.

A. N log N
B. 2 N
C. N*N*N
D. N

Q NO 81:

there are 100 elements in an equivalence classes then will have_state initially

A. 50
B. 100
C. 1000
D. 80

Q NO 82:

_____objects (objects accessed by pointers) are called anonymousobjects.

A. Private
B. Nameless
C. Friend
D. Public

Q NO 83:

_____is a self-balancing tree.

A. AVL
B. Binary Tree
C. Binary Search Tree

Mickey ch

D. ALV

Q NO 84:

Which of the following operation returns but do not removes top valueof the stack?

A. Push
B. Pop
C. Top
D. First

Q NO 85:

Int htdiff = height(root->getLeft()) _____ height(root->getRight());
The above line of code istaken from AVL insert method.Complete it by selecting an appropriate symbol.

A. -
B. +
C. /
D. *

Q NO 86:

Which operation of the queue data structure is used to insert anelement into the Queue?

A. Enqueue()
B. Dequeue()
C. Fornt()
D. Remove()

Q NO 87:

For making binary search tree for strings we need, _____datatype.

A. Char
B. Int
C. Float
D. Double

Q NO 88:

Local variables defined inside function body are _____ automatically at the end of function execution.

A. Created
B. Destroyed
C. Incremented
D. Decremented

Q NO 89:

If a node has three fields, then this node will be related to

A. Linked list
B. Doubly linked list
C. Circular linked list
D. All of the given

Q NO 90:

Which of the following function(s) is/are used for function call by using pointers?

```
void func1(int& num) {num++;
}
void func2(int* num){num++;
}
```

A. Func2
B. Func1
C. Both
D. None of these

Q NO 91:

Mickey ch

Learning With Mickey ch

To create a reference variable, we need to use_____sign.

A. Dollar
B. Sigma
C. Asterisk
D. Ampersand

Q NO 92:

Which of the following is correct syntax to pass a constant variable by reference to a function?

A. int display(int const val)
B. int display(const int val)
C. int display(const &int val)
D. Int display (const int& val)

Q NO 93:

One should be careful about transient_____that are stored by reference in data structures.

A. Tree
B. Stack
C. Objects
D. Function

Q NO 94:

In the perspective of memory organization every process executing, the second part of the memory is for the_____of the program.

A. Stack
B. Data
C. Static code
D. None of these

Q NO 95:

In AVL tree insertion occurs on the inside in cases_____and 3 which a single rotation cannot fix.

A. 1
B. 2
C. 5
D. 4

Q NO 96:

In the perspective of memory organization every process executing, the last part of the memory is for the_____of the program.

A. Stack
B. Data
C. Heap
D. Code

Q NO 97:

In a strictly complete binary tree, the number of_____at any levelk will be 2k.

A. Sets
B. Link
C. Nodes
D. Children

Q NO 98:

What will be level order traversal of the given BST ?

A. 1435286
B. 6281534
C. 1234568

Mickey ch

Whatsapp#0333-6166150

D. 1243568

Q NO 99:

_____objects (objects accessed by pointers) are calledanonymous objects.

A. Public
B. Private
C. Friend
D. Nameless

Q NO 100:

Which of the following tree is correct next step to balance the given AVL tree?

A. A
B. B
C. C
D. D

Q NO 101:

Through both recursive method call and non-recursive method call After deletion of a node from a binary search tree_____traversalmethod should be maintained.

A. Inorder
B. Preorder
C. Post order
D. Level order

Q NO 102:

In which of the following function signatures, the value of variable "num" cannot be changed in function body?

A. int cube(int num)
B. int cube(int &num)
C. int cube(int *num)
D. int &cube(int num)

Q NO 103:

Each node in singly linked list contains_____.

A. One Pointers
B. Two Pointers
C. Six Pointers
D. Five Pointers

Q NO 104:

The back() method decreases the value of variable current by____.

A. One
B. Two
C. Four
D. Three

Q NO 105:

The_____method of list will position the currentNode and lastCurrentNode at the start of the list.

A. Start
B. End
C. Middle
D. None of these

Q NO 106:

What will be the result of evaluating following expression? 5+3*2/(6-3)

A. 1
B. 3

Mickey ch

C. 7
D. 5

Q NO 107:
In singly linked list a node comprises of_____field/s.
A. Two
B. One
C. Six
D. Five

Q NO 108:
In Left-Right case of rotation in_____tree. A double rotation is performed.
A. AVL
B. VLA
C. EVL
D. LVA

Q NO 109:
The -- is a decrement operator in C++ that decreases the value of the operand by___.
A. One
B. Two
C. Five
D. Six

Q NO 110:
int htdiff = height(root->getLeft()) height(root->getRight()); The aboveline of code is taken from AVL insert method. Complete it by selecting an appropriate symbol.
A. Minus (-)
B. Add
C. Sub
D. Multiple

Q NO 111:
The principal benefit of a linked list over a conventional array is that theorder of the linked items may be_____from the order that the data items are stored in memory.
A. Same
B. Different
C. Both
D. None of these

Q NO 112:
The computer memory can be thought of as a/an
A. Tree
B. Array
C. Heap
D. Pointer

Q NO 113:
If one converts the above expression into postfix, what would be the resultant expression?
A. 78/9+
B. 87/9+
C. +78/*
D. 9/78+

Q NO 114:
_____tree has been named after two persons Adelson-Velskii and Landis.
A. AVL
B. RED
C. Tree
D. Binary search

Mickey ch

Learning With Mickey ch

Q NO 115:

There are_____cases of Rotation in AVL tree.

A. 2
B. **4**
C. 6
D. 8

Q NO 116:

~BinarySearchTree( ) is a_____.

A. Destructor
B. Constructor
C. Switch case
D. Template method call

Q NO 117:

Which of the following is a nonlinear data structure?

A. Tree
B. Heap
C. Stack
D. Pointer

Q NO 118:

All the objects created using_____operator have to be explicitlydestroyed using the delete operator.

A. New
B. Build
C. Create
D. Construct

Q NO 119:

A BST generated from the data in ascending order is_____.

A. Linear
B. Un sorted
C. Balanced
D. Nonlinear

Q NO 120:

If the root of a tree is at level two in case of a complete binary tree i.e nodes will be at____.

A. 2
B. 4
C. 6
D. 8

Q NO 121:

In AVL tree during insertion, a single rotation can fix the balance in cases____and.

A. 1
B. 2
C. 3
D. 4

Q NO 122:

Which type of rotation can balance the following AVL tree?

A. Single left
B. Single right
C. Double right-left
D. Double left-right

Q NO 123:

If the root of a tree is at level three in case of a complete binary tree i.e nodes will be at___.

Mickey ch

Whatsapp#0333-6166150

A. 4
B. 6
C. 8
D. 10

Q NO 124:

Suppose we have the following values to be inserted in constructing AVL tree,10,13,15,5,7,8 Tell when first rotation will take place,

A. After inserting the node 10
B. After inserting the node 15
C. After inserting the node 20
D. After inserting the node 25

Q NO 125:

If the root of a tree is at level zero, its two children (subtrees) i.e. nodes will be at ___.

A. Level 1
B. Level 2
C. Level 3
D. Level 4

Q NO 126:

Which of the following is known as "Last-In, First-Out" or LIFO Data Structure?

A. Tree
B. Stack
C. Heap
D. Pointer

Q NO 127:

Left, right, info, and parent are the operations of_____data structure.

A. Tree
B. Heap
C. Stack
D. Pointer

Q NO 128:

The balance of a node in a binary tree is defined as the height of its_sub tree minus height of its right sub tree.

A. Left
B. Right
C. Upper
D. Lower

Q NO 129:

For searching a particular number in Binary Search Tree (if it is not present), the maximum number of comparisons will be _____ comparison(s) at each level.

A. 1
B. 2
C. 3
D. 4

Q NO 130:

Link List can be special case of,

A. Parse Tree
B. AVL tree
C. Binary Search Tree
D. Heap

Q NO 131:

When a function calling itself is called as _____.

Mickey ch

A. Inline
B. Recursion
C. Iteration
D. Nested Loop

Q NO 132:

___is used for Reference variables in C++.

A. &
B. @
C. #
D. !

Q NO 133:

The process of getting the value of a variable using pointers iscalled:

A. Dereferencing
B. Refrencing
C. Memory Deallocation
D. Memory allocation

Q NO 134:

We can use Binary Search Tree with _____

A. Integer Data only
B. String Data Only
C. Both
D. Non-Integer Data 0nly

Q NO 135:

After deletion of a node from a binary search tree _____traversal method should be maintained.

A. Inorder
B. Post order
C. Level Order
D. Preorder

Q NO 136:

If a function has recursive call as the last statement, it is knownas__.

A. Function recursion
B. Tail recursion
C. Last recursion
D. Local Recursion

Q NO 137:

In a strictly complete binary tree the number of _ at any level kwill be 2k.

A. Link
B. Nodes
C. Children
D. Sets

Q NO 138:

We can calculate the_____of a subtree by counting itslevels from the bottom.

A. Height
B. Data Items
C. Nodes
D. Balance

Q NO 139:

In level-order traversal for Binary Search Tree, ____ data structure is used.

A. Queue

Mickey ch

B. Linked List
C. Stack
D. Heap

Q NO 140:

What will be the return type of the findMin method in thestatement given below?int& findMin( ) const;

A. Integers Variable
B. Integer Refrence
C. Constant Integer
D. Integer Pointer

Q NO 141:

Which of the following data structure is/are linear type?

A. AVL Tree
B. Graphs
C. Binary Search Tree
D. Heap and Stack

Q NO 142:

_____of an empty AVL tree is defined to be -1.

A. Height
B. Size
C. Width
D. Length


Q NO 143:

We can make a lexicographic order of characters based on their____.

A. RANDOM choice
B. ASCII values
C. Binary DIGITS
D. Memory Address

Q NO 144:

What will be the inorder traversal of the given tree?



A. 15 25 35 45 75
B. 25 15 35 45 75
C. 75 35 25 15 45
D. 35 25 75 45 15

Q NO 145:

The structure of tree with_____data is like a linked list.

A. Sorted
B. Small
C. Large
D. Unsorted

Q NO 146:

Analyze the given code carefully and identify which type ofbinary tree traversal this is;

```
Void traversal ( treeNode*treeNode)
{ if(treeNode !=Null)
{ cout << *(treeNode->getinfo( ))<< " "; Traversal ( treeNode->getleft( )); Traversal ( treeNode->getRight( )); } }
```

A. Inorder

Mickey ch

B. Preorder
C. Postorder
D. Sorted Order


Q NO 147:

In binary search tree deleting a node is easy if it is a_____node.

A. ROOT
B. LEFT
C. RIGT
D. LEAF

Q NO 148:

If we delete node 2 from the given BST then which node willreplace it?



A. 1
B. 2
C. 3
D. 4

Q NO 149:

Generally there is/are _____case(s) to delete a node fromBST.

A. 1
B. 2
C. 3
D. 4

Q NO 150:

there is no such Node whose next filed is NULL which one ofthe given option support the statement

A. Linked List
B. Circular Link list
C. Array
D. Queue

Q NO 151:

What will be the output of following code?Void explode(int& num)
{ Num++;} Main()
{ Int power = 15;explode(power);

A. 16
B. 14
C. 17
D. 15

Q NO 152:

Which of the following is the correct conservation from infix topostfix expression A*B+C/(E-F).

A. ABC*+EF-/
B. AB*CFE-/*
C. AB*C+EF/*
D. AB+C*E-F/

Q NO 153:

Y=&x[0];
In the above statement, we get the address of the Locatio of the array xand store it in y. Here

Mickey ch

"Y" is;

A. Xvalue
B. Zvalue
C. Ivalue
D. Nvalue

Q NO 154:

Stack push(15) will push 15 on_____.

A. Top of the Stack
B. Anywhere of the Stack
C. Middle of the Stack
D. Bottom of the Stack

Q NO 155:

Trying to remove an element from an empty Stack is called_____.

A. Garbage Collection
B. Overflow stack
C. Empty collection
D. Underflow of Stack

Q NO 156:

we cannot remove items randomly from_____.

A. Stack
B. Queue
C. Stack and Queue
D. List

Q NO 157:

In Queue data structure element are full from_____.

A. Pop
B. Push
C. Rear
D. Front

Q NO 158:

"end()" method of list performs its tasks in

A. Many Steps
B. Three Steps
C. One Steps
D. Two Steps

Q NO 159:

Complete the push method code of stack void push (int x) {A{__}=x}

A. Count++
B. Count—
C. ++count
D. –count

Q NO 160:

In Queue data structure element are removed from_____.

A. Pop
B. Push
C. Rear
D. Front

Q NO 161:

Before using the Pop method of a stack, the user must callthe__method.

A. isFull()
B. push()
C. pop()

Mickey ch

D. isEmpty()

Q NO 162:

A stack carries_____behavior.

A. FIFO
B. FEFO
C. LIFO
D. AVCO

Q NO 163:

A template is a Function or Class that is Written a_____data type.

A. Generic
B. None of These
C. Define
D. Specific

Q NO 164:

In singly linked list a node consists of two parts:

A. Object and structure
B. Two pointers
C. Two objects
D. Object and pointer

Q NO 165:

Binary search algorithm cannot be applied to_____.

A. Sorted linked list
B. sorted binary trees
C. sorted linear array
D. None of the given

Q NO 166:

The principal benefit of a link list over a conventional array isthat the order of the linked items may be_from the order that thedata seems are stored in memory.

A. Different
B. Identical
C. Same
D. Equivalent

Q NO 167:

A hash function returns a _____value.

A. Integer
B. Double
C. Float
D. Char

Q NO 168:

Which property of equivalence relation is satisfied if we say:Ahmad R(is related to) Ahmad

A. Reflexivity
B. Symmetry
C. Transitivity
D. All of the given

Q NO 169:

Which of the following statement is false?

A. Arrays are dense lists and static data structure
B. data elements in linked list need not be stored in adjecent space inmemory
C. pointers store the next data element of a list
D. linked lists are collection of the nodes that contain information part andnext pointer

Q NO 170:

If the height of a perfect binary tree is 4. What will be the totalnumber of nodes in it?

Mickey ch

A. 15
B. 16
C. 31
D. 32

Q NO 171:

In 1990, Bill pugh proposed an enhancement on linked lists andthe new data structure was termed as

A. Linked list
B. B-Tree
C. Skip list
D. Spelling checker

Q NO 172:

In the statement int& a=b;

A. a and b pointing to two different memory location
B. a and b are two different names of the same memory location
C a and b are two different variable names
D. b hold the address of variable a

Q NO 173:

What is the hash function used in linear probing?

A. hi(x)=hash(x) mod table size
B. hi(x)=(hash(x) + f(i^2)) mod table size
C. hi(x)= (hash(x)+ f(i)) mod table size
D. hi(x)= X mod 17

Q NO 174:

Each operator in a postfix expression refers to the previous____operand(s).

A. One
B. Two
C. Three
D. Four

Q NO 175:

If there are N elements in an array then the number of maximumsteps needed to find an element using Binary Search is_____.

A. N
B. N2
C. Nlog2N
D. log2N

Q NO 176:

Suppose that a main program has two integer variables x and y, which are given the value 0. Then the main program calls f(x,y); What are the values ofx and y after the function f finishes?

A. Both x and y are still 0.
B. x is now 1, but y is still 0.
C. x is still 0, but y is now 2.
D. x is now 1, and y is now 2.

Q NO 177:

For a perfect binary tree of height h, having N nodes, the sum ofhights of nodes ia__.

A. N - h - 1
B. N - 1
C. N - 1 + h
D. N - (h - 1)

Q NO 178:

"new int[11]" will allocate memory for_____integers.

Mickey ch

A. 10
B. 11
C. 12
D. 13

Q NO 179:

The_____method of list data structure removes the elementresiding at the current position.

A. Add
B. Next
C. Remove
D. Find

Q NO 180:

Avl tree takes maximum _____time to search an element.

A. 1.44 Log2n
B. Log2(n+n)
C. Log2(n+1)+1
D. 1.88 Log2n

Q NO 181:

The array in binary search is sub divided_____.

A. Once
B. Twice
C. N time
D. Untill a sublist is no more divisible

Q NO 182:

If unions are done by weight (size), the depth of any element isnever greater than.

A. log 3n
B. log2 n
C. n log2 n
D. log n*n

Q NO 183:

What is the depth of any tree if the union operation is performedby height?

A. O(N)
B. O(N log N)
C. O(log N)
D. O(M log N)

Q NO 184:

Which operation of queue data structure is used to get frontelement from the queue and then remove it from the queue?

A. enqueue()
B. dequeue()
C. front()
D. remove()

Q NO 185:

Suppose we have been given the following data set for a Queue.7 5 2 4
What will be the resultant Queue if we call enqueue(3) method? Note that 7 is the front element whereas 4 is rear element of queue.

A. 7 5 2 4
B. 7 5 2 4
C. 7 5 2 4 3
D. 5 2 4 3

Q NO 186:

Recursive call of a function use _____data structure.

A. Linked List
B. Queue

Mickey ch

C. Stack
D. Table

Q NO 187:

A Linear Data Structure is the data structure in which dataelements are arranged in a sequence or a linear list. Which of thefollowing is Non Linear Data Structure?

A. Arrays
B. Linked Lists
C. Binary Search Trees
D. Stack

Q NO 188:

If Ahmad is cousin of Ali and Ali is cousin of Asad then Ahmadis also cousin of Asad. This statement has the following property

A. Reflexivity
B. Symmetry
C. Transitivity
D. All of the given

Q NO 189:

Which of the is NOT true regarding the maze generation?

A. Randomly remove walls until the entrance and exit cells are in sameset.
B. Removing a wall is the same as doing a union operation
C. Remove a randomly chosen wall if the cells it separates are alreadly insame set
D. Do not remove a randomly chosen wall if the cells it separates arealready in same set.

Q NO 190:

A queue where the dequeue operation does not depend uponFIFO, is called:

A. enqueue
B. simple queue
C. stack
D. priority queue

Q NO 191:

In simple or singly linked list there is/are_____pointer/s ineach node.

A. One
B. Two
C. Three
D. Four

Q NO 192:

if (! heap ->isEmpty())checks

A. Heap is empty
B. Heap is full
C. Heap is not empty
D. Not a valid expression

Q NO 193:

The main use of AVL tree is:

A. Searching of data
B. Storing of data
C. Insertion of data
D. Security of data

Q NO 194:

During union by size method, which data structure is used toimprove the balancing of tree?

A. Array
B. Stack
C. Linked List

Mickey.ch

D. Tree

Q NO 195:

Can we store elements with different data types in a single array?

A. Yes
B. No
C. In some cases
D. None of the given

Q NO 196:

isEmpty() method of stack class will return true when.

A. Stack is full
B. Stack is Partially
C. Stack is not empty or Null
D. Stack is empty

Q NO 197:

If we singly linked list to implement list, then there is an issuethat it gives difficulty when we:

A. Move forward in the list
B. Move backward in the list
C. We will increase its size
D. We will decrease its size

Q NO 198:

"New int[11]" will allocate memory for_____integers.

A. 13
B. 12
C. 11
D. 10

Q NO 199:

Suppose we have the following values to be inserted inconstructing AVL tree, 20,23,25,10, 12,13 Tell when first rotation will take place.

A. After increasing Node 25
B. After increasing Node 23
C. After increasing Node 10
D. After increasing Node 12

Q NO 200:

The percolate down procedure will move the smaller value___and Bigger value____.

A. Left, right
B. Right, left
C. Down, up
D. Up, down

Q NO 201:

"+" is a __operator.

A. Unary
B. Binary
C. Ternary
D. None of the above

Q NO 202:

Which of the following a nonlinear tree

A. Stack
B. Que
C. Tree
D. Linked List

Q NO 203:

Mickey ch

Learning With Mickey ch

While implement non recursive traversal for binary search treewe need to implement____ _____.

A. Que
B. Stack
C. Min heap
D. Max Heap

Q NO 204:

Leaf node of binary search tree contains _____.

A. One null pointer
B. Three null pointers
C. Two null pointers
D. All of the given

Q NO 205:

Memory address is stored in

A. Address operator
B. Reference
C. Pointer
D. All of the given

Q NO 206:

Which of the following is the correct conversion of infixto postfix expression? Z+B-(D-H)/K

A. ZB+D-H-K/
B. ZB+DH-K-/
C. ZB+DH-K/-
D. ZB+DHK--/

Q NO 207:

What will be result of following postfix expression?123*+2–

A. 3
B. 4
C. 5
D. 10

Q NO 208:

y = &x[0];
In the above statement, we get the address of the fist location of thearray x and store it in y.
Here “y” is:

A. R value
B. x value
C. l value
D. z value

Q NO 209:

During deletion of node from BST. if we found this node don'thave in- order successor and predecessor. it means this node is_____.

A. Left Most node in the binary search tree
B. Right most node in the binary search tree
C. Root node
D. None of the given option

Q NO 210:

_____rule applies for evaluating operators of same precedence inan expression.

A. right to left
B. Cascading

Mickey ch

Whatsapp#0333-6166150

C. Associative
D. None of the above

Q NO 211:

Which of the following is the correct option for priority Queue?

A. The type of Queue that is not FIFO i.e the person who comes firstmay not leave first
B. The type of Queue that is not FIFO i.e the person who comes firstshould leave first
C. The type of Queue that is not FIFO i.e the person who comes firstshould leave first
D. The type of Queue that is not FIFO i.e the person who comes firstmay not leave first

Q NO 212:

For String-based Binary Search Tree, We use ASCII values ofcharacters for comparing among letters. This method is known as___.

A. Lexicographic order
B. Alphabet coding procedure
C. Asymmetric technique
D. heap-based approach

Q NO 213:

If numbers 5,222,4,48 are inserted in a queue. Which one will beremove first?

A. 48
B. 4
C. 222
D. 5

Q NO 214:

if there are ______nodes in an avl tree its levels will be roughly aslog2(10 million)

A. 100 million
B. 10 million
C. 5 million
D. 2 million

Q NO 215:

Which one is the correct function call for the following functionof calculatincube?

```
int cube(int&num)
{
.
.
.
```

A. Cube(&num)
B. Cube(&&num)
C. Cube(*num)
D. Cube(num)

Q NO 216:

In a complete binary tree, for 25000 nodes the depth will be___.

A. 13
B. 14
C. 15
D. 16

Q NO 217:

The smallest value element in a binary search tree(Each nodewith left and right pointer)lies at

A. Root Node
B. Left Child of Root
C. Right Most Node
D. Left Most Node

Mickey ch

Learning With Mickey ch

Q NO 218:

We can not remove items randomly from _____.

A. Stack
B. Queue
C. Both of these
D. None of these

Q NO 219:

NULL is an invalid address and _____.

A. Accessible
B. Inaccessible
C. Points to the start point of the list
D. Points to the last point of the list

Q NO 220:

copy() method of list data structure _____.

A. copy first item of list
B. set one list to be a copy of another
C. copy last item of list
D. copy any item of list

Q NO 221:

The tree data structure is a

A. Linear data structure
B. Non-linear data structure
C. Graphical data structure
D. Data structure like queue

Q NO 222:

If we write functions for recursive and non recursive inordertraversal method of BST, what will be the difference between its functions prototypes?

A. Different return types
B. Different function names
C. Different arguments list
D. Nothing will be different

Q NO 223:

ABST generated from the data in ascending order is_____.

A. Linear
B. Nonlinear
C. Balanced
D. Un sorted

Q NO 224:

_____is utilized at the time of memory allocation in dynamicmanner.

A. Stack
B. Queue
C. Heap
D. All of the given

Q NO 225:

How many cases of rotation are there in AVL tree?

A. 2
B. 4
C. 6
D. 8

Q NO 226:

A list is the collection of items of the _____.

Mickey ch

Whatsapp#0333-6166150

A. May be of same or may be of different type
B. Different type
C. Same type
D. None of the above

Q NO 227:

Int * i =new int[10]; Above given code will:

A. Create an integer having value 10
B. Allocate memory for 9 integers
C. Allocate memory for 10 integers
D. Create 10 pointers of integer type

Q NO 228:

The depth of a binary tree is

A. Total number of nodes in the tree
B. Number of leaf nodes in the tree
C. Number of non-leaf nodes in the tree
D. Maximum level of a leaf

Q NO 229:

A_____model attempts to model a real-world phenomenon

A. Physical
B. Logical
C. Simulation
D. Conceptual

Q NO 230:

In level-order traversal for binary search tree, we visit the nodesat each level before proceeding to the next level, in a _____order.

A. Right-to-left
B. Left-to-right
C. Top-to-bottom
D. Bottom-to-top

Q NO 231:

The balance of a node in a binary tree is defined as the heightof its _sub tree minus height of its right sub tree.

A. Right
B. Left
C. Upper
D. Lower

Q NO 232:

Allocating and de-allocating memory for linked list nodesdoes take _time than pre-allocated array.

A. Less
B. More
C. Equal
D. No

Q NO 233:

After the completion of all operation, the top element in stack is_____.

A. 10
B. 20
C. 40
D. 50

Q NO 234:

Each operator in a postfix expression refers to the previous___operand(s).

Mickey ch

A. One
B. Two
C. Three
D. Four

Q NO 235:

In doubly linked list a node consists of three parts:

A. 1 pointer and 2 objects
B. 2 pointers and 1 object
C. 3 objects
D. 3 pointers

Q NO 236:

For reference variables,_____sign is used.

A Ampersand
B. Asterisk
C. Sigma
D. Dollar

Q NO 237:

Which of the following data structure is linear type?

A. Stack
B. List
C. Queue
D. All of the above

Q NO 238:

The - - is a decrement operator in C++ that decreases the value ofthe operand by ___.

A. One
B. Two
C. Three
D. Four

Q NO 239:

Which of the following statement is correct for the variable“current- -“?

A. Current = current + 1
B. Current = current - 1
C. Current = current - 2
D. Current – 1 = current

Q NO 240:

When an executable program runs, it is loaded in the computermemory and becomes a___.

A. Thread
B. .h file
C. Process
D. None of the above

Q NO 241:

start() method of list class is used to:

A. Moves the “current” pointer to very first element
B. Moves the “current” pointer to very last element
C. Moves the “current” pointer to one step after the first element ofthe array
D. Moves the “current” pointer to one step before the first elementof the array

Q NO 242:

a * (b + c) – d is an example of _____expression.

A. Infix
B. Prefix
C. Postfix

Mickey ch

D. Alfix

Q NO 243:

In a program a reference variable, say x, can be declared as

A. int &x;

B. int *x;

C. int x;

D. none of the given options

Q NO 244:

We allocate memory dynamically by using_____operator.

A. This

B. New

C. Increment

D. Decrement

Q NO 245:

Get(?) method of list class is used to:

A. Get element from the last position

B. Get element from the first position

C. Get element from the middle position

D. Get element at the given position

Q NO 246:

STL is a __that is a part of the official standard of C++.

A. C program file

B. .h file

C. .cpp file

D. Library

Q NO 247:

There are_ cases for deleting a node from binary search tree.

A. 1

B. 2

C. 3

D. 4

Q NO 248:

In a list, tail() method of current pointer _____.

A. Returns the last element of the “current” pointer

B. Moves the “current” pointer to the very first element

C. Moves the “current” pointer to the very last element

D. Returns the first element of the “current” pointer

Q NO 249:

Suppose we have been given the following data set for a queue:37524
What will be the resultant queue if we call a front() method?

A. 7524

B. 37524

C. 75243

D. 5 2 4

Q NO 250:

Suppose we have been given the following data set for a queue:7524 What will be the resultant queue if we call enqueue(3) method? Note that 7 is the frontelement whereas 4 is rear element of queue.

A. 7524

B. 37524

C. 75243

Mickey ch

D. 5243

Q NO 251:

Maximum time that an insertion operation can take in AVL treeis _____.
Here log stands for log to the base of 2.

A. Log (n)
B. 1.44 log (n)
C. 1.66 log (n)
D. Log (n+1)

Q NO 252:

_____is when function is calling to itself.

A. Loop
B. Recursion
C. Iteration
D. Nested loop

Q NO 253:

Left, right, info, and parent are the operations of_____datastructure.

A. Stack
B. Tree
C. Queue
D. Linked list

Q NO 254:

Following is a keyword of C++

A. Del
B. Delete
C. Remove
D. Eliminate

Q NO 255:

The expression DE+H* is called _____.

A. Prefix expression
B. Infix expression
C. Postfix expression
D. Hybrid expression

Q NO 256:

A software solution is said to be efficient if it solves the problem____.

A. By using some extra resources
B. Within no time
C. By consuming more hardware resources
D. Within its resources constraints

Q NO 257:

field while other field contains:

A. Pointer to an integer
B. Pointer to character
C. Pointer to next node
D. Pointer to class

Q NO 258:

Each node in singly linked list contains _____.

A. One pointer
B. Two pointers
C. No pointer
D. NULL pointer

Q NO 259:

Mickey ch

Every AVL tree is a binary search tree.

A. True
B. False
C. Not in some cases
D. None of the given

Q NO 260:

In singly linked list "next" field of node contains:

A. Address of next node
B. Object of next node
C. Object of current node
D. Address of head node

Q NO 261:

Two common models of simulation are _____and____.

A. Circuit-based simulation and Event- based simulation
B. Circuit-based simulation and Time-based simulation
C. Time-based simulation and Event- based simulation
D. None of the above

Q NO 262:

Stack and Queue can be implements using _____.

A. Singly Link List
B. Binary Tree
C. Binary search Tree
D. AVL Tree

Q NO 263:

What are the basic things associated with data structures?

A. Space for each data item it stores
B. Time to perform each basic operation
C. Programming effort
D. All of the above

Q NO 264:

In AVL tree insertion occurs on the inside in case_____and 3which a single rotation cannot fix.

A. 1
B. 2
C. 4
D. 5

Q NO 265:

add(12) method of linked list class will

A. Add 12 nodes in linked list
B. Add 12 pointers in linked list
C. Add 12 as value in linked list
D. Add 12 values in linked list

Q NO 266:

Which of the following is a non- linear data structure?

A. Stack
B. Queue
C. Tree
D. Linked list

Q NO 267:

Which data structure allows deleting data elements from front anfinserting at rear?

A. Stacks

Mickey ch

B. Queues
C. Deques
D. Binary search tree

Q NO 268:

Array cells are _____in computer memory.

A. Contiguous
B. Random
C. Store in multiple Variables
D. Store in multiple functions

Q NO 269:

A kind of expression where the operator is present between twooperands called_____ _____expressions.

A. Infix
B. Postfix
C. Prefix
D. None of the above

Q NO 270:

back() method of list class is used to

A. Moves the "current" pointer to backward one element.
B. Moves the "current" pointer to backward two element.
C. Moves the "current" pointer to backward three element.
D. Moves the "current" pointer to backward four element.

Q NO 271:

next() method of List class is used to:

A. Moves the Current position backward one element
B. Moves the "Current" pointer to two steps after the last element ofthe array
C. Moves the Current position forward one element
D. Moves the "Current" pointer to two steps before the last elementof the array

Q NO 272:

_____tree has been named after two persons Adelson-Velskii and Landis.

A. Binary
B. Black
C. AVL
D. VLA

Q NO 273:

There are four cases of rotation in an_____tree.

A. ELV
B. EVL
C. AVL
D. ALV

Q NO 274:

_____is used for reference variable in C++.

A. !
B. @
C. #
D. &

Q NO 275:

A_____is a tree in which every level, except possibly thelast, is completely filled, and all nodes are as far left as possible.

A. Strict binary tree
B. Full binary tree

Mickey ch

C. Perfect binary tree
D. Complete binary tree

Q NO 276:

A queue is a data structure where elements are

A. Inserted at the front and removed from the back
B. Inserted and removed from the top
C. Inserted at the back and removed from the front
D. Inserted and removed from both ends

Q NO 277:

Longest path from root node to farthest leaf node is called____of tree.

A. Level
B. Length
C. Depth
D. Node level

Q NO 278:

Length() method of list class is used to:

A. Return the length of the array
B. Return the length of the list
C. Return the length of empty part of the array
D. Return the length of empty part of the list

Q NO 279:

The function calls are made with the help of _____.

A. Stack
B. Heap
C. Dynamic memory
D. External memory

Q NO 280:

An efficient program execute faster and helps in_____ theusage of resources like memory and disk

A. Maximizing
B. Minimizing
C. Equalizing
D. None of the given

Q NO 281:

"set()" method of list class is used to:

A. Set the value of Pointer
B. Set the value of Null Nodes
C. Set the value of objects
D. Set the value of Value

Q NO 282:

In C++, we place the class interface in _____file.

A. .cpp
B. .cppp
C. .h
D. .hh

Q NO 283:

If both left and right nodes of a node are NULL then this type ofnode is called_node.

A. Non leaf
B. internal
C. inner
D. leaf

Mickey ch

Learning With Mickey ch

Q NO :284

Which of the following function don't belongs to the stack class?

A. push()
B. pop()
C. crash()
D. top()

Q NO 285:

_____ only removes items in reverse order as they were entered.

A. Queue
B. Stack
C. Both of these
D. None of these

Q NO 286:

What will be the postfix expression of following infixexpression? D+E*F/G

A. DE*F/G
B. DE+F*G/
C. DEF*/+
D. DE+FG*/

Q NO 287:

The back() method decreases the value of Variable currentby__.

A. Four
B. Three
C. Two
D. One

Q NO 288:

In doubly linked list there is/are_____pointer/s in each node.

A. One
B. Two
C. Three
D. Four

Q NO 289:

Suppose we have the following values to be inserted inconstructing AVL tree,10, 13, 15, 5, 7, 8 Tell when first rotation will take place.

A. After inserting node 13
B. After inserting node 15
C. After inserting node 5
D. After inserting node 7

Q NO 290:

Binary search algorithm cannot be applied to _____.

A. Sorted linked list
B. sorted binary trees
C. sorted linear array
D. None of given option

Q NO 291:

During the execution of a process operating system constructs focus things for that process which of the following isnot part of that process.

A. A section for static data including global variable
B. Stack
C. Heap
D. Linked list

Q NO 292:

Mickey.ch

Whatsapp#0333-6166150

Learning With Mickey ch

_____is the major factor to see the efficiency of a program.

A. Quality
B. Time
C. Correctness
D. None of the given

Q NO 293:

While implementing stack with an array and to achieve LIFObehavior, we used push and pop elements at_____.

A. The start of the array
B. The end of the array
C. The mid of the array
D. At least one position before array starting index.

Q NO 294:

A template is a function or class that is written with a _____.

A. Specific
B. Definite
C. Generic
D. None of the above

Q NO 295:

In the linked list implementation of the stack class, where does the push member function places the new entry on the linkedlist?

A. After all other entries that are greater than the new entry
B. At the head
C. After all other entries that are smaller than the new entry
D. At the tail

Q NO 296:

The next field in the last node in a singly-linked list is set to___.

A. 0
B. 1
C. NULL
D. False

Q NO 297:

In singly linked list a node comprises of _____field/s.

A. One
B. Two
C. Three
D. Four

Q NO 298:

Linked list is generally considered an example of_____typeof memory location.

A. Static
B. Compile time
C. Dynamic
D. None of given options

Q NO 299:

What's wrong with following loop?while((i < 10) && (i > 24)){}

A. The logical operator && cannot be used in a test condition
B. The while loop is an exit-condition loop
C. The test condition is always false
D. The test condition is always true

Q NO 300:

Making the tree unbalanced, it violates the_____rule.

Mickey.ch

Whatsapp#0333-6166150

A. Linked list
B. Stack
C. AVL
D. Queue

Q NO 301:

Can we store elements with different data types in a single array?

A. Yes
B. No
C. In some cases
D. None of given

Q NO 302:

In a tree, we link the nodes in such a way that italinear structure.

A. Does not remain
B. Forms
C. Reverses
D. Remains

Q NO 303:

Factorialis an example of_____function.

A. Recursive
B. Non-recursive
C. Cube
D. Log

Q NO 304:

All the objects created using_____operator have to beexplicitly destroyed using delete operator.

A. New
B. Delete
C. Del
D. Create

Q NO 305:

In the calling function, after the execution of the function called, the program continues its execution from the _____afterthe function call.

A. Previous line
B. Next line
C. Beginning
D. None of the above

Q NO 306:

Last node in circular linked list contains

A. At least one null pointer
B. No null pointer
C. Maximum two null pointers
D. None of the given

Q NO 307:

_____is an area in computer memory that is allocateddynamically.

A. Heap
B. Stack
C. Queue
D. Linked list

Q NO 308:

Linked list use_____to store data.

A. Array
B. 2-D Array

Mickey ch

C. Variables
D. Linked Memory

Q NO 309:

The lifetime of a transient object cannot exceed that of theapplication.

A. True
B. False
C. In some cases
D. None of the given

Q NO 310:

To represent hierarchical relationship between elements, whichdata structure is suitable?

A. Dequeue
B. Priority
C. Stack
D. Tree

Q NO 311:

Local variables of a function are stored in,

A. Binary search tree
B. Stack
C. Queue
D. AVL tree

Q NO 312:

In-order traversal method traverses tha data in

A. Non sorted order
B. Random order
C. Sorted order
D. None of the given

Q NO 313:

One should be careful about transient that are stored byreference in data structures.

A. Objects
B. Stack
C. Function
D. Tree

Q NO 314:

Binary search tree violates the condition of AVL tree when anynode has balance equal to

A. 2 or -2
B. 1 or -1
C. 0
D. None of the options

Q NO 315:

Security of data is the main usage of AVL tree.

A. True
B. False
C. In some cases
D. None of the given

Q NO 316:

A binary tree whose every node has either zero or two children iscalled_____.

A. Complete binary tree
B. Binary search tree
C. Strictly binary tree
D. None of above

Q NO 317:

Mickey ch

Learning With Mickey ch

In internal memory organization of a process, there is some areaof memory for static data that holds_variables.

A. Static
B. Global
C. Not static neither global
D. Both static and global

Q NO 318:

Following is true in case of using recursive method calls.

A. The code becomes very long
B. There is no effect on length of code
C. The code becomes very short
D. Code becomes very easy to understand

Q NO 319:

In which traversal method, the recursive calls can be used totraverse a binary tree?

A. In preorder traversal only
B. In inorder traversal only
C. In postorder traversal only
D. All of the given options

Q NO 320:

If we use doubly linked list to implement list then there is anissue of

A. Next pointer of first node and pre pointer of last node are NULL
B. Next pointer of first node and next pointer of last node are NULL
C. Pre pointer of first node and next pointer of last node are NULL
D. Pre pointer of first node and pre pointer of last node are NULL

Q NO 321:

In case of insertion of left outer node in BST,

A. We apply single right rotation to make it AVL tree.
B. We apply single left rotation to make it AVL tree.
C. We first apply right rotation and then left rotation to make it AVLtree.
D. We first apply left rotation and then right rotation to make it AVLtree.

Q NO 322:

Whenever we call a function, the complier makes a stack, the topelement of the stack is __ of the function.

A. First argument
B. Return address
C. Last argument
D. None of the above

Q NO 323:

Suppose a stack class has been defined using template. Now, wewant to declare a Stack object of an int type. What will be the correct syntax?

A. <int>Stack stack;
B. Stack<int> stack;
C. Stack int stack;
D. Int Stack stack;

Q NO 324:

In node class one field is an integer data and other field will be___.

A. Pointer to class
B. Pointer to node
C. Pointer to integer
D. None of given options

Q NO 325:

Mickey ch

Whatsapp#0333-6166150

If there are 100,0000 unique members (nodes) stored in acomplete binary tree, the tree will have__levels.

A. 10
B. 20
C. 30
D. 40

Q NO 326:

~BinarySearchTree() is a _____.

A. Constructor
B. Destructor
C. Switch case
D. Template method call

Q NO 327:

Dequeue() operation of queue data structure is used to_____.

A. Get an element from the front of the queue
B. Remove an element from the front and return it
C. Insert an element at the front
D. Insert an element at the back

Mickey ch