Question *it* 2 of 10 ( Start time; O3;37;OO PM, 05 January 2024 )

Total Marks;

The counter in PL/SQL FOR Loop is by default incremented by ..... .

Select the correct option

| | |
|---|---|
| o | NULL |
| o | 0 |
| 0 | 2 |
| ® | 1 |

Click to Answer A Move to Nett Question

VU Academic Consultant 03222254114

Question # 3 of 10 ( Start time: 03:37:57 PM, 05 January 2024 ) Total Marks:

Wheri you jvant to execute a series of statements repeatedly, you use the PL/SQL _____loop

Select the correct option

| | |
|---|---|
| o | cursor |
| ® | For |
| o | While |
| o | Cursor For |

► 1

P Type here to search 25-C Haze ~ <fe) ENG

VU Academic Consultant 03222254114

Question # 4 of 10 (Start time: 03:40:08 PM, 05 January 2024 ) Total Marks:

Where is rhe control transferred while using a CONTINUE statement?

Select the correct option

| | | |
|---|---|---|
| o | Lost iteration of the current loop | |
| o | First iteration of the current loop | |
| © | Next iteration of the current loop | |
| o | First statement after the end of the loop | |

VU Academic Consultant 03222254114

Question # 5 of 10 ( Start time: 03:40:41 PM, 05 January 2024 ) Total Marks:

Which of the operations o' a cursor checks for the validity of a SQL statement[0]

Select the correct option

Reload Math Equations

| | |
|---|---|
| o | BIND |
| o | OPEN z |
| o | FETCH z |
| ® | PARSE z |

Click lu Save Answer & Wave to Next Question

VU Academic Consultant 03222254114

question B10 of 10 ( start time: 03:46:05 PM. 05 January 2024)

Total Marks:

What is the initial value of index for a reverse for loop?

Select the correct option

| | |
|---|---|
| o | 1 z |
| ® | UPPER bound z |
| o | Lower bound .Z |
| o | Upper bound-Lower bound/2 z |

Click to Save Answer & Movo to Noxt Question

VU Academic Consultant 03222254114

Question # 6 of 10 (Start time: 03:41:16 PM 05 January 2024 ) Total Marks

Which of the following is TRUE while using Pi/SQl FOR loop'

Select thecorrect option

Reload Math Equations

| | |
|---|---|
| o | ir is not necessary ro explicitly increment the counter variable since it is ncremented by 1 |
| o | The counter varianle is implicitly declared in the declaration Section so you do not need to declare it explicitly |
| o | FOR loops con use EXIT WHEN cind EXIT statements, but it isn't often used |
| ® | All of the mentioned |

Click to save Answer & Move to Next Question

VU Academic Consultant 03222254114

Question # 7 of 10 (Start time: 03:42:06 PM, 05 January 2024 ) Total Marks: '

How many types of cursors?

Select the correct option

| | |
|---|---|
| ® | 2. z |
| o | 1 z |
| o | 4 z |
| o | 3 & |

Click to Save Answer & Move to Norf Question

VU Academic Consultant 03222254114

Question # 8 of 10 (Start time: 03:43:30 PM, OS January 2024 ) Total Marks:'

YOU con also use CONTINUE IO termmoie on .....loop and continue immediately on to the next iteration of an outer oop s ooay

Select the correct option

| | |
|---|---|
| o | Simple |
| 0 | Nested |
| ® | inner |
| o | Outer |

Click to Save Answer & Move to Next Question

VU Academic Consultant 03222254114

question B10 of 10 ( start time: 03:46:05 PM. 05 January 2024)

Total Marks:

What is the initial value of index for a reverse for loop?

Select the correct option

| | |
|---|---|
| o | 1 z |
| ® | UPPER bound z |
| o | Lower bound .Z |
| o | Upper bound-Lower bound/2 z |

Click to Save Answer & Movo to Noxt Question

VU Academic Consultant 03222254114

**Question *ft* 9 of30 {Start time: 0344:43 PM. 05 January 2024}** **Total Marks**

BEGIN

FOR • INI_5 LOOP If I

= 31htN CONTINUE;

END IF; DBMS_UUIl'JIJ'UI_LJNt|Iteralor » || EhD

lOOP, FND; Output lor this piece o' code

**Select the correct option**

Iteration I

Iteration e 5

Iteration # 5

Iteration # I

Iteration » 2

Iteration » 4

iterationC

Iteration « i

iteration «r 4

Itoration »

© O Li
© <3 ©
VU Academic Consultant 03222254114