

AR Lucky Term



Cs 201

Searching File

Mid/Final Term

AR Lucky Term

**SUBSCRIBE**
AR Lucky Bahi

**SUBSCRIBE** AR Lucky Bahi

اسلام علیکم!

اگر آپ میں سے کوئی (Student) **LMS Handling** کروانا چاہتا ہے یا۔۔۔
پھر اپنے LMS کو ٹائم نہیں دے پاتے۔ تو وہ مجھ سے اپنے LMS کے لیے رابطہ کر سکتا ہے۔
اس میں آپ کی تمام (Assignment, Quizzes And GDB's) جمع (Submit) کروائی جائیں گی۔

We are also provide these services:

- LMS handling
- Quizes
- Assignments
- GDB
- Circular Activities
- Project Handling from A to Z.

(SRS, DESIGN DOCUMENT, TEST PHASE, VIVA, FINAL DELIVERABLE, PRE VIVA, FINAL VIVA)

- ★ Gurantee of 95% maximum to 90% minimum Marks.
- ★ You will be charged a reasonable Amount

اور اگر آپ میں سے کوئی (Online Classes) لینا چاہتا ہے تو وہ بھی رابطہ کر سکتا ہے

WhatsApp No:

Miss Hurain Fatima
0313-4103116

Sir Abdul Rehman
0304-2387216

**SUBSCRIBE**

AR Lucky Bahi



AR Lucky Term

CS201 Midterm Past Paper

Objective Questions

Question # 1

Which of the following is one of the main categories of software?

Operating system

System Software

Device drivers

Utilities

Question # 2

*data means _____.

the value of whatever the data points

the address of the variable data **Correct Ans** By **AR**

dereferencing

none of the given

Question # 3

Which statement is used to close a file?

myFile.off();

myFile.shut();

myFile.closefile();

myFile.close(); **Correct Ans** By **AR**

Question # 4

What will be correct syntax for declaration of the following statement?

"ptr is a constant pointer to an integer"

const * int myptr;



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

const int *myptr; **Correct Ans** By **AR**

int const *ptr;

int *const ptr ;

Question # 5

Select the correct way to assign the address of first element of array to pointer?

int data[10];

int *ptr = &data[1];

int *ptr = &data; **Correct Ans** By **AR**

int *ptr = data;

int *ptr = data[0];

Question # 6

To manipulate n-dimensional array array _____ nested loops are required.

n-2

n-1 **Correct Ans** By **AR**

n+1

n

Question # 7

In if structure the block of statements executes when the condition is ____.

Contains logical operator

Contains arithmetic operator

False

True



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Question # 8

Character strings are terminated by _____.

\0 **Correct Ans** By **AR**

\o

\n

\t

Question # 9

_____ are conventional names of the command line parameters of the 'main()' function.

'argv' and 'argc'

'argc' and 'argv' **Correct Ans** By **AR**

'argc' and 'argu'

None of the given

Question # 10

To perform repetition tasks for a known number of repetitions, most often used structure is _____.

For structure

While structure

Do-while structure

None of the above **Correct Ans** By **AR**

Question # 11

In two-dimensional array, we use _____ 'for loop(s)' to populate the array.

1

2



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

3

4

Question # 12

_____ loop is mostly used to perform repetition of a tasks for a known number of times.

While

Do-While

For **Correct Ans** By **AR**

Nested Loop

Question # 13

If $y = 20$ and $z = y++$, then the value of z will be _____.

19

20

21 **Correct Ans** By **AR**

22

Question # 14

For the following statement, how much memory will be allocated to myarray[0]?

```
char * myarray[] = {"Arif"; "Sadiah"};
```

4 Bytes

5 Bytes

6 Bytes

7 Bytes

Question # 15



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

What will be the output of the following code snippet?

```
string str1 = "Hello beautiful";  
string str2 = "Yes we can";  
string str3 = strcpy(str1,str2);  
cout<< str3 <<endl;< h2="" style="box-sizing: border-box;"></endl;<>
```

Hello beautiful

Yes we can

Hello beautiful Yes we can

Yes we can Hello beautiful

Question # 16

&& is a _____ operator.

Arithmetic

Relational

Logical **Correct Ans** By **AR**

Mathematical

Question # 17

When No. of repetition is known then we use the _____ structure to perform repetition tasks.

While loop **Correct Ans** By **AR**

Do While loop

For loop

Switch

Question # 18



AR Lucky Term

Following is an array of _____ rows and _____ columns. `int num[3][4];`

4 . 5

4 . 3

2 . 3

3 . 4 **Correct Ans** By **AR**

Question # 19

Correcting the errors from a program is termed as _____.

Linking

Loading

Executing

Debugging **Correct Ans** By **AR**

Question # 20

Identify the logical error in the following if condition

If `)i < 5) && (i > 15)`

Condition is always true

Condition is always false **Correct Ans** By **AR**

& will be used instead of &&

&& cannot be used with if condition

Question # 21

What will be the value of 'a' and 'b' after executing the following statements?

`int a = 9;`

`int b = a++;`



AR Lucky Term

```
cout<<.a; .  
cout<<.b;
```

10.9

9.10 Correct Ans By AR

9.9

10.10

Question # 22

When we access a multidimensional array, each array index is surrounded by _____.

Single quotes

Double quotes " "

Brackets [] Correct Ans By AR

Commas ..

Question # 23

The structure, in which the body of the loop executed at-least once is called_____.

For structure

While structure

Do-while structure

none of the above

Question # 24

Each array declaration must provide the information about all these things except _____.

Name of the array



AR Lucky Term

Type of data stored in the array

The location of the first element to be stored

Number of elements of the array **Correct Ans** By **AR**

Question # 25

For breaking complex problems into smaller pieces we use _____.

if/else

Loops

Functions

Break statement

Question # 26

Which of the following options is/are correct about array?

Different types of elements can store in an array

Only one type of elements can store in an array **Correct Ans** By **AR**

Elements in an array cannot be sorted

All the given options

Question # 27

Suppose we have `int y[10];`

To access the 4th element of the array we write_____.

`y[4];`

`y[3];` **Correct Ans** By **AR**

`y[2];`

none of given

Question # 28

In C/C++, a variable's name can start with the symbol _____.

; Semicolon



AR Lucky Term

: Colon

_ Underscore

+ Plus

Question # 29

When the if statement consists of more than one statement then enclosing these statement in braces is _____.

Compulsory **Correct Ans** By **AR**

Optional

Not required

Relevant

Question # 30

Which of the following is not a valid variable name in C++?

NameOfStudent

nameOfStudent

_studentName

@studentName **Correct Ans** By **AR**

Question # 31

Using a segment of source code again by adding new functionalities with slight or no modification is termed as _____.

Code efficiency

Code modification **Correct Ans** By **AR**

Code Reusability

Code Generation

Question # 32

Why we use "cout"?



AR Lucky Term

To send data to printer

To read data from keyboard **Correct Ans** By **AR**

To display output on the console screen

None of the given options

Question # 33

pointer points to a particular_____.

Value

variable

data type

memory address **Correct Ans** By **AR**

Question # 34

What will be the resultant value of this expression $x = 17 \% 3$?

1

2 **Correct Ans** By **AR**

3

4

Question # 35

Default mechanism of calling a function by passing it array is call by _____ and in case of passing variable is call by _____.

Reference, Reference

Reference, value **Correct Ans** By **AR**

Value, Reference

Value, Value

Question # 36



AR Lucky Term

Which of the following is the correct way to initialize two dimensional array along with declaration?

`int x[2][3] = {{22, 23, 10}, {15, 25, 13}};`

`int x[2][3] = {22, 23, 10}, {15, 25, 13};`

`int [2][3]x = {};`

`int x[2][3]x = {{0}, {0}};`

Question # 37

From the following; which one is used as an assignment operator?

Equal sign '=' **Correct Ans** By **AR**

Double equal sign "=="

Both equal and double equal sign

None of the given options

Question # 38

`char name [] = "Hello World" ;`

In the above statement, a memory of _____ characters will be allocated

13

11

12 **Correct Ans**

10

Question # 39

The data in the memory is _____

volatile **Correct Ans** By **AR**

non-volatile

both



AR Lucky Term

none

Question # 40

NOT operator is a _____

Single input operator **Correct Ans** By **AR**

Binary operator

Ternary operator

None of the given

Question # 41

The structure, which can execute zero or more times is called _____.

For structure

While structure **Correct Ans**

Do-While structure

None of the above

Question # 42

If x is declare as an integer, what will be result of the given expression?

$x = 3 * 5 \% (2 + 1) / 2$

4 **Correct Ans** By **AR**

3.5

1

3.75

Question # 43

A string in C is

1-D array of integer

2-D array of character



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

1-D Array of Character

None of the above

Question # 44

Operating System is a type of _____ software.

Device Driver

Application

System **Correct Ans** By **AR**

Utility

Question # 45

We comment code as it makes program _____

Heavy i.e. more space is needed for executable.

Difficult to compile.

All of these.

Easy to understand.

Question # 46

_____ is the pointer which determines the position in a file from where the next read operation occurs.

Set

Get May be

Put **Correct Ans** By **AR**

Tell

Question # 47

_____ allow us to have a memory location and use it as int or char interchangeably

structures



AR Lucky Term

union

construct

None of the given **Correct Ans** By **AR**

Question # 48

What logical error exists in the following arithmetic expression?

$$X = 50 / (2 \% 2) + 9$$

() parenthesis are not allowed in expressions

Division by zero will occur in this expression **Correct Ans** By **AR**

Order of the expression is not according to rules

We can not use % operator in expressions

Question # 49

What is output of following code?

```
int data[10] = {10,20,30,40,50,60,70,80,90,100};  
int *xptr = &data[4];  
int &yptr = &data[6];  
cout<<"" h2="" style="box-sizing: border-box;">
```

110

120 **Correct Ans** By **AR**

130

Syntax error

Question # 50

Bitwise AND Operator works just like the logical _____but on bits

AND operator



AR Lucky Term

OR operator

NAND operator

None of the given

Question # 51

< , <= , > , >= are called _____ operators.

Arithmetic

Logical

Relational

Correct Ans By AR

Conational

Question # 52

In shifting operations if zero is inserted at the left most bit, the negative number will become a _____ number

Positive Correct Ans By AR

Negative

Absolute

Smaller

Question # 53

How many times the following do-while loop will execute?

```
int k = 10;
```

```
do
```

```
{
```

```
cout<< "Statements" << endl;
```

4

5

6 Correct Ans By AR



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

7

Question # 54

The parameter passed to isdigit() function is _____variable.

Character **Correct Ans** By **AR**

Boolean

Double

Float

Question # 55

A file opened with _____ is used for input and cannot be used for output.

iostream

ofstream

ifstream **Correct Ans** By **AR**

none

Question # 56

When a = 26; then the expression a%= 5; will calculate the value of a as,

1 **Correct Ans** By **AR**

0

3

5

Question # 57

The an n-dimensional array, we use _____ 'for loop(s)' to populate the array.

n **I think** By **AR**

n+1



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

n-1

n+2

Question # 58

Pointers are a special types of _____ in which a memory address is stored.

Variables **Correct Ans**

Location

Characters

None of the given

Question # 59

Pointers store the _____.

Value of a variable **Correct Ans**

Memory address

Characters

None of the given

Question # 60

After evaluating the expression

$x = 10 + 3 * 4 / 2 - 1$, the value of x will be

25

22 **Correct Ans**

52

15

Question # 61

When an identifier is declared with keyword const then,

Its value can be changed during execution.



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Its value cannot be changed **Correct Ans**

Its value can be changed with arithmetic operator

Its value can be overwritten

Question # 62

= operator is used for _____.

Decision making

Assigning values to variables **Correct Ans**

Checking equality

Comparison

Question # 63

12 & 8 =(1000) 2 =_____. & is used to AND two numbers bit-wise

4

8

6 **Correct Ans**

12

Question # 64

If int a = 50; then the value of a/=3; will be,

15

18

16 **Correct Ans**

17

Question # 65

Why do we use "cout"?

To send data to printer

To read data from keyboard



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

To display output on the console screen **Correct Ans**

None of the given options

Question # 66

Remainder operator (%) is a _____operator.

Conditional

Logical

Arithmetic **Correct Ans**

Relational

Question # 67

A function's prototype is written _____the function call.

After

Before

With **Correct Ans**

At the end of

Question # 68

What will be the output of the following code?

```
string grade [3]={"A", "B", "C"}
```

```
grade[2] = "F";
```

```
cout << grade[2];
```

A

B

C

F **Correct Ans**

Question # 69

We can define a matrix as_____array.



AR Lucky Term

Sorted

Unsorted

Single dimensional

Multi dimensional **Correct Ans**

Question # 70

When $x = 9$; then the expression $x\% = 2$; will calculate the value of x as,

4

3

2

1 **Correct Ans**

Question # 71

What will be the output of following code segment?

```
for (int number = 3; num <= 5; num++)
```

```
{
```

```
if (num % 2 != 0)
```

```
continue;
```

```
cout << num << " ";
```

```
}
```

2

3

4

5 **Correct Ans**

Question # 72

What will be the correct output for the given program?

```
int num = 1;
```



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

```
switch ()  
{  
case 1 :  
cout << " 15 " ;  
break;
```

15

20

15

20

Error

Question # 73

To get the values stored at a memory address, we use the_____.

referencing operator

dereferencing operator **Correct Ans** By **AR**

binary operator

AND(&&) operator

Question # 74

While loop becomes infinite in which scenario _____.

When the condition is always False **Correct Ans** By **AR**

When the condition is always True

Condition contains logical operators

Condition contains arithmetic operators

Question # 75



AR Lucky Term

From the following; which one is the correct syntax of an array declaration: array size is 5 and it is of float data type?

float [5] name;

name [5] float;

float name[5];

none of the given options **Correct Ans** By **AR**

Question # 76

In_____. we have different data members and all of these have their own memory space.

structures **Correct Ans** By **AR**

union

construct

None of the given

Question # 77

student s[100]: means that 's' is an array of hundred students of type 'students' structure. What will be the correct statement to access the 'name' data element of the fifty sixth student from the array?

s[55].name;

s[56].name;

s.name[55];

s.name[56];

Question # 78

The most suitable data type for number 325.25 is _____.

char

int



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

short

float **Correct Ans** By **AR**

Question # 79

eof is used to check for the _____ of file when a file is being read.

Start

End **Correct Ans** By **AR**

Middle

Name

Question # 80

A _____ is a precise sequence of steps to solve a particular problem.

Code

Program **Correct Ans** By **AR**

Statement

None of the given options

Question # 81

If we assign 2.06721 to an integer variable x. what will be the output if we print x using cout<< statement?

2 **Correct Ans** By **AR**

2.1

2.06

2.07

Question # 82

For the following given function prototype,

int add (int *);

Which one of the given function calls is "call by reference".



AR Lucky Term

add(&x);

add(intx);

add(x);

add("x"); **Correct Ans** By **AR**

Question # 83

While loop executes at least _____ if the condition is false.

Zero time

One time **Correct Ans** By **AR**

Two times

Undefined times

Question # 84

What will be the output of the following code segment?

```
char myName[] = "Student ID";
```

```
int n= sizeof(myName); cout<<="" h2="" style="box-sizing: border-box;">
```

10

9

11

12

Question # 85

Learning to program is important because it develops _____ and _____ abilities.

Reading. Writing

Reading, Problem solving



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Analytical, Problem solving

Analytical, Writing

Question # 86

The original value remains unchanged in_____.

Pointers

Static Variables

Multi-way decisions

Call by value **Correct Ans** By **AR**

Question # 87

What will be the result of $z = x \% y$; if $x = 29$ and $y = 5$?

4 **Correct Ans** By **AR**

3

2

1

Question # 88

AT the_____, we try to break up the problem into functional units

analysis phase

design phase **Correct Ans**

implementation phase

None of the given

Question # 89

If a file is opened with `ios::out` mode, then_____.

file is deleted

we can write in this file **Correct Ans** By **AR**



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

content of file discarded

a new file is created

Question # 90

in the given expression which operator will be evaluated first?

$10 + (6 / 2) - 2 * 3$?

+

-

/

Correct Ans By AR

*

Question # 91

What will be the value of the variable output in the given piece of code?
piece of code?

double output = 0;

output = (2 + 2) * 4 + 2 / (4 - 2);

15

17 Correct Ans By AR

12

11

Question # 92

Telling a computer what to do is called _____.

Designing

Implementing

Programming Correct Ans By AR

Compiling

Question # 93



AR Lucky Term

C++ is a_____ language.

High level **Correct Ans** By **AR**

Low level

Machine

Assembly language

Question # 94

_____ Returns true if c is a digit or a letter and false otherwise.

int isalpha(int c)

int isalnum(int c) **Correct Ans** By **AR**

int isxdigit(int c)

int isdigit(int c)

CS201 Midterm Past Paper

Objective Questions

Question # 1

!= operator is used to check whether the operand on the left-hand-side is _____ to the operand on the right-hand-side

Less then or equal

Greater than or equal

Not equal **Correct Ans** By **AR**

Approximately equal to

Question # 2

_____ function is used to find the number of characters in a string.

str()

Str_len()

Strlength ()

strlen()**Correct Ans** By **AR**

Question # 3



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

What will be the output of the following code snippet?

```
char dest[50] = "Using strcat function,";  
char src[50] = " this part is added and this is ignored";  
strncat(dest, src, 19);
```

Using strcat function, this part is added

Using strcat function, and this is ignored

Using strcat function, this part is added and this is ignored

Using strcat function, this part

Question # 4

The increment of a pointer depends on its_____.

variable

value

data type **Correct Ans** By **AR**

None of the given

Question # 5

If we pass more than one arguments to a function then they are separated by _____.

Comma , **Correct Ans** By **AR**

Colon :

Semicolon ;

Double quotes "

Question # 6

+= , *= , /= , etc are called

Assignment operators

Logical operators

Compound assignment operators **Correct Ans** By **AR**

Unary operator

Question # 7

What will be output of the following code segment?

```
int value = 1;  
switch (value+value){
```



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

case 1 :

```
cout << "Punjab " ;
```

```
break;
```

case 2 :

Punjab

Lahore

Pakistan

Syntax error

Question # 8

Which step is not performed during a proper program design?

Analyze a problem statement, typically expressed as a word problem

Formulate statements and comments in a precise language

Write details about the performance of program **Correct Ans** By **AR**

Pay attention to detail

Question # 9

Comments are written to explain the _____ of programs

Performance

Reliability

Functionality

Consistency

Question # 10

What is the output of Bitwise OR operation on (0110 | 110)?

1110

1101

1000

1010

Question # 11

_____ will be used for enclosing function statements into a block.

""

()

[]

{ } **Correct Ans** By **AR**



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Question # 12

Following is the declaration a _____ array. `int arr[2][2][2];`

1-Dimensional

2-Dimensional

3-Dimensional **Correct Ans** By **AR**

4-Dimensional

Question # 13

Why do we use "cin"?

To send data to printer

To read data from keyboard **Correct Ans** By **AR**

To display message

To display output on the screen

Question # 14

We can access a global variable _____

From the functions only

From the loops only

From the main() function only

From anywhere in the program **Correct Ans** By **AR**

Question # 15

Which of the following is true about streams?

A. It is a sequence of bytes

B. It is an ordered sequence

C. All bytes can go through the stream simultaneously

D. Bytes that enters first into the stream will go out at last

A only

C only

A and B **Correct Ans** By **AR**

A and D

Question # 16

What will be the output of the following program?

```
void car() {
```



AR Lucky Term

```
cout << "Honda";  
}  
int main() {  
Car();  
}
```

Syntax Error

Car

Honda

Honda car

Question # 17

What will be the output of the following while loop?

```
int counter = 0 ;  
while(counter < 15)  
cout << counter <<"";  
counter++;
```

1 2 3 4

1 2 3 4 5

Compile time error

Infinite loop **Correct Ans** By **AR**

Question # 18

Find the syntax error in the following piece of code?

```
if (x>y);  
cout<<" x is greater than y ";  
else  
cout<<"y is greater than x";
```

Braces not given for if an else blocks

Condition in the if statement is wrong

Semicolon should not be after the if statement

No error in the code



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Question # 19

What is the output of the following code?

```
for (int i=0; i<5; i++) cout << i%2 << " ";
```

0 1 2 3 4 5
0 2 4 6 8 10
0 1 0 1 0
1 0 1 0 1

Question # 20

Following is the declaration a _____ array. `int arr[2][2];`

1-Dimensional

2-Dimensional **Correct Ans** By **AR**

3-Dimensional

None of the given

Question # 21

_____ will explain in the functionality of a program.

Comments **Correct Ans** By **AR**

Debugger

Compiler

Linker

Question # 22

X is an integer variable; what does X++ means,

Add 1 two times in X value

Add 1 in X value **Correct Ans** By **AR**

Add 2 in X value

None of these

Question # 23

Structures are syntactically defined with the word_____.

struc

struct **Correct Ans** By **AR**

structure

None of the given

Question # 24



AR Lucky Term

Switch statement can be used in place of _____ statement.

break

continue

Multiple if **Correct Ans** By **AR**

goto

Question # 25

A function is a block of statements that can be defined once and used _____ in the program.

One time

Two times

Three times

As many times as user wants **Correct Ans** By **AR**

Question # 26

Which of the following option is correct to complete the declaration of the function?

_____ (parameter1, parameter2)

{

// code to be executed

}

void functionName

int functionName;

functionName void

void (functionName)

Question # 27

An object of _____ class can be created for saving the current position of any opened file before reading from the file.

Stream

Filepos

Streampos

Filestream **Correct Ans** By **AR**

Question # 28



AR Lucky Term

'multi [3] [3]' element can also be accessed by '_____'.
Correct Ans By AR

`** (multi+3)+3`

`*(*(multi+3)+3)`

`*(multi+3)`

None of the given

Question # 29

Which header file is required to use file I/O operations?

`ifstream`

`ostream`

`fstream`

`iostream`

Question # 30

When accessing a structure member, the identifier to the left of the dot operator is the name of _____.

Structure variable

Structure member

Structure tag

Structure data

Question # 31

A string which is assigned to a string variable is terminated by _____.

Colon

Semicolon

Null character

Boolean expression

Question # 32

`if`

`int a = 17;`

`int b = b 3;`

`double c = a / b;`

What will be value of variables c?



AR Lucky Term

5.5

5.6

5 Correct Ans By AR

5.7

Question # 33

The data, contained in the structure, is defined in the _____.

curly braces

parenthesis

inverted commas

none

Question # 34

The operators ++ and - are used to increment or decrement the value of a variable by _____

1 Correct Ans By AR

2

3

4

Question # 35

Following is the declaration of a 2D array, how many columns are declared for this array.

int arr[3][2];

3

2 Correct Ans By AR

32

23

Question # 36

Strings are accessed by variable of type _____,

char Correct Ans By AR

int

double

None of the given

Question # 37

The value of a pointer can be _____.



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- address of a variable
- name of the variable
- value of the variable
- none of the given options

Question # 38

A hierarchy of classes which are used to deal with console and disk files are called _____..

- Stream classes
- Simple classes
- Binary classes
- 10 classes

Question # 39

Switch support _____ data

- Integer
- Character
- Float

Both integer and character **Correct Ans** By **AR**

Question # 40

How many bytes an integer type pointer intPtr will jump in memory of the statement below is executed?

intPtr += 2 ;

- 2
- 4
- 8 **Correct Ans** By **AR**
- 12

Question # 41

According to c++ norms; the first character of a variable name must be an alphabet or

- Underscore
- Special character
- Digit
- None of the given options



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Question # 42

" <"and">"both are _____ operators.

Arithmetic

Relational

Logical **Correct Ans** By **AR**

Mathematical

Question # 43

Which is not true tegarding structures?

We can declare arrays of structure **Correct Ans** By **AR**

We can take the size of structure

We can't declare pointers to structure

both b & c

Question # 44

The string in the array is terminated by a _____

Zero

Null

Null **Correct Ans** By **AR**

One

Question # 45

How can we declare an array of characters whose size is 12 with array name "country"?

char country[12]; **Correct Ans** By **AR**

char country[11];

char [12] country;

char country[0-11];

Question # 46

What will be the output of the following code?

```
char greeting[6] = {'H', 'e', 'l', 'l', 'o', '\0'}
```

```
cout << "greeting message:";
```

```
cout << greeting << endl;
```

Greeting message: Hello

Greeting: message: 'H', 'e', 'l', 'l', 'o'.



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Greeting message 6

Greeting message greeting

Question # 47

_____ is used for input file or for reading from the file.

tellg() **Correct Ans** By **AR**

seekg()

tellp()

seekp()

Question # 48

Which of the following is the correct way to write a compound assignment operator?

x += 4;

x + = 4;

x += = 4;

None of the above

Question # 49

What is the output of the following code if the 3rd case is true
switch (var)

```
{  
case'a':  
cout<<"apple"<  
cout<<"mango"<  
}
```

Mango **Correct Ans** By **AR**

mango any fruit

apple

none of the above

Question # 50

We use _____ to open a file or stream for insertion.

in

out **Correct Ans** By **AR**



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

app

ate

Question # 51

char **argv can be read as_____.

pointer to pointer

pointer to char

pointer to pointer to char **Correct Ans** By **AR**

None of the given

Question # 52

Computer can understand only _____ language code.

High level

Low level

Machine **Correct Ans** By **AR**

Fourth generation

Question # 53

A = a + 1; can be written as _____.

a + 1;

a += 1; **Correct Ans** By **AR**

a + a + 1;

1 + a = a;

Question # 54

Array indexes start from

0 **Correct Ans** By **AR**

1

2

3

Question # 55

Which of the following is the correct operator to compare the values of two variables?

:-

=

*=

== **Correct Ans** By **AR**



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Question # 56

In case of two-dimensional array, if you add some number in a two-dimensional array name, it will jump to the next _____.

Row **Correct Ans** By **AR**

column

character

array

Question # 57

Following is the declaration of a 2D array, how many rows are declared for this array.

```
int arr[3][2];
```

3

2 **Correct Ans** By **AR**

32

23

Question # 58

student s[100]; means that 's' is an array of type 'student' structure. What will be the correct statement to access the 'name' data element of the fifty sixth student from the array?

s[55].name;

s[56].name;

s.name[55];

s.name[56];

Question # 59

A record is a group of related _____.

Data

Fields **Correct Ans** By **AR**

Bytes

Files

Question # 60

What is the output of the following code?

```
for (int i = 5; i <= 5; i++) {
```



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

```
cout << i++;  
cout <  
}
```

56
65
55
13

Question # 61

how we declare an array of integer data whose size is 20 with array name "count".

```
int count[19];  
int count[20]; Correct Ans By AR  
float count[20];  
int count[21];
```

Question # 62

The_____ is an unconditional branch of execution.

Switch statement
Continue statement
Goto statement
Default statement

Question # 63

At the design phase, we try to break up the problem into_____

functional units **Correct Ans** By **AR**
non-functional units
small units
None of the given

Question # 64

There is a pointer variable named ptr of type float. Which type of variable address can be stored by ptr?

int **Correct Ans** By **AR**
float
char



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

double

Question # 65

What will be the size of following array?

int arr[29];

0

30 **Correct Ans** By **AR**

29

28

Question # 66

The name of the array is a constant pointer which contains the memory address of the _____ of the array.

first element **Correct Ans** By **AR**

Last element

Second element

None of the given

Question # 67

In while loop the loop counter must be initialized,

With in the loop

Before entering the loop **Correct Ans** By **AR**

At the end of the loop

None of the given options

Question # 68

We get $12 | 8 = \underline{\hspace{2cm}}$. Where "|" is (bit-wise OR)

12 **Correct Ans** By **AR**

10

8

14

Question # 69

If a _____ finds an error, it stops translating without generating any executable code.

linker

Loader

Compiler **Correct Ans** By **AR**



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Interpreter

Question # 70

_____ will be used for clarity and to force the order of evaluation in an expression.

" "

() **Correct Ans** By **AR**

' '

[]

Question # 71

C was developed with the help of _____ language(s).

FORTRAN

JAVA

BCPL and B **Correct Ans** By **AR**

none of the above

Question # 72

To read command-line arguments, the main() function itself must be given _____ arguments.

1

2 **Correct Ans** By **AR**

3

4

Question # 73

When we call a function, its control

transfers to its Prototype

transfers to its definition **Correct Ans** By **AR**

returns to statement following function call

The compiler stops execution of whole program

Question # 74

In _____, we try to have a precise problem statement

Analysis **Correct Ans** By **AR**

Design

Coding

None of the given



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Question # 75

These functions seekg() requires an argument of type _____ to let them how many bytes to move forward or backward.

int **Correct Ans** By **AR**

short

long

double

Question # 76

!(x > 3) means in C++ that

x is greater than 3 **Correct Ans** By **AR**

x is less than or equal to 3

x is less than 3

x is equal to 3

Question # 77

We use _____ to include all those functions in our program which are located in different files

Linker **Correct Ans** By **AR**

Loader

Compiler

Debugger

Question # 78

If

```
int sum = 54;
```

Then the value of the following statement is

```
sum = sum - 3 ;
```

52

50

51 **Correct Ans** By **AR**

57

Question # 79



AR Lucky Term

What will be the result of the expression

`k = ++m;`

if initially `k = 0` and `m = 5`?

0

5 **Correct Ans** By **AR**

6

4

Question # 80

When the logical operator OR (`||`) combine two expressions `exp1` and `exp2` then the result will be false only,

When both `exp1` and `exp2` are true **Correct Ans** By **AR**

When both `exp1` and `exp2` are false

When `exp1` is true and `exp2` is false

When `exp1` is false and `exp2` is true

Question # 81

Which of the following is used to create an output stream?

`ofstream`

`ifstream`

`iostream`

`fsstream`

Question # 82

_____ will explain the functionality of a program.

Comments **Correct Ans** By **AR**

Debugger

Compiler

Linker

1. For binary member operators, operands on the _____ drives (calls) the operation.

0. Left **Correct Ans** By **AR**

1. Right



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

2. Both left and right
3. None of the given
2. We cannot increment _____.
 0. pointers
 1. arrays
 2. references **Correct Ans** By **AR**
 3. variables
3. We can _____ pointer.
 0. increment
 1. decrement
 2. reassign
 3. all of the given **Correct Ans** By **AR**
4. We can _____ references.
 0. increment
 1. decrement
 2. reassign
 3. None of the given **Correct Ans** By **AR**
5. What will be the correct syntax for the following function call?
float add (int &);
 0. add(int x);
 1. add(&x);
 2. add(x); **Correct Ans** By **AR**
 3. add(*x);
6. An instance of a class is called _____.
 0. structure
 1. data type
 2. object **Correct Ans** By **AR**
 3. member function
7. The _____ is called automatically when an object destroys



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

0. destructor **Correct Ans** By **AR**

- 1. constructor
- 2. main program
- 3. default constructor

8. The destructor is used to _____.

0. allocate memory

1. deallocate memory **Correct Ans** By **AR**

- 2. create objects
- 3. allocate static memory

9. _____ data isn't accessible by non-member functions or outside classes.

0. Public

1. private **Correct Ans** By **AR**

- 2. Static
- 3. Globally declared

10. Member functions of the class _____ main program.

0. are not accessible

1. are accessible from **Correct Ans** By **AR**

- 2. are defined within the
- 3. are private to

11. Overloading means :

0. Using the same name to perform multiple tasks or different tasks depending on the situation. **Correct Ans** By **AR**

- 1. Using the different name to perform multiple tasks or different tasks depending on the situation
- 2. Using the same name to perform multiple tasks or same tasks depending on the situation
- 3. Using the same name to perform difficult tasks or complex tasks and it does not depend on the situation

12. The main advantage of function overloading is _____.



AR Lucky Term

- 0. The program becomes portable
- 1. The program becomes complex
- 2. The function becomes inline
- 3. The program becomes more readable **Correct Ans** By **AR**

13. You cannot overload the _____ operator.

- 0. ? : **Correct Ans** By **AR**
- 1. *
- 2. /
- 3. ++

14. In C++, a variable can be declared anywhere in the program this will increase _____.

- 0. writability
- 1. readability
- 2. portability
- 3. efficiency **Correct Ans** By **AR**

15. Memory allocated from heap or free store _____.

- 0. can be returned back to the system automatically
- 1. can be allocated to classes only
- 2. cannot be returned back unless freed explicitly using malloc and realloc
- 3. cannot be returned back unless freed explicitly using free and delete operators **Correct Ans** By **AR**

16. We cannot use _____ pointer for storing and reading data from it.

- 0. 'NULL' **Correct Ans** By **AR**
- 1. integer
- 2. double
- 3. zero

17. The dynamic memory allocation uses _____ whereas static memory allocation uses _____.



AR Lucky Term

0. heap , stack **Correct Ans** By **AR**

1. stack , lists
2. array , stack
3. classes , array

18. What will be the output of the given code?

```
#include #define MAX( A, B ) ((A) > (B) ? (A) : (B))
void main() {
int i, x, y;
x = 23;
y = 45;
i = MAX( x++, y++ );
// Side-effect: // larger value incremented twice
cout << "x = " << x << " y = " << y << "\n";
}
```

0. x=23 y=45
1. x=24 y=46
2. x=24 y=47 **Correct Ans** By **AR**
3. x=22 y=47

19. NULL has been defined in _____ header file.

0. Iostream.h
1. Stdlib.h **Correct Ans** By **AR**
2. Stdio.h
3. String.h

20. Symbolic constant PI can be defined as:

0. #define PI 3.14 ;
1. #define PI 3.14 **Correct Ans** By **AR**
2. #define PI=3.14
3. # include pi= 3.14

21. The friend function of a class can have access _____.



AR Lucky Term

0. to the public data members only
1. to the private data members **Correct Ans** By **AR**
2. to the protected data members
3. to the main program
22. C++ was developed by _____.
0. Charles Babbage
1. Graham Bell
2. Bejarne Stroustrup **Correct Ans** By **AR**
3. Von Nuemann
23. Once the _____ are created, they exist for the life time of the program.
0. local variables
1. non static variables
2. static variables **Correct Ans** By **AR**
3. automatic variables
24. Encapsulation means _____.
0. that the data of a class cannot be accessed from outside
1. that the data of a class can be accessed from outside **Correct Ans** By **AR**
2. the data becomes public
3. that the data can be accessible anywhere within a main program
25. An address is a _____, while a pointer is a _____.
0. constant, variable
1. variable, constant **Correct Ans** By **AR**
2. global, variable
3. non static variable, constant
26. The syntax of declaration of a function that returns the reference to an integer is _____.
0. `int & myfunc();` **Correct Ans** By **AR**



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

1. int myfunc();
 2. int myfunc() &;
 3. integer & myfunc();
27. Which one of the following is mandatory preprocessor directive for c++?
0. #undef
 1. #include **Correct Ans** By **AR**
 2. #undef
 3. All of the given
28. The members of a class declared with the keyword struct are _____ by default.
0. static
 1. Private
 2. protected
 3. public **Correct Ans** By **AR**
29. With user data type variables (Objects) self assignment can produce
0. Link error
 1. Run time error
 2. Syntax error
 3. Logical error **Correct Ans** By **AR**
30. To prevent dangling reference the functions returning reference should be used with _____.
0. arrays
 1. global variables only
 2. local variables
 3. static and global variables **Correct Ans** By **AR**
31. When an operator function is defined as member function for a Unary operator then the number of extra arguments it takes is/are,
0. Zero



AR Lucky Term

1. Two
 2. One **Correct Ans** By **AR**
 3. N arguments
32. What is the function of the following statement to delete an array of 5 objects named 'arr' allocated using new operator?
delete arr;
0. Results into syntax error **Correct Ans** By **AR**
 1. Deletes all the objects of array
 2. Do not delete any object
 3. Deletes only one object of array
33. getch() is a _____ function and defined in _____ header file.
0. user-define function , conio.h
 1. built-in function , conio.h **Correct Ans** By **AR**
 2. built-in function, stlib.h
 3. built -in function, iostream.h
34. _____ operators are the ones that require two operands on both sides of the operator.
0. Double
 1. Tow sided
 2. Binary **Correct Ans** By **AR**
 3. None of the given
35. _____ will return the number of bytes reserved for a variable or data type.
0. sizeof operator **Correct Ans** By **AR**
 1. free operator
 2. void pointer
 3. new operator
36. _____ are not available in C language.



AR Lucky Term

- 0. User defined functions
 - 1. Built in functions
 - 2. Library functions **Correct Ans** By **AR**
 - 3. Inline functions
37. The members of a class declared without any keyword are _____ by default.
- 0. protected
 - 1. private **Correct Ans** By **AR**
 - 2. public
 - 3. constant
38. For console input and output we use _____.
- 0. conio.h header file **Correct Ans** By **AR**
 - 1. stdlib.h header file
 - 2. process.h header file
 - 3. getch.h header file
39. The name of the destructor is the same as that of a class proceeding with a _____.
- 0. & sign
 - 1. # sign
 - 2. @ sign
 - 3. ~ sign **Correct Ans** By **AR**
40. A reference cannot be NULL it has to point a data type.
- 0. True **Correct Ans** By **AR**
 - 1. False
41. A pointer is _____.
- 0. the address of a variable
 - 1. an indication of the variable to be accessed next
 - 2. a variable for storing address **Correct Ans** By **AR**
 - 3. the data type of an address variable



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

42. Constructor is a special function, called whenever we _____.

0. create a function

1. instantiate an object of a class **Correct Ans** By **AR**

2. destroy an object

3. create a class

43. Symbolic constant PI can be defined as:

0. #define PI 3.14;

1. #define PI 3.14 **Correct Ans** By **AR**

2. #define PI=3.14

3. # include pi=3.14

44. Object code is machine code but it is not _____ and _____.

0. relocatable, executable **Correct Ans** By **AR**

1. faster, efficient

2. compiled, debugged

3. tested, compiled

45. The default visibility for the data members of the class is

0. private **Correct Ans** By **AR**

1. protected

2. public

3. accessible outside the class

46. The _____ is called automatically when an object destroys.

0. destructor **Correct Ans** By **AR**

1. constructor

2. main program

3. default constructor

47. Constructor is special type of function :

0. which has no return type **Correct Ans** By **AR**

1. which returns NULL pointer



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

2. which returns zero
 3. which returns integer type data
48. _____ variables are those that are defined outside of main.
0. Local
 1. Dynamic
 2. Global **Correct Ans** By **AR**
 3. Static
49. Within the statement `obj1=obj2`; `obj1` will call the assignment operator function and `obj2` will be passed as an argument to function.
0. True **Correct Ans** By **AR**
 1. False
50. When the compiler overload the assignment (=) operator by default then
0. Class members are not assigned properly
 1. Compiler does not allow default assignment operator
 2. Compiler does member wise assignment. **Correct Ans** By **AR**
 3. None of the given
51. It is possible to return an object from function using this pointer.
0. True **Correct Ans** By **AR**
 1. False
52. Overloaded assignment operator must be
0. Member function of class **Correct Ans** By **AR**
 1. Non-member function of class
 2. Friend function of class
 3. Global function
53. Let suppose
`int a, b, c, d, e;`
`a = b = c = d = e = 42;`
This can be interpreted by the compiler as



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

0. $(a = b = (c = (d = (e = 42))))$;
1. $a = (b = (c = (d = (e = 42))))$; Correct Ans By AR
2. $a = b = (c = (d = (e = 42)))$;
3. $(a = b) = (c = d) = (e = 42)$;
54. In statement $a+b+c$, at first
0. $a+b$ is executed first
1. $b+c$ is executed first Correct Ans By AR
2. All executed at the same time
3. None of the given
55. Suppose $\text{int } i = 10$; then what is the output of `cout<<oct<<i`;
0. 10
1. 11
2. 12 Correct Ans By AR
3. 13
56. `ostream` is a _____ operator.
0. dependent
1. member
2. standalone Correct Ans By AR
3. None of the given
57. _____ must be included to use stream manipulation in your code.
0. `conio.h`
1. `iostream`
2. `stdlib.h`
3. `iomanip` Correct Ans By AR
58. _____ operators are the ones that require only one operator to work.
0. Unit
1. Unary Correct Ans By AR



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

2. Single
3. None of the given
59. The endl and flush are _____.
0. Functions
1. Operators
2. Manipulators **Correct Ans** By **AR**
3. Objects
60. When operator function is implemented as member function then return type of function _____.
0. Must be an object of same class
1. Must be user-defined data type
2. Must be built-in data type
3. Can be any data type **Correct Ans** By **AR**
61. When a variable is defined as static in a class then _____.
0. Separate copy of this variable is created for each object
1. Only one copy is created for all objects of this class **Correct Ans** By **AR**
2. A copy of this variable is created for only static objects
3. None of the given
62. Automatic variables are created on _____.
0. Heap
1. Free store
2. Static storage
3. stack **Correct Ans** By **AR**
63. `cout << i << " ";`
`cout << d << " ";`
`cout << f;`

Above statements can be written within statement of one line as:



AR Lucky Term

- 0. `cout << i << " " << d " " << f << ;`
- 1. `cout << i << << d << << f << ;`
- 2. `cout << i << " " << d << " " << f;` Correct Ans By AR
- 3. `cout << i << " " << d << " " f << ;`

64. dec, hex, oct are all _____.

- 0. Member functions
- 1. Objects of input/output streams
- 2. Parameterized manipulators
- 3. Non-parameterized manipulators Correct Ans By AR

65. What will be the output of following statement?

`cout<<setfill('0')<<setw(7)<< 128;`

- 0. 0128128
- 1. 0000128 Correct Ans By AR
- 2. 1280000
- 3. 0012800

66. Which of the following syntax is best used to delete an array of 5 objects named 'string' allocated using new operator.

- 0. `delete string;`
- 1. `delete []string;` Correct Ans By AR
- 2. `delete string[];`
- 3. `delete string[5];`

67. If we have a program that writes the output data(numbers) to the disc, and if we collect the output data and write it on the disc in one write operation instead of writing the numbers one by one.

In the above situation the area where we will gather the number is called

- 0. Heap
- 1. Stack
- 2. Buffer Correct Ans By AR
- 3. Cache

68. The first parameter of operator function for << operator _____.



AR Lucky Term

- 0. Must be passed by value
 - 1. Must be passed by reference **Correct Ans** By **AR**
 - 2. Can be passed by value or reference
 - 3. Must be object of class
69. The second parameter of operator function for >> operator must always be passed
- 0. By reference **Correct Ans** By **AR**
 - 1. Function takes no argument
 - 2. By value
 - 3. None of the given
70. The only operator that the compiler overloads for user define data type by default is
- 0. Plus (+) operator
 - 1. Minus (-) operator
 - 2. Assignment (=) operator **Correct Ans** By **AR**
 - 3. Equal (==) operator
71. Consider the following code, the printed value will be converted into:
int n=10;
cout <<oct<<n;
- 0. Base 8 **Correct Ans** By **AR**
 - 1. Base 2
 - 2. Base 10
 - 3. Decimal number system
72. _____ variables are defined in the main.
- 0. Global
 - 1. Dynamic
 - 2. Local **Correct Ans** By **AR**
 - 3. All
73. ostream class is _____ and not under our control.



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- 0. user-defined
- 1. built-in **Correct Ans** By **AR**
- 2. both user-defined and built-in
- 3. None of the given

74. The memory allocation in C++ is carried out with the help of _____.

- 0. NULL pointer
- 1. new operator **Correct Ans** By **AR**
- 2. dot operator
- 3. + operator

75. If B is designated as friend of A, B can access A's non-public members.

- 0. B cannot access private member of A
- 1. B cannot access protected member of A
- 2. A can access non-public members of B **Correct Ans** By **AR**
- 3. A cannot access B

76. If the request of new operator is not fulfilled due to insufficient memory in the heap _____.

- 0. the new operator returns 2
- 1. the new operator returns 1
- 2. the operator returns 0 **Correct Ans** By **AR**
- 3. free operator returns nothing

77. We should not use such variable names that are starting with _____ because in C++, there are lots of internal constants and symbolic names that start with it.

- 0. upper case alphabets
- 1. lower case alphabets
- 2. double underscore **Correct Ans** By **AR**
- 3. None of the given

78. The friend keyword provides access _____.



AR Lucky Term

0. in one direction only **Correct Ans** By **AR**

1. in two directions

2. to all classes

3. to the data members of the friend class only

79. The malloc function takes _____ argument(s).

0. two

1. three

2. four

3. one **Correct Ans** By **AR**

80. The constructor contains _____.

0. return type

1. no return type **Correct Ans** By **AR**

2. objects

3. classes

81. What will be the output of the following c++ code?

```
#include<iostream.h>
```

```
#define max 100
```

```
main()
```

```
{
```

```
#ifdef max
```

```
Cout<<"Hellow;
```

```
}
```

0. Hello

1. "Hellow"

2. Max is 100

3. Error **Correct Ans** By **AR**

82. Once we have defined a symbolic constant value using #define, that value _____ during program execution

0. can be changed

1. cannot be changed **Correct Ans** By **AR**



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

2. varies
3. becomes zero
83. The memory allocation functions return a chunk of memory with a pointer of type _____.
0. integer
1. float
2. ptr **Correct Ans** By **AR**
3. void
84. A class can be declared as a _____ of other class.
0. member **Correct Ans** By **AR**
1. member function
2. friend
3. part
85. To avoid dangling reference, don't return _____.
0. the reference of a local variable from the function **Correct Ans** By **AR**
1. the reference of a global variable from the function
2. the reference of a static variable from the function
3. the reference of a private data member from the function
86. Constructor is itself a _____ of C++ and _____.
0. class, can be overloaded
1. function, cannot be overloaded
2. function, can be overloaded **Correct Ans** By **AR**
3. object, can not be initialized
87. The parameter passed to isdigit() function is _____ variable.
0. Character
1. Boolean
2. Integer **Correct Ans** By **AR**
3. Float



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

88. `char **argv` can be read as _____.
0. pointer to pointer
1. pointer to char
2. pointer to pointer to char **Correct Ans** By **AR**
3. None of the given
89. To read command-line arguments, the `main()` function itself must be given _____ arguments.
0. 1
1. 2 **Correct Ans** By **AR**
2. 3
3. 4
90. How many bytes an integer type pointer `intPtr` will jump in memory if the statement below is executed?
`intPtr += 2 ;`
0. 2
1. 4
2. 8 **Correct Ans** By **AR**
3. 12
91. The increment of a pointer depends on its _____.
0. variable
1. value
2. data type **Correct Ans** By **AR**
3. None of the given
92. The statement `cout << yptr` will show the _____ the `yptr` points to.
0. Value
1. memory address **Correct Ans** By **AR**
2. variable
3. None of the given



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

93. _____ is used as a dereferencing operator.
- 0. * **Correct Ans** By **AR**
 - 1. +
 - 2. -
 - 3. None of the above
94. Transpose of a matrix means that when we interchange rows and columns _____.
- 0. the first row becomes the Last column
 - 1. the first row becomes the first column **Correct Ans** By **AR**
 - 2. the Last row becomes the first column
 - 3. the first column becomes the first row
95. Individual characters in a string stored in an array can be accessed directly using array _____.
- 0. superscript
 - 1. script
 - 2. subscript **Correct Ans** By **AR**
 - 3. value
96. We can define a matrix as _____ array.
- 0. Sorted
 - 1. Unsorted
 - 2. Single dimensional
 - 3. Multi dimensional **Correct Ans** By **AR**
97. A _____ is an array of characters that can store number of character specified.
- 0. Char
 - 1. String **Correct Ans** By **AR**
 - 2. Multidimensional array
 - 3. Data type



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

98. Given a two dimensional array of integers, what would be the correct way of assigning the value 6 to the element at third row and fourth column?

- 0. array[3][4] = 6 ;
- 1. array[2][4] = 6 ;
- 2. array[4][3] = 6 ;
- 3. array[2][3] = 6 ; **Correct Ans** By **AR**

99. _____ of a variable means the locations within a program from where it can be accessed.

- 0. Data type
- 1. Visibility **Correct Ans** By **AR**
- 2. Value
- 3. Reference

100. Which of the following function call is "call by reference" for the following function prototype?

int add (int *);

- 0. add(&x); **Correct Ans** By **AR**
- 1. add(int x);
- 2. add(x);
- 3. add(*x);

101. Which of the following function call is "call by reference" for the following function prototype?

float add (float *);

- 0. add(&x); **Correct Ans** By **AR**
- 1. add(float x);
- 2. add(x);
- 3. add(*x);

102. Which of the function call is call by value for the following function prototype?

float add(float);



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- 0. add(&x);
- 1. add(x); **Correct Ans** By **AR**
- 2. add(float x);
- 3. add(*x);

103. Which of the function call is "call by value" for the following function prototype?
float add(int);

- 0. add(&x);
- 1. add(x); **Correct Ans** By **AR**
- 2. add(int x);
- 3. add(*x);

104. Return type of a function that does not return any value must be _____.

- 0. char
- 1. int
- 2. void **Correct Ans** By **AR**
- 3. double

105. _____ will be used for enclosing function statements into a block.

- 0. " "
- 1. ()
- 2. []
- 3. {} **Correct Ans** By **AR**

106. What is the output of the following code if the 2nd case is true

```
switch (var) {  
case 'a': cout<<"apple"<<endl;  
case 'b':cout<<"banana"<<endl;  
case 'm':cout<<"mango"<<endl;  
default: cout<<"any fruit"<<endl;  
}
```



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- 0. banana
- 1. banana
any fruit
- 2. banana mango any fruit **Correct Ans** By **AR**
- 3. None of the given

107. When the break statement is encountered in a loop's body, it transfers the control _____ from the current loop.

- 0. Inside
- 1. Outside **Correct Ans** By **AR**
- 2. To break statement
- 3. To continue statement

108. What is the output of the following code if the 3rd case is true

```
switch (var) {  
case 'a':cout<<"apple"<<endl;  
case 'b':cout<<"banana"<<endl;  
case 'm':cout<<"mango"<<endl;  
default: cout<<"any fruit"<<endl;  
}
```

- 0. mango
- 1. mango any fruit **Correct Ans** By **AR**
- 2. apple
- 3. None of the given

109. What is the output of the following code, if the first case is true

```
switch (var) {  
case 'a':cout<<"apple"<<endl;  
case 'b':cout<<"banana"<<endl;  
case 'm':cout<<"mango"<<endl;  
default: cout<<"any fruit"<<endl;  
}
```



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- 0. apple
- 1. apple
any fruit
- 2. apple banana mango any fruit **Correct Ans** By **AR**
- 3. none of above

110. What will be the output of following code segment?

```
for (int i = 2; i<10; i++) {  
if ( i == 5) continue;  
cout << i << "," ;  
}
```

- 0. 2,3,7,8,9
- 1. 2,3,4,6,7,8,9 **Correct Ans** By **AR**
- 2. 2,3,4
- 3. 4,6,7,8,9

111. _____ statement is used to terminate the processing of a particular case and exit from switch structure.

- 0. if
- 1. goto
- 2. break **Correct Ans** By **AR**
- 3. continue

112. What will be the result of the expression $j = i++$; if initially $j = 0$ and $i = 5$?

- 0. 0
- 1. 5 **Correct Ans** By **AR**
- 2. 6
- 3. 4

113. What will be the result of the expression $k = ++m$; if initially $k = 0$ and $m = 4$?

- 0. 0



AR Lucky Term

1. 5 **Correct Ans** By **AR**

2. 6

3. 4

114. What will be the result of the expression $k = ++m$; if initially $k = 0$ and $m = 5$?

0. 0

1. 5

2. 6 **Correct Ans** By **AR**

3. 4

115. How many times the following do-while loop will execute?

`int k = 10; do { cout << "Statements" << endl; k -= 2; } while(k>0);`

0. 4

1. 5

2. 6 **Correct Ans** By **AR**

3. 7

116. Which of the following loops checks the test condition at the end of the loop?

0. While

1. Do-While **Correct Ans** By **AR**

2. For

3. Nested Loop

117. The operators $++$ and $--$ are used to increment or decrement the value of a variable by _____.

0. 3

1. 2

2. 1 **Correct Ans** By **AR**

3. 4

118. How many times the following loop will execute?

`int j = 3; while(j > 0) { cout << "Statements" << endl; j -= 2; }`



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

0. 0

1. 1

2. 2 **Correct Ans** By **AR**

3. 3

119. A _____ structure specifies that an action is to be repeated while some condition remains true.

0. Control **Correct Ans** By **AR**

1. Logical

2. Repetition

3. Relational

120. $!(x > 3)$ means in C++ that

0. x is greater than 3

1. x is less than or equal to 3 **Correct Ans** By **AR**

2. x is less than 3

3. x is equal to 3

121. When the logical operator $\&\&$ combines two expressions then the result will be true only when the both expressions are _____.

0. Logical

1. Arithmetic

2. true **Correct Ans** By **AR**

3. false

122. $<$ and $>$ both are _____ operators.

0. Arithmetic

1. Relational **Correct Ans** By **AR**

2. Logical

3. Mathematical

123. What will be the value of variable "input" if the initial value of input is 67?

if(input $\geq$ 50)



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

```
input = input + 1;  
if(input <= 75)  
input = input + 2;  
else  
input = input - 1;
```

- 0. 68
- 1. 69
- 2. 70 **Correct Ans** By **AR**
- 3. 66

124. $!(x < 3)$ means in C++ that

- 0. x is less than 3
- 1. x is greater than or equal to 3 **Correct Ans** By **AR**
- 2. x is greater than 3
- 3. x is equal to 3

125. $!=$ operator is used to check whether the operand on the left-hand-side is _____ to the operand on the right-hand-side.

- 0. Less than or equal
- 1. Greater than or equal
- 2. Not equal **Correct Ans** By **AR**
- 3. Approximately equal to

126. When the if statement consists more than one statement then enclosing these statement in curly braces is,

- 0. Not required
- 1. Good programming
- 2. Relevant
- 3. Must **Correct Ans** By **AR**

127. The most suitable data type for number 325.25 is _____.

- 0. char
- 1. int



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

2. short

3. float **Correct Ans** By **AR**

128. What will be the result of arithmetic expression $6+48/4*3$?

0. 10

1. 40.5

2. 42 **Correct Ans** By **AR**

3. 41

129. Which of the following will be the most appropriate data type to store the value 63.547?

0. Integer

1. Character

2. Short

3. Float **Correct Ans** By **AR**

130. In the given expression which operator will be evaluated first? $10 + (6 / 2) - 2 * 3$?

0. +

1. -

2. / **Correct Ans** By **AR**

3. *

131. What will be the value of the variable output in the given piece of code?

```
double output = 0;
```

```
output = (2 + 2) * 4 + 2 / (4 - 2);
```

0. 15

1. 17 **Correct Ans** By **AR**

2. 12

3. 11

132. It is the job of _____ to transfer the executable code from hard disk to main memory.



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- 0. interpreter
- 1. Debugger
- 2. Linker
- 3. Loader **Correct Ans** By **AR**

133. In computer systems there are mainly _____ type of softwares.

- 0. 1
- 1. 2 **Correct Ans** By **AR**
- 2. 3
- 3. 4

134. _____ will explain the function of a program.

- 0. Comments **Correct Ans** By **AR**
- 1. Debugger
- 2. Compiler
- 3. Linker

135. if ($a > b$ && $a > c$) then the condition will be true only if

- 0. Both $a > b$ and $a > c$ are true **Correct Ans** By **AR**
- 1. $a > b$ is false and $a > c$ is true
- 2. $a > b$ is true and $a > c$ is false
- 3. Both $a > b$ and $a > c$ are false

136. A variable of character data type occupies _____ byte(s) in memory.

- 0. 1 **Correct Ans** By **AR**
- 1. 2
- 2. 4
- 3. 8

137. We must include the header file _____ to convert the value of one type into another type using built-in functions.

- 0. conio.h
- 1. stdlib.h



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

2. string.h **Correct Ans** By **AR**

3. iostream.h

138. A function is a block of statements that can be defined once and used _____ in the program.

0. One time

1. Two times

2. Three times

3. As many times as user wants **Correct Ans** By **AR**

139. Select the correct way to assign the address of first element of array to pointer?

0. int *ptr = &data[1];

1. int *ptr = &data; **Correct Ans** By **AR**

2. int *ptr = data;

3. int *ptr = data[0];

140. Consider the following code segment. What will be the output of following code?

```
int addValue (int *a){  
    int b = (*a) + 2;  
    return b;  
}  
main() {  
    int x = 6;  
    cout<<addValue(&x)<<" ";  
    cout<<x;  
}
```

0. 6,8,6 **Correct Ans** By **AR**

1. 6,6,8

2. 6,8,8

3. 6,6,6



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

141. Here the code is given below. You have to identify the problem in the code.

```
while(i < 10) && (i > 24))
```

- 0. the logical operator && cannot be used in test condition
- 1. the while loop is an exit-condition loop
- 2. the test condition is always true
- 3. the test condition is always false **Correct Ans** By **AR**

142. The correct syntax of do-while loop is _____.

- 0. (condition) while; do {statements};
- 1. {statements;} do-while();
- 2. while(condition); do {statements};
- 3. do {statements;} while (condition); **Correct Ans** By **AR**

143. Matrix is defined as _____.

- 0. Single dimensional array
- 1. Multi-dimensional array **Correct Ans** By **AR**
- 2. Vector product
- 3. Scalar product

144. In programming, comments are used to explain the functioning of the _____.

- 0. Debugger
- 1. Editor
- 2. Program **Correct Ans** By **AR**
- 3. Linker

145. Operating System is a type of a/an _____.

- 0. application software
- 1. system software **Correct Ans** By **AR**
- 2. computer language
- 3. interpreter



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

146. From the options given, you need to choose the option which is true for the given code.

```
for (int i = 1; i>0; i++) {  
/*loop code*/  
}
```

- 0. the logical operator && cannot be used in a test condition
- 1. the while loop is an exit-condition loop
- 2. the test condition is always false
- 3. the test condition is always true **Correct Ans** By **AR**

147. Which of the following values are used in C/C++ to represent true and false?

- 0. v1 and 0 **Correct Ans** By **AR**
- 1. 1 and -1
- 2. 11 and 00
- 3. any numerical value

148. 'While' loop may execute _____ or more times.

- 0. three
- 1. zero **Correct Ans** By **AR**
- 2. two
- 3. one

149. Body of any function is enclosed within _____.

- 0. { } **Correct Ans** By **AR**
- 1. ()
- 2. []
- 3. " "

150. What will be the correct syntax for initialization of a pointer ptr with string "programming"?

- 0. char ptr = 'programming';



AR Lucky Term

1. `char *ptr = "programming";` Correct Ans By AR
2. `char *ptr = 'programming';`
3. `*ptr = "programming";`

151. Which one of the given option is not a mode for reading/writing the data from a file?

0. in
1. out
2. trunc
3. get Correct Ans By AR

152. Which of the following operators is used to access the value of variable pointed by a pointer?

0. * operator Correct Ans By AR
1. -> operator
2. && operator
3. & operator

153. In case of single dereferencing, the value of the _____ is the address of the _____.

0. pointer, variable Correct Ans By AR
1. pointer, constant
2. variable, pointer
3. constant, pointer

154. The remainder (%) operator is a _____ operator.

0. Logical
1. Arithmetic Correct Ans By AR
2. Relational
3. Conditional

155. What will be the output of following code?

```
int x = 10;  
cout<<"x="<<x;
```



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

0. 10

1. "x=10"

2. x=10 **Correct Ans** By **AR**

3. 10=x

156. The purpose of using cout<< is to _____.

0. Display information on the screen **Correct Ans** By **AR**

1. Read the data from keyboard

2. Read the data from a file

3. Write into a file

157. Which of the following data types will be assumed if no data type is specified with constant?

0. short **Correct Ans** By **AR**

1. float

2. int

3. double

158. When an array element is passed to a function, it is passed by _____.

0. reference **Correct Ans** By **AR**

1. data type

2. value

3. data

159. While programming, it is good to provide an easy to understand and easy to use interface; this programming skill is called _____.

0. scalability

1. usability **Correct Ans** By **AR**

2. reliability

3. sustainability

160. _____ executes all the lines before error and stops at the line which contains the error.



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

0. Interpreter **Correct Ans** By **AR**

1. Compiler
2. Linker
3. Debugger

161. Which of the following is the correct syntax to access the value of first element of an array using pointer ptr?

0. ptr[0]
1. *(ptr+1)
2. ptr[1]
3. *ptr[0] **Correct Ans** By **AR**

162. C is a/an _____ language.

0. low level
1. object based
2. object oriented
3. function oriented **Correct Ans** By **AR**

163. _____ of a function is also known as signature of a function.

0. Definition
1. Declaration **Correct Ans** By **AR**
2. Calling
3. Invoking

164. _____ are very good tools for code reuse.

0. operators
1. loops
2. functions **Correct Ans** By **AR**
3. variables

165. If any break statement is missed in switch statement then _____.

0. compiler will give error
1. this may cause a logical error **Correct Ans** By **AR**
2. no effect on program



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

3. program stops its execution

166. A 2D array `multi[5][10]` can be accessed using the array name as `**multi`, this technique is called _____.

0. Single referencing

1. Single dereferencing

2. Double referencing

3. Double dereferencing **Correct Ans** By **AR**

167. In C/C++, the default command line arguments passed to the main function are _____.

0. `float argc, char **argv`

1. `int argc, char **argv` **Correct Ans** By **AR**

2. `int *argc, char *argv`

3. `int argc, float **argv`

168. A record is a group of related _____.

0. Data

1. Fields **Correct Ans** By **AR**

2. Bytes

3. Files

169. The microsoft word document (.doc) is a kind of _____.

0. Sequential File

1. Random Access File **Correct Ans** By **AR**

2. Binary Access File

3. Executable File

170. NULL character is used to indicate the _____ of string.

0. Start

1. End **Correct Ans** By **AR**

2. Begin

3. Middle

171. How many dimensions does n-dimensional array has?



AR Lucky Term

0. n dimensions **Correct Ans** By **AR**

1. 2n dimensions

2. (n+1) dimensions

3. (n-1) dimensions

172. Which of the following function call is "call by reference" for the following function prototype?

0. func(int &num);

1. func(&num); **Correct Ans** By **AR**

2. func(*num);

3. func(num);

173. The loop which is most suitable to be used when the number of iterations is known is called _____.

0. for **Correct Ans** By **AR**

1. while

2. do-while

3. all looping processes require that the iterations be known.

174. In C/C++, the string constant is enclosed in _____.

0. curly braces { }

1. parentheses()

2. single quotes ' '

3. double quotes " " **Correct Ans** By **AR**

175. In order to get the right most digit of a number, we divide this number by 10 and take _____.

0. Its remainder **Correct Ans** By **AR**

1. Its quotient

2. Its divisor

3. The number

176. What is the correct syntax to declare an array of size 10 of int data type?



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- 0. int [10] name;
- 1. name[10] int;
- 2. int name[10]; **Correct Ans** By **AR**
- 3. int name[];

177. How many bytes of memory are occupied by array 'str'?

```
char str[] = "programming";
```

- 0. 10
- 1. 11 **Correct Ans** By **AR**
- 2. 12
- 3. 13

178. Suppose that an integer type pointer contains a memory address 0x22f230. What will be the new memory address if we increment this pointer by one?

- 0. 0x22f231
- 1. 0x22f234 **Correct Ans** By **AR**
- 2. 0x22f226
- 3. 0x22f238

179. Which of the following if missing would result in infinite recursion in case of recursive function?

- 0. Recursive call **Correct Ans** By **AR**
- 1. Base case
- 2. Function parameters
- 3. Local variables

180. Whenever we use a library function or a predefined object or macro, we need to use a _____.

- 0. source file
- 1. object file
- 2. header file **Correct Ans** By **AR**
- 3. exe file



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

181. Switch statement deals with _____ type of data.

- 0. Integer
- 1. Float
- 2. Character
- 3. Both Integer and Character **Correct Ans** By **AR**

182. Both compiler and _____ are used to translate program into machine language code.

- 0. debugger
- 1. linker
- 2. loader
- 3. interpreter **Correct Ans** By **AR**

183. TWAIN stands for _____.

- 0. Technology With An Interesting Name
- 1. Technology Without An Informative Name
- 2. Technology Without An Interesting Name **Correct Ans** By **AR**
- 3. Technology With An Informative Name

184. The parameter passed to isdigit() function is _____.

- 0. a character variable **Correct Ans** By **AR**
- 1. a boolean variable
- 2. an integer variable
- 3. a character string

185. C++ views each file as a sequential stream of _____.

- 0. Bits
- 1. Bytes **Correct Ans** By **AR**
- 2. Numbers
- 3. Words

186. Structure is a collection of _____ under a single name.

- 0. only functions



AR Lucky Term

1. only variables **Correct Ans** By **AR**
2. both functions and variables
3. only data types

187. The default mode for writing into a file using ofstream object is _____.

0. out **Correct Ans** By **AR**
1. bin
2. app
3. ate

188. The memory address of the first element of an array is called _____.

0. floor address
1. foundation address
2. first address
3. base address **Correct Ans** By **AR**

189. We want to access array in random order which of the following approach is better?

0. Pointer **Correct Ans** By **AR**
1. Array index
2. Both pointers and array index are better
3. Matrix

190. The _____ structure is a multiple-selection construct which makes the code more efficient and easy to read and understand.

0. multiple-if
1. switch **Correct Ans** By **AR**
2. if-else
3. else-if

191. Which of the following is not a reserved word in C/C++?

0. int



AR Lucky Term

1. float
2. double
3. sum **Correct Ans** By **AR**

192. To access rand(), which library is required to be included in program?

0. conio.h
1. stdio.h
2. stdlib.h **Correct Ans** By **AR**
3. iostream.h

193. What is the highest legal index for the following array?
int arr[4]

0. 4
1. 3 **Correct Ans** By **AR**
2. 2
3. 1

194. Word processor is a type of a/an _____.

0. operating system
1. application software **Correct Ans** By **AR**
2. device driver
3. utility software

195. Identify the correct option which is used for calling the function float area (int).

0. area(&num);
1. area(num);
2. area(int num); **Correct Ans** By **AR**
3. area(*num);

196. The _____ statement allows us to select from multiple choices based on a set of fixed values for a given expression.

0. switch **Correct Ans** By **AR**



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

1. break
2. continue
3. goto

197. C is widely known as development language of _____ operating system.

0. Windows
1. Unix **Correct Ans** By **AR**
2. Mac OS
3. Linux

198. To convert the value of one type into another type using built-in functions, we include _____ header file.

0. conio.h
1. stdlib.h **Correct Ans** By **AR**
2. iostream.h
3. string.h

199. The keyword _____ is used to get some value back from a function.

0. return **Correct Ans** By **AR**
1. break
2. continue
3. goto

200. The function seekg() takes _____ parameter(s).

0. 0
1. 1
2. 2 **Correct Ans** By **AR**
3. 3

201. The function write() takes _____ as parameter(s).

0. String of pointer type
1. String of variable lengths, no. of bytes to be read and flags



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

2. Pointer array of characters and a delimiter

3. String and no. of bytes to be written **Correct Ans** By **AR**

202. When the logical operator AND (&&) combines two expressions exp1 and exp2 then the result will be true only _____.

0. When both exp1 and exp2 are true **Correct Ans** By **AR**

1. When both exp1 and exp2 are false

2. When exp1 is true and exp2 is false

3. When exp1 is false and exp2 is true

203. Syntax of a union is identical to _____.

0. structure **Correct Ans** By **AR**

1. class


2. function

3. loop

204. Which one of the symbol is used to represent a decision in a flow chart?



1.  **Correct Ans** By **AR**



205. In Flow Chart, flow of control is represented by _____.

0. Rectangle

1. Circle

2. Diamond

3. Arrow **Correct Ans** By **AR**

206. There can be _____ 'default' statement(s) in any switch structure.



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

0. 1

1. 2 **Correct Ans** By **AR**

2. 3

3. n

207. The condition in loop should be a(n) _____.

0. Constant Expression

1. Boolean Expression

2. Primary Expression

3. Arithmetic Expression **Correct Ans** By **AR**

208. How many nested loops would be required to manipulate n-dimensional array?

0. n

1. $n + 1$

2. $n - 1$

3. $2n$ **Correct Ans** By **AR**

209. Which of the following is not an example of int data type?

0. 0

1. -32

2. 65531

3. -4 **Correct Ans** By **AR**

210. We should use _____ for clarity and to force the order of evaluation in an expression.

0. brackets []

1. parenthesis () **Correct Ans** By **AR**

2. curly braces {}

3. quotation marks " "

211. Which of the following is the starting index of an array in C++?

0. 0 **Correct Ans** By **AR**

1. 1



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

2. -1

3. 2

212. The statement $x += y$ can be interpreted as _____.

0. Adding the value of the x to the value of the y and storing the result in x **Correct Ans** By **AR**

1. Adding the value of the y to the value of x, store the result in y

2. Adding the value of the x to the value of x, store the result in x

3. Adding the value of the y to the value of y, store the result in x

213. Given a 2D array of integers, what would be the correct way of assigning the value 5 to the element at second row and third column?

0. $m[2][3] = 5;$

1. $m[3][2] = 5;$

2. $m[1][2] = 5;$ **Correct Ans** By **AR**

3. $m[2][3] = '5';$

214. Array is a data structure that stores _____.

0. Memory addresses

1. Variables **Correct Ans** By **AR**

2. Data type

3. Data

215. A program statement that invokes a function is called _____.

0. function declaration

1. function call **Correct Ans** By **AR**

2. function definition

3. function prototype

216. If a function has been declared but not defined before its function call then it is termed as _____.

0. logical error

1. syntax error

2. run time error



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

3. program time error

217. The compiler of C language is written in _____ language.

0. JAVA

1. BASIC

2. FORTRAN

3. C **Correct Ans** By **AR**

218. Which one of the below functions is not included in ctype.h header file?

0. isdigit(int c)

1. isxdigit(int c)

2. tolower(int c)

3. getdigit(int c)

219. Which function is used to locate the first occurrence of a character in any string?

0. strchr()

1. strstr()

2. strtok()

3. strlen() **Correct Ans** By **AR**

220. To access the data members of structure, _____ is used.

0. Logical operator

1. Dereference operator

2. Dot operator **Correct Ans** By **AR**

3. Address operator

221. In the following nested For Loop, which loop will run most number of times?

```
for( int i = 0; i < 5; i++)  
{  
  for(int k = 0; k < 5; k++)  
  {  
    ....
```



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

```
}  
}
```

- 0. Outer loop
- 1. Inner loop
- 2. Both loops run equal number of times
- 3. Depends upon the statements in the inner loop's body **Correct Ans**
By **AR**

222. Structure use _____ allocation.

- 0. Queue
- 1. Heap **Correct Ans** By **AR**
- 2. Cache
- 3. Stack

223. _____ function give the position of the next character to be read from that file.

- 0. tellp() **Correct Ans** By **AR**
- 1. tellg()
- 2. seekg()
- 3. seekp()

224. What will be the size of the following character array?
char name[] = "Adeel";

- 0. 5 **Correct Ans** By **AR**
- 1. 6
- 2. 4
- 3. 7

225. Function prototype is written,

- 0. Within main function
- 1. After the return statement in main
- 2. Before the return statement in main
- 3. Before call of that function **Correct Ans** By **AR**



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

226. Which one of the following languages has been used to write the compiler of "C" language?

- 0. Java
- 1. Fortran
- 2. Basic
- 3. C **Correct Ans** By **AR**

227. A hierarchy of classes which are used to deal with console and disk files are called _____.

- 0. Stream classes **Correct Ans** By **AR**
- 1. Simple classes
- 2. Binary classes
- 3. IO classes

228. _____ stops execution at the line that contains error(s) in the code.

- 0. Compiler
- 1. Debugger
- 2. Interpreter **Correct Ans** By **AR**
- 3. Linker

229. C++ is a _____ language.

- 0. High level **Correct Ans** By **AR**
- 1. Low level
- 2. Machine
- 3. Assembly language

230. How many elements are stored in the following?
int matrix [4][5];

- 0. 9
- 1. 20 **Correct Ans** By **AR**
- 2. 25
- 3. 10



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

231. _____ is a substitute of multiple if statement.

- 0. if. . .elseif statement **Correct Ans** By **AR**
- 1. Continue statement
- 2. Break statement
- 3. Default statement

232. if

int sum = 54;

Then the value of the following statement is

sum = sum - 3;

- 0. 52
- 1. 50
- 2. 51 **Correct Ans** By **AR**
- 3. 57

233. What will be the correct syntax for declaration of the following statement?

"ptr is a constant pointer to an integer"

- 0. const * int myptr;
- 1. const int *myptr; **Correct Ans** By **AR**
- 2. int const *ptr;
- 3. int *const ptr;

234. _____ operator is used to pass the address of a variable in call by reference method.

- 0. %
- 1. +
- 2. @
- 3. & **Correct Ans** By **AR**

235. _____ data type can operate on modulus operator.

- 0. int **Correct Ans** By **AR**
- 1. float



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- 2. char
- 3. double

236. Whenever some number is added in an array name, it will jump as many _____ as the added number.

- 0. rows **Correct Ans** By **AR**
- 1. value
- 2. column
- 3. bytes

237. Suppose that an integer type pointer contains a memory address 0x22f220. What will be the new memory address if we increment this pointer by one?

- 0. 0x22f221
- 1. 0x22f222
- 2. 0x22f223
- 3. 0x22f224 **Correct Ans** By **AR**

238. Which of the following structure is correct for WHILE loop?

- 0. While (start; condition; end)
- 1. While (start; condition)
- 2. While (condition; end)
- 3. While (condition) **Correct Ans** By **AR**

239. Which of the following is true about the switch statement?

- 0. It is valid for the large programs only.
- 1. It is valid for the small programs only.
- 2. It works efficiently on compound conditions which use logical operators.
- 3. It cannot handle the compound conditions which use logical operators. **Correct Ans** By **AR**

240. If the condition is not made false in while loop, what will happen?

- 0. Loop will become infinite. **Correct Ans** By **AR**



AR Lucky Term

1. Program will not run at all.
2. Program will terminate early.
3. Syntax errors occur.

241. If a function does not return anything, its return type will be _____.

0. Return 0
1. Null
2. Zero
3. Void **Correct Ans** By **AR**

242. What will be the output of the following piece of code?

```
int square(int number)
{
    int result 0;
    result = number * number;
    return result;
}

int main()
{
    cout<<square(9);
}

0. 49
1. 99
```



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

2. 89

3. 81 **Correct Ans** By **AR**

243. Which of the following is the first step in FOR loop?

0. Incrementing condition

1. Termination condition

2. Continuation condition

3. Initialization condition **Correct Ans** By **AR**

244. Learning "how to program" is important, because it develops _____ and problem-solving abilities.

0. Analytical **Correct Ans** By **AR**

1. Writing

2. Listening

3. Reading

245. In C++, which of the following option has the correct meaning of the expression `a <= b`?

0. a is greater than or equal to b

1. a is less than b

2. a is greater than b

3. a is less than or equal to b **Correct Ans** By **AR**

246. What will be the output of following code?

```
int i = 1;
```

```
while(i<10){
```

```
if(i%2 == 0)
```

```
cout<<i<<" ";
```

```
i++;
```



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

}

0. 2 4 6 10

1. 1 3 5 7

2. 2 4 6 8 **Correct Ans** By **AR**

3. 2 4 8 10

247. What will be the output of following code?

```
int x = 15;
```

```
int y = 10;
```

```
int z = 5;
```

```
cout<< x * x - 4 * y * z;
```

0. 25 **Correct Ans** By **AR**

1. -25

2. -5

3. 5

248. Which of the following expression is correct in C/C++ language?

0. $X = X + 3$ **Correct Ans** By **AR**

1. $3 = X + 3$

2. $Y + X = 7$

3. $X + 5 = Y + 7$

249. Which of the following C++ statements is used take input from the user?

0. cin **Correct Ans** By **AR**

1. cerr

2. cout

3. cget

250. Which of the following is an example of logical operator?



AR Lucky Term

0. &&|| Correct Ans By AR

1. <,>

2. +,*

3. /,%

251. In C/C++, which of the following data type is used to store real numbers?

0. float Correct Ans By AR

1. char

2. boolean

3. int

252. C/C++ has many libraries which contain variables and function names normally starting with _____.

0. Hyphen

1. Hash

2. Underscore Correct Ans By AR

3. emi-Colon

253. The coding of a program is translated into machine language by _____.

0. Debugger

1. Compiler Correct Ans By AR

2. Loader

3. Linker

254. What will be the output of the following code?

```
int i = 0;
```

```
while(i!=15){
```

```
cout<<i<<" ";
```

```
i = i + 5;
```



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

}

0. 1 5 10

1. 5 10

2. 0 5

3. 0 5 10 **Correct Ans** By **AR**

255.

256. In C/C++, the algebraic expression $(b^2 - 4ac) / 2a$ can be written as:vv

0. $(b*b - 4*a*c) / (2*a)$ **Correct Ans** By **AR**

1. $b*b - 4*a*c / (2*a)$

2. $b*b - 4*a*c / 2*a$

3. $b*b - (4*a*c) / 2*a$

257. _____ is the pointer which determines the position in a file from where the next read operation occurs.

0. put **Correct Ans** By **AR**

1. seek

2. get

3. tell

Question # 1

When an identifier is declared with keyword const then,

- Its value can be overwritten
- Its value cannot be changed
Correct Ans By **AR**
-



AR Lucky Term

Its value can be changed with arithmetic operator

-

Its value can be changed during execution.

Question # 2

Transpose of a matrix means that when we interchange rows and columns_____

-

the first row becomes the Last column

-

the Last row becomes the first column

-

the first row becomes the first column

Correct Ans By AR

-

the first column becomes the second column

Question # 3

Which of the following is true about streams?

A. It is a sequence of bytes

B. It is an ordered sequence

C. All bytes can go through the stream simultaneously

D. Bytes that enters first into the stream will go out at last

-

A and B

Correct Ans By AR

-

C only

-



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

A only

-

A and D

Question # 4

In two-dimensional array, we use _____ 'for loop(s)' to populate the array.

-

4

-

3

-

2

Correct Ans By AR

-

1

Question # 5

The data in the memory is _____.

-

none

-

non-volatile

-

both

-

volatile

Correct Ans By AR

Question # 6



AR Lucky Term

A string which is assigned to a string variable is terminated by _____.

- Colon
- Null character
Correct Ans By AR
- Semicolon
- Boolean expression

Question # 7

In case of two-dimensional array, if you add some number in a two-dimensional array name, it will jump to the next _____.

- array
- row
Correct Ans By AR
- character
- column

Question # 8

_____ are conventional names of the command line parameters of the 'main()' function.

- 'argc' and 'argv'



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Correct Ans By AR

- 'argb' and 'argv'
- 'argc' and 'argu'
- None of the given

Question # 9

To get the value stored at a memory address, we use the_____.

- dereferencing operator
- referencing operator
- binary operator
- AND(&&) operator

Correct Ans By AR

Question # 10

When an identifier is declared with keyword const then,

- Its value cannot be changed
- Its value can be changed during execution.
- Its value can be overwritten

Correct Ans By AR



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- Its value can be changed with arithmetic operator

Question # 11

Dereferencing operator is represented by _____.

- *

Correct Ans By AR

- &

- +

- -

Question # 12

_____ Returns true if c is a digit or a letter and false otherwise.

- `int isdigit( int c )`

- `int isalpha( int c )`

- `int isalnum( int c )`

Correct Ans By AR

- `int isxdigit( int c )`

Question # 13

Pointer points to a particular_____.

-



AR Lucky Term

memory address

Correct Ans By AR

- Value
- data type
- variable

Question # 14

Which of the following is a correct way to assign the address of the first element of array to pointer? `int data[10];`

- `int *ptr = data[0];`
Correct Ans By AR
- `int *ptr = data;`
- `int *ptr = &data;`
- `int *ptr = data[2];`

Question # 15

There is a pointer variable named `ptr` of type `float`. Which type of variable address can be stored by `ptr`?

- `int`
- `char`
-



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

float

Correct Ans By AR

-

double

Question # 16

Which of the following is a correct way to assign the address of the first element of array to pointer? int data[10];

-

int *ptr = &data;

-

int *ptr = data[2];

-

int *ptr = data[0];

Correct Ans By AR

-

int *ptr = data;

Question # 17

Base address is the memory address of _____ element of an array.

-

1st

Correct Ans By AR

-

2nd

-

3rd

-

4th

Question # 18



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

eof is used to check for the _____ of file when a file is being read.

- Start
- Middle
- End

Correct Ans By AR

- Name

Question # 19

suppose we have int y[10];

To access the 4th element of the array we write_____

- y[3];

Correct Ans By AR

- y[2];
- y[4];

- none of given

Question # 20

The name of the array is a constant pointer which contains the memory address of the _____ of the array.

- second element
-



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

first element

Correct Ans By AR

- Last element
- None of the given

Question # 21

At the _____, we try to break up the problem into functional units.

- testing phase
 - design phase
- Correct Ans By AR
- analysis phase
 - Implementation phase

Question # 22

Whenever some number is added in an array name, it will jump as many _____ as the added number.

- bytes
- column
- value
- rows



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Correct Ans By AR

Question # 23

Following is the declaration of a _____ array. `int arr[2][2];`

- 1-Dimensional
- 2-Dimensional

Correct Ans By AR

- 3-Dimensional
- None of the given

Question # 24

Following is an array of _____ rows and _____ columns. `int num[3][4];`

- 4 , 5
- 2, 3
- 4 , 3
- 3 , 4

Correct Ans By AR

Question # 25

A character is stored in the memory in _____

- byte



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Correct Ans By AR

- None of the given
- string
- integer

Question # 26

The increment of a pointer depends on its_____.

- value
- data type

Correct Ans By AR

- variable
- None of the given

Question # 27

What will be the correct syntax for declaration of the following statement?
"ptr is a constant pointer to an integer"

- `int *const ptr ;`
- `const int *myptr;`

Correct Ans By AR

- `const * int myptr;`



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- int const *ptr;

Question # 28

The parameter passed to isdigit() function is _____variable.

- Double
- Float
- Boolean
- Character

Correct Ans By AR

Question # 29

In the case of pointer to pointer or _____, the first pointer contains the address of the second pointer, which contains the address of the variable, which contains the desired value.

- Dereference
- double dereference
- Single dereference
- None of the given

Question # 30



AR Lucky Term

Given a two dimensional array of integers, what would be the correct way of assigning the value 6 to the element at third row and fourth column?

- `array[4][3] = 6 ;`
- `array[2][4] = 6 ;`
- `array[3][4] = 6 ;`
Correct Ans By AR
- `array[2][3] = 6 ;`

Question # 31

The value of a pointer can be _____.

- none of the given options
- name of the variable
- value of the variable
- address of a variable

Correct Ans By AR

Question # 32

The use of * sign in first and second statements is called _____ and _____ of pointer.

```
int *ptr = &x;
```

```
cout<<*ptr;
```

-



AR Lucky Term

referencing, dereferencing

Correct Ans By AR

- referencing, referencing
- dereferencing, dereferencing
- dereferencing, referencing

Question # 33

Which header file must be included to use the functions tolower() and toupper()?

- ctype.h
- conio.h
- stdlib.h
- iostream.h

Correct Ans By AR

Question # 34

Following is the declaration of a _____ array. `int arr[2][2][2];`

- 3-Dimensional
- 2-Dimensional
-

Correct Ans By AR



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

1-Dimensional

- None of the given

Question # 35

Pointers are a special type of _____ in which a memory address is stored.

- Strings
- Characters
- variables

Correct Ans By AR

- Locations

Question # 36

Which mode of file is used to open a file or stream for insertion.

- out
- in

Correct Ans By AR

- ate
- app

Question # 37

char **argv can be read as_____.



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- pointer to char
- pointer to pointer to char
Correct Ans By AR
- pointer to pointer
- None of the given

Question # 38

_____ contains functions for manipulations of character data.

- string.h
- ctype.h
Correct Ans By AR
- iostream.h
- None of the given

Question # 39

The statement `cout << yptr` will show the _____ the yptr points to.

- Value
- memory address
Correct Ans By AR



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- Variable
- None of the given

Question # 40

Which statement is used to close a file?

- `myFile.shut();`
- `myFile.close();`
Correct Ans By AR
- `myFile.off();`
- `myFile.closefile();`

Question # 41

What is output of following code?

```
int data[10] = {10,20,30,40,50,60,70,80,90,100};  
int *xptr = &data[4];  
int *yptr = &data[6];  
cout<<="" h2="" style="box-sizing: border-box;">
```

- 120
Correct Ans By AR
- 110
- 130



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- Syntax error

Question # 42

If we have a pointer on the left hand side then the right hand side should have a/an_____.

- Address

Correct Ans By AR

- Value

- Operator

- Pointer

Question # 43

What will be the output of following program?

```
int data[10] = {10,20,30,40,50,60,70,80,90,100};
```

```
int *yptr = &data[5];
```

```
cout<<*++yptr;
```

- 60

- 70

- 61

- Syntax error

Question # 44



AR Lucky Term

For the following statement, how much memory will be allocated to myarray[0]? `char * myarray[] = {"Arif", "Sadia"};`

- 6 Bytes
- 5 Bytes
- 4 Bytes
- 7 Bytes

Question # 45

Following is the declaration of a 2D array, how many columns are declared for this array.

`int arr[3][2];`

- 3
- 2
- 23
- 23

Correct Ans By AR

Question # 46

Following is the declaration of a 2D array, how many rows are declared for this array. `int arr[3][2];`

- 2



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

-

3

Correct Ans By AR

-

32

-

23

Question # 47

Which of the following option is correct about array?

-

Only one type of elements can be stored in an array.

-

Elements in an array cannot be sorted.

-

Array is not used to store elements.

-

Different types of elements can be stored in an array.

Question # 48

In one-dimensional array, we use _____ 'for loop(s)' to populate the array.

-

4

-

3

-

2

-

1



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Question # 49

Which of the following option is correct about array?

- Different types of elements can be stored in an array.
- Array is not used to store elements.
- Elements in an array cannot be sorted.
- Only one type of elements can be stored in an array.

Question # 50

*data means _____.

- the address of the variable data
- the size of whatever the data points
- reference
- the value of whatever the data points to

Question # 51

While handling files, one can have _____ options

- read the file
- write in some file
-



AR Lucky Term

read and write in the same file

- All of the given
Correct Ans By AR

Question # 52

fstream is used for_____

- Input file stream
- Input and output file stream
- All of the given
- Output file stream

Correct Ans By AR

Question # 53

To read command-line arguments, the main() function itself must be given _____ arguments

- 2
- 3
- 4
- 1

Correct Ans By AR

Question # 54



AR Lucky Term

We can read, write and manipulate the same file using ----

- iomanip.h
- fstream.h
Correct Ans By AR
- stdio.h
- iostream.h

Question # 55

---- function is used to find the number of character in a string.

- Strlen()
Correct Ans By AR
- strlen()
- str()
- str()_len()

Question # 56

String are accessed by variable of type----

- Char
Correct Ans By AR
- int



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- double
- None of the given

Question # 57

How many bytes an integer type pointer intPtr will jump in memory if the statement below is executed?

```
intPtr += 2;
```

- 8
Correct Ans By AR
- 2
- 4
- 12

Question # 58

A hierarchy of classes which are used to deal with console and disk files are called _____.

- Binary classes
- Simple classes
- Stream classes

Correct Ans By AR

-



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

IO classes

Question # 59

What will be the output of the following code segment?

```
char myName[] = "Student ID";
```

```
int n= sizeof(myName);
```

```
cout<<"" h2="" style="box-sizing: border-box;">
```

- 10
- 11
- 12
- 9

CS201 Grand Quiz

Objective Questions

Question # 1

When accessing a structure member, the identifier to the left of the dot operator is the name of _.

- a structure variable
- Correct Ans** By **AR**

Question # 2



AR Lucky Term

TWAIN stands for _ .

- Technology Without An Interesting Name

Correct Ans By AR

Question # 3

_____ translates high level language program into machine language code.

- Compiler

Correct Ans By AR

Question # 4

The functions that have already been defined as a part of the language are called _____.

- built-in functions

Correct Ans By AR

Question # 5

Given that doubleArray is an array of 7 integers. Which of the below is the correct statement to access the 5th element of the array?

- doubleArray[4]

Correct Ans By AR

Question # 6

The symbol which is used to represent a process in a flow chart is _____.

- Rectangle

Correct Ans By AR

Question # 7



AR Lucky Term

When an array is passed to a function, by default it will be passed by _.

- Reference

Correct Ans By **AR**

Question # 8

What is the range of Random number generator function rand()?

- 0 – 32767

Correct Ans By **AR**

Question # 9

The first character of a variable name must be an alphabet or _____.

- Underscore

Correct Ans By **AR**

Question # 10

In , the first pointer stores the address of the some other pointer, which contains the address of any variable.

- single dereference

Correct Ans By **AR**

Question # 11

Initialization of variable at the time of definition is practice.

- Good Programming

Correct Ans By **AR**

Question # 12

Which looping process checks the test condition at the end of the loop?



AR Lucky Term

-

do-while

Correct Ans By **AR**

Question # 13

You can use a statement to transfer control elsewhere out of the nested structure.

-

Goto

Correct Ans By **AR**

Question # 14

Which of the following array is the most suitable for storing a matrix structure?

-

Single-dimensional array

Correct Ans. By **AR**

Question # 15

The microsoft word document(.doc) is a kind of _ .

-

Random Access File

Correct Ans.. By **AR**

Question # 16

A union is a user-defined data type that contains only from its list of members at a time.

-

one object

Correct Ans. By **AR**

Question # 17

In C/C++, are the doors through which data can enter and come out of a program.



AR Lucky Term

-

Streams

Correct Ans. By **AR**

Question # 18

Which one of the given option is not a mode for reading/writing the data from a file?

-

Trunk

Correct Ans By **AR**

Question # 19

C++ views each file as a sequential stream of _.

-

Bytes

Correct Ans By **AR**

Question # 20

In 2D array, the technique used to access the array elements is called

-

Double dereferencing

Correct Ans By **AR**

Question # 21

From the options given below, identify the correct option which is used for calling the function float square (int &);

-

square (num);

Correct Ans. By **AR**

Question # 22

Identify the correct option which is used for calling the function float area (int).



AR Lucky Term

-

area(num) ;

Correct Ans By **AR**

Question # 23

A program statement that invokes a function is called _.

-

function call

Correct Ans By **AR**

Question # 24

What will be the output of the following code segment?

```
main()
```

```
{
```

```
int a = 10 ;
```

```
int b =0;
```

```
int *x = &a; b = (*x)+3 ;
```

```
cout << a << " , || << b ;
```

```
}
```

-

10,13

Correct Ans By **AR**

Question # 25

When the logical operator AND (&&) combines two expressions exp1 and exp2 then the result will be true only _____

-

When both exp1 and exp2 are true

Correct Ans By **AR**

Question # 26

For which array, the size of the array should be one more than the number of elements in an array?



AR Lucky Term

-

char

Correct Ans By **AR**

Question # 27

What is the range of Random number generator function rand()?

-

0 – 32767

Correct Ans By **AR**

Question # 28

To assigned a value to a character type variable, are used around the value.

-

single qoutes ' '

Correct Ans By **AR**

Question # 29

In C/C++, the #include is called _.

-

Preprocessor Directive

Correct Ans By **AR**

Question # 30

The number 544.53 must be stored in data type.

-

Float

Correct Ans By **AR**

Question # 31

Use of the statement violates the rules of structured programming.

-

Goto

Correct Ans By **AR**



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Question # 32

In Flow Chart, flow of control is represented by _.

- Arrow

Correct Ans By **AR**

Question # 33

What will be the correct syntax for initialization of pointer ptr of type int with variable x?

- `int *ptr = &x ;`

Correct Ans By **AR**

Question # 34

Syntax of a union is identical to _ .

- structure

Correct Ans By **AR**

Question # 35

A union is a user-defined data type that contains only from its list of members at a time.

- one object

Correct Ans By **AR**

Question # 36

Which of the given file handling modes are similar in their functionality ?

- `ios::trunc, ios::ate`

Correct Ans By **AR**

Question # 37



AR Lucky Term

Which one of the given option is not a mode for reading/writing the data from a file?

- Trunk

Correct Ans By **AR**

Question # 38

Stream which sends data to the program is called _.

- Input stream

Correct Ans By **AR**

Question # 39

If the return type of a function is void then it means that it will _.

- return no data

Correct Ans By **AR**

Question # 40

Given that doubleArray is an array of 7 integers. Which of the below is the correct statement to access the 5th element of the array?

- doubleArray[4]

Correct Ans By **AR**

Question # 41

The value returned by the eof() function is of type.

- Character

Correct Ans By **AR**

Question # 42



AR Lucky Term

If a file is not properly closed in a program then what is the status of the program ?

- The program will terminate normally

Correct Ans By **AR**

Question # 43

The parameter passed to isdigit() function is _.

- a character variable

Correct Ans By **AR**

Question # 44

In C/C++, the header file used for string manipulation is _.

- string.h

Correct Ans By **AR**

Question # 45

Arrays are best data structures _.

- for relatively permanent collections of data

Correct Ans By **AR**

Question # 46

Each array declaration must provide the information about all these things except _____.

- Number of elements of the array

Correct Ans By **AR**

Question # 47

The First step for developing a program is _.



AR Lucky Term

-

Linking Analysis

Correct Ans By AR

Question # 48

_____ transfers the executable code from hard disk to main memory.

-

Loader

Correct Ans By AR

Question # 49

_____ operator is used to pass the address of a variable to the called function.

-

&

Correct Ans By AR

Question # 50

In call by reference, of a variable is passed to the called function.

-

Address

Correct Ans By AR

Question # 51

_____ of a function is also known as signature of a function.

-

Declaration

Correct Ans By AR

Question # 52

Preprocessor program performs its function before phase takes place.

-



AR Lucky Term

Compiling

Correct Ans By AR

Question # 53

The remainder (%) operator is a operator.

-

Arithmetic

Correct Ans By AR

Question # 54

Which of the following array is the most suitable for storing a matrix structure?

-

Two-dimensional array

Correct Ans By AR

Question # 55

*.doc is by type.

-

Random Access File

Correct Ans By AR

Question # 56

Which of the following is NOT a preprocessor directive?

-

#define

Correct Ans By AR

Question # 57

The return type of operator function must always be void.

-

False

Correct Ans By AR

Question # 58



AR Lucky Term

The statement `cin.get ();` is used to,

- Read a character from keyboard

Correct Ans By **AR**

Question # 59

When we do dynamic memory allocation in the constructor of a class, then it is necessary to provide a destructor.

- True

Correct Ans By **AR**

Question # 60

Overloaded new operator function takes parameter of type `size_t` and returns

- void pointer

Correct Ans By **AR**

Question # 61

The second parameter of operator functions for `<<` and `>>` are objects of the class for which we are overloading these operators.

- True

Correct Ans By **AR**

Question # 62

C++ is a case-sensitive language

- True

Correct Ans By **AR**

Question # 63



AR Lucky Term

To include code from the library in the program, such as iostream, a directive would be called up using this command.

-

#include

Correct Ans By **AR**

Question # 64

A template function must have only generic data types.

-

True

Correct Ans By **AR**

Question # 65

Template class can not have static variables.

-

False

Correct Ans By **AR**

Question # 66

What will be the correct syntax to access the value of fourth element of an array using pointer ptr?

-

Both 1 and 3

Correct Ans By **AR**

Question # 67

If most significant bit of un-signed number is 1 then it represents a positive number.

-

True

Correct Ans By **AR**

Question # 68



AR Lucky Term

If there is a symbol (& sign) used with the variable name followed by data type then it refers to and if & is being used with variable name then it refers to ____.

- Reference variable, address of variable
Correct Ans By **AR**

Question # 69

We can also do conditional compilation with preprocessor directives.

- True
Correct Ans By **AR**

Question # 70

The default value of a parameter can be provided inside the

- function definition
Correct Ans By **AR**

Question # 71

What purpose do classes serve?

- All of the given options
Correct Ans By **AR**

Question # 72

Every class contains _.

- Constructor
Correct Ans By **AR**

Question # 73



AR Lucky Term

new operator is used to allocate memory from the free store during

- None of the given options

Correct Ans By **AR**

Question # 74

When an object of a class is defined inside another class then,

- Destructor of inner object will be called first

Correct Ans By **AR**

Question # 75

It is possible to define a class within another class.

- True

Correct Ans By **AR**

Question # 76

New and Delete are also used with and data types as well.

- Class, Objects

Correct Ans By **AR**

Question # 77

With New keyword, data types and class members are initialized with meaningful values instead of garbage.

- True

Correct Ans By **AR**

Question # 78

C language is developed by

-



AR Lucky Term

Dennis Ritchie

Correct Ans By AR

Question # 79

Which of the following choice is not an example of an int data type?

- -4.0

Correct Ans By AR

Question # 80

In flow chart, the symbol used for decision making is,

- Diamond

Correct Ans By AR

Question # 81

Switch statement deals with,

- Integer and character data

Correct Ans By AR

Question # 82

Default case in switch statement is,

- Optional

Correct Ans By AR

Question # 83

Member function tellg() returns the current location of the _____ pointer.

- tellptr()

Correct Ans By AR

Question # 84



AR Lucky Term

Dealing with structures and functions passing by reference is the most economical method

- True

Correct Ans By **AR**

Question # 85

In C/C++ all character strings are terminated with,

- Null character

Correct Ans By **AR**

Question # 86

Which of the following can not be a variable name?

- 10area

Correct Ans By **AR**

Question # 87

Which looping process is best, when the number of iterations is known?

- while

Correct Ans By **AR**

Question # 88

By default an array of characters is passed by value to a function

- False

Correct Ans By **AR**

Question # 89

Which of the following operator is used to access the address of a variable?



AR Lucky Term

-

& operator

Correct Ans By AR

Question # 90

The name of an array represents address of first location of array element.

-

False

Correct Ans By AR

Question # 91

Compiler is a

-

Application Software

Correct Ans By AR

Question # 92f

If Num is an integer variable then Num++ means,

-

Add 1 with Num

Correct Ans By AR

Question # 93

For one byte there are combinations of values that can be stored in computer.

-

2^8

Correct Ans By AR

Question # 94

In C/C++ language the header file which is used to perform useful task and manipulation of character data is

-



AR Lucky Term

ctype.h

Correct Ans By AR

Question # 95

Default case in switch statement is,

-

Optional

Correct Ans By AR

Question # 96

What will be the result of arithmetic expression $6 + 27/3 * 3$?

-

33

Correct Ans By AR

Question # 97

What is the correct syntax to declare an array of size 10 of int data type?

-

int name[10] ;

Correct Ans By ARf

Question # 98

How many dimensions does n-dimensional array has?

-

n dimensions

Correct Ans By AR

Question # 99

What will be the correct syntax to access the value of fourth element of an array using pointer ptr?

-

ptr[3]

Correct Ans By AR

Question # 100



AR Lucky Term

Which of the following values C++ use to represent true and false?

- 1 and 0

Correct Ans By **AR**

Question # 101

Declaring structures does not mean that memory is allocated.

- True

Correct Ans By **AR**

Question # 102

For which array, the size of the array should be one more than the number of elements in an array?

- char

Correct Ans By **AR**

Question # 103

If a variable is passed by value to a function and the function makes some changes to that variable then it

- does not affect the original variable

Correct Ans By **AR**

Question # 104

In C/C++ the #include is called,

- Preprocessor Directive

Correct Ans By **AR**

Question # 105

Loops are _____ Structure.



AR Lucky Term

-

Repetition

Correct Ans By AR

Question # 106

the sizeof operator is used to determine the size of _.

-

data type

Correct Ans By AR

Question # 107

Structures use_____ allocation.

-

Stack

Correct Ans By AR

Question # 108

Which header file must be included to use the functions tolower() and toupper()?

-

ctype.h

Correct Ans By AR

Question # 109

In Analysis, we try to have a_____

-

Precise problem statement

Correct Ans By AR

Question # 110

Pointers store the _____

-

memory address

Correct Ans By AR



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Question # 111

_____ Returns true if c is a digit and false otherwise.

- int isdigit(int c)

Correct Ans By AR

Question # 112

eof is used to check for the of file when a file is being read.

- End

Correct Ans By AR

Question # 113

The statement cout << yptr will show the the yptr points to.

- memory address

Correct Ans By AR

Question # 114

Which of the following is true about streams?

- A& B

Correct Ans By AR

Question # 115

While handling files, one can have options

- All of the given

Correct Ans By AR

Question # 116

A structure is a collection of under a single name.

-



AR Lucky Term

variables

Correct Ans By **AR**

Question # 117

Ifstream is used for_____

-

Input file stream

Correct Ans By **AR**

Question # 118

The ASCII code of null character is_____

-

000

Correct Ans By **AR**

Question # 119

Whenever some number is added in an array name, it will jump as many _____ as the added number.

-

rows

Correct Ans By **AR**

Question # 120

To access the data members of structure, is used.

-

Dot operator

Correct Ans By **AR**

Question # 121

char **argv can be read as _.

-

pointer to pointer to char

Correct Ans By **AR**

Question # 122



AR Lucky Term

From following; which one is the correct syntax of an array initialize:
Array size is 10 and it is of double data type to value 0?

- double arr[10] = {0.0};

Correct Ans By **AR**

Question # 123

Pointers work by pointing to a particular_____

- data type

Correct Ans By **AR**

Question # 124

_____function give the position of the next character to be read from that file.

- tellg()

Correct Ans By **AR**

Question # 125

An object of class can be created for saving the current position of any opened file before reading from the file.

- Stream

Correct Ans By **AR**

Question # 126

Structures are syntactically defined with the word _.

- struct

Correct Ans By **AR**

Question # 127



AR Lucky Term

_____ allow us to have a memory location and use it as int or char interchangeably

- union

Correct Ans By **AR**

Question # 128

A hierarchy of classes which are used to deal with console and disk files are called _.

- IO classes

Correct Ans By **AR**

Question # 129

_____ function is used to determine the next position to write a character while writing into a file.

- tellp()

Correct Ans By **AR**

Question # 130

For binary member operators, operands on the drives (calls) the operation.

- Left

Correct Ans By **AR**

Question # 131

references

- references

Correct Ans By **AR**

Question # 132



AR Lucky Term

We can_____ pointer.

- all of the given
Correct Ans By **AR**

Question # 133

We can_____ references.

- None of the given
Correct Ans By **AR**

Question # 134

An instance of a class is called _.

- object
Correct Ans By **AR**

Question # 135

The is called automatically when an object destroys

- destructor
Correct Ans By **AR**

Question # 136

The destructor is used to _.

- deallocate memory
Correct Ans By **AR**

Question # 137

_____ data isn't accessible by non-member functions or outside classes.

-



AR Lucky Term

private

Correct Ans By AR

Question # 138

The main advantage of function overloading is _.

- The program becomes more readable

Correct Ans By AR

Question # 139

NULL has been defined in header file.

- Stdlib.h

Correct Ans By AR

Question # 140

Symbolic constant PI can be defined as:

- #define PI 3.14

Correct Ans By AR

Question # 141

The friend function of a class can have access _.

- to the private data members

Correct Ans By AR

Question # 142

C++ was developed by _.

- Bejarne Stroustrup

Correct Ans By AR

Question # 143



AR Lucky Term

Once they are created, they exist for the life time of the program.

- static variables

Correct Ans By **AR**

Question # 144

An address is a _____, while a pointer is a __.

- constant, variable

Correct Ans By **AR**

Question # 145

The syntax of declaration of a function that returns the reference to an integer is __.

- `int & myfunc();`

Correct Ans By **AR**

Question # 146

Which one of the following is mandatory preprocessor directive for c++?

- `#include`

Correct Ans By **AR**

Question # 147

The members of a class declared with the keyword struct are by default.

- Public

Correct Ans By **AR**

Question # 148

`getche()` is a _____ function and defined in header file.

-



AR Lucky Term

built-in function , conio.h

Correct Ans By **AR**

Question # 149

_____ operators are the ones that require two operands on both sides of the operator.

-

Binary

Correct Ans By **AR**

Question # 150

We cannot use pointer for storing and reading data from it.

-

'NULL

Correct Ans By **AR**

Question # 151

The dynamic memory allocation uses whereas static memory allocation uses _.

-

heap , stack

Correct Ans By **AR**

Question # 152

_____ will return the number of bytes reserved for a variable or data type.

-

sizeof operator

Correct Ans By **AR**

Question # 153

_____ are not available in C language.

-



AR Lucky Term

Library functions

Correct Ans By **AR**

Question # 154

The members of a class declared without any keyword are by default.

-

private

Correct Ans By **AR**

Question # 155

For console input and output we use _.

-

conio.h header file

Correct Ans By **AR**

Question # 156

The name of the destructor is the same as that of a class proceeding with a

_.

-

~ sign

Correct Ans By **AR**

Question # 157

A reference cannot be NULL it has to point a data type.

-

True

Correct Ans By **AR**

Question # 158

A pointer is _.

-

a variable for storing address

Correct Ans By **AR**

Question # 159



AR Lucky Term

Constructor is a special function, called whenever we _.

- instantiate an object of a class

Correct Ans By **AR**

Question # 160

Symbolic constant PI can be defined as:

- #define PI 3.14

Correct Ans By **AR**

Question # 161

Object code is machine code but it is not _____ and _.

- relocatable, executable

Correct Ans By **AR**

Question # 162

_____ variables are those that are defined outside of main.

- Global

Correct Ans By **AR**

Question # 163

Within the statement obj1=obj2; obj1 will call the assignment operator function and obj2 will be passed as an argument to function.

- True

Correct Ans By **AR**

Question # 164

It is possible to return an object from function using this pointer.

-



AR Lucky Term

True

Correct Ans By AR

Question # 165

Overloaded assignment operator must be

- Member function of class

Correct Ans By AR

Question # 166

_____ must be included to use stream manipulation in your code.

- Iomanip

Correct Ans By AR

Question # 167

_____ operators are the ones that require only one operator to work.

- Unary

Correct Ans By AR

Question # 168

The endl and flush are _.

- Manipulators

Correct Ans By AR

Question # 169

When operator function is implemented as member function then return type of function _.

- Can be any data type

Correct Ans By AR

Question # 170



AR Lucky Term

What will be the output of following statement?

```
cout<<setfill('0')<<setw(7)<< 128;<="" h2="" style="box-sizing: border-box;"></setfill('0')<<setw(7)<<>
```

- 0000128

Correct Ans By **AR**

Question # 171

Which of the following syntax is best used to delete an array of 5 objects named 'string' allocated using new operator.

- delete []string;

Correct Ans By **AR**

Question # 172

The first parameter of operator function for << operator _.

- Must be passed by reference

Correct Ans By **AR**

Question # 173

The second parameter of operator function for >> operator must always be passed

- By reference

Correct Ans By **AR**

Question # 174

The only operator that the compiler overloads for user define data type by default is-----

- Assignment (=) operator

Correct Ans By **AR**



AR Lucky Term

Question # 175

Consider the following code, the printed value will be converted into:

```
int n=10;
```

```
cout <<oct<<n;< h2="" style="box-sizing: border-box;"></oct<<n;<>
```

-

Base 8

Correct Ans By **AR**

Question # 176

_____ variables are defined in the main.

-

Local

Correct Ans By **AR**

Question # 177

ostream class is and not under our control.

-

built-in

Correct Ans By **AR**

Question # 178

The memory allocation in C++ is carried out with the help of _.

-

new operator

Correct Ans By **AR**

Question # 179

If B is designated as friend of A, B can access A's non-public members.

-

A can access non-public members of B

Correct Ans By **AR**

Question # 180



AR Lucky Term

If the request of new operator is not fulfilled due to insufficient memory in the heap _.

- the operator returns 0

Correct Ans By **AR**

Question # 181

The friend keyword provides access _.

- in one direction only

Correct Ans By **AR**

Question # 182

The malloc function takes argument(s).

- one

Correct Ans By **AR**

Question # 183

The constructor contains _.

- no return type
By **AR**

Question # 184

What will be the output of the following c++ code?

```
#include  
#define max 100  
main()  
{  
#ifdef max Cout<<"Hellow;  
}
```



AR Lucky Term

-

Error

Correct Ans By **AR**

Question # 185

Once we have defined a symbolic constant value using #define, that value _____ during program execution

-

cannot be changed

Correct Ans By **AR**

Question # 186

The memory allocation functions return a chunk of memory with a pointer of type _.

-

ptr

Correct Ans By **AR**

Question # 187

A class can be declared as a of other class.

-

member

Correct Ans By **AR**

Question # 188

To avoid dangling reference, don't return _.

-

the reference of a local variable from the function

Correct Ans By **AR**

Question # 189

The parameter passed to isdigit() function is variable.

-



AR Lucky Term

Integer

Correct Ans By AR

Question # 190

How many bytes an integer type pointer intPtr will jump in memory if the statement below is executed?

intPtr += 2;

-

8

Correct Ans By AR

Question # 191

The increment of a pointer depends on its _.

-

data type

Correct Ans By AR

Question # 192

The statement cout << yptr will show the the yptr points to.

-

memory address

Correct Ans By AR

Question # 193

_____ is used as a dereferencing operator.

-

*

Correct Ans By AR

Question # 194

Transpose of a matrix means that when we interchange rows and columns

_.

-



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

the first row becomes the first column

Correct Ans By **AR**

Question # 195

Individual characters in a string stored in an array can be accessed directly using array `_`.

-

subscript

Correct Ans By **AR**

Question # 196

We can define a matrix as array.

-

Multi dimensional

Correct Ans By **AR**

Question # 197

A is an array of characters that can store number of character specified.

-

String

Correct Ans By **AR**

Question # 198

Given a two dimensional array of integers, what would be the correct way of assigning the value 6 to the element at third row and fourth column?

-

`array[2][3] = 6;`

Correct Ans By **AR**

Question # 199

_____ of a variable means the locations within a program from where it can be accessed.

-



AR Lucky Term

Visibility

Correct Ans By AR

Question # 200

Which of the following function call is "call by reference" for the following function prototype? `int add (int *)`;

-

`add(&x);`

Correct Ans By AR

Question # 1

An object of class can be created for saving the current position of any opened file before reading from the file.

-

Streampos

Correct Ans By AR

Question # 2

In while loop, the loop counter is initialized at -----

-

Before entering the loop

Correct Ans By AR

Question # 3

What is the output of thw following code if the 3rd case is true
`Switch (var)`



AR Lucky Term

{Case 'a';

Cout<<"apple"<<="" h2="" style="box-sizing: border-box;">

•

Mango

Correct Ans By AR

Question # 4

In computer system there are mainly type of software's.

•

2

Correct Ans By AR

Question # 5

26. Following is the declaration of a 2d array, how many columns are declared for this array.

Int arr[3][2];

•

2

Correct Ans By AR

Question # 6

A character is stored in the memory in -----

•

Byte

Correct Ans By AR

Question # 7

will be used for enclosing function statements into a block?

•

{ }

Correct Ans By AR

Question # 8



AR Lucky Term

We can access a global variable ----

- From anywhere in the program

Correct Ans By **AR**

Question # 9

. What will be output of the following code?

```
String name [4] = {"ali", "bilal", "omer", "Ayesha"};
```

```
Cout<< name [0];
```

- Ali

Correct Ans By **AR**

Question # 10

The data type before a function name represents its,

- Return type

Correct Ans By **AR**

Question # 11

is used for input file or for reading from the file.

- Tellg()

Correct Ans By **AR**

Question # 12

Following is the declaration a array. `Int arr[2][2][2]`

- 3-dimensional

Correct Ans By **AR**

Question # 13

! ($x < 3$) means in c++ that



AR Lucky Term

-

X is greater than 3

Correct Ans By **AR**

Question # 14

Which of the following option is correct to compare the declaration of the function?

----- (parameter1, parameter2)

{

// code to be executed

}

-

Void functionNAME

Correct Ans By **AR**

Question # 15

Ofstream is used for -----

-

Output file stream

Correct Ans By **AR**

Question # 16

By default, the starting index of an array in c++ is ____

-

0

Correct Ans By **AR**

Question # 17

How we declare an array of integer data whose size is 20 with array name “count”.

-

Int count [20];

Correct Ans By **AR**



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Question # 18

Which of the following is a reserve word for data types in c/c++?

- Int
Correct Ans By **AR**

Question # 19

C was developed with the help of language

- BCPL and B
Correct Ans By **AR**

Question # 20

C ++ is a language.

- High level
Correct Ans By **AR**

Question # 21

_____ character is used to indicate the end of the string.

- Null
Correct Ans By **AR**

Question # 22

Which of the following is used to perform bit-wise exclusive OR operation?

- |
Correct Ans By **AR**

Question # 23

If $x = 11$, and $x \% = 3$, the value of x will be----



AR Lucky Term

-

2

Correct Ans By AR

Question # 24

A variable of character data type occupies bytes in memory.

-

1

Correct Ans By AR

Question # 25

Null character is represented by in c ++?

-

\0

Correct Ans By AR

Question # 26

There is pointer variable named ptr of type float. Which type of variable address can be store by ptr?

-

Float

Correct Ans By AR

Question # 27

X is an integer variable; what does x++ means,

-

Add 1 in x value

Correct Ans By AR

Question # 28

When we call a function, its control-----

-

Transfers to its definition

Correct Ans By AR



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Question # 29

'\0' takes space in the memory.

- 1 byte

Correct Ans By AR

Question # 30

How can we declare an array of characters whose size is 12 with array name "country"?

- Char country[12];

Correct Ans By AR

Question # 31

Following is the declaration of a 2d array, how many columns are declared for this array. Int arr[3][2];

- 2

Correct Ans By AR

Question # 32

If we assign 2.06721 to an integer variable x, what will be the output if we print x using cout<< statement?

- 2

Correct Ans By AR

Question # 33

We use to include all those functions which are located in different files.

- Linker

Correct Ans By AR



AR Lucky Term

Question # 34

A character is stored in the memory in ----

- Byte

Correct Ans By AR

Question # 35

Which is not true regarding structure?

- We can declare array of structure

Correct Ans By AR

Question # 36

Mr. ahmad sleeps thirty hours every day. This sentence is

- Grammatically correct but illogical

Correct Ans By AR

Question # 37

will explain the function of a program.

- Comments

Correct Ans By AR

Question # 38

Char **argv can be read as ----

- Pointer to pointer to char

Correct Ans By AR

Question # 39

The expression $((a+b) == 10) \parallel ((x+y) == 20)$ is true only if?

-



AR Lucky Term

Either $((a+b) =)$ OR $((x + y) = =20)$ is true

Correct Ans By AR

Question # 40

= operator is used for ----

-

Assigning values to variables

Correct Ans By AR

Question # 41

What is the use of ios::trunc mode?

-

To truncate an existing file to zero

Correct Ans By AR

Question # 42

X is an integer variable; what does $x ++$ means,

-

Add 1 in x value

Correct Ans By AR

Question # 43

Structures use allocation.

-

Heap

Correct Ans By AR

Question # 44

What will be the size of the following character array? `Char name[] = "adeel";`

-

6

Correct Ans By AR

Question # 45



AR Lucky Term

A _____ is an array of characters that can store number of character specified.

-

String

Correct Ans By AR

Question # 46

statement is used to terminate the processing of a particular case and exit from switch structure.

-

Break

Correct Ans By AR

Question # 47

If $y = 20$ and $z = y ++$, then the value of z will be-----

2146. If

Int $a = 17$;

int $b = 3$;

double $c = a/b$;

what will be value of variable c ?

-

5

Correct Ans By AR

Question # 48

What will be the output of the following code?

String grade [3] = {"a", "b", "c"};

Grade[2] = "f";

Cout<< grade[2];

-

F

Correct Ans By AR



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Question # 49

Declaration of two-dimensional array of integers having 3 rows and 5 columns is following?

- Int arr [3][5];
Correct Ans By **AR**

Question # 50

$A = a + 1$; can be written as ----

- $A++ = 1$;
Correct Ans By **AR**

Question # 51

A record is a group of related

- Fields
Correct Ans By **AR**

Question # 52

What will be the result of arithmetic expression $6 + 48 / 4 * 3$?

- 42
Correct Ans By **AR**

Question # 53

_____ construct is used to execute a set of instructions when a condition is true and other set when it is false?

- If\else
Correct Ans By **AR**

Question # 54



AR Lucky Term

If an array has 50 elements, what is allowable range of subscripts?

- 0 – 49

Correct Ans By **AR**

Question # 55

If `int a = 50;` then the value of `a/= 3;` will be?

- 16

Correct Ans By **AR**

Question # 56

Which of the following option is/are correct about array?

- Only one type of elements can store in an array

Correct Ans By **AR**

Question # 57

Whenever some number is added in an array name, it will jump as many as the added number?

- Rows

Correct Ans By **AR**

Question # 58

_____ returns true if c is a digit or a letter and false otherwise.

- `Int isalnum(int c)`

Correct Ans By **AR**

Question # 59

which of the following is the default mode of the opening using of `ofstream` class?



AR Lucky Term

-

Ios::trunc

Correct Ans By AR

Question # 60

In which language the compiler of c language is written?

-

C

Correct Ans By AR

Question # 61

While loop executes at least?

-

One time

Correct Ans By AR

Question # 62

String are accessed by variable of type----

-

Char

Correct Ans By AR

Question # 63

Which of the following is the correct operator to compare the values of two variables?

-

= =

Correct Ans By AR

Question # 64

Not operator is a -----

-

Single input operator

Correct Ans By AR



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Question # 65

Pointer points to a particular-----

- Memory address

Correct Ans By AR

Question # 66

A function is a block of statements that can be defined once and used- --- in the program.

- As many times as user wants

Correct Ans By AR

Question # 67

_____ function is used to find the number of characters in a string?

- Strlen()

Correct Ans By AR

Question # 68

! = operator is used to check whether the operand on the left-hand side is to the operand on the right-hand-side.

- Not equal

Correct Ans By AR

Question # 69

A while loop may execute or more times.

- 0

Correct Ans By AR

Question # 70



AR Lucky Term

How we declare an array of integer data whose size is 20 with array name “count”.

- Int count[20];
Correct Ans By **AR**

Question # 71

A variable declared within a code block becomes variable for that block.

- Local
Correct Ans By **AR**

Question # 72

If a file is opened with ios::out mode, then -----

- We can write in this file
Correct Ans By **AR**

Question # 73

A function's prototype is written --- the function call.

- Before
Correct Ans By **AR**

Question # 74

---- Loop is mostly used to perform repetition of a tasks for a known number of times.

- For
Correct Ans By **AR**

Question # 75



AR Lucky Term

In shifting operations if zero is inserted at the least most bit, the negative number will become a number.

-

Positive

Correct Ans By **AR**

Question # 76

It is the job of to transfer the executable code from hard disk to main memory.

-

Loader

Correct Ans By **AR**

Question # 77

If x is declare as an integer, what will be result of the given expression?

$X = 2 + 3 * 5 \% 2 + 3 / 2$??

-

4

Correct Ans By **AR**

Question # 78

What will be the correct syntax of declaration of the following statements?

“ptr is a pointer to const int” ??

-

Const int *ptr

Correct Ans By **AR**

Question # 79

After evaluating the expression

$X = 10 + 3 * 4 / 2 - 1$, the value of x will be?

-



AR Lucky Term

15

Correct Ans By AR

Question # 80

We can read, write and manipulate the same file using ----

-

Fstream.h

Correct Ans By AR

Question # 81

Return type of a function that does not return any value must be ----

-

Void

Correct Ans By AR

Question # 82

Pointers store the ----

-

Memory address

Correct Ans By AR

Question # 83

operator uses the sign ^.

-

Exclusive OR

Correct Ans By AR

Question # 84

RAID stands for-----

-

Redundant array of inexpensive devices

Correct Ans By AR

Question # 85



AR Lucky Term

Array indexes start from ----

-

0

Correct Ans By **AR**

Question # 86

In call by reference, of a variable is passed to the called function.

-

Address

Correct Ans By **AR**

Question # 87

How many times the following do-while loop will execute?

Int k = 10;

Do

{

Cout << "statements" << endl; ?

-

6

Correct Ans By **AR**

Question # 88

The name of a location in memory is called ----

-

Variable

Correct Ans By **AR**

Question # 89

function is used to find the number of character in a string.

-

Strlen()

Correct Ans By **AR**

Question # 90



AR Lucky Term

Which statement is used to close a file?

- Myfile.close();
Correct Ans By **AR**

Question # 91

Allow us to have a memory location and use it as int or char interchangeably.

- None of the given
Correct Ans By **AR**

Question # 92

While handling files, one can have options

- All of the given
Correct Ans By **AR**

Question # 93

_____ function is used to determine the next position to write a character while writing into a file.

- Tello() **Correct Ans** By **AR**

Question # 94

< and > both are operators.

- Logical
Correct Ans By **AR**

Question # 95



AR Lucky Term

Identify the logical error in the following
if condition If $((i < 5) \& \& (i > 15))$?

- Condition is always false

Correct Ans By **AR**

Question # 96

Not operator is a ----

- Single input operator

Correct Ans By **AR**

Question # 97

The use of *sign in first and second statements is called --- and ---- of
pointer.

Int *ptr = &x;

Cout<<*ptr; ?

- Referencing, dereferencing

Correct Ans By **AR**

Question # 98

C is widely known as development language of operating system.

- Linux

Correct Ans By **AR**

Question # 99

To get the value stored at a memory address, we use the ----

- Dereferencing operator

Correct Ans By **AR**

Question # 100



AR Lucky Term

Telling a computer what to do is called ----

- Programming
Correct Ans By **AR**

Question # 101

Compiler translates high level language program into language code.

- Machine
Correct Ans By **AR**

Question # 102

Each array declaration must provide the information about all these things except----

- The location of the first element to be stored
Correct Ans By **AR**

Question # 103

_____of is used to check for the of file when a file is being resd.

- End
Correct Ans By **AR**

Question # 104

The result of $4\%3$ will be?

- 1
Correct Ans By **AR**

Question # 105

When the logical operator AND (&&) combine two expression exp1 and exp2 then the result will be true only?



AR Lucky Term

- When both exp1 and exp2 are true

Correct Ans By **AR**

Question # 106

‘multi[3][3]’ element can also be accessed by -----

- $*(*(multi + 3) + 3)$

Correct Ans By **AR**

Question # 107

What is output of following code?

```
Int data [10] = {10,20,30,40,50,60,70,80,90,100};
```

```
Int *xptr =&data [4];
```

```
Int *xptr =&data [6];
```

```
Cout<<="" h2="" style="box-sizing: border-box;">
```

- 120

Correct Ans By **AR**

Question # 108

Which of the following is not the subcategory of the system software?

- None of the above

Correct Ans By **AR**

Question # 109

We get $12 | 8 =$ where “|” is (bit-wise OR) ?

- 12

Correct Ans By **AR**

Question # 110

_____ is a substitute of multiple if statement.



AR Lucky Term

-

If..elseif statement

Correct Ans By **AR**

Question # 111

Find out the logical error in following lines of code.

If (x = 10)

Cout << “x is 10”; ?

-

Assignment operator should not be used for comparison

Correct Ans By **AR**

Question # 112

Which is not true regarding structure?

-

we can't declare pointers to structure

Correct Ans By **AR**

Question # 113

are used to compiler the code.

-

Compiler

Correct Ans By **AR**

Question # 114

```
#include
```

```
#include Using
```

```
namespace std;
```

```
Int main ()
```

```
{
```

```
Char str1[10] = “hello”; Char
```

```
str2[10] = “world”;
```

-



AR Lucky Term

? 10

Correct Ans By AR

Question # 115

A _____ structure specifies that an action is to be repeated while some condition remains true.

-

Repetition

Correct Ans By AR

Question # 116

Characters string are terminated by -----

-

\0

Correct Ans By AR

Question # 117

A function is a block of statements that can be defined once and used - in the program.

-

As many times as user wants

Correct Ans By AR

Question # 118

_____ is used for output during the process of writing to the file.

-

Seekp()

Correct Ans By AR

Question # 119

In case of two-dimensional array, if you add some number in a two-dimensional name, it will jump to the next----

-



AR Lucky Term

Row

Correct Ans By AR

Question # 120

In while loop the condition is checked the execution of loop.

-

Before

Correct Ans By AR

Question # 121

Array indexes start from ----

-

0

Correct Ans By AR

Question # 122

Pointers store the ----

-

Memory address

Correct Ans By AR

Question # 123

Which step is not not performed during a proper program design?

-

Write details about the performance of program

Correct Ans By AR

Question # 124

We can say that a pointer is a variable that holds the address.

-

Memory

Correct Ans By AR

Question # 125



AR Lucky Term

When accessing a structure memory, the identifier to the left of the dot operator is the name of ----

- Structure variable

Correct Ans By **AR**

Question # 126

From the following; which one is the range of random number generator rand() ?

- - 32767

Correct Ans By **AR**

Question # 127

To read command-line arguments, the main () function itself must be given arguments.

- 2

Correct Ans By **AR**

Question # 128

Which operator has the highest precedence? (*, -, /, +) ?

- and / both have the same highest precedence

Correct Ans By **AR**

Question # 129

Suppose we have int y[10];

To access the 4th element of the array we write----

- Y[3];

Correct Ans By **AR**

Question # 130



AR Lucky Term

What will be the value of the variable output in the given piece of code?

Double output = 0;

Output = (2 + 2) * 4 + / (4 - 2);

-

17

Correct Ans By **AR**

Question # 131

Searching is easier when an array is already sorted

-

True

Correct Ans By **AR**

Question # 132

If an array has 100 elements, what is allowable range of subscripts?

-

0 - 99

Correct Ans By **AR**

Question # 133

While developing a program; should we think about the user interface?

-

//handouts main Yes

Correct Ans By **AR**

Question # 134

A character is stored in the memory in _____

-

String

Correct Ans By **AR**

Question # 135



AR Lucky Term

These functions seekg() and seekp() requires an argument of type _____ to let them how many bytes to move forward or backward.

•

Int

Correct Ans By AR

Question # 136

dereferencing operator is represented by _____

•

*

Correct Ans By AR

Question # 137

_____ transfers the executable code from main memory to hard disk.

•

Loader

Correct Ans By AR

Question # 138

When the logical operator OR (||) combine two expressions exp1 and exp2 then the result will be false only, //bitwise “or” applies here....

•

When both exp1 and exp2 are false

Correct Ans By AR

Question # 139

suppose we have int y[10]; To access the 4th element of the array we write_____

•

none of given

Correct Ans By AR

Question # 140



AR Lucky Term

we have opened a file stream myfile for reading (getting), myfile.tellg () gives us the current get position of the file pointer. It returns a whole number of type_____

-

int

Correct Ans By **AR**

Question # 141

ofstream is used for_____

-

Output file stream

Correct Ans By **AR**

Question # 142

A structure is a collection of under a single name.

-

Variables

Correct Ans By **AR**

Question # 143

In C/C++ the string constant is enclosed corrected r red one

-

In curly braces

Correct Ans By **AR**

Question # 144

The size of int data

-

type is 4 bytes

Correct Ans By **AR**

Question # 145

In Flow chart process is



AR Lucky Term

- represented by Rectangle
Correct Ans By **AR**

Question # 146

If the break statement is missed in switch statement then, // a break statement with no label always completes abruptly, the reason being a break with no label. If no switch, while, do, or for statement in the immediately enclosing method, constructor or initializer encloses the break statement, a compile-time error occurs?

- This may cause a logical error
Correct Ans By **AR**

Question # 147

When we are using const keyword with a variable x then initializing it at the time of declaration is, ?

- Optional
Correct Ans By **AR**

Question # 148

How many total elements must be in two-dimensional array of 3 rows and 2 columns?

- 6
Correct Ans By **AR**

Question # 149

Which of the following is the correct statement for the following declaration?

- *ptr is a pointer to const int



AR Lucky Term

Correct Ans By **AR**

Question # 150

What will be the correct syntax to assign an array named arr of 5 elements to a pointer ptr?

- `*ptr = arr[5] ;`

Correct Ans By **AR**

Question # 151

C is a/an language

- object oriented

Correct Ans By **AR**

Question # 152

The variables having a name, type and size are just like empty boxes.

- True

Correct Ans By **AR**

Question # 153

What's wrong with this for loop? for (int k = 2, k <=12, k++)

- the commas should be semicolons

Correct Ans By **AR**

Question # 154

Most efficient method of dealing with structure variables is to define the structure globally

- True

Correct Ans By **AR**



AR Lucky Term

Question # 155

There are mainly types of software.//

-

Two

Correct Ans By **AR**

Question # 156

When a pointer is incremented, it actually jumps the number of memory addresses ?

-

According to data type

Correct Ans By **AR**

Question # 157

setw is a parameterized manipulator.

-

True

Correct Ans By **AR**

Question # 158

_____ of a variable means the locations within a program from where it can be accessed.

-

Reference

Correct Ans By **AR**

Question # 159

Switch support data. Integer Character Float

-

Both integer and character

Correct Ans By **AR**

Question # 160



AR Lucky Term

_____statement is used to terminate the processing of a particular case and exit from switch structure.

- break

Correct Ans By **AR**

Question # 161

The most suitable data type for number 325.25 is _.

- float

Correct Ans By **AR**

Question # 162

X is an integer variable; what does X++

- means, Add 1 in X value

Correct Ans By **AR**

Question # 163

The operators ++ and -- are used to increment or decrement the value of a variable by _____

- 1

Correct Ans By **AR**

Question # 164

Which of the following loops checks the test condition at the end of the loop?

- Do-While

Correct Ans By **AR**

Question # 165



AR Lucky Term

The operator to free the allocated memory using new operator is _____.

- delete

Correct Ans By **AR**

Question # 166

suppose we have `int y[10]`; To access the 4th element of the array we write_____

- `y[3];`

Correct Ans By **AR**

Question # 167

From the following; which one is the range of Random number generator function `rand()`?

- 0 – 32767

Correct Ans By **AR**

Question # 168

From following; which one is the correct syntax of an array initialize: Array size is 10 and it is of double data type to value 0?

- `double arr[10] = {0.0};`

Correct Ans By **AR**

Question # 169

The string in the array is terminated by a_____

- null

Correct Ans By **AR**

Question # 170



AR Lucky Term

In C/C++; by default arguments are passed by to a function.

-

Value

Correct Ans By **AR**

Question # 171

char name [] = "Hello World" ; In the above statement, a memory of characters will be allocated

-

12

Correct Ans By **AR**

Question # 172

_____Keyword is used to return some value from a function.

-

return

Correct Ans By **AR**

Question # 173

Which of the function call is call by value for the following function prototype? float add(int);

-

add(x);

Correct Ans By **AR**

Question # 174

The increment of a pointer depends on its _.

-

data type

Correct Ans By **AR**

Question # 175

The ASCII code of null character is_____



AR Lucky Term

-

000

Correct Ans By **AR**

Question # 176

Transpose of a matrix means that when we interchange rows and columns_____

-

the first row becomes the first column

Correct Ans By **AR**

Question # 177

Pointers store the _____

-

value of a variable

Correct Ans By **AR**

Question # 178

Which of the following function call is “call by reference” for the following function prototype?

-

int add (int *); add(&x);

Correct Ans By **AR**

Question # 179

The name of the array is a constant pointer which contains the memory address of the of the array.

-

first element

Correct Ans By **AR**

Question # 180

array name always contains the memory address of the of the array



AR Lucky Term

- first element

Correct Ans By **AR**

Question # 181

A union is a user-defined data type that contains only from its list of members at a time.

- one object

Correct Ans By **AR**

Question # 182

Which of the given file handling modes are similar in their functionality ?

- ios::trunc, ios::ate

Correct Ans By **AR**

Question # 183

Which one of the given option is not a mode for reading/writing the data from a file?

- Trunk

Correct Ans By **AR**

Question # 184

In C/C++, the header file used for string manipulation is _.

- string.h

Correct Ans By **AR**

Question # 185

A 2D array multi[5][10] can be accessed using the array name as **multi , this technique is called _.



AR Lucky Term

- Double dereferencing
Correct Ans By **AR**

Question # 186

C language was evolved from language(s).

- B and BCPL
Correct Ans By **AR**

Question # 187

The statement forces the immediate next iteration of the loop.

- Continue
Correct Ans By **AR**

Question # 188

_____ are very good tools for code reuse.

- Functions
Correct Ans By **AR**

Question # 189

When an argument is passed by reference, _____

- the function accesses the argument's original value in the calling program.
Correct Ans By **AR**

Question # 190

_____ executes all the lines before error and stops at the line which contains the error.

- Interpreter



AR Lucky Term

Correct Ans By **AR**

Question # 191

Analysis is the step in designing a program.

-

First

Correct Ans By **AR**

Question # 192

Which of the following is the correct function call, having array named student of 10 elements as a parameter?

-

addRecord(student);

Correct Ans By **AR**

Question # 193

When an array element is passed to a function, it is passed by

_____.

-

Reference

Correct Ans By **AR**

Question # 194

What is the correct syntax to declare an array of size 10 of int data type?

-

int name[10] ;

Correct Ans By **AR**

Question # 195

If we want to copy an array, both arrays need to be of same _.

-

Data type and size

Correct Ans By **AR**



AR Lucky Term

Question # 196

Which of the following is the correct syntax to print multiple values or variables in a single command using cout?

- `cout << "H" << x << "\n";`

Correct Ans By **AR**

Question # 197

The condition in loop should be a(n) _.

- Boolean Expression

Correct Ans By **AR**

Question # 198

Which structure is represented by following flow chart ?

- if structure

Correct Ans By **AR**

Question # 199

Stream which sends data to the program is called _.

- Input stream

Correct Ans By **AR**

Question # 200

Syntax of a union is identical to _ .

- Structure

Correct Ans By **AR**



AR Lucky Term

CS201 Grand Quiz

Objective Questions

Question # 1

Which of the following function call is "call by reference" for the following function prototype? float add (float *);

add(&x);

Correct Ans By AR

Question # 2

Which of the function call is call by value for the following function prototype? float add(float)

add(x);

Correct Ans By AR

Question # 3

Which of the function call is "call by value" for the following function prototype? float add(int);

add(x);

Correct Ans By AR

Question # 4

Return type of a function that does not return any value must be _.

void

Correct Ans By AR

Question # 5

_____ will be used for enclosing function statements into a block.

{ }

What is the output of the following code if the 2nd case is true switch



AR Lucky Term

```
(var)
{
case 'a':
cout<<"apple"<<<"banana"<
case
'm':cout<<"mango"<<<"any="" fruit"<
}
```

Banana mango any fruit

Correct Ans By **AR**

Question # 6

When the break statement is encountered in a loop's body, it transfers the control from the current loop.

Outside

Correct Ans By **AR**

Question # 7

What is the output of the following code if the 3rd case is true

```
switch (var) {
case
'a':cout<<"apple"<
case
'b':cout<<"banana"<
case
'm':cout<<"mango"<
default: cout<<"any fruit"<<endl;
}</endl;
```

Mango any fruit

Correct Ans By **AR**

Question # 8



AR Lucky Term

What is the output of the following code, if the first case is true switch

```
(var) {  
case  
'a':cout<<"apple"<<endl;  
case  
'b':cout<<"banana"<<endl;  
case  
'm':cout<<"mango"<  
default: cout<<"any <br.fruit"<<endl;  
}</br.fruit"<<endl;  
</endl;  
</endl;
```

- Apple banana mango any fruit

Correct Ans By **AR**

Question # 9

What will be the output of following code segment?

```
for (int i = 2; i<10; i++)  
{  
if ( i == 5) |  
continue; cout << i << ", " ;  
}
```

- 2,3,4,6,7,8,9

Correct Ans By **AR**

Question # 10

_____ statement is used to terminate the processing of a particular case and exit from switch structure.

-



AR Lucky Term

break

Correct Ans By AR

Question # 11

What will be the result of the expression $j = i++$; if initially $j = 0$ and $i = 5$?

•

5

Correct Ans By AR

Question # 12

What will be the result of the expression $k = ++m$; if initially $k = 0$ and $m = 5$?

•

6

Correct Ans By AR

Question # 13

How many times the following do-while loop will execute?

```
int k = 10;
```

```
do { cout << "Statements" << endl; k -= 2;
```

```
}
```

```
while(k>0);
```

•

6

Correct Ans By AR

Question # 14

Which of the following loops checks the test condition at the end of the loop?

•

Do-While

Correct Ans By AR



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Question # 15

The operators ++ and -- are used to increment or decrement the value of a variable by _.

•

1

Correct Ans By AR

Question # 16

How many times the following loop will execute?

```
int j = 3;
while(j > 0)
{
cout << "Statements" << endl; j -= 2;
}
```

•

2

Correct Ans By AR

Question # 17

A structure specifies that an action is to be repeated while some condition remains true.

•

Control

Correct Ans By AR

Question # 18

!(x > 3) means in C++ that x is less than or

•

equal to 3

Correct Ans By AR

Question # 19



AR Lucky Term

When the logical operator && combines two expressions then the result will be true only when the both expressions are _.

- true

Correct Ans By **AR**

Question # 20

< and > both are operators.

- Relational

Correct Ans By **AR**

Question # 21

!(x < 3) means in C++ that

- x is greater than or equal to 3

Correct Ans By **AR**

Question # 22

!= operator is used to check whether the operand on the left-hand-side is _____ to the operand on the right-hand-side.

- Not equal

Correct Ans By **AR**

Question # 23

When the if statement consists more than one statement then enclosing these statement in curly braces is,

- Must

Correct Ans By **AR**

Question # 24



AR Lucky Term

The most suitable data type for number 325.25 is _.

-

Float

Correct Ans By **AR**

Question # 25

What will be the result of arithmetic expression $6 + 48 / 4 * 3$?

-

42

Correct Ans By **AR**

Question # 26

Which of the following will be the most appropriate data type to store the value 63.547?

-

Float

Correct Ans By **AR**

Question # 27

What will be the value of the variable output in the given piece of code?

double output = 0;

output = (2 + 2) * 4 + 2 / (4 - 2);

-

17

Correct Ans By **AR**

Question # 28

It is the job of to transfer the executable code from hard disk to main memory.

-

Loader

Correct Ans By **AR**

Question # 29



AR Lucky Term

In computer systems there are mainly type of softwares.

-

2

Correct Ans By AR

Question # 30

_____ will explain the function of a program.

-

Comments

Correct Ans By AR

Question # 31

if (a>b && a>c) then the condition will be true

-

only if Both a>b and a>c are true

Correct Ans By AR

Question # 32

A variable of character data type occupies byte(s) in memory.

-

1

Correct Ans By AR

Question # 33

We must include the header file to convert the value of one type into another type using built-in functions.

-

string.h

Correct Ans By AR

Question # 34

A function is a block of statements that can be defined once and used _____ in the program.



AR Lucky Term

- As many times as user wants

Correct Ans By **AR**

Question # 35

Select the correct way to assign the address of first element of array to pointer?

- `int *ptr = &data;`

Correct Ans By **AR**

Question # 36

Consider the following code segment. What will be the output of following code?

```
int addValue (int *a){ int b = (*a) + 2; return b;
}
main()
{ int x = 6;
cout<<addvalue(&x)<<" ";
cout<<x;
}</x>
</addvalue(&x)<<" ">
```

- 6,8,6

Correct Ans By **AR**

Question # 37

Here the code is given below. You have to identify the problem in the code.

```
while(i < 10) && (i > 24))
```

- the test condition is always false



AR Lucky Term

Correct Ans By AR

Question # 38

Matrix is defined as _.

- Multi-dimensional array

Correct Ans By AR

Question # 39

In programming, comments are used to explain the functioning of the _____.

- Program

Correct Ans By AR

Question # 40

Operating System is a type of a/an _.

- system software

Correct Ans By AR

Question # 41

From the options given, you need to choose the option which is true for the given code.

```
for (int i = 1; i>0; i++)  
{ /*loop code*/ }
```

- the test condition is always true

Correct Ans By AR

Question # 42

Which of the following values are used in C/C++ to represent true and false?



AR Lucky Term

-

1 and 0

Correct Ans By **AR**

Question # 43

'While' loop may execute or more times.

-

zero

Correct Ans By **AR**

Question # 44

Body of any function is enclosed within _.

-

{ }

Correct Ans By **AR**

Question # 45

Which one of the given option is not a mode for reading/writing the data from a file?

-

Get

Correct Ans By **AR**

Question # 46

Which of the following operators is used to access the value of variable pointed by a pointer?

-

operator

Correct Ans By **AR**

Question # 47

In case of single dereferencing, the value of the is the address of the _.

-



AR Lucky Term

pointer, variable

Correct Ans By **AR**

Question # 48

The remainder (%) operator is a operator.

-

Arithmetic

Correct Ans By **AR**

Question # 49

The purpose of using cout<< is to _.

-

Display information on the screen

Correct Ans By **AR**

Question # 50

Which of the following data types will be assumed if no data type is specified with constant?

-

short

Correct Ans By **AR**

Question # 51

When an array element is passed to a function, it is passed by _.

-

reference

Correct Ans By **AR**

Question # 52

While programming, it is good to provide an easy to understand and easy to use interface; this programming skill is called _.

-

usability



AR Lucky Term

Correct Ans By AR

Question # 53

_____ executes all the lines before error and stops at the line which contains the error.

-

Intrepreter

Correct Ans By AR

Question # 54

C is a/an language.

-

function oriented

Correct Ans By AR

Question # 55

_____ of a function is also known as signature of a function.

-

Declaration

Correct Ans By AR

Question # 56

_____ are very good tools for code reuse.

-

functions

Correct Ans By AR

Question # 57

If any break statement is missed in switch statement then _.

-

this may cause a logical error

Correct Ans By AR

Question # 58



AR Lucky Term

A 2D array `multi[5][10]` can be accessed using the array name as `**multi`, this technique is called _.

- Double dereferencing
Correct Ans By **AR**

Question # 59

In C/C++, the default command line arguments passed to the main function are _.

- `int argc, char **argv`
Correct Ans By **AR**

Question # 60

A record is a group of related _.

- Fields
Correct Ans By **AR**

Question # 61

The microsoft word document (.doc) is a kind of _.

- Random Access File
Correct Ans By **AR**

Question # 62

NULL character is used to indicate the end of string.

- End
Correct Ans By **AR**

Question # 63

How many dimensions does n-dimensional array has?



AR Lucky Term

-

n dimensions

Correct Ans By **AR**

Question # 64

Which of the following function call is "call by reference" for the following function prototype?

-

func(&num);

Correct Ans By **AR**

Question # 65

The loop which is most suitable to be used when the number of iterations is known is called _.

-

for

Correct Ans By **AR**

Question # 66

In C/C++, the string constant is enclosed in _.

-

double quotes " "

Correct Ans By **AR**

Question # 67

In order to get the right most digit of a number, we divide this number by 10 and take _.

-

Its remainder

Correct Ans By **AR**

Question # 68

What is the correct syntax to declare an array of size 10 of int data type?



AR Lucky Term

-

int name[10];

Correct Ans By **AR**

Question # 69

How many bytes of memory are occupied by array 'str'?

char str[] = "programming";

-

11

Correct Ans By **AR**

Question # 70

Suppose that an integer type pointer contains a memory address 0x22f230.

What will be the new memory address if we increment this pointer by one?

-

0x22f234

Correct Ans By **AR**

Question # 71

Which of the following if missing would result in infinite recursion in case of recursive function?

-

Recursive call

Correct Ans By **AR**

Question # 72

Whenever we use a library function or a predefined object or macro, we need to use a _.

-

header file

Correct Ans By **AR**

Question # 73



AR Lucky Term

Switch statement deals with type of data.

- Both Integer and Character

Correct Ans By **AR**

Question # 74

Both compiler and are used to translate program into machine language code.

- Interpreter

Correct Ans By **AR**

Question # 75

TWAIN stands for _.

- Technology Without An Interesting Name

Correct Ans By **AR**

Question # 76

The parameter passed to isdigit() function is _.

- a character variable

Correct Ans By **AR**

Question # 77

C++ views each file as a sequential stream of _.

- Bytes

Correct Ans By **AR**

Question # 78

Structure is a collection of under a single name.

-



AR Lucky Term

only variables

Correct Ans By **AR**

Question # 79

The default mode for writing into a file using ofstream object is _.

-

out

Correct Ans By **AR**

Question # 80

The memory address of the first element of an array is called _.

-

base address

Correct Ans By **AR**

Question # 81

We want to access array in random order which of the following approach is better?

-

Pointer

Correct Ans By **AR**

Question # 82

The structure is a multiple-selection construct which makes the code more efficient and easy to read and understand.

-

switch

Correct Ans By **AR**

Question # 83

Which of the following is not a reserved word in C/C++?

-

Sum



AR Lucky Term

Correct Ans By AR

Question # 84

To access rand(), which library is required to be included in program?

- stdlib.h

Correct Ans By AR

Question # 85

Word processor is a type of a/an _.

- application software

Correct Ans By AR

Question # 86

Identify the correct option which is used for calling the function float area (int).

- area(int num);

Correct Ans By AR

Question # 87

The statement allows us to select from multiple choices based on a set of fixed values for a given expression.

- switch

Correct Ans By AR

Question # 88

C is widely known as development language of operating system.

- Unix

Correct Ans By AR



AR Lucky Term

Question # 89

To convert the value of one type into another type using built-in functions, we include header file.

- stdlib.h
 Correct Ans By AR

Question # 90

The keyword is used to get some value back from a function.

- return
 Correct Ans By AR

Question # 91

The function seekg() takes parameter(s).

- 2
 Correct Ans By AR

Question # 92

The function write() takes as parameter(s).

- String and no. of bytes to be written
 Correct Ans By AR

Question # 93

When the logical operator AND (&&) combines two expressions exp1 and exp2 then the result will be true only _.

- When both exp1 and exp2 are true
 Correct Ans By AR

Question # 94



AR Lucky Term

Syntax of a union is identical to _.

- structure

Correct Ans By **AR**

Question # 95

In Flow Chart, flow of control is represented by _.

- Arrow

Correct Ans By **AR**

Question # 96

There can be 'default' statement(s) in any switch structure.

- 2

Correct Ans By **AR**

Question # 97

The condition in loop should be a(n) _.

- Arithmetic Expression

Correct Ans By **AR**

Question # 98

How many nested loops would be required to manipulate n-dimensional array?

- $2n$

Correct Ans By **AR**

Question # 99

Which of the following is not an example of int data type?

-



AR Lucky Term

-4

Correct Ans By AR

Question # 100

We should use for clarity and to force the order of evaluation in an expression.

-

parenthesis ()

Correct Ans By AR

Question # 101

Array is a data structure that stores _.

-

Variables

Correct Ans By AR

Question # 102

A program statement that invokes a function is called _.

-

function call

Correct Ans By AR

Question # 103

The compiler of C language is written in language.

-

C

Correct Ans By AR

Question # 104

Which function is used to locate the first occurrence of a character in any string?

-

strlen()



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Correct Ans By AR

Question # 105

To access the data members of structure, is used.

-

Dot operator

Correct Ans By AR

Question # 106

In the following nested For Loop, which loop will run most number of times?

```
for( int i = 0; i < 5; i++)  
{  
  for(int k = 0; k < 5; k++)  
  {  
    .....  
  }  
}
```

-

Depends upon the statements in the inner loop's body

Correct Ans By AR

Question # 107

Structure use allocation.

-

Heap

Correct Ans By AR

Question # 108

_____ function give the position of the next character to be read from that file.

-

tellp()



AR Lucky Term

Correct Ans By **AR**

Question # 109

What will be the size of the following character array? `char name[] = "Adeel";`

- 5

Correct Ans By **AR**

Question # 110

Which one of the following languages has been used to write the compiler of "C" language?

- C

Correct Ans By **AR**

Question # 111

A hierarchy of classes which are used to deal with console and disk files are called _.

- Stream classes

Correct Ans By **AR**

Question # 112

_____ stops execution at the line that contains error(s) in the code.

- Interpreter

Correct Ans By **AR**

Question # 113

C++ is a language.

- High level



AR Lucky Term

Correct Ans By **AR**

Question # 114

How many elements are stored in the following?
int matrix [4][5];

- 20

Correct Ans By **AR**

Question # 115

_____ is a substitute of multiple if statement.

- if. . .elseif statement

Correct Ans By **AR**

Question # 116

How many elements are stored in the following?
int matrix [4][5];

- 20

Correct Ans By **AR**

Question # 117

_____ is a substitute of multiple if statement.

- if. . .elseif statement

Correct Ans By **AR**

Question # 118

if

int sum = 54;

Then the value of the following
statement is sum = sum - 3;



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

-

51

Correct Ans By **AR**

Question # 119

What will be the correct syntax for declaration of the following statement?
"ptr is a constant pointer to an integer"

-

const int *myptr;

Correct Ans By **AR**

Question # 120

_____ operator is used to pass the address of a variable in call by reference method.

-

&

Correct Ans By **AR**

Question # 121

_____ data type can operate on modulus operator.

-

int

Correct Ans By **AR**

Question # 122

Whenever some number is added in an array name, it will jump as many _____ as the added number.

-

rows

Correct Ans By **AR**

Question # 123



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Suppose that an integer type pointer contains a memory address 0x22f220. What will be the new memory address if we increment this pointer by one?

- 0x22f224

Correct Ans By AR

Question # 124

_____ is the pointer which determines the position in a file from where the next read operation occurs.

- put

Correct Ans By AR

Question # 125

what is the correct centex to declare an array of 15 elements of type float?

- float array [14]

Correct Ans By AR

Question # 126

suppose we have a file with name “mylife.txt” . what will be the correct Syntax of file opening for input?

- my file (“myfile.txt”. ios::in)

Correct Ans By AR

Question # 127

which of the following will be the most appropriate data type to store the value 63.5 47?

- Float

Correct Ans By AR



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Question # 128

----- will explain the function of a program

- Comments

Correct Ans By AR

Question # 129

all elements of an array must be of data type

- Same

Correct Ans By AR

Question # 130

what will be the result of arithmetic expression $6 + 48 / 4 * 3$?

- 42

Correct Ans By AR

Question # 131

----- allow us to have a memory location and use it as int or char interchangeably

- none of the given

Correct Ans By AR

Question # 132

accessing a structure member the identifier to the left of the dot operator is the name of-----

- structural variable

Correct Ans By AR

Question # 133



AR Lucky Term

< and > both are operators

-

Arithmetic

Correct Ans By **AR**

Question # 134

what will be the output of the following code segment?

For (int = 2; i<10; i ++)

{

If (i == 5)

Continue;

cout<< i << “.”;

}

-

2,3,4,5,6,7,8,9

Correct Ans By **AR**

Question # 135

----- returns true if she is a digit or a letter and false

-

otherwise Int isalnum (int c)

Correct Ans By **AR**

Question # 136

if a ----- find an error, it stop translating without generating any E executable code

-

Compiler

Correct Ans By **AR**

Question # 137

the ASCII code of null character is-----



AR Lucky Term

-

000

Correct Ans By **AR**

Question # 138

the original value means unchanged in -----

-

Call by Value

Correct Ans By **AR**

Question # 139

which of the following is used to create an account stream?

-

Ofstream

Correct Ans By **AR**

Question # 140

how many times the following loop will execute?

```
Int j = 3;
```

```
While (j > 0)
```

```
{
```

```
Cout << " statements" << endl;
```

```
J - = 2;
```

```
}
```

-

2

Correct Ans By **AR**

Question # 141

Use of word processor for writing the code of a program is not good because -----

-

It has less feature for writing code of a program



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Correct Ans By **AR**

Question # 142

how many bytes and integer type pointer intptr will jump in memory if the statement below is executed?

Intptr += 2;

- 8

Correct Ans By **AR**

Question # 143

Avoid loop may execute or more Times

- 0

Correct Ans By **AR**

Question # 144

Raid stands for -----

- redundant array of inexpensive discs

Correct Ans By **AR**

Question # 145

in a file is opened with iOS:: out mode, then-----

- a new file is created

Correct Ans By **AR**

Question # 146

A structure specify that an action is to be repeated while some condition remains

- true Control



AR Lucky Term

Correct Ans By AR

Question # 147

The most suitable data type for number 325.25 is-----

- float

Correct Ans By AR

Question # 148

Which one of the following should be placed immediately either before or after the noun?

- Modifiers of Nouns

Correct Ans By AR

Question # 149

Titles typically include both

- a number and a description

Correct Ans By AR

Question # 150

For what purposes colons are used?

- All of the above

Correct Ans By AR

Question # 151

The name of the array is a constant pointer which contains the memory address of the of the array.

- first element

Correct Ans By AR



AR Lucky Term

Question # 152

In C/C++; by default arguments are passed by to a function.

-

Value

Correct Ans By **AR**

Question # 153

< , <= , > , >= are called operators.

-

Relational

Correct Ans By **AR**

Question # 154

char name [] = "Hello World" ; In the above statement, a memory of _____ characters will be allocated

-

12

Correct Ans By **AR**

Question # 155

While developing a program; should we think about the reusability?

-

Yes

Correct Ans By **AR**

Question # 156

C is widely known as development language of operating system.

-

Unix

Correct Ans By **AR**

Question # 157

Why we use "cin"?



AR Lucky Term

- To read data from keyboard
Correct Ans By **AR**

Question # 158

Loops are Structure

- Repetition
Correct Ans By **AR**

Question # 159

Which of the following function call is “call by reference” for the following

function prototype? `int add (int *);`

- `add(&x);`
Correct Ans By **AR**

Question # 160

If a function has not been declared before its definition, It is a

- None of these
Correct Ans By **AR**

Question # 161

While loop executes at least----

- one
Correct Ans By **AR**

Question # 162

A is a precise sequence of steps to solve a particular problem.

-



AR Lucky Term

Program

Correct Ans By AR

Question # 163

In while loop the loop counter must be initialized,

- Before entering the loop
Correct Ans By AR

Question No: 1 (Marks: 1) - Please choose one

A precise sequence of steps to solve a problem is called

▶ Statement

▶ Program

▶ Utility



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

► Routine

Question No: 2 (Marks: 1) - Please choose one

The Compiler of C language is written in

► Java Language

► UNIX

► FORTRON Language

► C Language

Question No: 3 (Marks: 1) - Please choose one

Initialization of variable at the time of definition is,

► Must

► Necessary



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

▶ Good Programming

▶ None of the given options

Question No: 4 (Marks: 1) - Please choose one

In if structure the block of statements is executed only,

▶ When the condition is false

▶ When it contain arithmetic operators

▶ When it contain logical operators

▶ When the condition is true

Question No: 5 (Marks: 1) - Please choose one

Which of the following function(s) is/are included in stdlib.h header file?



AR Lucky Term

- ▶ `double atof(const char *nptr)`
- ▶ `int atoi(const char *nptr)`
- ▶ `char *strcpy ( char *s1, const char *s2)`
- ▶ 1 and 2 only

Question No: 6 (Marks: 1) - Please choose one

Dealing with structures and functions passing by reference is the most economical method

▶ True

▶ False

Question No: 7 (Marks: 1) - Please choose one

Pointer is a variable which store,



AR Lucky Term

▶ Data

▶ Memory Address

▶ Data Type

▶ Values

Question No: 8 (Marks: 1) - Please choose one

Preprocessor program perform its function before _____ phase takes place.

▶ Editing

▶ Linking

▶ Compiling

▶ Loading

Question No: 9 (Marks: 1) - Please choose one



AR Lucky Term

Which of the following can not be a variable name?

▶ area

▶ _area

▶ 10area

▶ area2

Question No: 10 (Marks: 1) - Please choose one

Which looping process is best, when the number of iterations is known?

▶ for

▶ while

▶ do-while



AR Lucky Term

- ▶ all looping processes require that the iterations be known

Question No: 11 (Marks: 1) - Please choose one

Which character is inserted at the end of string to indicate the end of string?

- ▶ new line
- ▶ tab
- ▶ null
- ▶ carriage return

Question No: 12 (Marks: 1) - Please choose one

How many bytes are occupied by declaring following array of characters?
`char str[] = "programming";`



AR Lucky Term

▶ 10

▶ 11

▶ 12

▶ 13

Question No: 13 (Marks: 1) - Please choose one

Which of the following header file defines the rand() function?

▶ iostream.h

▶ conio.h

▶ [stdlib.h](#)

▶ stdio.h

Question No: 14 (Marks: 1) - Please choose one



AR Lucky Term

Commenting the code _____

- ▶ Makes a program easy to understand for others.
- ▶ Make programs heavy, i.e. more space is needed for executable.
- ▶ Makes it difficult to compile
- ▶ All of the given options.

Question No: 15 (Marks: 1) - Please choose one

What's wrong with this for loop?

```
for (int k = 2, k <=12, k++)
```

- ▶ the increment should always be ++k
- ▶ the variable must always be the letter i when using a for loop
- ▶ there should be a semicolon at the end of the statement



AR Lucky Term

▶ the commas should be semicolons

Question No: 16 (Marks: 1) - Please choose one

For which array, the size of the array should be one more than the number of elements in an array?

▶ int

▶ double

▶ float

▶ char

Question No: 1 (Marks: 1) - Please choose one

In C/C++ the string constant is enclosed

▶ In curly braces

▶ In small braces



AR Lucky Term

▶ In single quotes

▶ In double quotes

Question No: 2 (Marks: 1) - Please choose one

The size of int data type is

▶ 1 bytes

▶ 2 bytes

▶ 3 bytes

▶ 4 bytes

Question No: 3 (Marks: 1) - Please choose one

In Flow chart process is represented by

▶ Rectangle

▶ Arrow symbol

▶ Oval

▶ Circle



AR Lucky Term

Question No: 4 (Marks: 1) - Please choose one

If the break statement is missed in switch statement then,

- ▶ The compiler will give error
- ▶ This may cause a logical error
- ▶ No effect on program
- ▶ Program stops its execution

Question No: 5 (Marks: 1) - Please choose one

When we are using const keyword with a variable x then initializing it at the time of declaration is,

- ▶ Must
- ▶ Optional
- ▶ Not necessary
- ▶ A syntax error



AR Lucky Term

Question No: 6 (Marks: 1) - Please choose one

Which of the following is the correct way to assign an integer value 5 to element of a matrix say 'm' at second row and third column?

▶ $m[2][3] = 5 ;$

▶ $m[3][2] = 5 ;$

▶ $m[1][2] = 5 ;$

▶ $m[2][3] = '5';$

Question No: 7 (Marks: 1) - Please choose one

How many total elements must be in two-dimensional array of 3 rows and 2 columns?

▶ 4

▶ 5



AR Lucky Term

► 6

► 7

Question No: 8 (Marks: 1) - Please choose one

Which of the following is the correct statement for the following declaration?

`const int *ptr.`

► ptr is a constant pointer

ptr is constant integer pointer (Sorry format ► disable)

ptr is a constant pointer to ► int

ptr is a pointer to const ► int

Question No: 9 (Marks: 1) - Please choose one

Consider the following code segment. What will be the output of this code segment?



AR Lucky Term

```
int arr[6] = {2, 3, 7, 4, 5, 6} ;
```

```
int *ptr1 = &arr[1] ;
```

```
int *ptr2 = &arr[4] ;
```

```
cout << (ptr2-ptr1) ;
```

► 3

► 9

► 12

► 2

Question No: 10 (Marks: 1) - Please choose one

What will be the correct syntax to assign an array named arr of 5 elements to a pointer ptr?

► *ptr = arr ;



AR Lucky Term

ptr = arr ; ▶

*ptr = arr[5] ▶ ;

ptr = arr[5] ; ▶

Question No: 11 (Marks: 1) - Please choose one

C is a/an _____ language

low ▶ level

object based ▶

object ▶ oriented

function oriented ▶

Question No: 12 (Marks: 1) - Please choose one

.exe ▶

.txt ▶

.h ▶



AR Lucky Term

.c ►

Question No: 13 (Marks: 1) - Please choose one

The variables having a name, type and size are just like empty boxes.

False ►

True ►

Question No: 14 (Marks: 1) - Please choose one

What's wrong with this for loop?

```
for (int k = 2, k <=12, k++)
```

- the increment should always be ++k
- the variable must always be the letter i when using a for loop
- there should be a semicolon at the end of the statement
- the commas should be semicolons



AR Lucky Term

Question No: 15 (Marks: 1) - Please choose one

Most efficient method of dealing with structure variables is to define the structure globally

► True

False ►

What will be the size of following array?

`int arr[29];` Select correct option:

0

30 PAGE 105-106

29



AR Lucky Term

28

If a function has not been declared before its definition, It is a logical error

syntax error Lecture 9

run time

errorNone

of these

When the break statement is encountered in a loop's body, it transfers the control

_____ from the current

loop. Inside

Outside By using break the loop will terminate.

To break

statement To

continue

statement

When we access a multidimensional array, each array index is surrounded by

_____.



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Single quotes

' ' Double

quotes " "

Brackets [] Lecture 11

None of the given

char name [] = "Hello World"; In the above statement, a memory of _____ character will be allocated



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

13

11

12 Lecture 12

10

A variable declared within a code block becomes `_variable` for that

block.

Integer

Local Lecture 9

Global

If we pass more than one arguments to a function then they are separated by

_____.

Comma , Lecture 9

Semicolo

n ; Colon:

Brackets()



AR Lucky Term

The data type before a function name represents its,

Return Type

Lecture

9 Switch support

_____ Integer

Character

Both integer and character Lecture 8

None

Characters of a string stored in an array can be accessed directly using
array

.Manipulation

Superscript



AR Lucky Term

Subscript PAGE 123

Postscript

A variable declared within a code block becomes `_variable` for that block.

Integer

Local Lec

9Global

The data type before a function name represents its,

Return Type

Lec

9Function data

Function

arguments

Function name

If we pass more than one arguments to a function then they are separated by

Comma , Repeated



AR Lucky Term

Colon :

Semicolon ;

Double

quotes "

From following; which one is the correct syntax of an array initialize:
Array size is 10 and it is of double data type to value 0?

`arr[10] = {0.0};`

`double arr[10] = 0.0;`

`double arr[10] = {0.0};` Lec 12

`double arr[] = 0.0;`

In C/C++, by default arguments are passed by___to a function.

Value Lec 9



AR Lucky Term

Referen

ce

Prototyp

e

None of the given

By default, the starting index of an array in

C++ is

.2

-1

1

0 Lec 11

In call by reference,_____of a variable is passed to the called

function.Name

Data

type

Value



AR Lucky Term

Address PAGE 199

_ Keyword is used to return some value from a function.

Break Lec 9

Individual characters in a string stored in an array can be accessed directly using arrays subscript script

subscript PAGE 123

value

_____character is used to indicate the end of the string. New line

Blank space

Null PAGE

144E



AR Lucky Term

What will be the size of the array declared as int array[1000]; Select correct option:

999 Lec 11

1000

1001

1002

_____Keyword is used to return some value from

a function.

- continue

- break

- return

- goto

return Lec 9

From the following; which one is the correct syntax of an array declaration: array size is 5 and it is of float data type?

Select correct option:

- float [5]

- name;

- name[5]

- float; float

- name[5];

None of the given options It will be float name[4];



AR Lucky Term

What is the correct syntax to declare an array of 15 elements of type float? Select correct option:

float

array[15];

float[15]

array; float

[15]array;

float array[14]; Lec 11

If a function has not been declared before its definition, It is a Select correct option:
logical error

syntax error Lec 9

run time

error None

of these

In C/C++, by default arguments are passed by ___ to a function. Select correct option:
Reference

Value Lec 9



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Siz

e

Dat

a

From the following; which one is the range of Random number generator function rand()?

Select correct option:

0 – 32768

1 – 32768

0 – 32767 Lec 10

1 – 32767

Null character is represented by ___ in

C++.Select correct option:

/0

\0 PAGE 113

\n

\t

What is the correct syntax to declare an array of 15 elements

of type float? float array[15];

float[15]

array;float

[15]array;



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

None of these It will be float array[14];

What will be the output of following code

```
segment?for (int i = 2; i<10; i++)
```

```
{
```

```
if ( i ==
```

```
5)
```

```
continuu
```

```
e;
```

```
cout << i << "," ;
```

```
}
```

```
2,3,7,
```

```
8,
```



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

2,3,4,6,7,8,9

2,3,4

4,6,7,8,9

In C/C++; by default arguments are passed by_value to a function.

Value Repeated

Referen

ceType

Data

If a function has not been declared before its definition, It is a logical error

syntax error Repeated

run time

errorNone

of these

All elements of an array must be of __data



AR Lucky Term

type(s).char and int

Same Lecture 11

Different

float and double

What is the output of the following code, if the first

case is true switch (var)

```
{
```

```
case „a“:
```

```
cout<<”apple”<<e
```

```
ndl;
```



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

```
case „b“:
```

```
cout<<”banana”<<e
```

```
endl;case „m“:
```

```
cout<<”mango”<<e
```

```
endl; default:
```

```
cout<<”any fruit”<<endl;
```

```
}
```

```
apple
```

```
apple anyfruit
```

```
apple banana mango anyfruit
```

none of above There is no any break

statement. What will be the size of the

following character array?char name[] =

“Adeel”;

4

5

6



AR Lucky Term

7 Lec 12

_____statement is used to terminate the processing of a particular case and exit from switch structure.

if

got

o

break Lecture 8 (Repeated)

continue



AR Lucky Term

char name [] = "Hello World" ; In the above statement, a memory of ____ characters will be

allocated 10

11

12 Lecture 12 (Repeated)

13

1- Return type of a function that does not return any value must be

____.Char

Void Lecture 9

Int
voi
d

2- Null character is used to indicate the ____ of string. Start

End PAGE 114

Begi
n
midd
le

3- _____ will be used for enclosing function statements into a block. " "



AR Lucky Term

()

Lecture 9

[]

4- What is the output of the following code, if the

first case is true

```
switch(var) {
```

```
case „a“:
```

```
cout<<"apple"<<endl;
```

```
case „b“:
```

```
cout<<"banana"<<endl;
```



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

case „m“:

cout”mango”endl;

default: cout”any fruit”endl;

}

- Apple
- apple anyfruit
- apple banana mango anyfruit

• none of above Repeated

5- When we access a multidimensional array, each array index is surrounded by

_____.

- Single quotes ' '
- Double quotes " "

• Brackets [] Lecture 11

- Commas , ,

6- If an array has 50 elements, what is allowable range of subscripts?

• 0 – 49 Lecture 11

- 1 – 49
- 0 – 50
- 1 – 50



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

7- What will be the size of the array declared as `int array[1000];`

• 999 Repeated

- 1000
- 1001
- 1002

8- All elements of an array must be of ___ data type(s).

- char and int

• Same Repeated

- Different

9- If we pass more than one arguments to a function then they are separated by

_____.



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

• Comma , Lecture 9 (Repeated)

- Colon :
- semicolon

10- To manipulate n-dimensional array___nested loops are required.

- n-2

• n-1

- n+1
- n

Question No: 1(Marks: 1)- Please choose one

What is the output of the following statement?

`int i = 2.5; do { cout << i * 2; } while (i > 3 && i < 10);`

- (a) 510
- (b) 5
- (c) 48
- (d) error

Question No: 2(Marks: 1)- Please choose one

What does `!(7)` evaluate to in decimal where `!` is a NOT operator?

- (a) 7
- (b) 8
- (c) 9
- (d) 10



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Question No: 3(Marks: 1)- Please choose one

The condition in while loop may contain logical expression but not relational expression.

- (a) True
- (b) False

Question No: 4(Marks: 1)- Please choose one

Searching is easier when an array is already sorted

- (a) True
- (b) False

Question No: 5(Marks: 1)- Please choose one

If an array has 100 elements, what is allowable range of subscripts?

- (a) 0 - 99
- (b) 1 - 99
- (c) 0 - 100
- (d) 1 - 100

Question No: 6(Marks: 1)- Please choose one

What will be the value of 'a' and 'b' after executing the following statements?

a = 3;

b = a++;

- (a) 3, 4



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (b) 4, 4
- (c) 3, 3
- (d) 4, 3

Question No: 7(Marks: 1)- Please choose one

What will be the correct syntax to initialize all elements of two-dimensional array to value 0?

- (a) `int arr[2][3] = {0,0} ;`
- (b) `int arr[2][3] = {{0},{0}} ;`
- (c) `int arr[2][3] = {0},{0} ;`
- (d) `int arr[2][3] = {0} ;`

Question No: 8(Marks: 1)- Please choose one

Which of the following function returns the size of a string variable?

- (a) `strlen()`
- (b) `stringlen()`
- (c) `strlen()`
- (d) `strLength()`

Question No: 9(Marks: 1)- Please choose one

What will be the range of numbers generated by function `rand () % 9`?

- (a) 0 to 9
- (b) to 9
- (c) to 8
- (d) 1 to 8

Question No: 11 (Marks: 1) - Please choose one

Computer can understand only machine language code.

- (c) True



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

(d) False

Question No: 13 (Marks: 1) - Please choose one

What does $5 \wedge 6$, evaluate to in decimal where ‘ $\wedge$ ’ is Exclusive OR operator?

(a) True

(b) **F**

alse

Detail:-

It mean

5 = 0101

6 = 0110

$5 \wedge 6 = 0011$

If both input is same then the output is 0 and if different then output is 1

Question No: 14 (Marks: 1) - Please
choose one

If the file is not properly closed in the program, the program_____.



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (a) **Terminate normally**
- (b) Indicate Runtime error
- (c) Indicate Compile time error
- (d) Crashes

Question No: 15 (Marks: 1) - Please choose one

Which of the following header file include string conversion functions?

- (a) **string.h**
- (b) stdlib.h
- (c) ctype.h
- (d) sconvert.h

Question No: 1 (Marks: 1) - Please choose one

The function of cin is

- (a) To display message
- (b) **To read data from keyboard**
- (c) To display output on the screen
- (d) To send data to printer

Question No: 2(Marks: 1) - Please choose one

In C/C++ language the header file which is used to perform useful task and manipulation of character data is

- (a) cplext.h
- (b) **ctype.h**
- (c) stdio.h
- (d) delay.h

Question No: 3 (Marks: 1) - Please choose one

How many parameter(s) function getline() takes?

- (a) 0



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (b) 1
- (c) 2
- (d) 3

Question No: 4(Marks: 1) - Please choose one



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Word processor is

- (a) Operating system
- (b) **Application software**
- (c) Device driver
- (d) Utility software

Question No: 5

(Marks:

1) - Please choose one

For which values of the integer `_value` will the following code becomes an infinite loop?

```
int
number=1;
while
(true) {
    cout << number;
    if (number == 3)
        break; number +=
        integer_value; }
```

- (a) any number other than 1 or 2
- (b) only 0
- (c) only 1
- (d) only 2

Question No: 6

(Marks:

1) - Please choose one

Each pass through a loop is called a/an



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (a) enumeration
- (b) **Iteration**
- (c) culmination
- (d) pass through

Question No: 7 _____ (Marks:

1) - Please choose one _____

A continue statement causes execution to skip to

- (a) the return 0; statement
- (b) the first statement after the loop
- (c) the statements following the continue statement
- (d) the next iteration of the loop

Question No: 8 _____ (Marks:

1) - Please choose one _____

What is the correct syntax to declare an array of size 10 of int data type?

- (a) int [10] name ;
- (b) name[10] int ;
- (c) **int name[10] ;**



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

(d) `int name[] ;`

Question No: 9 (Marks:

1) - Please choose one

Consider the following code segment. What will the following code segment display?

```
int main(){  
int age[10] =  
{0};cout <<  
age ;  
}
```

- (a) Values of all elements of array
- (b) Value of first element of array
- (c) Starting address of array
- (d) Address of last array element

Question No: 10 (Marks:

1) - Please choose one

What will be the correct syntax to initialize all elements of two-dimensional array to value 0?

- (a) `int arr[2][3] = {0,0} ;`
- (b) `int arr[2][3] = {{0},{0}} ;`
- (c) `int arr[2][3] = {0},{0} ;`
- (d) `int arr[2][3] = {0} ;`

Question No: 11 (Marks:

1) - Please choose one

How many bytes will the pointer *intPtr* of type `int` move in the following statement?



AR Lucky Term

`intPtr += 3 ;`

- (a) 3 bytes
- (b) 6 bytes
- (c) 12 bytes
- (d) 24 bytes

Question No: 12

(Marks:

1) - Please choose one

If there are $2^{(n+1)}$ elements in an array then what would be the number of iterations required to search a number using binary search algorithm?

- (a) n elements
- (b) $n+1$ elements
- (c) $2(n+1)$ elements
- (d) $2^{(n+1)}$ elements



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Question No: 13 (Marks: 1) - Please choose one

Which of the following operator is used to access the value of variable pointed to by a pointer?

- (a) * operator
- (b) -> operator
- (c) && operator
- (d) & operator

Question No: 14 (Marks: 1) - Please choose one

The _____ statement interrupts the flow of control.

- (a) switch
- (b) continue
- (c) goto
- (d) break

Question No: 15 (Marks: 1) - Please choose one

Analysis is the-----step in designing a program

- (a) Last
- (b) Middle
- (c) Post Design
- (d) First

Question No: 16 (Marks: 1) - Please choose one



AR Lucky Term

Paying attention to detail in designing a program is ____

- (a) Time consuming
- (b) Redundant
- (c) Necessary
- (d) Somewhat GoodQ1

When the if statement consists more than one statement then enclosing these



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

statement in curly braces is,

- (a) Not required
- (b) Good programming
- (c) Relevant
- (d) **Must**

Q2

The while loop becomes infinite,

- (a) When the condition is always false
- (b) . When the condition is less than zero
- (c) **When the condition is always true**
- (d) When the condition contains a logical operator

Q3

Which of the following function(s) is/are included in stdlib.h header file?

- (a) double atof(const char *nptr)
- (b) int atoi(const char *nptr)
- (c) char *strcpy (char *s1, const char *s2)
- (d) **1 and 2 only**

Q4

If we want to store a string “abc” in an array str then the size of this array must be at least,

- (a) **2**
- (b) 3
- (c) 4
- (d) 5

Q5



AR Lucky Term

No executable code will be generated if error is found during translation of the program using interpreter.

- (a) True
- (b) False

Q6

Word processor is

- (a) Operating system
- (b) Application software
- (c) Device driver
- (d) Utility software

Q7

Which of the following is the correct syntax to print multiple values or variables in



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

a single command using cout?

(a) `cout << "Hello" + x + "\n";`

(b) `cout << "H" << x << "\n";`

(c) `cout << "H", x, "\n";`

(d) `cout << ("H" & x & "\n");`

Q8

Which of the following is correct way to initialize a variable x of int type with value 10?

(a) `int x ; x = 10 ;`

(b) `int x = 10 ;`

(c) `int x, x = 10;`

(d) `x = 10 ;`

Q9

If there is more than one statement in the block of a for loop, which of the following must be placed at the beginning and the ending of the loop block?

(a) parentheses ()

(b) braces { }

(c) brackets []

(d) arrows < >

Q10

Name of an array is a constant pointer.

(a) True

(b) False

Q11



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

How many bytes will the pointer *intPtr* of type `int` move in the following statement?

```
intPtr += 3  
;
```

- (a) 3 bytes
- (b) 6 bytes
- (c) 12 bytes
- (d) 24 bytes

Q12

What will be the value of 'a' and 'b' after executing the following statements?

```
a = 3;  
b = a++;
```

(a) 3, 4

(b) 4, 4



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (c) 3, 3
- (d) 4, 3

Q13

Loader loads the executable code from hard disk to main memory.

- (a) True
- (b) False

Q14

Which of the following is used with bit manipulation?

- (a) Signed integer
- (b) Un-signed integer
- (c) Signed double
- (d) Un-signed double

Q15

Which of the following values C++ use to represent true and false?

- (a) 1 and 0
- (b) 1 and -1
- (c) 11 and 00
- (d) Any numerical value

Q16

The argument of the isdigit() function is _____

- (a) a character,
- (b) a C-string,
- (c) a C++ string class variable
- (d) None of the given options.

Question No: 1

(Marks:



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

1) - Please choose one

A precise sequence of steps to solve a problem is called

- ▶ Statement
- ▶ Program
- ▶ Utility
- ▶ Routine

Question No: 2

(Marks:

1) - Please choose one

The Compiler of C language is written in

- ▶ Java Language
- ▶ UNIX
- ▶ FORTRON Language
- ▶ C Language

Question No: 3

(Marks:

1) - Please choose one

Initialization of variable at the time of definition is,

- ▶ Must
- ▶ Necessary
- ▶ Good Programming
- ▶ None of the given options

Question No: 4

(Marks:

1) - Please choose one

In if structure the block of statements is executed only,

- ▶ When the condition is false
- ▶ When it contain arithmetic operators
- ▶ When it contain logical operators
- ▶ When the condition is true

Question No: 5

(Marks:



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

1) - Please choose one

Which of the following function(s) is/are included in stdlib.h header file?

- ▶ double atof(const char *nptr)
- ▶ int atoi(const char *nptr)
- ▶ char *strcpy (char *s1, const char *s2)
- ▶ 1 and 2 only

Question No: 6

(Marks:

1) - Please choose one

Dealing with structures and functions passing by reference is the most economical method

- ▶ True
- ▶ False

Question No: 7(Marks: 1) - Please choose one



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Pointer is a variable which store,

- ▶ Data
- ▶ Memory Address
- ▶ Data Type
- ▶ Values

Question No: 8 (Marks:

1) - Please choose one

Preprocessor program perform its function before phase takes place.

- ▶ Editing
- ▶ Linking
- ▶ Compiling
- ▶ Loading

Question No: 9 (Marks:

1) - Please choose one

Which of the following can not be a variable name?

- ▶ area
- ▶ _area
- ▶ 10area
- ▶ area2

Question No: 10 (Marks:

1) - Please choose one

Which looping process is best, when the number of iterations is known?

- ▶ for
- ▶ while
- ▶ do-while
- ▶ all looping processes require that the iterations be known

Question No: 11 (Marks:



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

1) - Please choose one

Which character is inserted at the end of string to indicate the end of string?

- ▶ new line
- ▶ tab
- ▶ **null**
- ▶ carriage return

Question No: 12

(Marks:

1) - Please choose one

How many bytes are occupied by declaring following array of characters?
char str[] = "programming";

- ▶ 10
- ▶ 11
- ▶ 12
- ▶ 13

Question No: 13

(Marks: 1) - Please choose one



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Which of the following header file defines the rand() function?

- ▶ iostream.h
- ▶ conio.h
- ▶ **stdlib.h**
- ▶ stdio.h

Question No: 14

(Marks:

1) - Please choose one

Commenting the code _____

- ▶ Makes a program easy to understand for others.
- ▶ Make programs heavy, i.e. more space is needed for executable.
- ▶ Makes it difficult to compile
- ▶ All of the given options.

Question No: 15

(Marks:

1) - Please choose one

What's wrong with this

for loop? for (int k = 2, k
<=12, k++)

- ▶ the increment should always be ++k
- ▶ the variable must always be the letter i when using a for loop
- ▶ there should be a semicolon at the end of the statement
- ▶ **the commas should be semicolons**

Question No: 16

(Marks: 1) - Please choose one

For which array, the size of the array should be one more than the number of elements in an array?

- ▶ int
- ▶ **double**
- ▶ float
- ▶ char



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Q1

In C/C++ the string constant is enclosed

- (a) In curly braces
- (b) In small braces
- (c) In single quotes
- (d) In double quotes

Q2

In flow chart, the symbol used for decision making is,

- a) Rectangle
- b) Circle
- c) Arrow
- d) Diamond

Q3

The data type before a function name represents its,



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (a) Return Type
- (b) Function data
- (c) Function arguments
- (d) Function name

Q4

The operator used to take the address of a variable is,

- (a) &&
- (b) ++
- (c) —
- (d) &

Q5

The header file which is used for input and output is

- (a) maths.h
- (b) string.h
- (c) iostream.h
- (d) ctype.h

Q6

When we are using command line argument(s), the default argument in C/C++ is/are__.

- a) argc
- b) argd
- c) argv
- d) argc and argv

Q7

In C++, Integer calculation occurs in bytes.

- a) 1 byte
- b) 2 bytes
- c) 4 bytes
- d) 8 bytes

Q8



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

In the declaration of two dimensional array,

- (a) First index represents row and second represents column
- (b) First index represents column and second represents row
- (c) Both indexes represent rows
- (d) Both indexes represent column

Q9

The address operator (&) can be used with,

- a) Statement
- b) Expression
- c) Variable
- d) Constant

Q10

_____ translates high level language program into machine language code

- (a) Debugger



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (b) Editor
- (c) **Compiler**
- (d) L

inkerQ11

Which of the following data type(s) can operate on modulus operator '%'?

- a) **float, int**
- b) float, double
- c) int
- d) cha

rQ12

What will be the result of the expression $z = x \% y$, if $x = 19$ and $y = 4$?

- a) **3**
- b) 4
- c) 15
- d) 1

9Q13

Which character is inserted at the end of string to indicate the end of string?

- a) new line
- b) tab
- c) **null**
- d) carriage

returnQ14

What will be the value of i and j in the following code segment?

```
int i, j ;  
int x[5] = {2, 3, 4, 8, 9} ;  
int *ptr  
=&x[2]; i =  
(*ptr)++ ;  
j = *ptr++ ;
```



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

a) $i = 5, j = 5$

b) $i = 5, j = 8$

c) $i = 4, j = 8$

d) $i = 5, j = 9$

Q15

Syntax of union is identical to _

a) **Structure**

b) Class

c) Function

d) None of the given options

Q1

What is function of cout ?

(a) To send data to printer

(b) To read data from keyboard

(c) To display message

(d) **To display output on the screen**

Q2

In Flow chart process is represented by

(a) **Rectangle**

(b) Arrow symbol

(c) Oval

(d) Circle

Q3

&& is ----- operator.

(a) An arithmetic

(b) **Logical**

(c) Relational

(d) Unary



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Q4



AR Lucky Term

An over Flow condition occurs when we try to assign a value to a variable which is,

- (a) Less than its maximum size
- (b) Greater than its maximum size
- (c) With in its range
- (d) Equal to its size

Q5

For dereferencing an array element using pointer, we use the operator

- (a) &
- (b) *
- (c) /
- (d) +

Q6

In the declaration of two dimensional array,

- (a) First index represents row and second represents column
- (b) First index represents column and second represents row
- (c) Both indexes represent rows
- (d) Both indexes represent column

Q7

Which of the following data type(s) can operate on modulus operator ‘%’?

- (a) float, int
- (b) float, double
- (c) int
- (d) char

Q8

Which of the following is the correct way to declare a variable x of integer type?

- (a) x int ;
- (b) integer x ;



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

(c) `int x;`

(d) x integer

Q9

Which of the following can not be a variable name?

(a) area

(b) _area

(c) 10area

(d) a

rea2Q10

Which of the function call is *call by value* for the following function prototype? `float area (int);`

(a) `area(&num);`

(b) `area(num);`

(c) `area(int num);`

(d) `area(*`

`num);` Q11

Recursive functions are used when there is a repetitive pattern.

(a) True



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

(b) F

alsoQ12

What will be the range of numbers generated by function `rand () % 9`?

(a) 0 to 9

(b) 1 to 9

(c) 0 to 8

(d) 1

to 8Q13

What will be the correct syntax to declare two-dimensional array of float datatype?

(a) `float arr{2}{2} ;`

(b) `float arr[2][2] ;`

(c) `float arr[2,2] ;`

(d) `float[2]`

`[2] arr ;`Q14

When a function finishes its execution then,

(a) The control return to its Prototype

(b) The control returns to its definition

(c) Control returns to statement following function call

(d) The compiler stop execution of

whole programQ15

Consider the following statements to initialize a two-dimensional array.

i. `int arr[2][3] = {4, 8, 9, 2, 1, 6} ;`

ii. `int arr[3][2] = {4, 8, 9, 2, 1, 6} ;`

iii. `int arr[][2] = {{4,8},{9, 2},{1, 6}} ;`

Which of the following option(s) are correct to initialize a two-dimensional array with 3 rows and 2 columns?

(a) (ii) only

(b) (iii) only



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

(c) (ii) and (iii)

(d) (i) and

(iii)Q16

Editors are used to compile the code.

(a)True

(b) **False**

Q1

What is function of cout ?

(a)To send data to printer

(b) To read data from keyboard

(c)To display message

(d) **To display output on the screen**

Q2

< , <= , > , >= are called -----operators.



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (a) Logical
- (b) Arithmetic
- (c) Relational
- (d) Conational

Q3

In while loop the loop counter must be initialized,

- (a) With in the loop
- (b) Before entering the loop
- (c) At the end of the loop
- (d) None of the given options

Q4

Data Size of the file is always_____the actual size of the file.

- (a) Greater than
- (b) Equal to
- (c) Less than or equal to
- (d) None of the above

Q5

The precedence of * is higher than dot operator (.)operator

- (a) True
- (b) False

Q6

Let ptr1 and ptr2 are pointer variables that points to integer data type then whichone of the following arithmetic is allowed,

- (a) $\text{ptr1} + \text{ptr2}$
- (b) $\text{ptr1} - \text{ptr2}$
- (c) $\text{ptr1} * \text{ptr2}$
- (d) $\text{ptr1} / \text{ptr2}$

Q7

Word processor is

- (a) Operating system
- (b) Application software



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (c) Device driver
- (d) Utility software

Q8

What will be the range of numbers generated by function `rand () % 9`?

- (a) 0 to 9
- (b) 1 to 9
- (c) 0 to 8
- (d) 1 to 8

Q9

How many bytes will the pointer *intPtr* of type `int` move in the following statement?

```
intPtr += 3 ;
```

- (a) 3 bytes
- (b) 6 bytes
- (c) 12 bytes



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

(d) 24

bytesQ10

What will be the correct syntax to assign an array named *arr* of 5 elements to a pointer *ptr*?

(a) `*ptr = arr ;`

(b) `ptr = arr ;`

(c) `*ptr = arr[5] ;`

(d) `ptr =`

`arr[5] ;`Q11

What will be the output of the following code segment?

```
char *x = "programming" ;
```

```
cout << *(x+2) << *(x+3) << *(x+5) << *(x+8) ;
```

(a)prgm

(b) rorm

(c)ogai

(d) r

amgQ12

There is a pointer variable named *ptr* of type `int` then address of which type of variable the *ptr* will store in it?

(a) variable of type `char`

(b) variable of type `short`

(c) variable of type `int`

(d) variable of

type `double`Q13

Flow charts explain the working of a program in pictorial format.

(a) True

(b) F

alseQ14

The object _____ may be used both for file input and file output



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (a) fstream,
- (b) ifstream,
- (c) ofstream,
- (d) none of the given

options. Q15

Most efficient method of dealing with structure variables is to define the structure globally

- (a) True
- (b) F

also Q16

If a variable is passed by value to a function and the function makes some changes to that variable then it

- (a) does not affect the original variable
- (b) affects the original variable
- (c) causes syntax error
- (d) None of the given options

Q1

In C/C++ language the header file which is used to perform useful task and manipulation of character data is

- (a) cplex.h
- (b) ctype.h
- (c) stdio.h
- (d) delay.h

Q2

The header file which is used for input and output is

- (a) maths.h
- (b) string.h
- (c) iostream.h



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

(d) ctype.h

Q3

Suppose `int multi[5][10]`; when we are using `**multi`, it means,

(a) Single dereferencing

(b) Single referencing

(c) Double referencing

(d) Double dereferencing

Q4

To access the data members of structure ____ is used.

(a) dot operator (.)

(b) * operator

(c) □ operator

(d) one of given.

Q5

The precedence of * is higher than dot operator (.) operator

(a) True

(b) False

Q6

Which of the following is the starting index of an array in C++?

(a) 0

(b) 1

(c) -1

(d) any number

Q7

When a call to function statement is encountered,

(a) The control transfers to its Prototype

(b) The control transfers to its definition

(c) Control returns to statement following function call

(d) The compiler stops execution of whole program

Q8

A function must always return value.



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (a) True
- (b) False

Q9

If an array has 100 elements, what is allowable range of subscripts?

- (a) 0 – 99
- (b) 1 – 99

(c) 0 – 100

- (d) 1 –

100Q10

If a pointer appears on left hand side of an assignment operator then right side of that assignment operator must be,

- (a) Variable name
- (b) Address of variable
- (c) Variable value
- (d) Constant



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Q11

Editors are used to compile the code.

- (a) True
- (b) False

Q12

Which bitwise operator returns false if both bits are 1?

- (a) AND
- (b) XOR
- (c) NOT
- (d) OR

Q13

What does !(7) evaluate to in decimal where ! is a NOT operator?

- (a) 7
- (b) 8
- (c) 9
- (d) 1

Q14

Structures cannot be passed as Function Parameters

- (a) True
- (b) False

Q15

When break statement is encountered in a loop body it,

- (a) Transfers the control outside from current loop
- (b) Transfers the control outside from current program
- (c) Enforces the next iteration of loop
- (d) Generates compile

time error.

Q16
A union is a user-defined data type that contains only__from its list of members at a time.



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (a) One object
- (b) Two objects
- (c) Three objects
- (d) None of the given options

Q1

The size of int data type is

- (a) 1 bytes
- (b) 2 bytes
- (c) 3 bytes
- (d) 4 bytes

Q2

When the logical operator AND (&&) combine two expressions exp1 and exp2 then the result will be true only,

- (a) When both exp1 and exp2 are true
- (b) When both exp1 and exp2 are false
- (c) When exp1 is true and exp2 is false
- (d) When exp1 is false and exp2 is true

Q3

The correct syntax of do-while loop is,

- (a) (condition) while; do { statements; };
- (b) { statements; } do-while ();
- (c) while(condition); do { statements; };
- (d) do { statements; } while (condition);

Q4

_____ provide communication channels between files and program.

- (a) Streams
- (b) Language like C++
- (c) Function seekg()
- (d) None of the above

Q5



AR Lucky Term

All elements of an array must be of,

- (a) different data type
- (b) float data only
- (c) character data only
- (d) same data type

Q6

Function seekg() takes_____parameter(s).

- (a) 0
- (b) 1
- (c) 2
- (d) 3

Q7

Structures help to define program-specific_.

- (a) functions



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (b) datatypes
- (c) Arithmetic operations
- (d) None of the given options.

Q8

In the declaration of two dimensional array,

- (a) First index represents row and second represents column
- (b) First index represents column and second represents row
- (c) Both indexes represent rows
- (d) Both indexes represent column

Q9

What will be the result of arithmetic expression $6 + 27/3 * 3$?

- (a) 33
- (b) 45
- (c) 9
- (d) 3

Q10

Which of the function call is *call by value* for the following function prototype?

float area (int);

- (a) area(&num) ;
- (b) area(num) ;
- (c) area(int num) ;
- (d) area(*

num) ;

Q11
How many bytes are occupied by declaring following array of characters?

char str[] = "programming";

- (a) 10
- (b) 11



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

(c) 12

(d) 1

3Q12

What will be the correct syntax to assign an array named *arr* of 5 elements to a pointer *ptr*?

(a) `*ptr = arr ;`

(b) `ptr = arr ;`

(c) `*ptr = arr[5] ;`

(d) `ptr =`

`arr[5] ;`Q13

Let *ptr1* and *ptr2* are pointer variables then which of the following arithmetic operation is allowed on pointers?

(a) Addition

(b) Subtraction

(c) Multiplication

(d) All of the above

Q14

The variables having a name, type and size are just like empty boxes.



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

(a) True

(b) F

also Q15

When break statement is encountered in a loop body it,

(a) Transfers the control outside from current loop

(b) Transfers the control outside from current program

(c) Enforces the next iteration of loop

(d) Generates compile

time error. Q16

If two programs a and b are trying to open a file xyz.txt at approximately same time then

(a) Both programs will generate error

(b) One of them will succeed in opening that file and other will fail

(c) Both programs will open the file

(d) One of the program

will re-start

Q1

The data type of size one byte is

(a) char

(b) int

(c) long

(d) double

Q2

If Num is an integer variable then Num*= 4; means,

(a) Multiply Num 4 times

(b) Multiply 4 with Num and display

(c) Multiply 4 with Num and assign the result to Num



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

(d) Add 4 with Num

Q3

Member function tellg() returns the current location of the ____ pointer.

(a) tellptr()

(b) write()

(c) seekg()

(d) get()

Q4

If we want to store a string “abc” in an array str then the size of this array must be at least,

(a) 2

(b) 3

(c) 4

(d) 5

Q5

Pointer is a variable which stores,

(a) Values

(b) Data

(c) Memory Address

(d) Data Type

Q6

C is widely known as development language of operating system.

(a) Linux

(b) Windows

(c) Unix

(d) Mac

OSQ7

C++ is a case-sensitive language

(a) True

(b) False



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Q8 What is the output of the following code?

```
for (int a = 1; a <= 1; a++) cout << a++; cout << a;
```

- (a) 22
- (b) 12
- (c) 23
- (d) 13

Q9

A continue statement causes execution to

skip to (a) the return 0; statement

(b) the first statement after the loop

(c) the statements following the continue

statement (d) the next iteration of the loop

Q10

If there is more than one statement in the block of a for loop, which of the following must be placed at the beginning and the ending of the loop block?

(a) parentheses ()

(b) braces { }

(c) brackets []

(d) arro

ws < > Q11

What will be the correct syntax for the following function call?

```
float square (int  
    &);
```

(a) square (int num);

(b) square (&num);

(c) square (num);

(d) square

(*num); Q12

Which of the following is the correct way to assign an integer value 5 to element of a matrix say 'm' at second row and third



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

column?

(a) $m[2][3] = 5$;

(b) $m[3][2] = 5$;

(c) $m[1][2] = 5$;

(d) $m[2][3]$

= '5'; Q13

How many dimensions does n-dimensional array has?

(a) **n dimensions**

(b) $2n$ dimensions

(c) $(n+1)$ dimensions

(d) $(n-1)$

dimensions Q14

Consider the following code segment. What will be the output of following code?

```
int addValue (int  
*a){ int b = (*a) +  
2; return b ;
```



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

```
}  
main ()  
{int x  
=6 ;  
cout << x << “,” ;  
cout << addValue(&x)  
<< “,” ;cout << x ;  
}
```

(a) 6,8,6

(b) 6,6,8

(c) 6,8,8

(d)

6,6,6Q15

If most significant bit of un-signed number is 1 then it represents a positive number.

(a) True

(b) F

alsoQ16

When we declare a multidimensional array the compiler store the elements of multidimensional array in the form of,

(a) Contiguous memory location

(b) Matrix

(c) Columns

(d) R

ows

Q1

What is function of cout ?

(a) To send data to printer

(b) To read data from keyboard

(c) To display message



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (d) To display output on the screen

Q2

For one byte there are ___ combinations of values that can be stored in computer.

- (A) 2^6
- (B) 2^7
- (C) 2^8
- (D) 2^4

Q3

_____ provide communication channels between files and program.

- (a) Streams
- (b) Language like C++
- (c) Function seekg()
- (d) None of the above

Q4

The data type before a function name represents its,

- (a) Return Type
- (b) Function data
- (c) Function arguments
- (d) Function name

Q5

In C/C++ language when an array is passed to a function then by default its passing mechanism is,

- (a) Call by value
- (b) Call by Reference
- (c) It depends on type of array
- (d) It depends on the return type of function.

Q6

Array is a data structure which store

- (a) Memory addresses
- (b) Variables



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

(c) Data Type

(d) Data

Q7

If there is more than one statement in the block of a for loop, which of the following must be placed at the beginning and the ending of the loop block?



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (a) parentheses ()
- (b) braces { }
- (c) brackets []
- (d) arrows < >

Q8

Array is passed by value to a function by default.

- (a) True
- (b) False

Q9

Which of the following is the correct function call having array named *student* of 10 elements as a parameter.

- (a) addRecord(student[]);
- (b) addRecord(student);
- (c) addRecord(student[10]);
- (d) addRecord(*student);

Q10

What will be the correct syntax for initialization of pointer *ptr* of type int with variable *x*?

- (a) int ptr = &x;
- (b) int ptr = x;
- (c) int *ptr = &x;
- (d) int

ptr* = &x ;

Q11
What will be the correct syntax for initialization of pointer *ptr* with string "programming"?

- (a) char ptr = 'programming' ;
- (b) char *ptr = "programming" ;
- (c) char *ptr = 'programming' ;
- (d) *ptr =

"programming" ;

Q12
The condition in while loop may contain logical expression but



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

not relational expression.

(a) True

(b) F

also Q13

We want to access array in random order which approach is better?

(a) Pointers

(b) Array index

(c) Both pointers and array index are better

(d) None of the

given options. Q14

Single line comments explaining code would be preceded like in the following example.

(a) /*

(b) //

(c) /



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

(d)

/*Q15

Function write() takes _____ as parameter(s).

- (a) String of pointer type
- (b) String and no. of bytes to be written
- (c) Pointer array of characters and delimiter
- (d) String of variable lengths, no. of bytes to be read and flags

Q16

Structure is a collection of _____ under a single name.

- (a) Only Functions
- (b) Only Variables
- (c) Both Functions and Variables
- (d) None of the

given options

Q1

Compiler is a

- (a) System software
- (b) Application Software
- (c) Driver
- (d) Editor

Q2

In while loop the loop counter must be initialized,

- (a) With in the loop
- (b) Before entering the loop
- (c) At the end of the loop
- (d) None of the given options

Q3

If Num is an integer variable then $\text{Num} *= 4;$ means,



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (a) Multiply Num 4 times
- (b) Multiply 4 with Num and display
- (c) Multiply 4 with Num and assign the result to Num
- (d) Add 4 with Num

Q4

In C/C++ ,the arguments are passed by__to a function by default .

- (a) reference
- (b) value
- (c) data
- (d) type

Q5

Disks is divided into_____with power of_____.

- (a) Chunks, 2^n
- (b) Blocks, n^2
- (c) Blocks, 2^n
- (d) Chunks, n^2

Q6

C is widely known as development language of _operating system.

- (a) Linux
- (b) Windows
- (c) Unix
- (d) Mac OS

Q7

Assignment operator '=' is a

- (a) Unary operator



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (b) Binary operator
- (c) Ternary operator
- (d) None of the given options

Q8

Consider the following code segment. What will be the output of the following program?

```
int func(int)
; int num =
10 ;
```

```
int
main(){
int num ;
num = 5
;
```

```
cout << num ;
```

```
cout << func(num) ;
```

```
}
```

```
int func(int
x){return
num ;
}
```

(a) 5, 5



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (b) 10, 5
- (c) 5, 10
- (d) 10, 10

Q9

Name of an array is a constant pointer.

- (a) True
- (b) F

also Q10

What will be the correct syntax to assign an array named *arr* of 5 elements to a pointer *ptr*?

- (a) `*ptr = arr ;`
- (b) `ptr = arr ;`
- (c) `*ptr = arr[5] ;`
- (d) `ptr =`

`arr[5] ;` Q11

If there are $2^{(n+1)}$ elements in an array then what would be the number of iterations required to search a number using binary search algorithm?

- (a) n elements
- (b) $(n+1)$ elements
- (c) $2(n+1)$ elements
- (d) $2^{(n+1)}$

elements Q12

In C/C++, null character is represented as

- (a) `\n`
- (b) `\0`



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

(c) \t

(d) \

rQ13

How many nested loop would be required to manipulate n-dimensional array?

(a) $2n$

(b) **n**

(c) $n + 1$

(d) n

-1Q14

What will be the correct syntax to access the value of fourth element of an array using pointer ptr?

(a) **ptr[3]**

(b) (ptr+3)

(c) *(ptr+3)

(d) Both

1and 3Q15

Single line comments explaining code would be preceded like in the following example.

(a) /*

(b) **//**

(c) /

(d)

/*Q16

If a variable is passed by value to a function and the function makes some changes to that variable then it

(a) **does not affect the original variable**

(b) affects the original variable

(c) causes syntax error

(d) None of the

given options

Q1



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

There are mainly-----types of software

- (a) Two
- (b) Three
- (c) Four
- (d) Five

Q2

$<$, $<=$, $>$, $>=$ are called -----operators.

- (a) Logical
- (b) Arithmetic
- (c) Relational
- (d) Conational

Q3

In order to get 256 from the number 2568 we divide this number by 10 and take,

- (a) Its remainder
- (b) The number
- (c) Its quotient
- (d) Its divisor

Q4



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

If `int x = 10;` then the value of `x/= 3;` will be,

- (a) 10
- (b) 3
- (c) 13
- (d) 1

Q5

How many parameter(s) function `getline()` takes?

- (a) 0
- (b) 1
- (c) 2
- (d) 3

Q6

Suppose `int multi[5][10];` when we are using `**multi`, it means,

- (a) Single dereferencing
- (b) Single referencing
- (c) Double referencing
- (d) Double dereferencing

Q7

To access the data members of structure ____ is used.

- (a) dot operator (.)
- (b) * operator
- (c) □ operator
- (d) None of given.

Q8

There is NO difference between bitwise AND operator (&) and Logical AND(&&) operator.

- (a) True
- (b) False

Q9

Which of the following data type(s) can operate on modulus operator '%'?

- (a) float, int



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

(b) float, double

(c) int

(d) c

harQ10

What's wrong with this

while loop? while((i < 10)

&& (i > 24))

(a) the logical operator && cannot be used in a test condition

(b) the while loop is an exit-condition loop

(c) the while loop is an exit-condition loop

(d) the test condition is

always trueQ11

The switch structure is a _____ construct

(a) single-selection

(b) bi-selection



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

(c) multiple-selection

(d) uncon

ditionalQ12

Keyword 'array' must be used to declare an array.

(a) True

(b) F

alseQ13

What will be the correct syntax to declare two-dimensional array of float datatype?

(a) float arr{2}{2} ;

(b) float arr[2][2] ;

(c) float arr[2,2] ;

(d) float[2]

[2] arr ;Q14

When an array element is passed to a function then this array element is passed to the function,

(a) By reference

(b) By data type

(c) By value

(d) B

y dataQ15

Which of the following operator is used to access the value of variable pointed to by a pointer?

(a) * operator

(b) -> operator

(c) && operator

(d) & operator

Q16

Paying attention to detail in designing a program is _

(a) Time consuming

(b) Redundant



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (c) Necessary
- (d) Somewhat Good

Q1

The remainder (%) operator is

- (a) A logical operator
- (b) An arithmetic operator
- (c) A relational operator
- (d) A division operator

Q2

If `int sum = 10;` then the value of the statement `sum = sum + 3 ;` is ,

- (a) 7
- (b) Illegal statement
- (c) Garbage value
- (d) 13

Q3

Which of the following function(s) is/are included in `ctype.h` header file?

- (a) `isdigit(int c)`
- (b) `isxdigit(int c)`
- (c) `tolower(int c)`
- (d) All of the above

Q4

In C/C++ which of the following header file is used for string manipulation?

- (a) `stdlib.h`
- (b) `string.h`



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (c) strings.h
- (d) stype.h

Q5

_____ provide communication channels between files and program.

- (a) Streams
- (b) Language like C++
- (c) Function seekg()
- (d) None of the above

Q6

_____ translates high level language program into machine language code

- (a) Debugger
- (b) Editor
- (c) Compiler
- (d) Linker

Q7

Which of the following data type(s) can operate on modulus operator ‘%’?

- (a) float, int
- (b) float, double
- (c) int
- (d) char

Q8

C++ is a case-sensitive language

- (a) True
- (b) False

Q9

To include code from the library in the program, such as iostream, a directive would be called up using this command.

- (a) #include “iostream.h”
- (b) include <iostream.h>
- (c) include <iostream.h>



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

(d) `#include`
`<iostream.h>` Q10

What will be the range of numbers generated by function `rand () % 9`?

- (a) 0 to 9
- (b) 1 to 9
- (c) 0 to 8
- (d) 1

to 8 Q11

An array stores the numbers into consecutive memory locations.

- (a) True
- (b) F

also Q12

Which of the following is the correct statement for the following declaration? `const int *ptr`.

- (a) `ptr` is a constant pointer
- (b) `ptr` is constant integer pointer



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

(c) ptr is a constant pointer to int

(d) ptr is a constant

pointer to intQ13

Which of the following header file defines the rand() function?

(a) iostream.h

(b) conio.h

(c) **stdlib.h**

(d) s

tdio.hQ14

Consider the following code segment. What will be the output of following code?

```
int addValue (int
```

```
*a){ int b = (*a) +
```

```
2; return b ;
```

```
}
```

```
main ()
```

```
{ int x
```

```
=6 ;
```

```
cout << x << “,” ;
```

```
cout << addValue(&x)
```

```
<< “,” ;cout << x ;
```

```
}
```

(a) **6,8,6**

(b) 6,6,8

(c) 6,8,8

(d)

6,6,6Q15

Identifier is a name that can be given to variables, labels and functions.

(a) **True**

(b) F

alseQ16



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

For which array, the size of the array should be one more than the number of elements in an array?

- (a) Int
- (b) Char
- (c) Double
- (d) float

Q1

In C/C++ language the header file which is used to perform useful task and manipulation of character data is

- (e) cplex.h
- (f) ctype.h
- (g) stdio.h
- (h) delay.h

Q2

The header file which is used for input and output is

- (e) maths.h
- (f) string.h
- (g) iostream.h
- (h) ctype.h

Q3

Suppose `int multi[5][10];` when we are using `**multi`, it means,

- (e) Single dereferencing
- (f) Single referencing
- (g) Double referencing
- (h) Double dereferencing

Q4

To access the data members of structure ____ is used.

- (e) dot operator (.)
- (f) * operator
- (g) □ operator
- (h) None of given.



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Q5

The precedence of * is higher than dot operator (.)operator

(c) **True**

(d) False

Q6

Which of the following is the starting index of an array in C++?

(e) **0**

(f) 1

(g) -1

(h) any number

Q7

When a call to function statement is encountered,

(e) **The control transfers to its Prototype**

(f) The control transfers to its definition

(g) Control returns to statement following function call

(h) The compiler stops execution of whole program

Q8

A function must always return value.



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (c) True
- (d) **False**

Q9

If an array has 100 elements, what is allowable range of subscripts?
(e) 0 – 99
(f) 1 – 99

(g) 0 – 100

(h) 1 –

100Q10

If a pointer appears on left hand side of an assignment operator then right side of that assignment operator must be,

- (e) Variable name
- (f) **Address of variable**
- (g) Variable value
- (h) Co

nstantQ11

Editors are used to compile the code.

- (c) True
- (d) **False**

Q12

Which bitwise operator returns false if both bits are 1?

- (e) AND
- (f) XOR
- (g) NOT
- (h) **OR**

Q13

What does !(7) evaluate to in decimal where ! is a NOT operator?

(e) 7



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

(f) 8

(g) 9

(h) 1

Q14

Structures cannot be passed as Function Parameters

(c) True

(d) False

Q15

When break statement is encountered in a loop body it,

(e) Transfers the control outside from current loop

(f) Transfers the control outside from current program

(g) Enforces the next iteration of loop

(h) Generates compile

time error. Q16

A union is a user-defined data type that contains only__from its list of members at a time.

(e) One object



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (f) Two objects
- (g) Three objects
- (h) None of the given options

1. In order to get 256 from the number 2568 we divide this number by 10 and take,

- ▶ Its remainder
- ▶ The number
- ▶ Its quotient
- ▶ Its divisor

2. The correct syntax of do-while loop is,

- ▶ (condition) while; do { statements; };
- ▶ { statements; } do-while ();
- ▶ while(condition); do { statements; };
- ▶ do { statements; } while (condition);

3. Which of the following function(s) is/are included in stdlib.h header file?

- ▶ double atof(const char *nptr)
- ▶ int atoi(const char *nptr)
- ▶ char *strcpy (char *s1, const char *s2)
- ▶ 1 and 2 only (Pg 191)

4. If the break statement is missed in switch statement then,

- ▶ The compiler will give error
- ▶ This may cause a logical error (Pg 76)
- ▶ No effect on program
- ▶ Program stops its execution

5. The data type before a function name represents its,

- ▶ Return Type (Pg 499)
- ▶ Function data
- ▶ Function arguments
- ▶ Function name



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

6. Member function tellg() returns the current location of the____pointer.

- ▶ tellptr()
- ▶ write()
- ▶ seekg()
- ▶ **get()** (Pg 215)

7. What does $5 | 6$, evaluate to in decimal where ‘|’ is bitwise OR operator?

- ▶ 3
- ▶ 4
- ▶ 5

▶ 7

$5 | 6 =$
0 1 0 1
0 1 1 0



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

0 $\frac{111}{7}$ =

8. C is widely known as development language of ___ operating system.

- ▶ Linux
- ▶ Windows
- ▶ **Unix (Pg 12)**
- ▶ Mac OS

9. What will be the result of arithmetic expression $6 + 27 / 3 * 3$?

- ▶ 33
- ▶ 45
- ▶ **9**
- ▶ 30

10. How many bytes are occupied by declaring following array of characters?

```
char str[] = "programming";
```

- ▶ 10
- ▶ 11
- ▶ **12**
- ▶ 13

11. What will be the correct syntax for initialization of pointer *ptr* with string "programming"?

- ▶ `char ptr = 'programming' ;`
- ▶ **`char *ptr = "programming" ;`**
- ▶ `char *ptr = 'programming' ;`
- ▶ `*ptr = "programming" ;`

pg 166

array element in each array initialized with a single character enclosed in singlequote. pg 21

AR Lucky Term

While assigning a character value to a char type variable single quotes are used around the character as 'a'.

12. What will be the result of expression $x \% 2$, if $x = 7$?

► $x = 1$

► $x = 3$

► $x = 7$

► $x = 2$

13. UNIX has been developed in ___ language.

► JAVA

► B

► C(pg 12)

► FORTRAN

14. What will be the value of i and j in the following code segment?

```
int i, j ;  
int x[5] = {2, 3, 4, 8, 9} ;  
int *ptr  
=&x[2]; i =  
(*ptr)++ ;
```



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

j = *ptr++ ;

- ▶ i = 5, j = 5
- ▶ i = 5, j = 8

- ▶ i = 4, j = 8
- ▶ i = 5, j = 9

15. ----- When an array element is passed to a function, it is passed by----- --.

▶ reference(Pg 266)

- ▶ data type
- ▶ value
- ▶ data

When we pass ordinary variables to functions, they are passed by value because of the default behavior. But when an array is passed to a function, the default behavior changes and array is passed by reference

16. What is the output of the following statement?
int i = 2.5; do { cout << i * 2; } while (i > 3 && i < 10);

- ▶ 510
- ▶ 5
- ▶ 48
- ▶ ERROR

17. What does !(7) evaluate to in decimal where ! is a NOT operator?

- ▶ 7
- ▶ 8
- ▶ 9
- ▶ 10

18. The condition in while loop may contain logical expression but not relational expression.

- ▶ True
- ▶ False

19. Searching is easier when an array is already sorted



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

► True

► False

20. If an array has 100 elements, what is allowable range of subscripts?

► 0-99

► 1-99

► 0 - 100

► 1 - 100

21. What will be the value of 'a' and 'b' after executing the following statements?

```
a = 3;
```

```
b = a++;
```

► 3, 4

► 4, 4

► 3, 3

► 4, 3

22. What will be the correct syntax to initialize all elements of two-dimensional array to value 0?

► `int arr[2][3] = {0,0} ;`



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

► `int arr[2][3] = {{0},{0}} ;`
► `int arr[2][3] = {0},{0} ;`
► `int arr[2][3] = {0} ;`

23. Which of the following function returns the size of a string variable?

- `strlen()`
- `stringlen()`
- `strlen()`
- `strLength()`

When applied to a character array, the `strlen` function returns the length of the string stored there,

not its allocated size.

24. What will be the range of numbers generated by function `rand () % 9`?

- 0 to 9
- 1 to 9
- 0 to 8
- 1 to 8

25. Computer can understand only machine language code.

- True
- False

26. What does $5 \wedge 6$, evaluate to in decimal where ‘ $\wedge$ ’ is Exclusive OR operator?

- True
- Fals

eDetail:-

It

mean

5 =

0101

6 = 0110

$5 \wedge 6 = 0011$



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

If both inputs are same then the output is 0 and if different then output is 1

27. If the file is not properly closed in the program, the program_____.

- ▶ Terminate normally
- ▶ Indicate Runtime error
- ▶ Indicate Compile time error
- ▶ Crashes

Eventually run out of file handles and/or memory space and crash.)

28. Which of the following header file include string conversion functions?

- ▶ `stdlib.h`



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

29. A precise sequence of steps to solve a problem is called

- ▶ Statement
- ▶ Program
- ▶ Utility
- ▶ Routine

30. In if structure the block of statements is executed only,

- ▶ When the condition is false
- ▶ When it contain arithmetic operators
- ▶ When it contain logical operators
- ▶ When the condition is true

31. Dealing with structures and functions passing by reference is the most economical method

- ▶ True
- ▶ False

32. _____ Preprocessor program perform its function before _____ phase takes place.

- ▶ Editing
- ▶ Linking
- ▶ Compiling
- ▶ Loading

33. Which looping process is best, when the number of iterations is known?

- ▶ for
- ▶ while
- ▶ do-while
- ▶ all looping processes require that the iterations be known

34. Which character is inserted at the end of string to indicate the end of string?

- ▶ new line
- ▶ tab
- ▶ null
- ▶ carriage return

35. Which of the following header file defines the rand() function?

AR Lucky Term

- ▶ iostream.h
- ▶ conio.h
- ▶ **stdlib.h**
- ▶ stdio.h

36. Commenting the code ____

- ▶ **Makes a program easy to understand for others.**
- ▶ Make programs heavy, i.e. more space is needed for executable.
- ▶ Makes it difficult to compile
- ▶ All of the given options.

37. What's wrong with this for loop? for (int k = 2, k <= 12, k++)

- ▶ the increment should always be ++k
- ▶ the variable must always be the letter i when using a for loop
- ▶ there should be a semicolon at the end of the statement
 - ▶ **the commas should be semicolons**



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

38. For which array, the size of the array should be one more than the number of elements in an array?

- ▶ int
- ▶ double
- ▶ float
- ▶ **char**

39. The function of cin is

- ▶ To display message
- ▶ **To read data from keyboard**
- ▶ To display output on the screen
- ▶ To send data to printer

40. In C/C++ language the header file which is used to perform useful task and manipulation of character data is

- ▶ cplex.h
- ▶ **ctype.h (Pg 188)**
- ▶ stdio.h
- ▶ delay.h

41. How many parameter(s) function getline() takes?

- ▶ 0
- ▶ 1
- ▶ 2
- ▶ **3**

The member function getline() also takes three parameters: the buffer to fill, one more than the maximum number of characters to get, and the termination character. getline() functions exactly like get() does with these parameters, except getline() throws away the terminating character.

42. Word processor is

- ▶ Operating system
- ▶ **Application software**



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- ▶ Device driver Utility software

43. For which values of the integer `_value` will the following code becomes an infinite loop?

```
int
number=1;
while (true)
{ cout <<
number;
if (number == 3)
break; number +=
integer_value; }
```

- ▶ any number other than 1 or 2
- ▶ **only 0**
- ▶ only 1
- ▶ only 2

Rational:

`number += integer_value` ..above line decide the fate of loop so any thing other then

zero leads

to value of 3 which will quite the loop. Only zero is the value which keeps the loop infinite.

46. Each pass through a loop is called a/an

- ▶ enumeration
- ▶ **Iteration**
- ▶ culmination
- ▶ pass through



SUBSCRIBE

AR Lucky Bahi



47. A continue statement causes execution to skip to

- ▶ the return 0; statement
- ▶ the first statement after the loop
- ▶ the statements following the continue statement
- ▶ **the next iteration of the loop**

Continue statement is used, when at a certain stage, you don't want to execute the remaining statements inside your loop and want to go to the start of the loop.

48. What is the correct syntax to declare an array of size 10 of int data type?

- ▶ int [10] name ;
- ▶ name[10] int ;
- ▶ **int name[10] ;**
- ▶ int name[] ;

49. Consider the following code segment. What will the following code segment display? int main(){

```
int age[10] =  
{0}; cout <<  
age ;  
  
}
```

- ▶ Values of all elements of array
- ▶ **Value of first element of array**
- ▶ Starting address of array
- ▶ Address of last array element

50. How many bytes will the pointer *INTPTR* of type int move in the following statement? intPtr += 3 ;

- ▶ 3 bytes
- ▶ 6 bytes
- ▶ **12 bytes**
- ▶ 24 bytes

one int is 4 bytes so $4 \times 3 = 12$ bytes movement.

51. If there are $2(n+1)$ elements in an array then what would be the number of iterations required to search a number using binary search algorithm?

- ▶ n elements
- ▶ **$(n+1)$ elements**
- ▶ $2(n+1)$ elements
- ▶ $2(n+1)$ elements

52. Which of the following operator is used to access the value of variable pointed to by a pointer?

- ▶ *** operator**
- ▶ $\rightarrow$ operator
- ▶ && operator
- ▶ & operator

53. The __ statement interrupts the flow of control.

- ▶ switch
- ▶ continue
- ▶ goto
- ▶ **break**

54. ----- Analysis is the step in designing a program

- ▶ Last
- ▶ Middle



SUBSCRIBE

AR Lucky Bahi



► Post Design

► First

Analysis will be always followed by design and then code.

55. _____ Paying attention to
detail in designing a program is _____

► Time consuming

► Redundant

► Necessary

► Somewhat Good

In programming, the details matter. This is a very important skill. A good programmer always analyzes the problem statement very carefully and in detail. You should pay attention to all the aspects of the problem.

56. _____ There are mainly _____ types of software

► Two

► Three

► Four

► Five

- System Software
- Application Software

57. In C/C++ the #include is called,

► Header file

► Preprocessor Directive (Pg 15)

► Statement

► Function

58. && is _____
operator.

► An arithmetic

► Logical



SUBSCRIBE

AR Lucky Bahi



- ▶ Relational
- ▶ Unary

we use logical operators (&& and ||) for AND and OR respectively with relational operators.

59. In flow chart, the symbol used for decision making is,

- ▶ Rectangle
- ▶ Circle
- ▶ Arrow

▶ Diamond (Pg 51)

60. C++ views each file as a sequential stream of _____.

- ▶ Bytes
- ▶ Bits
- ▶ 0's or 1's
- ▶ Words

61. If the elements of an array are already sorted then the useful search algorithm is, ▶ Linear search

▶ Binary search (Pg 188)

- ▶ Quick search
- ▶ Random search

In binary search algorithm, the 'divide and conquer' strategy is applied. This plies only to sorted arrays in ascending or descending order.



SUBSCRIBE

AR Lucky Bahi



62. The address operator (&) can be used with,

- ▶ Statement
- ▶ Expression

▶ Variable

▶ Constant

63. When a pointer is incremented, it actually jumps the number of memory addresses

▶ According to data type (Pg 160)

- ▶ 1 byte exactly
- ▶ 1 bit exactly
- ▶ A pointer variable can not be incremented

64. Call by reference mechanism should be used in a program when there is

- i. large amount of data to be passed
 - ii. small amount of data to be passed
 - iii. need to change the passed data
 - iv. no need to change the passed data
- ▶ and (ii) only
 - ▶ (i) and (iii) only
 - ▶ (ii) and (iii) only
 - ▶ (ii) and (iv) only

65. Which of the following is the starting index of an array in C++?

▶ 0

- ▶ 1
- ▶ -1
- ▶ any number

66. _____ The return type of a function that do not return any value must be ____

▶ int

▶ void

- ▶ double
- ▶ float



SUBSCRIBE

AR Lucky Bahi



67. Which of the following is an extension of header file?

- ▶ .exe
- ▶ .txt
- ▶ .h
- ▶ .c

68. We want to access array in random order which approach is better?

- ▶ Pointers
- ▶ Array index (Pg 176)
- ▶ Both pointers and array index are better
- ▶ None of the given options.

69. When we declare a multidimensional array the compiler store the elements of multidimensional array in the form of,

- ▶ Columns
- ▶ Rows
- ▶ Contiguous memory location (Pg 174)
- ▶ Matrix



SUBSCRIBE

AR Lucky Bahi



70. In C/C++ the string constant is enclosed

- ▶ In curly braces
- ▶ In small braces
- ▶ In single quotes
- ▶ In double quotes

71. The size of int data type is

- ▶ 1 bytes
- ▶ 2 bytes
- ▶ 3 bytes
- ▶ 4 bytes (Pg 257)

72. In Flow chart process is represented by

- ▶ Rectangle (Pg 51)
- ▶ Arrow symbol
- ▶ Oval
- ▶ Circle

73. When we are using const keyword with a variable x then initializing it at the time of declaration is,

- ▶ Must
- ▶ Optional
- ▶ Not necessary
- ▶ A syntax error

74. Which of the following is the correct way to assign an integer value 5 to element of a matrix say 'm' at second row and third column?

- ▶ $m[2][3] = 5 ;$
- ▶ $m[3][2] = 5 ;$
- ▶ $m[1][2] = 5 ;$
- ▶ $m[2][3] = '5' ;$

75. How many total elements must be in two-dimensional array of 3 rows and 2 columns?

- ▶ 4
- ▶ 5
- ▶ 6 ($3*2=6$)
- ▶ 7



SUBSCRIBE

AR Lucky Bahi



76. Which of the following is the correct statement for the following declaration? `const int *ptr.`

- ▶ `ptr` is a constant pointer
- ▶ `ptr` is constant integer pointer
- ▶ `ptr` is a constant pointer to `int`
- ▶ `ptr` is a pointer to `const int`

77. Consider the following code segment. What will be the output of this code segment? `int arr[6] = {2, 3, 7, 4, 5, 6} ;`

```
int      *ptr1  
=&arr[1] ; int  
*ptr2    =  
&arr[4] ; cout  
<< (ptr2-ptr1) ;
```

- ▶ 3
- ▶ 9
- ▶ 12
- ▶ 2



SUBSCRIBE

AR Lucky Bahi



78. C is a/an _language

- ▶ low level
- ▶ object based
- ▶ object oriented
- ▶ **function oriented** (Pg 77)

78. The variables having a name, type and size are just like empty boxes.

- ▶ False
- ▶ **True**

79. Most efficient method of dealing with structure variables is to define the structure globally

- ▶ True
- ▶ False

80. Syntax of union is identical to ____

- ▶ **Structure (pg 242)**
- ▶ Class
- ▶ Function
- ▶ None of the given options

81. In Program commenting the code liberally is

- ▶ **Useful.**
- ▶ Time consuming
- ▶ Not necessary

82. If we want to store a string “abc” in an array str then the size of this array must be at least,

- ▶ 2
- ▶ 3
- ▶ **4**
- ▶ 5

83. The remainder (%) operator is,

- ▶ **An arithmetic operator (Pg 258)**

- ▶ A logical operator
- ▶ A relational operator
- ▶ A division operator

84. When a call to function statement is encountered,

- ▶ The control is transfer to its Prototype
 - ▶ The control is transfer to its definition
- ▶ The compiler stop execution of whole program
- ▶ The program hangs

85. The value of $2*15/3*7+3*2$ is

- ▶ 146
- ▶ 76
- ▶ 8
- ▶ 70

86. Carefully analyze the following lines of code and chose the correct option.

```
ch1="a";  
ch2='a';
```

- ▶ ch1 and ch2 are strings
 - ▶ ch1 is string and ch2 is character
- ▶ ch2 is string and ch1 is character



SUBSCRIBE

AR Lucky Bahi



- ▶ ch1 and ch2 are characters

87. The size of a double variable is

- ▶ 2 bytes
- ▶ 4 bytes
- ▶ 8 bytes
- ▶ 10 bytes

The size of an int & a long int
is:4 bytes
The size of a short int
is:2 bytes
4bytes
The size of a
char is:1 byte

The size of a double variable is:8 byte

88. An array is also
called

- ▶ an array variable
- ▶ array declaration
 - ▶ struct
 - ▶ constant pointer

89. Compiler is a

- ▶ System software
- ▶ Application Software
- ▶ Driver
- ▶ Editor

90. If Num is an integer variable then Num++ means,

- ▶ Add 1 two times with Num
 - ▶ Add 1 with Num
- ▶ Add 2 with Num
- ▶ Subtract 2 from Num

91. For one byte there are combinations of values
that can be stored in computer.

- ▶ 26



SUBSCRIBE

AR Lucky Bahi



- ▶ 27
- ▶ 28
- ▶ 24

Each bit is capable of holding two possible values, the number of possible different combinations of values that can be stored in n bits is 2^n .
For example: 1 bit can hold $2 = 2^1 = 2$ possible values (0 or 1)
2 bits can hold $2 \times 2 = 2^2 = 4$ possible values
so 8 bits (one byte)
 $= 2^8 = 256$

92. Default case in switch statement is,

- ▶ Must
 - ▶ Optional
- ▶ syntax error
- ▶ Necessary

93. When break statement is encountered in switch statement, it

- ▶ Stops the entire program
- ▶ Stops the execution of current statement
 - ▶ Exits from switch statement
- ▶ None of the given options



SUBSCRIBE

AR Lucky Bahi



94. How many dimensions does n-dimensional array has?

- ▶ **n dimensions**
- ▶ 2n dimensions
- ▶ (n+1) dimensions
- ▶ (n-1) dimensions (Array starts from 0th element)

95. What will be the correct syntax to access the value of fourth element of an array using pointer ptr?

- ▶ **ptr[3]**
- ▶ (ptr+3)
- ▶ *(ptr+3)
- ▶ Both 1 and 3

100 Which of the following values C++ use to represent true and false?

- ▶ **and 0**
- ▶ and -1
- ▶ and 00
- ▶ Any numerical value

101 Declaring structures does not mean that memory is allocated.

- ▶ **True**
- ▶ False

102 If a variable is passed by value to a function and the function makes some changes to that variable then it

- ▶ **Does not affect the original variable pg 83**
- ▶ affects the original variable
- ▶ causes syntax error
- ▶ None of the given options

103 Loops are ----- Structure.

Decision

Repetition pg

560



SUBSCRIBE

AR Lucky Bahi



104 _____ is manipulator and it inserts new line character and flushes stream.

► **endl**

105 Switch statement deals with,

- Integer data only
- float data only
- character data only
- **Integer and character data**

106 A record is a group of related_____.

- Files
- Bytes
- **Fields**
- Data

107 To access the element of two dimensional array we use,

- ▶ Single referencing
- ▶ Single dereferencing
- ▶ Double dereferencing
- ▶ Double referencing Pg175

108 If it is required to copy an array to another array then,
▶ Both arrays must be of the same size and data type Pg 105

- ▶ Both arrays may be of different size
- ▶ Both arrays may be of different data type
- ▶ Both arrays may be of different size and type

109 The precedence of * is higher than dot operator

- ▶ True
- ▶ False

110 Which of the following data type(s) can operate on modulus operator '%'?

- ▶ float, int
- ▶ float, double
- ▶ int Pg 22
- ▶ char

111 What will be the output of following code?

```
int x = 10 ;  
cout << "x =" << x ;
```

- ▶ 10
- ▶ "x=10"
- ▶ x=10
- ▶ 10=x

112 Which looping process checks the test condition at the end of the loop?

- ▶ for

▶ while

▶ do while

▶ no looping process checks the test condition at the end

113 What will be the correct syntax of the following statement?

ptr is a constant pointer to integer.

▶ const int *ptr ;

▶ const *int ptr ;

▶ int const *ptr ;

▶ int *const ptr ; Pg 154

114 A function must always return value.

▶ True

▶ False

115 Assignment operator is used for____.

▶ calculation



SUBSCRIBE

AR Lucky Bahi



- ▶ reading
- ▶ assigning value to variables Pg 17
- ▶ None of the given options.

116 What is the difference between switch statement and if statement.

1. if statement is used when we have to check two conditions while switch is a multi conditional control statement.
2. SWITCH statement can be executed with all cases if the “break” statement is not used whereas IF statement has to be true to be executed further.

117 What is wrong with following code and also give the reason of error?

```
int x , y ;
int *ptr1 =
&x ;int
*ptr2 =&y ;
ptr1+ptr2 ;
```

Answer:

We need one more variable in which we put sum of ptr1 and ptr2 like Int z;
z=ptr1+ptr2;

(Answer provided by Ferhat Qudsia)

118 Which bit of the number is used as a sign bit?

The most significant bit of the number is used as a sign bit (to denote the sign of the number). (Answer provided by Ferhat Qudsia)



SUBSCRIBE

AR Lucky Bahi



119 What happened when we try to copy the array 'arr1' into the array 'arr2' in the following code segment, justify your answer?

```
main()
{
    int
    arr1[3]={2,3,5
    };int arr2[3];
    arr2=arr1;
}
```

We can not copy array directly in this way (arr2=arr1;) Each member of arr1 to be copied by each member of arr2.

We can use for loop to copy array 1 to array2 (Answer provided by Ferhat Qudsia)

120 Differentiate between random access and sequential access file? Random access file:

Random access files are not in sequence mean its not necessary put that's thing first that written first we put any thing from file any where. So tellg() and tellp() are the two very useful functions while reading from or writing into the files at some certain position.

Sequential access file:

Sequential access files are simple character files. while working with thesequential access files we write in a sequence not in a random manner



SUBSCRIBE

AR Lucky Bahi



121 When the logical operator AND (&&) combine two expressions exp1 and exp2 then the result will be true only,

- ▶ When both exp1 and exp2 are true Pg 246
- ▶ When both exp1 and exp2 are false
- ▶ When exp1 is true and exp2 is false
- ▶ When exp1 is false and exp2 is true

122 Which of the following function(s) is/are included in ctype.h header file?

- ▶ isdigit(int c)
- ▶ isxdigit(int c)
- ▶ tolower(int c)
- ▶ All of the above Pg 188

123 To access the data members of structure __ is used.

- ▶ dot operator (.) pg 231
- ▶ * operator
- ▶ operator □
- ▶ None of given.

124 Both compiler and interpreter are used to translate program into machine language code.

- ▶ True
- ▶ False

125 Missing semicolon ';' at the end of C++ statement is

- ▶ Logical error
- ▶ Syntax error Pg 16
- ▶ Runtime error
- ▶ None of the given options

126 Switch statement is an alternative of __statement



SUBSCRIBE

AR Lucky Bahi



- ▶ multiple if
- ▶ continue
- ▶ break
- ▶ goto

127 Array is passed by value to a function by default.

- ▶ True
- ▶ False Pg 266

128 Which of the following is the correct function call having array named *student* of 10 elements as a parameter.

- ▶ addRecord(student[]) ;
- ▶ addRecord(student) ;
- ▶ addRecord(student[10]) ;
- ▶ addRecord(*student) ;

129 What will be the output of following code segment?main(){

```
int x = 5 ;
```

```
{
```



SUBSCRIBE

AR Lucky Bahi



```
int x =  
4 ;cout  
<x  
  
}
```

```
cout <x  
  
}
```

- ▶ 5, 5
- ▶ 4, 4
- ▶ 4, 5
- ▶ 5, 4

130 The object _____ may be used both for file input and file output

- ▶ **fstream, Pg 199**
- ▶ ifstream,
- ▶ ofstream,
- ▶ none of the given options.

138. Let suppose

```
Union  
intorDouble{ Int  
ival;
```

```
Double charvar;
```

```
};
```

```
main(){  
intorDouble  
VAZ;
```

```
int size ;
```

```
size = sizeof(VAZ);
```



SUBSCRIBE

AR Lucky Bahi



}

What will be the value of variable "size", if int occupies 4 bytes and double occupies 8 bytes?

- ▶ 2
- ▶ 4
- ▶ 8
- ▶ 12

139. How a program can use a function?

The calling program just needs to write the function name and provide its arguments (without data types). It is important to note that while calling a function, we don't write the return value data type or the datatypes of arguments.

140. Which function is used to read/write more than a single character or single line while handling files?

We use the `getline` function to read more than single character

Suppose the pointer `yptr` is pointing to the first element of the array `y` and the size of array is 10. Can we increment the `yptr` up to 12 times? And what will happen?

(i) An array `day` is declared as: `int day[] = {1, 2, 3, 4, 5, 6, 7};` How many elements does array 'day' has?



SUBSCRIBE

AR Lucky Bahi



(ii) If the declaration is changed as:
`int day[7] = {1,2, 3, 4, 5, 6, 7};` How
many elements does array 'day' has?

In both the case array day has the 7 elements.

141. C language is developed by

- ▶ Bill Gates
- ▶ Robert Lafore
- ▶ **Dennis Ritchie Pg 12**
- ▶ Deitel & Deitel

142. Which of the following choice is not an example of an int datatype?

- ▶ 0
- ▶ -32
- ▶ 65531
- ▶ **-4.0**

143. *doc is by type.

- ▶ **Sequential File**
- ▶ Random Access File
- ▶ Data File
- ▶ Record File

144. In C/C++ all character strings are terminated with,

- ▶ Null character
- ▶ String
- ▶ **Zero Pg 166**
- ▶ Full stop

145. Which of the following can not be a variable name?



SUBSCRIBE

AR Lucky Bahi



- ▶ area
- ▶ _area
- ▶ 10area
- ▶ area2

146. By default an array of characters is passed by value to a function.

- ▶ True
- ▶ False

147. Which of the following operator is used to access the address of a variable?

- ▶ * operator
- ▶ -> operator
- ▶ && operator
- ▶ & operator Pg 480

148. The name of an array represents address of first location of array element.

- ▶ True Pg 120

149. Let suppose

```
Union intorDouble{
```

```
Int ival;
```

```
Double charvar;
```

```
};
```



SUBSCRIBE

AR Lucky Bahi



```
main(){
intorDouble
VAZ;int size ;

size = sizeof(VAZ);

}
```

What will be the value of variable "size", if int occupies 4 bytes and double occupies 8 bytes?

- ▶ 2
- ▶ 4
- ▶ 8
- ▶ 12

150. What is the difference between for loop and while loop?

When number of iterations known we use for loop otherwise we will use while loop

151. To access the element of two dimensional array we use,

- ▶ Single referencing
- ▶ Single dereferencing
- ▶ **Double dereferencing Pg175**
- ▶ Double referencing

152. _____ Data Size of the file is always the actual size of the file.

- ▶ Greater than
 - ▶ Equal to
 - ▶ Less than or equal to
- ▶ **None of the above Pg 216**



SUBSCRIBE

AR Lucky Bahi



Similarly in case of files, the space occupied by a file (file size) can be more than the actual data length of the file itself.

153. When an identifier is declared with keyword const then,

- ▶ Its value can be changed during execution.
- ▶ Its value can not be changed Pg110
- ▶ Its value can be changed with arithmetic operator
- ▶ Its value can be overwritten

154. In C/C++ if we define an array of size eight (8) i.e. `intArr [8];` then the last element of this array will be stored at,

- ▶ `Arr[0]`
- ▶ `Arr[8]`
- ▶ `Arr[7]`
- ▶ `Arr[-1]`

155. In C/C++ all character strings are terminated with,

- ▶ Null character Pg 166
- ▶ String
- ▶ Zero
- ▶ Full stop



SUBSCRIBE

AR Lucky Bahi



156. Let

suppose

struct

intorDoubl

e {

int ival;

Double

charvar;

};

main(){

intorDou

bleVAZ;

int

size ;

size =

sizeof(VAZ);

}

What will be the value of variable size, if int occupies 4 bytes and double occupies 8 bytes?

► 2

► 4

► 8

► 12

157. Do-while loop executes at least,



SUBSCRIBE

AR Lucky Bahi



- ▶ Zero Time
- ▶ One Time
- ▶ Two Times
- ▶ N Times

158. += , *= , /= , etc are called,

- ▶ Assignment operators
- ▶ Logical operator
- ▶ Compound assignment operator Pg 63
- ▶ Unary operator

159. Computer can understand only machine language code.

- ▶ True Pg 12
- ▶ False

160. Which of the following is the correct syntax to print multiple values or variables in a single command using cout?

- ▶ cout <
- ▶ cout <
- ▶ cout <
- ▶ cout <

161. The compilers and interpreters also belong to the System Software category.



SUBSCRIBE

AR Lucky Bahi



▶ True Pg 11

▶ False

162. Editors are used to compile the code.

163. ▶ True

▶ False

Compilers are used for compilation of source codes,
However Editors are used to write the source codes.

164. What will be the result of the statement

`rand ( ) % 50`

When 50 divides any number, the remainder will always be less than 50.

165. `\n` is control character which is used to insert.

▶ line break

166. Default constructor takes_.

▶ one parameter

▶ two parameters

▶ no parameters

▶ character type parameter

167. All the preprocessors directives start with_____.

▶ \$

▶ &

▶ #

▶ _

168. The members of a class declared with the keyword `struct` are__by default.



SUBSCRIBE

AR Lucky Bahi



- ▶ static
- ▶ **private**
- ▶ protected
- ▶ public

169. We cannot use ___pointer for storing and reading data from it.

- ▶ **NULL**
- ▶ integer
- ▶ double
- ▶ zero

170. When an object of a class is defined inside another class then,

- ▶ Destructor of enclosing class will be called first
- ▶ **Destructor of inner object will be called first**
- ▶ Constructor and Destructor will be called simultaneously
- ▶ None of the given options

181. Consider the following code segment. Which of the following will be called while executing code at line 2?
String s1 , s2; s1 = s2 ;

- ▶ Copy constructor



SUBSCRIBE

AR Lucky Bahi



- ▶ **Default constructor**
- ▶ Assignment operator
- ▶ Parameterized constructor

182. We cannot increment_____.

- ▶ pointers
- ▶ arrays
- ▶ **references**
- ▶ variables

183. In statement Matrix m2 = m1 ;

- ▶ **Assignment operator is being used**
- ▶ Copy constructor is being used.
- ▶ Statement has syntax error
- ▶ None of the given options

184. From the following; which on is the correct syntax of an array declaration: array size is 5 and it is of float data type?

- ▶ float [5] name;
- ▶ name[5] float;
- ▶ **float name[5];**
- ▶ None of the given options

185. If an array has 50 elements, what is allowable range of subscripts?

- ▶ **0–49**
- ▶ 1–49
- ▶ 0–50
- ▶ 1–50

186. A structure is a collection of_____under a single name.

- ▶ values
- ▶ **variables**
- ▶ data
- ▶ None of the given

187. If a function has not been declared before its definition, It is a

- ▶ **logical error**

- ▶ syntax error
- ▶ run time error
- ▶ None of these

188. When the if statement consists more than one statement then enclosing these statement in curly braces is,

- ▶ Not required
- ▶ **Good programming**
- ▶ Relevant
- ▶ Must

189. _____ allow us to have a memory location and use it as int or char interchangeably

- ▶ structures
- ▶ union
- ▶ construct



SUBSCRIBE

AR Lucky Bahi



▶ None of the given

190. In Analysis, we try to have a_____

- ▶ Determined the inputs
- ▶ Break up of problem
- ▶ **Precise problem statement**
- ▶ None of the given

191. _____function give the position of the next character to be read from that file.

- ▶ tellp()
- ▶ **tellg()**
- ▶ seekg()
- ▶ seekp()

192. Pointers store the _____

- ▶ value of a variable
- ▶ **memory address**
- ▶ characters
- ▶ None of the given

193. In order to get the right most digit of a number, we divide this number by 10 and take its

- ▶ **Remainder**
- ▶ Quotient
- ▶ Divisor
- ▶ None of the given options

194. _____ Returns true if c is a digit and false otherwise.

- ▶ int isalpha(int c)
- ▶ int isalnum(int c)
- ▶ int isxdigit(int c)
- ▶ **int isdigit(int c)**

195. If int a = 50; then the value of a/= 3; will be,



SUBSCRIBE

AR Lucky Bahi



- ▶ 15
- ▶ 18
- ▶ 16
- ▶ 17

196. _____ contains functions for manipulations of character data.

- ▶ **ctype.h**
- ▶ iostream.h
- ▶ string.h
- ▶ None of the given

197. _____ Returns true if c is a digit or a letter and false otherwise.

- ▶ int isalpha(int c)
- ▶ **int isalnum(int c)**
- ▶ int isxdigit(int c)
- ▶ int isdigit(int c)



SUBSCRIBE

AR Lucky Bahi



198. If `int sum = 54;` Then the value of the following statement is `sum = sum - 3 ;`

- ▶ 52
- ▶ 50
- ▶ 51
- ▶ 57

199. To get the value stored at a memory address, we use the_

- ▶ referencing operator
- ▶ dereferencing operator
- ▶ simple operator
- ▶ None of the given

200. In C/C++; by default arguments are passed by__to a function.

- ▶ Reference
- ▶ Value
- ▶ Type
- ▶ Data

201. The string in the array is terminated by a

- ▶ zero
- ▶ nil
- ▶ null
- ▶ one

202. Structures are syntactically defined with the word .

- ▶ struc
- ▶ struct
- ▶ structure
- ▶ None of the given

203. At the_____, we try to break up the problem into functional units

- ▶ analysis phase
- ▶ design phase
- ▶ Implementation phase



SUBSCRIBE

AR Lucky Bahi



▶ None of the given

204. While developing a program; should we think about the user interface?

▶ Yes

▶ No

205. What will be the result of arithmetic expression $5+25/5*5$?

▶ 45

▶ 6

▶ 30

▶ 9

206. Why we use "cin"?

▶ To send data to printer

▶ To read data from keyboard

▶ To display message

▶ To display output on the screen



SUBSCRIBE

AR Lucky Bahi



207. _____operator uses the sign ^.

- ▶ Bit-wise OR
- ▶ Exclusive OR
- ▶ AND Operator
- ▶ NOT operator

208. C++ is a_____language.

- ▶ High level
- ▶ Low level
- ▶ Machine
- ▶ Fourth Generation

209. $12 \& 8 = (1000)_2 = \underline{\hspace{1cm}}$. & is used to AND two numbers bit-wise

- ▶ 4
- ▶ 8
- ▶ 6
- ▶ 12

210. From the following; which one is used as an assignment operator?

- ▶ Equal sign '='
- ▶ Double equal sign '=='
- ▶ Both equal and double equal sign
- ▶ None of the given options

211. What will be the value of 'a' and 'b' after executing the following statements? `int a`

`= 9; int b = a++; cout<<`

- ▶ 10,9
- ▶ 9,10
- ▶ 9,9
- ▶ 10,10

212. These functions `seekg()` and `seekp()` requires an argument of type_____to

let them how many bytes to move forward or backward.

- ▶ int
- ▶ short



SUBSCRIBE

AR Lucky Bahi



- ▶ long
- ▶ double

213. A character is stored in the memory in ____

- ▶ byte
- ▶ integer
- ▶ string
- ▶ None of the given

214. dereferencing operator is represented by __

- ▶ *
- ▶ +
- ▶ -
- ▶ None of the given

215. _____ transfers the executable code from main memory to hard disk.



SUBSCRIBE

AR Lucky Bahi



▶ **Loader**

▶ Debugger

▶ Compiler

▶ Linker

216. When the logical operator OR (||) combine two expressions exp1 and exp2 then the result will be false only,

▶ When both exp1 and exp2 are true

▶ **When both exp1 and exp2 are false**

▶ When exp1 is true and exp2 is false

▶ When exp1 is false and exp2 is true

217. suppose we have int y[10]; To access the 4th element of the array we write_____

▶ y[4];

▶ y[3];

▶ y[2];

▶ **none of given**

218. We have opened a file stream myfile for reading (getting), myfile.tellg () gives us the current get position of the file pointer. It returns a whole number of type_____

▶ long

▶ **int**

▶ short

▶ double

219. ofstream is used for___

▶ Input file stream

▶ **Output file stream**

▶ Input and output file stream

▶ All of the given

220. A structure is a collection of_____under a single name.

▶ values

▶ **variables**

▶ data

▶ None of the given



SUBSCRIBE

AR Lucky Bahi



221. The first character of a variable name must be an alphabet or

- ▶ Underscore
- ▶ Digit
- ▶ Special character
- ▶ Comma

222. Suppose `int multi[5][10]`; when we are using `**multi` , it means,

- ▶ Single dereferencing
- ▶ Single referencing
- ▶ Double referencing
- ▶ Double dereferencing

223. `eof( )`, `bad( )`, `good( )`, `clear( )` all are manipulators.

- ▶ True
- ▶ False

224. It is possible to return an object from a function through this pointer.



SUBSCRIBE

AR Lucky Bahi



225. True

- ▶ False

226. Function implementation of friend function must be defined outside the class.

- ▶ True
- ▶ False

227. The default scope for members of structures is public whereas the default visibility for class members is private.

- ▶ True
- ▶ False

228. The operator function of << and >> operators are always the member function of a class.

- ▶ True
- ▶ False

229. What does STL stand for?

- ▶ Source template library
- ▶ Standard template library
- ▶ Stream template library
- ▶ Standard temporary library

230. Which of the following array is the most suitable for storing a matrix structure

- ▶ Single-dimensional array
- ▶ Two-dimensional array
- ▶ Three-dimensional array
- ▶ Four-dimensional array

231. What will be the output of following code segment?

```
main()  
{ int x
```



SUBSCRIBE

AR Lucky Bahi



```

= 5 ;
{
    int x = 4 ;
    cout << x << “,” ;
}
cout << x ;
}

```

- ▶ 5, 5
- ▶ 4, 4

- ▶ 4, 5
- ▶ 5, 4

232. Single line comments explaining code would be preceded like in the following example.

```

▶ /*
▶ //
▶ /
▶ /*

```

233. Which of the following will be the correct function call for function prototype given below?

```
int func (int &);
```

- ▶ func(int num);
- ▶ func(&num);
- ▶ func(num);
- ▶ func(*num);



SUBSCRIBE

AR Lucky Bahi



234. If there is a symbol (& sign) used with the variable name followed by data type then it refers to ____ and if & is being used with variable name then it refers to ____

- ▶ Address of variable, reference variable
- ▶ Reference variable, value of variable
- ▶ **Reference variable, address of variable**
- ▶ Address of variable, value of variable

235. Which of the following operator the compiler overloads for objects by default?

- ▶ + operator
- ▶ operator
- ▶ = operator
- ▶ **== operator**

236. If overloaded plus operator is implemented as member function then which of the following option will be true for the statement given below?

`obj3 = obj1 + obj2 ;`

- ▶ obj1 will be passed as an argument to + operator whereas obj2 will drive the + operator
- ▶ **obj1 will drive the + operator whereas obj2 will be passed as an argument to + operator**
- ▶ Both objects (obj1, obj2) will be passed as arguments to the + operator
- ▶ Any of the objects (obj1, obj2) can drive the + operator

237. The operator function will be implemented as ___, if both objects (obj1, obj2) are passed as arguments to - operator in the statement given below.

`obj3 = obj1 - obj2;`

- ▶ friend function



SUBSCRIBE

AR Lucky Bahi



- ▶ member function
- ▶ **non-member function**
 - ▶ either non-member or friend function

238. The input/output streams cin and cout are _____ therefore have _____.

- ▶ Structures, function
- ▶ **Objects, member functions**
- ▶ Functions, objects
- ▶ None of the given options

239. What will be the output of following statement?

```
cout << setfill('0') << setw(7) << 128
```

- ▶ **0000128**
- ▶ 0128128
- ▶ 1280000
- ▶ 0012800

240. The static data members of a class will be _____

- ▶ shared by objects
- ▶ created for each object
- ▶ **initialized within class**
- ▶ initialized within main function

241. Which of the following is used for allocating space for static variables?

- ▶ Heap
- ▶ **Static storage area**
- ▶ Free store
- ▶ Stack



SUBSCRIBE

AR Lucky Bahi



242. Templates provide way of abstracting____information.

- ▶ type
- ▶ data
- ▶ method
- ▶ access

243. A pointer is a special type of variable that contain ____

- ▶ Memory Address
- ▶ Data values
- ▶ Both Values and Memory
- ▶ None of given of options

244. Which is NOT a protection level provided by classes in C++?

- ▶ protected
- ▶ hidden
- ▶ private
- ▶ public

245. Users must not know about_____.

- ▶ Functions Name within Class
- ▶ Class implementation of Functionality and Interfaces
- ▶ Methods Functionality with in Class
- ▶ None of the given options

246. Assignment operator is used to initialize a newly declared object from existing object

- ▶ True
- ▶ False

247. The operator function for << (stream insertion) >> and stream extraction must be

- ▶ Member function of class
- ▶ Non-member function of class
- ▶ Both member and non-member function
- ▶ None of the given options

248. A template function must have

- ▶ One or more than one arguments



SUBSCRIBE

AR Lucky Bahi



- ▶ Only one argument
- ▶ Zero arguments
- ▶ None of the given options

249. Truth tables are used for analyzing__.

- ▶ **logical expressions**
- ▶ arithmetic expressions
- ▶ both logical and arithmetic expressions
- ▶ none of the given options.

250. Which of the following array is the most suitable for storing a matrix structure?

- ▶ Single-dimensional array
- ▶ **Two-dimensional array**
- ▶ Three-dimensional array
- ▶ Four-dimensional array

11 bytes for 11 characters of word programming and 1 for '\n'

251. When we do dynamic memory allocation in the constructor of a class, then it is necessary to provide a destructor.

- ▶ **True**



SUBSCRIBE

AR Lucky Bahi



252. The prototype of friend functions must be written____the class and its definition must be written _____
- ▶ inside, inside the class
 - ▶ inside, outside the class
 - ▶ **outside, inside the class**
 - ▶ outside, outside the class

253. Copy constructor becomes necessary while dealing with _____ allocation in the class.
- ▶ **Dynamic memory**
 - ▶ Static memory
 - ▶ Both Dynamic and Static memory
 - ▶ None of the given options

254. what is the function of flush command?

1): when we specify the buffer size, normally the operating system or compiler does this for us. A typical size of buffer is 512 bytes. When the information is of 512 byte size, output will take place. But in the program, we may want at some point that whatever is in the buffer, show them. For that purpose the normal mechanism is flush. Flush the stream. The flush command forces the data from the buffer to go to its destination which is normally a screen or file and make the buffer empty.

Lec 34

255. what are the types of templates?
- a template is a sketch to draw some shape or figure.
- There are two different types of templates in C++ language i.e.' function templates and class templates. Lec 41

256. The declaratory of Plus (+) member operator function is
- ▶ **Class-Name operator + (Class-Name rhs)**
 - ▶ operator Class-Name + ()
 - ▶ operator Class-Name + (rhs)
 - ▶ Class-Name operator + ()



SUBSCRIBE

AR Lucky Bahi



257. $12 \& 8 = (1000) 2 = \underline{\hspace{1cm}}$. $\&$ is used to AND two numbers bit-wise Select correct option:

- ▶ 4
- ▶ 8
- ▶ 6
- ▶ 12

258. Truth table for $\&$

Bit1	Bit2	Bit1 & Bit2
1	1	1
1	0	0
0	1	0
0	0	0

Therefore, when we apply the

conditions, we get $12 = 1\ 1\ 1\ 0$

(binary conversion of 12)

▶ $= 1\ 0\ 0\ 0$ (binary conversion of 8)

$1\ 0\ 0\ 0$, which is equals to 8

The reserved words public and private comes under the category



SUBSCRIBE

AR Lucky Bahi



259. Which of the following operators can not be overloaded?

- ▶ :new
- ▶ :delete
- ▶ :+=
- ▶ :sizeof

260. The reserved words public and private comes under the category

- ▶ :structures
- ▶ :strings
- ▶ :accessibility modifiers
- ▶ :types of functions

261. What is the sequence of event(s) when allocating memory using new operator?

- ▶ Only block of memory is allocated for objects
- ▶ Only constructor is called for objects
- ▶ Memory is allocated first before calling constructor
- ▶ Constructor is called first before allocating memory

262. What is the sequence of event(s) when deallocating memory using delete operator?

- ▶ Only block of memory is deallocated for objects
- ▶ Only destructor is called for objects
- ▶ Memory is deallocated first before calling destructor
- ▶ Destructor is called first before deallocating memory

263. new and delete operators cannot be overloaded as member functions.

- ▶ True
- ▶ False

264. The operator function of << and >> operators are always the member function of a class.

- ▶ True
- ▶ False

265. A template function must have at least generic data type

- ▶ Zero
- ▶ One
- ▶ Two
- ▶ Three

266. If we do not mention any *return_value_type* with a function, it will return an _____ value.

- ▶ **int**
- ▶ void
- ▶ double
- ▶ float

267. Suppose a program contains an array declared as int arr[100]; what will be the size of array?

- ▶ 0
- ▶ 99
- ▶ **100**
- ▶ 101

268. The name of an array represents address of first location of array element.



SUBSCRIBE

AR Lucky Bahi



- ▶ True
- ▶ False

269. Reusing the variables in program helps to save the memory

- ▶ True
- ▶ False

270. Which of the following option is true about new operator to dynamically allocate memory to an object?

- ▶ The new operator determines the size of an object
- ▶ Allocates memory to object and returns pointer of valid type
- ▶ Creates an object and calls the constructor to initialize the object
- ▶ All of the given options

271. new and delete are_ whereas malloc and free are_.

- ▶ Functions, operators
- ▶ Classes, operators
- ▶ Operators, functions
- ▶ Operators, classes

272. Like member functions, can also access the private data members of a class.

- ▶ Non-member functions
- ▶ Friend functions
- ▶ Any function outside class
- ▶ None of the given options

273. Which of the following statement is best regarding declaration of friend function?

- ▶ Friend function must be declared after public keyword.
- ▶ Friend function must be declared after private keyword.
- ▶ Friend function must be declared at the top within class definition.
- ▶ It can be declared anywhere in class as these are not affected by the public and private keywords.

274. The operator function overloaded for an Assignment operator (=)

must be

- ▶ Non-member function of class
- ▶ **Member function of class**
- ▶ Friend function of class
- ▶ None of the given options

275. For non-member operator function, object on left side of the operator may be

- ▶ Object of operator class
- ▶ Object of different class
- ▶ **Built-in data type**
- ▶ All of the given options

276. The operator function will be implemented as ___, if obj1 drive the - operator whereas obj2 is passed as arguments to - operator in the statement given below.

obj3 = obj1 - obj2;

- ▶ Member function
- ▶ Non-member function
- ▶ **Friend function**
- ▶ None of the given options



SUBSCRIBE

AR Lucky Bahi



277. Which one of the following is the declaration of overloaded pre-increment operator implemented as member function?

- ▶ Class-name operator +() ;
- ▶ Class-name operator +(int) ;
- ▶ **Class-name operator ++() ;**
- ▶ Class-name operator ++(int) ;

278. The static data members of a class are initialized ____

- ▶ **at file scope**
- ▶ within class definition
- ▶ within member function
- ▶ within main function

279. Class is a user defined ____.

- ▶ **data type**
- ▶ memory referee
- ▶ value
- ▶ none of the given options.

280. We can also define a user-defined manipulators.

- ▶ True
- ▶ **False**

281. Automatic variable are created on ____.

- ▶ Heap
- ▶ Free store
- ▶ **static storage**
- ▶ stack

282. A pointer variable can be,

- ▶ Decremented only
- ▶ Incremented only
- ▶ Multiplied only
- ▶ **Both 1 and 2**

283. setprecision is a parameter less manipulator.



SUBSCRIBE

AR Lucky Bahi



- ▶ True
- ▶ False

284. We can change a Unary operator to Binary operator through operator overloading.

- ▶ False
- ▶ True

285. What is the functionality of the following statement?

```
String str[5] = {String("Programming"), String("CS201")};
```

- ▶ Default constructor will call for all objects of array
- ▶ Parameterized constructor will call for all objects of array
- ▶ Parameterized constructor will call for first 2 objects and default constructor for remaining objects
- ▶ Default constructor will call for first 3 objects and Parameterized constructor for remaining objects



SUBSCRIBE

AR Lucky Bahi



286. There is an array of characters having name 'course' that has to be initialized by string 'programming' which of the following is the correct way to do this,

- i. `course[] = {'p', 'r', 'o', 'g', 'r', 'a', 'm', 'm', 'i', 'n', 'g'};`
- ii. `course[] = 'programming';`
- iii. `course[12] = "programming";`
- iv. `course = "programming";`

Choose the correct options.

- ▶ (i) and (ii) only
- ▶ (i) and (iv) only
- ▶ (i) and (iii) only
- ▶ (ii) and (iii) only

287. Overloaded member operator function is always called by _

- ▶ Class
- ▶ Object
- ▶ Compiler
- ▶ Primitive data type

288. Copy constructor becomes necessary while dealing with ___ allocation in the class.

- ▶ Dynamic memory
- ▶ Static memory
- ▶ Both Dynamic and Static memory
- ▶ None of the given options

289. What will be the correct syntax to assign an array named arr of 5 elements to a pointer ptr?

- ▶ `*ptr = arr ; ptr = arr ;`
- ▶ `*ptr = arr[5]`



SUBSCRIBE

AR Lucky Bahi



▶ ptr = arr[5] ; ▶

290. The variables having a name, type and size are just like empty boxes.

- ▶ False
- ▶ True

291. Syntax of union is identical to _

- ▶ Structure
- ▶ Class
- ▶ Function
- ▶ None of the given options

292. Like member functions, can also access the private data members of a class.

- ▶ Non-member functions
- ▶ Friend functions
- ▶ Any function outside class
- ▶ None of the given options

293. Function created within function called?

- ▶ nested
- ▶ overloaded
- ▶ grouped
- ▶ none of them

Question No: 1(Marks: 1)- Please choose one

What is the output of the following statement?
int i = 2.5; do { cout << i * 2; } while (i > 3 && i < 10);



SUBSCRIBE

AR Lucky Bahi



- (a) 510
- (b) 5
- (c) 48
- (d) **error**

Question No: 2(Marks: 1)- Please choose one

What does !(7) evaluate to in decimal where ! is a NOT operator?

- (a) 7
- (b) 8
- (c) 9
- (d) 10

Question No: 3(Marks: 1)- Please choose one

The condition in while loop may contain logical expression but not relational expression.

- (a) True
- (b) False

Question No: 4(Marks: 1)- Please choose one

Searching is easier when an array is already sorted

- (a) **True**
- (b) False

Question No: 5(Marks: 1)- Please choose one

If an array has 100 elements, what is allowable range of subscripts?

- (a) **0 - 99**
- (b) 1 - 99
- (c) 0 - 100
- (d) 1 - 100

Question No: 6(Marks: 1)- Please choose one



What will be the value of 'a' and 'b' after executing the following statements?

a = 3;

b = a++;

(a) 3, 4



SUBSCRIBE

AR Lucky Bahi



- (b) 4, 4
- (c) 3, 3
- (d) 4, 3

Question No: 7(Marks: 1)- Please choose one

What will be the correct syntax to initialize all elements of two-dimensional array to value 0?

- (a) `int arr[2][3] = {0,0} ;`
- (b) `int arr[2][3] = {{0},{0}} ;`
- (c) `int arr[2][3] = {0},{0} ;`
- (d) `int arr[2][3] = {0} ;`

Question No: 8(Marks: 1)- Please choose one

Which of the following function returns the size of a string variable?

- (a) `strlen()`
- (b) `stringlen()`
- (c) `strlen()`
- (d) `strLength()`

Question No: 9(Marks: 1)- Please choose one

What will be the range of numbers generated by function `rand () % 9`?

- (a) 0 to 9
- (b) to 9
- (c) to 8
- (d) 1 to 8

Question No: 11 (Marks: 1) - Please choose one

Computer can understand only machine language code.

- (c) True
- (d) False



SUBSCRIBE

AR Lucky Bahi



Question No: 13 (Marks: 1) - Please choose one

What does $5 \wedge 6$, evaluate to in decimal where ‘ $\wedge$ ’ is Exclusive OR operator?

(a) True

(b) **F**

alse

Detail:-

It mean

5 = 0101

6 = 0110

$5 \wedge 6 = 0011$

If both input is same then the output is 0 and if different then output is 1

Question No: 14 (Marks: 1) - Please
choose one

If the file is not properly closed in the program, the program_____.



SUBSCRIBE

AR Lucky Bahi



- (a) **Terminate normally**
- (b) Indicate Runtime error
- (c) Indicate Compile time error
- (d) Crashes

Question No: 15 (Marks: 1) - Please choose one

Which of the following header file include string conversion functions?

- (a) **string.h**
- (b) stdlib.h
- (c) ctype.h
- (d) sconvert.h

Question No: 1 (Marks: 1) - Please choose one

The function of cin is

- (a) To display message
- (b) **To read data from keyboard**
- (c) To display output on the screen
- (d) To send data to printer

Question No: 2(Marks: 1) - Please choose one

In C/C++ language the header file which is used to perform useful task and manipulation of character data is

- (a) cplext.h
- (b) **ctype.h**
- (c) stdio.h
- (d) delay.h

Question No: 3 (Marks: 1) - Please choose one

How many parameter(s) function getline() takes?

- (a) 0



- (b) 1
- (c) 2
- (d) 3

Question No: 4(Marks: 1) - Please choose one



Word processor is

- (a) Operating system
- (b) **Application software**
- (c) Device driver
- (d) Utility software

Question No: 5 (Marks:

1) - Please choose one

For which values of the integer `_value` will the following code becomes an infinite loop?

```
int
number=1;
while
(true) {
    cout << number;
    if (number == 3)
        break; number +=
        integer_value; }
```

- (a) any number other than 1 or 2
- (b) only 0
- (c) only 1
- (d) only 2

Question No: 6 (Marks:

1) - Please choose one

Each pass through a loop is called a/an
(a) enumeration



SUBSCRIBE

AR Lucky Bahi



- (b) **Iteration**
- (c) culmination
- (d) pass through

Question No: 7 _____ (Marks:

1) - Please choose one _____

A continue statement causes execution to skip to

- (a) the return 0; statement
- (b) the first statement after the loop
- (c) the statements following the continue statement
- (d) the next iteration of the loop

Question No: 8 _____ (Marks:

1) - Please choose one _____

What is the correct syntax to declare an array of size 10 of int data type?

- (a) int [10] name ;
- (b) name[10] int ;
- (c) **int name[10] ;**



SUBSCRIBE

AR Lucky Bahi



(d) `int name[] ;`

Question No: 9 (Marks:

1) - Please choose one

Consider the following code segment. What will the following code segment display?

```
int main(){
int age[10] =
{0};cout <<
age ;
}
```

- (a) Values of all elements of array
- (b) Value of first element of array
- (c) Starting address of array
- (d) Address of last array element

Question No: 10 (Marks:

1) - Please choose one

What will be the correct syntax to initialize all elements of two-dimensional array to value 0?

- (a) `int arr[2][3] = {0,0} ;`
- (b) `int arr[2][3] = {{0},{0}} ;`
- (c) `int arr[2][3] = {0},{0} ;`
- (d) `int arr[2][3] = {0} ;`

Question No: 11 (Marks:

1) - Please choose one

How many bytes will the pointer *intPtr* of type `int` move in the following statement?

```
intPtr += 3 ;
```



SUBSCRIBE

AR Lucky Bahi



- (a) 3 bytes
- (b) 6 bytes
- (c) 12 bytes
- (d) 24 bytes

Question No: 12 (Marks: 1) - Please choose one

If there are $2^{(n+1)}$ elements in an array then what would be the number of iterations required to search a number using binary search algorithm?

- (a) n elements
- (b) $n+1$ elements
- (c) $2(n+1)$ elements
- (d) $2^{(n+1)}$ elements



Question No: 13 (Marks: 1) - Please choose one

Which of the following operator is used to access the value of variable pointed to by a pointer?

- (a) * operator
- (b) -> operator
- (c) && operator
- (d) & operator

Question No: 14 (Marks: 1) - Please choose one

The _____ statement interrupts the flow of control.

- (a) switch
- (b) continue
- (c) goto
- (d) break

Question No: 15 (Marks: 1) - Please choose one

Analysis is the-----step in designing a program

- (a) Last
- (b) Middle
- (c) Post Design
- (d) First

Question No: 16 (Marks: 1) - Please choose one



Paying attention to detail in designing a program is ____

- (a) Time consuming
- (b) Redundant
- (c) **Necessary**
- (d) Somewhat Good

Q1

When the if statement consists more than one statement then enclosing these



AR Lucky Term

statement in curly braces is,

- (a) Not required
- (b) Good programming
- (c) Relevant
- (d) **Must**

Q2

The while loop becomes infinite,

- (a) When the condition is always false
- (b) . When the condition is less than zero
- (c) **When the condition is always true**
- (d) When the condition contains a logical operator

Q3

Which of the following function(s) is/are included in stdlib.h header file?

- (a) double atof(const char *nptr)
- (b) int atoi(const char *nptr)
- (c) char *strcpy (char *s1, const char *s2)
- (d) **1 and 2 only**

Q4

If we want to store a string “abc” in an array str then the size of this array must be at least,

- (a) **2**
- (b) 3
- (c) 4
- (d) 5

Q5



AR Lucky Term

No executable code will be generated if error is found during translation of the program using interpreter.

- (a) True
- (b) False

Q6

Word processor is

- (a) Operating system
- (b) Application software
- (c) Device driver
- (d) Utility software

Q7

Which of the following is the correct syntax to print multiple values or variables in



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

a single command using cout?

(a) `cout << "Hello" + x + "\n";`

(b) `cout << "H" << x << "\n";`

(c) `cout << "H", x, "\n";`

(d) `cout << ("H" & x & "\n");`

Q8

Which of the following is correct way to initialize a variable x of int type with value 10?

(a) `int x ; x = 10 ;`

(b) `int x = 10 ;`

(c) `int x, x = 10;`

(d) `x = 10 ;`

Q9

If there is more than one statement in the block of a for loop, which of the following must be placed at the beginning and the ending of the loop block?

(a) parentheses ()

(b) braces { }

(c) brackets []

(d) arrows < >

Q10

Name of an array is a constant pointer.

(a) True

(b) False

Q11



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

How many bytes will the pointer *intPtr* of type `int` move in the following statement?

```
intPtr += 3  
;
```

- (a) 3 bytes
- (b) 6 bytes
- (c) 12 bytes
- (d) 24 bytes

Q12

What will be the value of 'a' and 'b' after executing the following statements?

```
a = 3;  
b = a++;
```

(a) 3, 4

(b) 4, 4



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (c) 3, 3
- (d) 4, 3

Q13

Loader loads the executable code from hard disk to main memory.

- (a) True
- (b) False

Q14

Which of the following is used with bit manipulation?

- (a) Signed integer
- (b) Un-signed integer
- (c) Signed double
- (d) Un-signed double

Q15

Which of the following values C++ use to represent true and false?

- (a) 1 and 0
- (b) 1 and -1
- (c) 11 and 00
- (d) Any numerical value

Q16

The argument of the isdigit() function is _____

- (a) a character,
- (b) a C-string,
- (c) a C++ string class variable
- (d) None of the given options.

Question No: 1

(Marks:



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

1) - Please choose one

A precise sequence of steps to solve a problem is called

- ▶ Statement
- ▶ Program
- ▶ Utility
- ▶ Routine

Question No: 2

(Marks:

1) - Please choose one

The Compiler of C language is written in

- ▶ Java Language
- ▶ UNIX
- ▶ FORTRON Language
- ▶ C Language

Question No: 3

(Marks:

1) - Please choose one

Initialization of variable at the time of definition is,

- ▶ Must
- ▶ Necessary
- ▶ Good Programming
- ▶ None of the given options

Question No: 4

(Marks:

1) - Please choose one

In if structure the block of statements is executed only,

- ▶ When the condition is false
- ▶ When it contain arithmetic operators
- ▶ When it contain logical operators
- ▶ When the condition is true

Question No: 5

(Marks:



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

1) - Please choose one

Which of the following function(s) is/are included in stdlib.h header file?

- ▶ double atof(const char *nptr)
- ▶ int atoi(const char *nptr)
- ▶ char *strcpy (char *s1, const char *s2)
- ▶ 1 and 2 only

Question No: 6

(Marks:

1) - Please choose one

Dealing with structures and functions passing by reference is the most economical method

- ▶ True
- ▶ False

Question No: 7(Marks: 1) - Please choose one



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Pointer is a variable which store,

- ▶ Data
- ▶ Memory Address
- ▶ Data Type
- ▶ Values

Question No: 8 (Marks:

1) - Please choose one

Preprocessor program perform its function before phase takes place.

- ▶ Editing
- ▶ Linking
- ▶ Compiling
- ▶ Loading

Question No: 9 (Marks:

1) - Please choose one

Which of the following can not be a variable name?

- ▶ area
- ▶ _area
- ▶ 10area
- ▶ area2

Question No: 10 (Marks:

1) - Please choose one

Which looping process is best, when the number of iterations is known?

- ▶ for
- ▶ while
- ▶ do-while
- ▶ all looping processes require that the iterations be known

Question No: 11 (Marks:



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

1) - Please choose one

Which character is inserted at the end of string to indicate the end of string?

- ▶ new line
- ▶ tab
- ▶ **null**
- ▶ carriage return

Question No: 12

(Marks:

1) - Please choose one

How many bytes are occupied by declaring following array of characters?
char str[] = "programming";

- ▶ 10
- ▶ 11
- ▶ 12
- ▶ 13

Question No: 13

(Marks: 1) - Please choose one



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

Which of the following header file defines the rand() function?

- ▶ iostream.h
- ▶ conio.h
- ▶ **stdlib.h**
- ▶ stdio.h

Question No: 14

(Marks:

1) - Please choose one

Commenting the code _____

- ▶ Makes a program easy to understand for others.
- ▶ Make programs heavy, i.e. more space is needed for executable.
- ▶ Makes it difficult to compile
- ▶ All of the given options.

Question No: 15

(Marks:

1) - Please choose one

What's wrong with this

for loop? for (int k = 2, k
<=12, k++)

- ▶ the increment should always be ++k
- ▶ the variable must always be the letter i when using a for loop
- ▶ there should be a semicolon at the end of the statement
- ▶ **the commas should be semicolons**

Question No: 16

(Marks: 1) - Please choose one

For which array, the size of the array should be one more than the number of elements in an array?

- ▶ int
- ▶ **double**
- ▶ float
- ▶ char

Q1



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

In C/C++ the string constant is enclosed

- (a) In curly braces
- (b) In small braces
- (c) In single quotes
- (d) In double quotes

Q2

In flow chart, the symbol used for decision making is,

- a) Rectangle
- b) Circle
- c) Arrow
- d) Diamond

Q3

The data type before a function name represents its,



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (a) Return Type
- (b) Function data
- (c) Function arguments
- (d) Function name

Q4

The operator used to take the address of a variable is,

- (a) &&
- (b) ++
- (c) —
- (d) &

Q5

The header file which is used for input and output is

- (a) maths.h
- (b) string.h
- (c) iostream.h
- (d) ctype.h

Q6

When we are using command line argument(s), the default argument in C/C++ is/are__.

- a) argc
- b) argd
- c) argv
- d) argc and argv

Q7

In C++, Integer calculation occurs in bytes.

- a) 1 byte
- b) 2 bytes
- c) 4 bytes
- d) 8 bytes

Q8



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

In the declaration of two dimensional array,

- (a) First index represents row and second represents column
- (b) First index represents column and second represents row
- (c) Both indexes represent rows
- (d) Both indexes represent column

Q9

The address operator (&) can be used with,

- a) Statement
- b) Expression
- c) Variable
- d) Constant

Q10

_____ translates high level language program into machine language code

- (a) Debugger



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

- (b) Editor
- (c) **Compiler**
- (d) L

inkerQ11

Which of the following data type(s) can operate on modulus operator '%'?

- a) **float, int**
- b) float, double
- c) int
- d) cha

rQ12

What will be the result of the expression $z = x \% y$, if $x = 19$ and $y = 4$?

- a) **3**
- b) 4
- c) 15
- d) 1

9Q13

Which character is inserted at the end of string to indicate the end of string?

- a) new line
- b) tab
- c) **null**
- d) carriage

returnQ14

What will be the value of i and j in the following code segment?

```
int i, j ;
int x[5] = {2, 3, 4, 8, 9} ;
int *ptr
=&x[2]; i =
(*ptr)++ ;
j = *ptr++ ;
```



SUBSCRIBE

AR Lucky Bahi



AR Lucky Term

a) $i = 5, j = 5$

b) $i = 5, j = 8$

c) $i = 4, j = 8$

d) $i = 5, j = 9$

Q15

Syntax of union is identical to _

a) **Structure**

b) Class

c) Function

d) None of the given options

Q16

Let suppose

Union

```
intorDouble{ Int  
ival;
```

```
Double charvar;
```



SUBSCRIBE

AR Lucky Bahi




```
};
```

```
main(){  
    intorDouble  
    VAZ;int size ;  
  
    size = sizeof(VAZ);  
  
}
```

What will be the value of variable "size", if int occupies 4 bytes and double occupies 8 bytes?

- a) 2
- b) 4
- c) 8
- d) 1

2

Q1

What is function of cout ?

- (a) To send data to printer
- (b) To read data from keyboard
- (c) To display message
- (d) To display output on the screen

Q2

In Flow chart process is represented by

- (a) Rectangle
- (b) Arrow symbol
- (c) Oval
- (d) Circle



SUBSCRIBE

AR Lucky Bahi



Q3

&& is ----- operator.

- (a) An arithmetic
- (b) **Logical**
- (c) Relational
- (d) Unary

Q4



SUBSCRIBE

AR Lucky Bahi



An over Flow condition occurs when we try to assign a value to a variable which is,

- (a) Less than its maximum size
- (b) Greater than its maximum size
- (c) Within its range
- (d) Equal to its size

Q5

For dereferencing an array element using pointer, we use the operator

- (a) &
- (b) *
- (c) /
- (d) +

Q6

In the declaration of two dimensional array,

- (a) First index represents row and second represents column
- (b) First index represents column and second represents row
- (c) Both indexes represent rows
- (d) Both indexes represent column

Q7

Which of the following data type(s) can operate on modulus operator '%'?

- (a) float, int
- (b) float, double
- (c) int
- (d) char

Q8

Which of the following is the correct way to declare a variable x of integer type?

- (a) x int ;
- (b) integer x ;
- (c) int x;



(d) x integer

Q9

Which of the following can not be a variable name?

(a) area

(b) _area

(c) 10area

(d) a

rea2Q10

Which of the function call is *call by value* for the following function prototype? float area (int);

(a) area(&num) ;

(b) area(num) ;

(c) area(int num) ;

(d) area(*

num) ;Q11

Recursive functions are used when there is a repetitive pattern.

(a) True



SUBSCRIBE

AR Lucky Bahi



(b) F

alsoQ12

What will be the range of numbers generated by function `rand () % 9`?

- (a) 0 to 9
- (b) 1 to 9
- (c) 0 to 8
- (d) 1

to 8Q13

What will be the correct syntax to declare two-dimensional array of float datatype?

- (a) `float arr{2}{2} ;`
- (b) `float arr[2][2] ;`
- (c) `float arr[2,2] ;`
- (d) `float[2]`

[2] arr ;Q14

When a function finishes its execution then,

- (a) The control return to its Prototype
- (b) The control returns to its definition
- (c) Control returns to statement following function call
- (d) The compiler stop execution of

whole programQ15

Consider the following statements to initialize a two-dimensional array.

- i. `int arr[2][3] = {4, 8, 9, 2, 1, 6} ;`
- ii. `int arr[3][2] = {4, 8, 9, 2, 1, 6} ;`
- iii. `int arr[][2] = {{4,8},{9, 2},{1, 6}} ;`

Which of the following option(s) are correct to initialize a two-dimensional array with 3 rows and 2 columns?

- (a) (ii) only
- (b) (iii) only
- (c) (ii) and (iii)



SUBSCRIBE

AR Lucky Bahi



(d) (i) and
(iii)Q16
Editors are used to compile the code.

(a) True

(b) False

Q1

What is function of cout ?

(a) To send data to printer

(b) To read data from keyboard

(c) To display message

(d) To display output on the screen

Q2

< , <= , > , >= are called -----operators.



SUBSCRIBE

AR Lucky Bahi



- (a) Logical
- (b) Arithmetic
- (c) Relational
- (d) Conational

Q3

In while loop the loop counter must be initialized,

- (a) With in the loop
- (b) Before entering the loop
- (c) At the end of the loop
- (d) None of the given options

Q4

Data Size of the file is always_____the actual size of the file.

- (a) Greater than
- (b) Equal to
- (c) Less than or equal to
- (d) None of the above

Q5

The precedence of * is higher than dot operator (.)operator

- (a) True
- (b) False

Q6

Let ptr1 and ptr2 are pointer variables that points to integer data type then whichone of the following arithmetic is allowed,

- (a) $\text{ptr1} + \text{ptr2}$
- (b) $\text{ptr1} - \text{ptr2}$
- (c) $\text{ptr1} * \text{ptr2}$
- (d) $\text{ptr1} / \text{ptr2}$

Q7

Word processor is

- (a) Operating system
- (b) Application software
- (c) Device driver



SUBSCRIBE

AR Lucky Bahi



(d) Utility software

Q8

What will be the range of numbers generated by function `rand () % 9`?

(a) 0 to 9

(b) 1 to 9

(c) 0 to 8

(d) 1 to 8

Q9

How many bytes will the pointer *intPtr* of type `int` move in the following statement?

```
intPtr += 3 ;
```

(a) 3 bytes

(b) 6 bytes

(c) 12 bytes



SUBSCRIBE

AR Lucky Bahi



(d) 24

bytesQ10

What will be the correct syntax to assign an array named *arr* of 5 elements to a pointer *ptr*?

(a) `*ptr = arr ;`

(b) `ptr = arr ;`

(c) `*ptr = arr[5] ;`

(d) `ptr =`

`arr[5] ;`Q11

What will be the output of the following code segment?

```
char *x = "programming" ;
```

```
cout << *(x+2) << *(x+3) << *(x+5) << *(x+8) ;
```

(a) prgm

(b) rorm

(c) ogai

(d) r

amgQ12

There is a pointer variable named *ptr* of type `int` then address of which type of variable the *ptr* will store in it?

(a) variable of type `char`

(b) variable of type `short`

(c) variable of type `int`

(d) variable of

type `double`Q13

Flow charts explain the working of a program in pictorial format.

(a) True

(b) F

alseQ14

The object _____ may be used both for file input and file output

(a) `fstream`,



SUBSCRIBE

AR Lucky Bahi



- (b) ifstream,
- (c) ofstream,
- (d) none of the given

options. Q15

Most efficient method of dealing with structure variables is to define the structure globally

- (a) True
- (b) F

also Q16

If a variable is passed by value to a function and the function makes some changes to that variable then it

- (a) does not affect the original variable
- (b) affects the original variable
- (c) causes syntax error
- (d) None of the given options



SUBSCRIBE

AR Lucky Bahi



Q1

In C/C++ language the header file which is used to perform useful task and manipulation of character data is

- (a) cplext.h
- (b) **ctype.h**
- (c) stdio.h
- (d) delay.h

Q2

The header file which is used for input and output is

- (a) maths.h
- (b) string.h
- (c) **iostream.h**
- (d) ctype.h

Q3

Suppose `int multi[5][10];` when we are using `**multi`, it means,

- (a) Single dereferencing
- (b) Single referencing
- (c) **Double referencing**
- (d) Double dereferencing

Q4

To access the data members of structure ____ is used.

- (a) **dot operator (.)**
- (b) * operator
- (c) □ operator
- (d) None of given.

Q5

The precedence of * is higher than dot operator (.) operator

- (a) **True**
- (b) False

Q6

Which of the following is the starting index of an array in C++?

- (a) **0**
- (b) 1



SUBSCRIBE

AR Lucky Bahi



(c)-1

(d) any number

Q7

When a call to function statement is encountered,

(a) The control transfers to its Prototype

(b) The control transfers to its definition

(c) Control returns to statement following function call

(d) The compiler stops execution of whole program

Q8

A function must always return value.

(a) True

(b) False

Q9

If an array has 100 elements, what is allowable range of subscripts?

(a) 0 – 99

(b) 1 – 99

(c) 0 – 100

(d) 1 –

100Q10

If a pointer appears on left hand side of an assignment operator then right side of that assignment operator must be,

(a) Variable name

(b) Address of variable

(c) Variable value

(d) Constant



SUBSCRIBE

AR Lucky Bahi



Q11

Editors are used to compile the code.

- (a) True
- (b) **False**

Q12

Which bitwise operator returns false if both bits are 1?

- (a) AND
- (b) XOR
- (c) NOT
- (d) **OR**

Q13

What does !(7) evaluate to in decimal where ! is a NOT operator?

- (a) **7**
- (b) 8
- (c) 9
- (d) 1

Q14

Structures cannot be passed as Function Parameters

- (a) True
- (b) **False**

Q15

When break statement is encountered in a loop body it,

- (a) **Transfers the control outside from current loop**
- (b) Transfers the control outside from current program
- (c) Enforces the next iteration of loop
- (d) Generates compile

time error.

Q16
A union is a user-defined data type that contains only__from its list of members at a time.



SUBSCRIBE

AR Lucky Bahi



- (a) One object
- (b) Two objects
- (c) Three objects
- (d) None of the given options

Q1

The size of int data type is

- (a) 1 bytes
- (b) 2 bytes
- (c) 3 bytes
- (d) 4 bytes

Q2

When the logical operator AND (&&) combine two expressions exp1 and exp2 then the result will be true only,

- (a) When both exp1 and exp2 are true
- (b) When both exp1 and exp2 are false
- (c) When exp1 is true and exp2 is false
- (d) When exp1 is false and exp2 is true

Q3

The correct syntax of do-while loop is,

- (a) (condition) while; do { statements; };
- (b) { statements; } do-while ();
- (c) while(condition); do { statements; };
- (d) do { statements; } while (condition);

Q4

_____ provide communication channels between files and program.

- (a) Streams
- (b) Language like C++
- (c) Function seekg()
- (d) None of the above

Q5



All elements of an array must be of,

- (a) different data type
- (b) float data only
- (c) character data only
- (d) same data type

Q6

Function seekg() takes _____ parameter(s).

- (a) 0
- (b) 1
- (c) 2
- (d) 3

Q7

Structures help to define program-specific_.

- (a) functions



SUBSCRIBE

AR Lucky Bahi



- (b) datatypes
- (c) Arithmetic operations
- (d) None of the given options.

Q8

In the declaration of two dimensional array,

- (a) First index represents row and second represents column
- (b) First index represents column and second represents row
- (c) Both indexes represent rows
- (d) Both indexes represent column

Q9

What will be the result of arithmetic expression $6 + 27/3 * 3$?

- (a) 33
- (b) 45
- (c) 9
- (d) 3

Q10

Which of the function call is *call by value* for the following function prototype?

float area (int);

- (a) area(&num) ;
- (b) area(num) ;
- (c) area(int num) ;
- (d) area(*

num) ;

Q11
How many bytes are occupied by declaring following array of characters?

char str[] = "programming";

- (a) 10
- (b) 11
- (c) 12



SUBSCRIBE

AR Lucky Bahi



(d) 1

3Q12

What will be the correct syntax to assign an array named *arr* of 5 elements to a pointer *ptr*?

(a) *ptr = arr ;

(b) ptr = arr ;

(c) *ptr = arr[5] ;

(d) ptr =
arr[5] ;

Q13
Let ptr1 and ptr2 are pointer variables then which of the following arithmetic operation is allowed on pointers?

(a) Addition

(b) Subtraction

(c) Multiplication

(d) All of the above

Q14

The variables having a name, type and size are just like empty boxes.



SUBSCRIBE

AR Lucky Bahi



(a) True

(b) F

alsoQ15

When break statement is encountered in a loop body it,

(a) Transfers the control outside from current loop

(b) Transfers the control outside from current program

(c) Enforces the next iteration of loop

(d) Generates compile

time error.Q16

If two programs a and b are trying to open a file xyz.txt at approximately same time then

(a) Both programs will generate error

(b) One of them will succeed in opening that file and other will fail

(c) Both programs will open the file

(d) One of the program

will re-startQ1

The data type of size one byte is

(a) char

(b) int

(c) long

(d) double

Q2

If Num is an integer variable then Num*= 4; means,

(a) Multiply Num 4 times

(b) Multiply 4 with Num and display

(c) Multiply 4 with Num and assign the result to Num

(d) Add 4 with Num

Q3

Member function tellg() returns the current location of the ____ pointer.

(a) tellptr()



SUBSCRIBE

AR Lucky Bahi



(b) write()

(c) seekg()

(d) get()

Q4

If we want to store a string “abc” in an array str then the size of this array must be at least,

(a) 2

(b) 3

(c) 4

(d) 5

Q5

Pointer is a variable which stores,

(a) Values

(b) Data

(c) Memory Address

(d) Data Type

Q6

C is widely known as development language of operating system.

(a) Linux

(b) Windows

(c) Unix

(d) Mac

OS

Q7
C++ is a case-sensitive language

(a) True

(b) False



SUBSCRIBE

AR Lucky Bahi



Q8 What is the output of the following code?

```
for (int a = 1; a <= 1; a++) cout << a++; cout << a;
```

- (a) 22
- (b) 12
- (c) 23
- (d) 13

Q9

A continue statement causes execution to skip to (a) the return 0; statement

- (b) the first statement after the loop
- (c) the statements following the continue statement
- (d) the next iteration of the loop

Q10

If there is more than one statement in the block of a for loop, which of the following must be placed at the beginning and the ending of the loop block?

- (a) parentheses ()
- (b) braces { }
- (c) brackets []
- (d) arro

ws < > Q11

What will be the correct syntax for the following function call?

```
float square (int  
    &);
```

- (a) square (int num);
- (b) square (&num);
- (c) square (num);
- (d) square
(*num);

Q12 Which of the following is the correct way to assign an integer value 5 to element of a matrix say 'm' at second row and third



SUBSCRIBE

AR Lucky Bahi



column?

(a) `m[2][3] = 5 ;`

(b) `m[3][2] = 5 ;`

(c) `m[1][2] = 5 ;`

(d) `m[2][3]`

= '5'; Q13

How many dimensions does n-dimensional array has?

(a) `n dimensions`

(b) `2n dimensions`

(c) `(n+1) dimensions`

(d) `(n-1)`

dimensions Q14

Consider the following code segment. What will be the output of following code?

```
int addValue (int  
*a){ int b = (*a) +  
2; return b ;
```



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



```
}  
main ()  
{int x  
=6 ;  
cout << x << “,” ;  
cout << addValue(&x)  
<< “,” ;cout << x ;  
}
```

(a) 6,8,6

(b) 6,6,8

(c) 6,8,8

(d)

6,6,6Q15

If most significant bit of un-signed number is 1 then it represents a positive number.

(a) True

(b) F

alsoQ16

When we declare a multidimensional array the compiler store the elements of multidimensional array in the form of,

(a) Contiguous memory location

(b) Matrix

(c) Columns

(d) R

ows

Q1

What is function of cout ?

(a) To send data to printer

(b) To read data from keyboard

(c) To display message



SUBSCRIBE

AR Lucky Bahi



(d) To display output on the screen

Q2

For one byte there are ___ combinations of values that can be stored in computer.

(A) 2^6

(B) 2^7

(C) 2^8

(D) 2^4

Q3

_____ provide communication channels between files and program.

(a) Streams

(b) Language like C++

(c) Function `seekg()`

(d) None of the above

Q4

The data type before a function name represents its,

(a) Return Type

(b) Function data

(c) Function arguments

(d) Function name

Q5

In C/C++ language when an array is passed to a function then by default its passing mechanism is,

(a) Call by value

(b) Call by Reference

(c) It depends on type of array

(d) It depends on the return type of function.

Q6

Array is a data structure which store

(a) Memory addresses

(b) Variables

(c) Data Type

(d) Data



SUBSCRIBE

AR Lucky Bahi



Q7

If there is more than one statement in the block of a for loop, which of the following must be placed at the beginning and the ending of the loop block?



SUBSCRIBE

AR Lucky Bahi



- (a) parentheses ()
- (b) braces { }
- (c) brackets []
- (d) arrows < >

Q8

Array is passed by value to a function by default.

- (a) True
- (b) False

Q9

Which of the following is the correct function call having array named *student* of 10 elements as a parameter.

- (a) addRecord(student[]) ;
- (b) addRecord(student) ;
- (c) addRecord(student[10]) ;
- (d) addRecord(*student) ;

Q10

What will be the correct syntax for initialization of pointer *ptr* of type int with variable *x*?

- (a) int ptr = &x ;
- (b) int ptr = x ;
- (c) int *ptr = &x ;
- (d) int

ptr* = &x ;

Q11
What will be the correct syntax for initialization of pointer *ptr* with string "programming"?

- (a) char ptr = 'programming' ;
- (b) char *ptr = "programming" ;
- (c) char *ptr = 'programming' ;
- (d) *ptr =

"programming" ;

Q12
The condition in while loop may contain logical expression but not relational expression.

- (a) True



SUBSCRIBE

AR Lucky Bahi



(b) F

also Q13

We want to access array in random order which approach is better?

(a) Pointers

(b) Array index

(c) Both pointers and array index are better

(d) None of the

given options. Q14

Single line comments explaining code would be preceded like in the following example.

(a) /*

(b) //

(c) /



SUBSCRIBE

AR Lucky Bahi



(d)

/*Q15

Function write() takes _____ as parameter(s).

- (a) String of pointer type
- (b) String and no. of bytes to be written
- (c) Pointer array of characters and delimiter
- (d) String of variable lengths, no. of bytes to be read and flags

Q16

Structure is a collection of _____ under a single name.

- (a) Only Functions
- (b) Only Variables
- (c) Both Functions and Variables
- (d) None of the given options

Q1

Compiler is a

- (a) System software
- (b) Application Software
- (c) Driver
- (d) Editor

Q2

In while loop the loop counter must be initialized,

- (a) With in the loop
- (b) Before entering the loop
- (c) At the end of the loop
- (d) None of the given options

Q3

If Num is an integer variable then Num*= 4; means,



SUBSCRIBE

AR Lucky Bahi



- (a) Multiply Num 4 times
- (b) Multiply 4 with Num and display
- (c) Multiply 4 with Num and assign the result to Num
- (d) Add 4 with Num

Q4

In C/C++ ,the arguments are passed by__to a function by default .

- (a)reference
- (b) value
- (c)data
- (d) type

Q5

Disk is divided into_____with power of_____.

- (a) Chunks, 2^n
- (b) Blocks, n^2
- (c) Blocks, 2^n
- (d) Chunks, n^2

Q6

C is widely known as development language of _operating system.

- (a)Linux
- (b) Windows
- (c)Unix
- (d) Mac OS

Q7

Assignment operator '=' is a

- (a)Unary operator



SUBSCRIBE

AR Lucky Bahi



- (b) Binary operator
- (c) Ternary operator
- (d) None of the given options

Q8

Consider the following code segment. What will be the output of the following program?

```
int func(int)
; int num =
10 ;
```

```
int
main(){
int num ;
num = 5
;
```

```
cout << num ;
```

```
cout << func(num) ;
```

```
}
```

```
int func(int
x){return
num ;
```

```
}
```

(a) 5, 5

(b) 10, 5



SUBSCRIBE

AR Lucky Bahi



- (c) 5, 10
- (d) 10, 10

Q9

Name of an array is a constant pointer.

- (a) True
- (b) F

also Q10

What will be the correct syntax to assign an array named *arr* of 5 elements to a pointer *ptr*?

- (a) `*ptr = arr ;`
- (b) `ptr = arr ;`
- (c) `*ptr = arr[5] ;`
- (d) `ptr =`

`arr[5] ;` Q11

If there are $2^{(n+1)}$ elements in an array then what would be the number of iterations required to search a number using binary search algorithm?

- (a) n elements
- (b) $(n+1)$ elements
- (c) $2(n+1)$ elements
- (d) $2^{(n+1)}$

elements Q12

In C/C++, null character is represented as

- (a) `\n`
- (b) `\0`



SUBSCRIBE

AR Lucky Bahi



(c) \t

(d) \

rQ13

How many nested loop would be required to manipulate n-dimensional array?

(a) $2n$

(b) **n**

(c) $n + 1$

(d) n

-1Q14

What will be the correct syntax to access the value of fourth element of an array using pointer ptr?

(a) **ptr[3]**

(b) (ptr+3)

(c) *(ptr+3)

(d) Both

1and 3Q15

Single line comments explaining code would be preceded like in the following example.

(a) /*

(b) **//**

(c) /

(d)

/*Q16

If a variable is passed by value to a function and the function makes some changes to that variable then it

(a) **does not affect the original variable**

(b) affects the original variable

(c) causes syntax error

(d) None of the

given options

Q1

There are mainly ----- types of software



SUBSCRIBE

AR Lucky Bahi



(a) Two

(b) Three

(c) Four

(d) Five

Q2

$<$, $\leq$, $>$, $\geq$ are called -----operators.

(a) Logical

(b) Arithmetic

(c) Relational

(d) Conational

Q3

In order to get 256 from the number 2568 we divide this number by 10 and take,

(a) Its remainder

(b) The number

(c) Its quotient

(d) Its divisor

Q4



SUBSCRIBE

AR Lucky Bahi



If $\text{int } x = 10$; then the value of $x /= 3$; will be,

- (a) 10
- (b) 3
- (c) 13
- (d) 1

Q5

How many parameter(s) function `getline()` takes?

- (a) 0
- (b) 1
- (c) 2
- (d) 3

Q6

Suppose `int multi[5][10]`; when we are using `**multi`, it means,

- (a) Single dereferencing
- (b) Single referencing
- (c) Double referencing
- (d) Double dereferencing

Q7

To access the data members of structure ____ is used.

- (a) dot operator (.)
- (b) * operator
- (c) □ operator
- (d) None of given.

Q8

There is NO difference between bitwise AND operator (&) and Logical AND(&&) operator.

- (a) True
- (b) False

Q9

Which of the following data type(s) can operate on modulus operator '%'?

- (a) float, int
- (b) float, double
- (c) int



SUBSCRIBE

AR Lucky Bahi



(d) c

harQ10

What's wrong with this

while loop?
while((i < 10)
&& (i > 24))

(a) the logical operator && cannot be used in a test condition

(b) the while loop is an exit-condition loop

(c) the while loop is an exit-condition loop

(d) the test condition is

always trueQ11

The switch structure is a _____ construct

(a) single-selection

(b) bi-selection



SUBSCRIBE

AR Lucky Bahi



(c) multiple-selection

(d) uncon

ditionalQ12

Keyword 'array' must be used to declare an array.

(a) True

(b) F

alseQ13

What will be the correct syntax to declare two-dimensional array of float datatype?

(a) float arr{2}{2} ;

(b) float arr[2][2] ;

(c) float arr[2,2] ;

(d) float[2]

[2] arr ;Q14

When an array element is passed to a function then this array element is passed to the function,

(a) By reference

(b) By data type

(c) By value

(d) B

y dataQ15

Which of the following operator is used to access the value of variable pointed to by a pointer?

(a) * operator

(b) -> operator

(c) && operator

(d) & operator

Q16

Paying attention to detail in designing a program is _

(a) Time consuming

(b) Redundant

(c) Necessary

(d) Somewha



SUBSCRIBE

AR Lucky Bahi



t GoodQ1

The remainder (%) operator is

- (a) A logical operator
- (b) **An arithmetic operator**
- (c) A relational operator
- (d) A division operator

Q2

If `int sum = 10;` then the value of the statement `sum = sum + 3 ;` is ,

- (a) 7
- (b) Illegal statement
- (c) Garbage value
- (d) **13**

Q3

Which of the following function(s) is/are included in `ctype.h` header file?

- (a) `isdigit(int c)`
- (b) `isxdigit(int c)`
- (c) `tolower(int c)`
- (d) **All of the above**

Q4

In C/C++ which of the following header file is used for string manipulation?

- (a) **`stdlib.h`**
- (b) `string.h`



SUBSCRIBE

AR Lucky Bahi



(c) strings.h

(d) stype.h

Q5

_____ provide communication channels between files and program.

(a) Streams

(b) Language like C++

(c) Function seekg()

(d) None of the above

Q6

_____ translates high level language program into machine language code

(a) Debugger

(b) Editor

(c) Compiler

(d) Linker

Q7

Which of the following data type(s) can operate on modulus operator '%'?

(a) float, int

(b) float, double

(c) int

(d) char

Q8

C++ is a case-sensitive language

(a) True

(b) False

Q9

To include code from the library in the program, such as iostream, a directive would be called up using this command.

(a) #include "iostream.h"

(b) include <iostream.h>

(c) include <iostream.h>

(d) #include
<iostream.h>

Q10



SUBSCRIBE

AR Lucky Bahi



What will be the range of numbers generated by function `rand () % 9`?

- (a) 0 to 9
- (b) 1 to 9
- (c) 0 to 8
- (d) 1

to 8Q11

An array stores the numbers into consecutive memory locations.

- (a) True
- (b) F

alsoQ12

Which of the following is the correct statement for the following declaration? `const int *ptr`.

- (a) `ptr` is a constant pointer
- (b) `ptr` is constant integer pointer



SUBSCRIBE

AR Lucky Bahi



(c) ptr is a constant pointer to int

(d) ptr is a constant

pointer to intQ13

Which of the following header file defines the rand() function?

(a) iostream.h

(b) conio.h

(c) **stdlib.h**

(d) s

tdio.hQ14

Consider the following code segment. What will be the output of following code?

```
int addValue (int
*a){ int b = (*a) +
2; return b ;
}
main ()
{ int x
=6 ;
cout << x << “,” ;
cout << addValue(&x)
<< “,” ;cout << x ;
}
```

(a) **6,8,6**

(b) 6,6,8

(c) 6,8,8

(d)

6,6,6Q15

Identifier is a name that can be given to variables, labels and functions.

(a) **True**

(b) F

alseQ16

For which array, the size of the array should be one more than



SUBSCRIBE

AR Lucky Bahi



the number of elements in an array?

- (a) Int
- (b) Char
- (c) Double
- (d) float

Q1

In C/C++ language the header file which is used to perform useful task and manipulation of character data is

- (e) cplex.h
- (f) ctype.h
- (g) stdio.h
- (h) delay.h

Q2

The header file which is used for input and output is

- (e) maths.h
- (f) string.h
- (g) iostream.h
- (h) ctype.h

Q3

Suppose `int multi[5][10]`; when we are using `**multi`, it means,

- (e) Single dereferencing
- (f) Single referencing
- (g) Double referencing
- (h) Double dereferencing

Q4

To access the data members of structure ____ is used.

- (e) dot operator (.)
- (f) * operator
- (g) □ operator
- (h) None of given.

Q5

The precedence of * is higher than dot operator (.) operator



SUBSCRIBE

AR Lucky Bahi



- (c) True
- (d) False

Q6

Which of the following is the starting index of an array in C++?

- (e) 0
- (f) 1
- (g) -1
- (h) any number

Q7

When a call to function statement is encountered,

- (e) The control transfers to its Prototype
- (f) The control transfers to its definition
- (g) Control returns to statement following function call
- (h) The compiler stops execution of whole program

Q8

A function must always return value.



SUBSCRIBE

AR Lucky Bahi



- (c) True
- (d) False

Q9

If an array has 100 elements, what is allowable range of subscripts?

- (e) 0 – 99
- (f) 1 – 99
- (g) 0 – 100

(h) 1 – 100

Q10
If a pointer appears on left hand side of an assignment operator then right side of that assignment operator must be,

- (e) Variable name
- (f) Address of variable
- (g) Variable value
- (h) Co

Q11
Editors are used to compile the code.

- (c) True
- (d) False

Q12

Which bitwise operator returns false if both bits are 1?

- (e) AND
- (f) XOR
- (g) NOT
- (h) OR

Q13

What does !(7) evaluate to in decimal where ! is a NOT operator?

- (e) 7



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



(f) 8

(g) 9

(h) 1

Q14

Structures cannot be passed as Function Parameters

(c) True

(d) False

Q15

When break statement is encountered in a loop body it,

(e) Transfers the control outside from current loop

(f) Transfers the control outside from current program

(g) Enforces the next iteration of loop

(h) Generates compile

time error. Q16

A union is a user-defined data type that contains only__from its list of members at a time.

(e) One object



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- (f) Two objects
- (g) Three objects
- (h) None of the given options

Question No: 1 (Marks: 1) - Please choose one

In order to get 256 from the number 2568 we divide this number by 10 and take,

- ▶ Its remainder
- ▶ The number
- ▶ Its quotient
- ▶ Its divisor

Question No: 2 (Marks: 1) - Please choose one

The correct syntax of do-while loop is,

- ▶ (condition) while; do { statements; };
- ▶ { statements; } do-while ();
- ▶ while(condition); do { statements; };
- ▶ do { statements; } while (condition);

Question No: 3 (Marks: 1) - Please choose one

Which of the following function(s) is/are included in stdlib.h header file?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- ▶ double atof(const char *nptr)
- ▶ int atoi(const char *nptr)
- ▶ char *strcpy (char *s1, const char *s2)
- ▶ 1 and 2 only

Question No: 4 (Marks: 1) - Please choose one

If the break statement is missed in switch statement then,

- ▶ The compiler will give error
- ▶ This may cause a logical error
- ▶ No effect on program
- ▶ Program stops its execution

Question No: 5 (Marks: 1) - Please choose one

The data type before a function name represents its,

- ▶ Return Type
- ▶ Function data
- ▶ Function arguments
- ▶ Function name

Question No: 6 (Marks: 1) - Please choose one

Member function tellg() returns the current location of the -
_____ pointer.

- ▶ tellptr()



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



▶ write()

▶ seekg()

▶ get()

Question No: 7 (Marks: 1) - Please choose one

What does $5 | 6$, evaluate to in decimal where '|' is bitwise OR operator?

3 ▶

4 ▶

5 ▶

7 ▶

Question No: 8 (Marks: 1) - Please choose one

C is widely known as development language of _____ operating system.

▶ Linux

▶ Windows



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



▶ Unix

▶ Mac OS

Question No: 9 (Marks: 1) - Please choose one

What will be the result of arithmetic expression $6 + 27/3 * 3$?

▶ 33

▶ 45

▶ 9

▶ 30

Question No: 10 (Marks: 1) - Please choose one

How many bytes are occupied by declaring following array of characters?

`char str[] = "programming";`

▶ 10

▶ 11

▶ 12

▶ 13

Question No: 11 (Marks: 1) - Please choose one

What will be the correct syntax for initialization of pointer *ptr* with string "programming"?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



▶ char ptr = 'programming' ;

▶ char *ptr = "programming" ;

▶ char *ptr = 'programming' ;

▶ *ptr = "programming" ;

Question No: 12 (Marks: 1) - Please choose one

What will be the result of expression $x \% 2$, if $x = 7$?

$x = 1$ ▶

$x = 3$ ▶

$x = 7$ ▶

$x = 2$ ▶

Question No: 13 (Marks: 1) - Please choose one

UNIX has been developed in _____ language.

JAVA ▶

B ▶

C ▶



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



FORTRAN ►

Question No: 14 (Marks: 1) - Please choose one

Declaring structures does not mean that memory is allocated.

True ►

False ►

Question No: 15 (Marks: 1) - Please choose one

What will be the value of i and j in the following code segment?

```
int i, j ;
```

```
int x[5] = {2, 3, 4, 8, 9} ;
```

```
int *ptr =&x[2];
```

```
i = (*ptr)++ ;
```

```
j = *ptr++ ;
```

i = 5, j = 5 ►

i = 5, j = 8 ►

i = 4, j = 8 ►

i = 5, j = 9 ►

Question No: 16 (Marks: 1) - Please choose one



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



When an array element is passed to a function, it is passed by -----
--.

reference ►

data type ►

value ►

data ►

Question No: 1 (Marks: 1) - Please choose one

A precise sequence of steps to solve a problem is called

► Statement

► Program

► Utility

► Routine

Question No: 2 (Marks: 1) - Please choose one

The Compiler of C language is written in

► Java Language

► UNIX



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- ▶ FORTRON Language
- ▶ C Language

The C language is so powerful that the compiler of C and other various operating systems are written in C.

Question No: 3 (Marks: 1) - Please choose one

Initialization of variable at the time of definition is,

- ▶ Must
- ▶ Necessary
- ▶ Good Programming
- ▶ None of the given options

Question No: 4 (Marks: 1) - Please choose one

In if structure the block of statements is executed only,

- ▶ When the condition is false
- ▶ When it contain arithmetic operators
- ▶ When it contain logical operators
- ▶ When the condition is true

Question No: 5 (Marks: 1) - Please choose one

Which of the following function(s) is/are included in stdlib.h header file?

- ▶ double atof(const char *nptr)
- ▶ int atoi(const char *nptr)



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- ▶ `char *strcpy ( char *s1, const char *s2)`
- ▶ 1 and 2 only

Question No: 6 (Marks: 1) - Please choose one

Dealing with structures and functions passing by reference is the most economical method

- ▶ True
- ▶ False

Question No: 7 (Marks: 1) - Please choose one

Pointer is a variable which store,

- ▶ Data
- ▶ Memory Address
- ▶ Data Type
- ▶ Values

Question No: 8 (Marks: 1) - Please choose one

Preprocessor program perform its function before _____ phase takes place.

- ▶ Editing
- ▶ Linking



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- ▶ Compiling
- ▶ Loading

The C preprocessor modifies a source code file before handing it over to the compiler. You're most likely used to using the preprocessor to include files directly into other files,

Question No: 9 (Marks: 1) - Please choose one

Which of the following can not be a variable name?

- ▶ area
- ▶ _area
- ▶ 10area
- ▶ area2

Question No: 10 (Marks: 1) - Please choose one

Which looping process is best, when the number of iterations is known?

- ▶ for
- ▶ while
- ▶ do-while
- ▶ all looping processes require that the iterations be known

Question No: 11 (Marks: 1) - Please choose one

Which character is inserted at the end of string to indicate the end of string?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- ▶ new line
- ▶ tab
- ▶ null
- ▶ carriage return

null character inserted at the end of the string by C automatically

Question No: 12 (Marks: 1) - Please choose one

How many bytes are occupied by declaring following array of characters?

`char str[] = "programming";`

- ▶ 10
- ▶ 11
- ▶ 12
- ▶ 13

11 plus one for null char (11+1= 12)

Question No: 13 (Marks: 1) - Please choose one

Which of the following header file defines the `rand()` function?

- ▶ `iostream.h`
- ▶ `conio.h`
- ▶ `stdlib.h`
- ▶ `stdio.h`



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



The function is *rand()* and is in the standard library. To access this function, we need to include `<stdlib.h>` library in our program. This function will return a random number. The number can be between 0 and 32767.

Question No: 14 (Marks: 1) - Please choose one

Commenting the code _____

- ▶ Makes a program easy to understand for others.
- ▶ Make programs heavy, i.e. more space is needed for executable.
- ▶ Makes it difficult to compile
- ▶ All of the given options.

Question No: 15 (Marks: 1) - Please choose one

What's wrong with this for loop?

`for (int k = 2, k <=12, k++)`

- ▶ the increment should always be `++k`
- ▶ the variable must always be the letter `i` when using a for loop
- ▶ there should be a semicolon at the end of the statement
- ▶ the commas should be semicolons

Question No: 16 (Marks: 1) - Please choose one

For which array, the size of the array should be one more than the number of elements in an array?

- ▶ `int`



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- ▶ double
- ▶ float
- ▶ char

Question No: 1 (Marks: 1) - Please choose one

In C/C++ the #include is called,

Header file

[Preprocessor](#) Directive

Statement

Function

Question No: 2 (Marks: 1) - Please choose one

To access the element of two dimensional array we use,

Single referencing

Single dereferencing

Double [dereferencing](#)

Double referencing

Question No: 3 (Marks: 1) - Please choose one

Data Size of the file is always _____ the actual size of the file.

[Greater](#) than

Equal to

Less than or equal to

None of the above



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question No: 4 (Marks: 1) - Please choose one

When an identifier is declared with keyword const then,
Its value can be changed during execution.

[Its value can not be changed](#)

Its value can be changed with arithmetic operator

Its value can be overwritten

Question No: 5 (Marks: 1) - Please choose one

In C/C++ if we define an array of size eight (8) i.e. int Arr [8]; then the last element of this array will be stored at,

Arr[0]

Arr[8]

[Arr\[7\]](#)

Arr[-1]

Question No: 6 (Marks: 1) - Please choose one

If it is required to copy an array to another array then,

[Both arrays must be of the same size and data type](#)

Both arrays may be of different size

Both arrays may be of different data type

Both arrays may be of different size and type

Question No: 7 (Marks: 1) - Please choose one

In C/C++ all character strings are terminated with,



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Null character

String

Zero

Full stop

Question No: 8 (Marks: 1) - Please choose one

Let suppose

```
struct intorDouble{
```

```
Int ival;
```

```
Double charvar;
```

```
};
```

```
main(){
```

```
intorDouble VAZ;
```

```
int size ;
```

```
size = sizeof(VAZ);
```

```
}
```

What will be the value of variable size, if int occupies 4 bytes and double occupies 8

bytes?

2

4

8

12



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question No: 9 (Marks: 1) - Please choose one

When a pointer is incremented, it actually jumps the number of memory addresses

[According to data type](#)

1 byte exactly

1 bit exactly

A pointer variable can not be incremented

Question No: 10 (Marks: 1) - Please choose one

Do-while loop executes at least,

Zero Time

[One Time](#)

Two Times

N Times

Question No: 11 (Marks: 1) - Please choose one

$+=$, $*=$, $/=$, etc are called,

Assignment operators

Logical operator

[Compound assignment operator](#)

Unary operator

Question No: 12 (Marks: 1) - Please choose one

Computer can understand only machine language code.

[True](#)



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



False

Question No: 13 (Marks: 1) - Please choose one

Which of the following is the correct syntax to print multiple values or variables in

a single command using cout?

`cout << "Hello" + x + "\n";`

`cout << "H" << x << "\n";`

`cout << "H", x, "\n";`

`cout << ("H" & x & "\n");`

Question No: 14 (Marks: 1) - Please choose one

The compilers and interpreters also belong to the System Software category.

True

False

Question No: 15 (Marks: 1) - Please choose one

Editors are used to compile the code.

True

False

Question No: 16 (Marks: 1) - Please choose one

The variables having a name, type and size are just like empty boxes.

True

False



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question No: 1 (Marks: 1) - Please choose one

A precise sequence of steps to solve a problem is called

- Statement
- Program
- Utility
- Routine

Question No: 2 (Marks: 1) - Please choose one

The Compiler of C language is written in

- Java Language
- UNIX
- FORTRON Language
- C Language

Question No: 3 (Marks: 1) - Please choose one

Initialization of variable at the time of definition is,

- Must
- Necessary
- Good Programming
- None of the given options

Question No: 4 (Marks: 1) - Please choose one

In if structure the block of statements is executed only,

- When the condition is false
- When it contain arithmetic operators
- When it contain logical operators
- When the condition is true

Question No: 5 (Marks: 1) - Please choose one

Which of the following function(s) is/are included in stdlib.h header file?

- double atof(const char *nptr)
- int atoi(const char *nptr)



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



➤ char *strcpy (char *s1, const char *s2)

➤ 1 and 2 only

Question No: 6 (Marks: 1) - Please choose one

Dealing with structures and functions passing by reference is the most economical method

➤ True

➤ False

Question No: 7 (Marks: 1) - Please choose one

Pointer is a variable which store,

➤ Data

➤ Memory Address

➤ Data Type

➤ Values

Question No: 8 (Marks: 1) - Please choose one

Preprocessor program perform its function before _____ phase takes place.

➤ Editing

➤ Linking

➤ Compiling

➤ Loading

Question No: 9 (Marks: 1) - Please choose one

Which of the following can not be a variable name?

➤ area

➤ _area

➤ 10area

➤ area2

Question No: 10 (Marks: 1) - Please choose one

Which looping process is best, when the number of iterations is known?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- for
- while
- do-while
- all looping processes require that the iterations be known

Question No: 11 (Marks: 1) - Please choose one

Which character is inserted at the end of string to indicate the end of string?

- new line
- tab
- null
- carriage return

Question No: 12 (Marks: 1) - Please choose one

How many bytes are occupied by declaring following array of characters?

`char str[] = "programming";`

- 10
- 11
- 12
- 13

11 plus one for null char (11+1= 12)

Question No: 13 (Marks: 1) - Please choose one

Which of the following header file defines the rand() function?

- iostream.h
- conio.h
- stdlib.h
- stdio.h

Question No: 14 (Marks: 1) - Please choose one

Commenting the code _____

- Makes a program easy to understand for others.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- Make programs heavy, i.e. more space is needed for executable.
- Makes it difficult to compile
- All of the given options.

Question No: 15 (Marks: 1) - Please choose one

What's wrong with this for loop?

for (int k = 2, k <=12, k++)

- the increment should always be ++k
- the variable must always be the letter i when using a for loop
- there should be a semicolon at the end of the statement
- the commas should be semicolons

Question No: 16 (Marks: 1) - Please choose one

For which array, the size of the array should be one more than the number of elements in an array?

- int
- double
- float
- char

To access the data members of structure,_____is used.

▶ dot operator

▶ dereference operator

▶ logical operator

▶ address operator

C is widely known as development language of___operating system.

▶ Linux

▶ Windows



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



▶ Unix

▶ Mac OS

What will be the result of arithmetic expression $6 + 27/3 * 3$?

▶ 33

▶ 45

▶ 9

▶ 30

How many bytes are occupied by declaring following array of characters? `char str[] = "programming";`

▶ 10

▶ 11

▶ 12

▶ 13

Declaring structures does not mean that memory is allocated.

▶ True

▶ False

What will be the value of i and j in the following code

segment? `int i, j ;`

`int x[5] = {2, 3, 4, 8, 9} ;`

`int *ptr`

`= &x[2]; i =`

`(*ptr)++ ;`

`j = *ptr++ ;`



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



▶ `i = 5, j = 5`

▶ `i = 5, j = 8`

▶ `i = 4, j = 8`

▶ `i = 5, j = 9`

When an array element is passed to a function, it is passed by-----.

▶ reference

▶ data type

▶ value

▶ data

Which of the following is a correct way to initialize a variable x of int type with value 10?

▶ `int x ; x = 10;`

▶ `int x = 10;`

▶ `int x, x = 10;`

▶ `x = 10;`



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



In C, direction of expression evaluation is from_____.

- ▶ Right to Left
- ▶ Left to Left
- ▶ Left to Right
- ▶ Right to Right

What is the size of following array?
`char str[] = "abcd";`

- ▶ 2
- ▶ 3
- ▶ 4
- ▶ 5

Let ptr1 and ptr2 are pointer variables that points to integer data types then which one of the following arithmetic is allowed?

- ▶ `ptr1 + ptr2`
- ▶ `ptr1 - ptr2`
- ▶ `ptr1 * ptr2`
- ▶ `ptr1 / ptr2`

A variable declared inside a code block becomes____variable for that block.

- ▶ Global



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



► Static

► Local

► Inner



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



From the options given below, identify the correct output of following code segment.

```
main(){  
int x = 5  
;  
{  
int x = 4 ;  
cout << x << “,” ;  
}  
cout << x ;  
}
```

▶ 5 , 5

▶ 4 , 4

▶ 4 , 5

▶ 5 , 4

Determine the output of the following while loop.
int counter = 0 ;



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



```
while(counter < 5)
```

```
cout << counter <<
```

```
“ ”;counter++;
```

▶ 5 4 3 2 1

▶ Infinite loop

▶ 1 2 3 4



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



► 1 2 3 4 5

What will be the correct syntax for initialization of a pointer ptr with string "programming"?

- char *ptr = 'programming' ;
- *ptr = "programming" ;
- char ptr = 'programming' ;
- char *ptr = "programming" ;

Correcting the errors from a program is termed as_____.

- Linking
- Loading
- Debugging
- Editing

_____is the pointer which determines the position in a file from where the next read operation occurs.

- Put
- Seek
- Get
- Tell



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



The function tellg() returns the current location of the __pointer.

- ▶ Get
- ▶ Tellptr
- ▶ Write



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



► Seekg

The memory address of the first element of an array is called

- floor address
- foundation address
- first address

► base address

'while' loop becomes infinite when_____.

- the condition is always false
- the condition is less than zero
- the condition is always true
- the condition contains a logical operator



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question # 3

What will be the result of the expression $j = i++$;
if initially $j = 0$ and $i = 5$?

0

5

6

4

Question # 4

Default mechanism of calling a function by
passing it array is call by _____ and in case of
passing variable is call by
_____.

Reference,

Reference

Reference, value

Value,

Reference

Value, Value

Question # 5

When the break statement is encountered in a
loop's body, it transfers the control from the
current loop.

Inside



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Outsi

de

To break

statement To

continue

statement

Question # 6

_____statement is used to terminate the processing of a particular case and exit from switch structure.

If

Goto

Brea

k

Continue

Question

7

If we pass more than one arguments to a function then they are separated by_ .

Comma, Lecture 9



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Semicol

on;

Colon:

Brackets ()

Question # 8

What will be the value of the variable output in the given piece of code? `double output = 0; output = (2 + 2) * 4 + 2 / (4 - 2);`

15

17

12

1

Question # 9

If we assign 2.06721 to an integer variable x, what will be the output if we print x using cout statement?

2

2.1

2.06

2.07

Question # 10



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



_____ will be used for clarity and to force the order of evaluation in an expression.

" "

() PG32

' '

[]

Question # 11

What will be the size of following array?

```
int arr[29];0
```

30 PAGE 105-106



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



29

28

Question # 12

If a function has not been declared before its definition, It is logical error

syntax error LECTURE

NO logical Error

run time

error none

of these

Question # 13

When the break statement is encountered in a loop's body, it transfers the control from the current loop.

Inside

Outside By using break the loop will terminate.

To break

statement To

continue



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



statement

Question # 14

When we access a multidimensional array, each array index is surrounded by_ .

Single quotes ' '

Double quotes " "

" Brackets[]

Lecture 11 None

of the given

Question # 15

char name [] = "Hello World" ; In the above statement, a memory of _ characters will be allocated

12 Lecture 12

10



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



11

13

Question # 16

A variable declared within a code block
becomes

variab

le for that block.

Static Integer

Local Lecture 9

When the if statement consists of more than
one statement then enclosing these statement
in braces is_____.

Compulso

ry

Optional

Not

required

Relevant



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question # 18

Characters of a string stored in an array can be accessed directly using array .

Manipulati

on

Superscrip

t

Subscript Page No 123

Postscript

Question # 19

A variable declared within a code block becomes for that block.

variable



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Static

Integ

er

Local

Lecture 9

Global

Question # 20

The data type before a function name represents its,

Return Type

Function data

Function

arguments

Function name

Question # 21

From following; which one is the correct syntax of an array initialize: Array size is 10 and it is of double data type to value 0?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



```
arr[10] = {0.0};
```

```
double arr[10]= 0.0;
```

```
Double arr[10] = {0.0};
```

Lecture 12 double arr[] =

0.0;

Question # 22

In C/C++, by default arguments are passed by to a function.

Value

Lecture 9

Reference

Prototype

None of the given

Question # 23

By default, the starting index of an array

in C++ is 0 Lecture 11



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



2

1

-1



SUBSCRIBE

AR Lucky Bahi



1. We use _____ to open a file or stream for extraction
In
2. Null character is represented by _____ in C++.
/0
3. An object of _____ class can be created for saving the current position of any opened file before reading from the file.
Streampos
5. We use _____ to open a file or stream for insertion.
Out
6. Base address is the memory address of _____ element of an array.
1st
7. _____ allow us to have a memory location and use it as int or char interchangeably
Union
8. To read command-line arguments, the main() function itself must be given _____ arguments.
2
10. To manipulate n-dimensional array _____ nested loops are required.
n-1
11. A character is stored in the memory in _
String
12. What will be the size of following array? Intarr[29];
29



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



13. An object of _____ class can be created for saving the current position of any opened file before reading from the file.
Streampos
14. We use _____ to open a file or stream for extraction. in
15. We use _____ to open a file or stream for Insertion. Out
16. _____ are conventional names of the command line parameters of the 'main()' function.
'argc' and 'argv'
17. In _____, we have different data members and all of these have their own memory space.
Structures
18. How we declare an array of integer data whose size is 20 with array name "count".
int count[20];
19. A _____ is an array of characters that can store number of character specified.
String
20. File. seekg (-10L, ios:cur)
backward direction
21. A function is a block of statements that can be defined once and used



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



___inthe program.

As many times as user wants

22. What will be the output of the following while loop?

```
int counter = 0 ;while(counter < 15)
    cout<< counter << “ ”; counter
```

Compile time error

23. We can access a global variable ____

From anywhere in the program



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



23. A repetition statement specifies that an action is to be continued while some _____ remains true.
Condition
24. Loops are _____
e.Repetition
25. _____ operator is used to pass the address of a variable in call by reference method.
&
26. How many times the following do-while loop will execute? `int k = 10; do { cout<<"Statements" <<endl; k -= 2; } while(k>0);`
5
27. What is the output of the following code if the 3rd case is true
`switch (var) { case 'a': cout<<"apple"<<endl; case 'b': cout<<"banana"<<endl; case 'm': cout<<"mango"<<endl; Default: cout<<"any fruit"<<endl; }`
mango any fruit
28. By default, the starting index of an array in C++ is ____.
2



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



-1



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question No.: 1 (Marks: 1)

Compiler is a

System

software

Application

Software Driver

Editor

Question No.: 2 (Marks: 1)

If Num is an integer variable then Num++ means,

Add 1 two times with Num

Add 1 with

Num Add 2

with Num

Subtract 2 from

Num

Question No.: 3 (Marks: 1)

For one byte there are__combinations of values that can be stored in computer.

2

6

2

7



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



2

8

2

4

Question No.: 4 (Marks: 1)

In C/C++ language the header file which is used to perform useful task and manipulation of character data is

cplex.h

ctype.h

188 stdio.h

delay.h

Question No.: 5 (Marks: 1)

Default case in switch statement is,



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Optional

syntax

error

Necessar

y

Question No.: 6 (Marks: 1)

When break statement is encountered in switch statement, it

Stops the entire program

Stops the execution of current statement

Exits from switch statement

None of the given options

Question No.: 7 (Marks: 1)

What will be the result of arithmetic expression $6 + 27/3 * 3$?

33

45

9

30

Question No.: 8 (Marks: 1)

What is the correct syntax to declare an array of size 10 of int data type?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



```
int    [10]
name    ;
name[10]
int    ; int
name[10] ;
int name[]
;
```

Question No.: 9 (Marks: 1)

How many dimensions does n-dimensional array has? [n dimensions](#)

2n dimensions

(n+1) dimensions

(n-1) dimensions (Array starts from 0th element)

Question No.: 10 (Marks: 1)

What will be the correct syntax to access the value of fourth element of an array using pointer ptr?

[ptr\[3\]](#)

(ptr+3)

*(ptr+3)

Both

1 and 3



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question No.: 11 (Marks: 1)

Which of the following values C++ use to represent true and false?

1 and 0

1 and -1

11 and 00

Any numerical value

Question No.: 12 (Marks: 1)

Declaring structures does not mean that memory is allocated.

True

False

Question No.: 13 (Marks: 1)

For which array, the size of the array should be one more than the number of elements in an array?

Int

doub

le

float

char Pg113

Question No.: 14 (Marks: 1)



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



If a variable is passed by value to a function and the function makes some changes to that variable then it

[Does not affect the original variable pg 83](#)

affects the original

variable causes

syntax error

None of the given options

Question No.: 15 (Marks: 1)

In C/C++ the #include is called,

Header file

[Preprocessor Directive pg 269](#)

Statement

ent

Function

n

Question No.: 16 (Marks: 1)

Loops are -----Structure.

Decision

[Repetition pg](#)

[560](#) Sequential

Hierarchical



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question No: 1 (Marks: 1)

In C/C++ the string constant is enclosed

- ▶ In curly braces
- ▶ In small braces
- ▶ In single quotes
- ▶ In double quotes

Question No.: 2 (Marks: 1)

For one byte there are__combinations of values that can be stored in computer.

2

6

2

7

2

8

2

4

Question No: 3 (Marks: 1)

Switch statement deals with,

- ▶ Integer data only



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- ▶ float data only
- ▶ character data only
- ▶ Integer and character data

Question No: 4 (Marks: 1)

A record is a group of related_____.

- ▶ Files
- ▶ Bytes
- ▶ Fields
- ▶ Data

Question No: 5 (Marks: 1)

C++ views each file as a sequential stream of_____.

- ▶ Bytes
- ▶ Bits
- ▶ 0's or 1's
- ▶ Words

Question No: 6 (Marks: 1)

To access the element of two dimensional array we use,

- ▶ Single referencing
- ▶ Single dereferencing
- ▶ Double dereferencing
- ▶ Double referencing Pg175

Question No: 7 (Marks: 1)



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



If it is required to copy an array to another array then,

- ▶ Both arrays must be of the same size and data type Pg 105
- ▶ Both arrays may be of different size
- ▶ Both arrays may be of different data type
- ▶ Both arrays may be of different size and type

Question No: 8 (Marks: 1)

The precedence of * is higher than dot operator

- ▶ True
- ▶ False

http://docs.realsoftware.com/index.php/Operator_Precedence

Question No: 9 (Marks: 1)

Pointers works by pointing to a data type, which can be of the form,

- ▶ Integer only
- ▶ double only
- ▶ character only
- ▶ All of the given options Pg 144

Question No: 10 (Marks: 1)

Which of the following data type(s) can operate on modulus operator ‘%’?

- ▶ float, int
- ▶ float, double
- ▶ int Pg 22
- ▶ char



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question No: 11 (Marks: 1)

What will be the output of following code?

```
int x = 10 ;
```

```
cout << "x =" << x ;
```

- ▶ 10
- ▶ "x=10"
- ▶ **x=10**
- ▶ 10=x

Question No: 12 (Marks: 1)

Which looping process checks the test condition at the end of the loop?

- ▶ for
- ▶ while
- ▶ **do while**

Question No: 13 (Marks: 1)

What will be the correct syntax of the following statement?

ptr is a constant pointer to integer.

- ▶ const int *ptr ;
- ▶ const *int ptr ;
- ▶ int const *ptr ;
- ▶ **int *const ptr ; Pg 154**

Question No: 14 (Marks: 1)



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



A function must always return value.

- ▶ True
- ▶ **False**

Question No: 1 (Marks: 1)

Compiler is a

No: 15 (Marks: 1)

C is a/an____language

- ▶ low level
- ▶ object based
- ▶ object oriented
- ▶ **function oriented pg 82**

Question No: 16 (Marks: 1)

Assignment operator is used for_____.

- ▶ calculation
- ▶ reading
- ▶ **assigning value to variables Pg 17**
- ▶ None of the given options.

Q

Question No: 3 (Marks: 1)

Which of the following function(s) is/are included in ctype.h header file?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- ▶ isdigit(int c)
- ▶ isxdigit(int c)
- ▶ tolower(int c)
- ▶ All of the above Pg 188

Question No: 4 (Marks: 1)

To access the data members of structure_ is used.

- ▶ dot operator (.) pg 231
- ▶ * operator
- ▶ operator
- ▶ None of given.

Question No: 5 (Marks: 1)

The address operator (&) can be used with,

- ▶ Statement
- ▶ Expression
- ▶ Variable Pg 149
- ▶ Constant



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question No: 6 (Marks: 1)

Both compiler and interpreter are used to translate program into machine language code.

- ▶ [True](#)
- ▶ False

Question No: 7 (Marks: 1)

Missing semicolon ';' at the end of C++ statement is

- ▶ Logical error
- ▶ [Syntax error Pg 16](#)
- ▶ Runtime error
- ▶ None of the given options

Question No: 8 (Marks: 1)

Switch statement is an alternative of__statement

- ▶ [multiple if](#)
- ▶ continue
- ▶ break
- ▶ goto



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question No: 9 (Marks: 1)

Array is passed by value to a function by default.

- ▶ True
- ▶ False Pg 266

Question No: 10 (Marks: 1)

Which of the following is the correct function call having array named *student* of 10 elements as a parameter.

- ▶ `addRecord(student[]);`
- ▶ `addRecord(student);`
- ▶ `addRecord(student[10]);`
- ▶ `addRecord(*student);`

Question No: 11 (Marks: 1)

What will be the result of expression $x\% = 2$, if $x = 7$?

- ▶ $x = 1$
- ▶ $x = 3$
- ▶ $x = 7$
- ▶ $x = 2$

Question No: 12 (Marks: 1)

What will be the output of following code segment?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



```
main()
{ int x
= 5 ;

{
int x =
4 ;cout
<x
}
cout <x
}

► 5, 5
► 4, 4
► 4, 55, 4
```

Question No: 13 (Marks: 1)

Which of the following operator is used to access the value of variable pointed to by a pointer?

- * operator
- -> operator
- && operator
- & operator

Question No: 14 (Marks: 1)

The object_____may be used both for file input and file output

- fstream, Pg 199
- ifstream,
- ofstream,



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



► none of the given options.

Question No: 15 (Marks: 1) What's wrong with this for loop?
`for (int k = 2, k <= 12, k++)`

- the increment should always be `++k`
- the variable must always be the letter `i` when using a for loop
- there should be a semicolon at the end of the statement
- [the commas should be semicolons](#)

Question No: 16 (Marks: 1)

Let suppose

```
Union  
intorDouble{  
    Int ival;
```

```
    Double charvar;
```

```
};
```

```
main(){  
    intorDouble  
    VAZ;
```

```
    int size ;
```

```
    size = sizeof(VAZ);
```

```
}
```



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



What will be the value of variable "size", if int occupies 4 bytes and double occupies 8bytes?

- ▶ 2
- ▶ 4
- ▶ 8
- ▶ 12

Question No: 1 (Marks: 1)

C language is developed by

- ▶ Bill Gates
- ▶ Robert Lafore
- ▶ [Dennis Ritchie Pg 12](#)
- ▶ Deitel & Deitel

Question No: 2 (Marks: 1)

Which of the following choice is not an example of an int datatype?

- ▶ 0
- ▶ -32
- ▶ 65531
- ▶ [-4.0](#)

Question No: 3 (Marks: 1)

In flow chart, the symbol used for decision making is,

- ▶ Rectangle
- ▶ Circle
- ▶ Arrow
- ▶ [Diamond Pg 51](#)



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question No: 4 (Marks: 1)

Switch statement deals with,

- ▶ Integer data only
- ▶ float data only
- ▶ character data only
- ▶ Integer and character data

Question No: 5 (Marks: 1)

Default case in switch statement is,

- ▶ Must
- ▶ Optional
- ▶ syntax error
- ▶ Necessary

Question No: 6 (Marks: 1)

*doc is_____by type.

- ▶ Sequential File
- ▶ Random Access File
- ▶ Data File
- ▶ Record File

Question No: 7 (Marks: 1)

Member function tellg() returns the current location of the__pointer.

- ▶ tellptr()
- ▶ write()
- ▶ seekg()



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



▶ `get()`

Question No: 8 (Marks: 1)

Dealing with structures and functions passing by reference is the most economical method

▶ True

▶ False

Question No: 9 (Marks: 1)

In C/C++ all character strings are terminated with,

▶ Null character

▶ String

▶ Zero Pg 166

▶ Full stop

Question No: 10 (Marks: 1)

Word processor is

▶ Operating system

▶ Application software

▶ Device driver

▶ Utility software

Question No: 11 (Marks: 1)

Which of the following can not be a variable name?

▶ area



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- ▶ `_area`
- ▶ `10area`
- ▶ `area2`

Question No: 12 (Marks: 1)

Which looping process is best, when the number of iterations is known?

- ▶ `for`
- ▶ `while`
- ▶ `do-while`
- ▶ all looping processes require that the

iterations be known

Question No: 13 (Marks: 1)

By default an array of characters is passed by value to a function.

- ▶ `True`
- ▶ `False`

Question No: 14 (Marks: 1)

Which of the following operator is used to access the address of a variable?

- ▶ `* operator`
- ▶ `-> operator`
- ▶ `&& operator`



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



▶ & operator Pg 480

Question No: 15 (Marks: 1)

The name of an array represents address of first location of array element.

▶ rue Pg 120



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



► False

Question (Marks: 1)

No: 16

Let
suppose

```
Union intorDouble{
```

```
Int ival;
```

```
Double charvar;
```

```
};
```

```
main(){
```

```
intorDouble
```

```
VAZ;int size ;
```

```
size = sizeof(VAZ);
```

```
}
```

What will be the value of variable "size", if int occupies 4 bytes and double occupies 8bytes?

- 2
- 4
- 8
- 12



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question No: 1 (Marks: 1)

In C/C++ the #include is called,

- ▶ Header file
- ▶ Preprocessor Directive pg 269
- ▶ Statement
- ▶ Function

Question No: 2 (Marks: 1)

To access the element of two dimensional array we use,

- ▶ Single referencing
- ▶ Single dereferencing
- ▶ Double dereferencing Pg175
- ▶ Double referencing

Question No: 3 (Marks: 1)

Data Size of the file is always____the actual size of the file.

- ▶ Greater than
- ▶ Equal to
- ▶ Less than or equal to

▶ None of the above Pg 216

Similarly in case of files, the space occupied by a file (file size) can be more than the actual datalength of the file itself.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question No: 4 (Marks: 1)

When an identifier is declared with keyword const then,

- ▶ Its value can be changed during execution.
- ▶ Its value can not be changed Pg110
- ▶ Its value can be changed with arithmetic operator
- ▶ Its value can be overwritten

Question No: 5 (Marks: 1)

In C/C++ if we define an array of size eight (8) i.e. int Arr[8]; then the last element of this array will be stored at,

- ▶ Arr[0]
- ▶ Arr[8]
- ▶ Arr[7]
- ▶ Arr[-1]

Question No: 6 (Marks: 1)

If it is required to copy an array to another array then,

- ▶ Both arrays must be of the same size and data type Pg 105
- ▶ Both arrays may be of different size
- ▶ Both arrays may be of different data type
- ▶ Both arrays may be of different size and type

Question No: 7 (Marks: 1)

In C/C++ all character strings are terminated with,

- ▶ Null character Pg 166
- ▶ String
- ▶ Zero



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



► Full stop

Question No: 9 (Marks: 1)

When a pointer is incremented, it actually jumps the number of memory addresses

- [According to data type Pg 160](#)
- 1 byte exactly
- 1 bit exactly
- A pointer variable can not be incremented

Question No: 10 (Marks: 1)

Do-while loop executes at least,

- Zero Time
- [One Time](#)
- Two Times
- N Times

Question No: 11 (Marks: 1)

$+=$, $*=$, $/=$, etc are called,



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- ▶ Assignment operators
- ▶ Logical operator
- ▶ [Compound assignment operator Pg 63](#)
- ▶ Unary operator

Question No: 12 (Marks: 1)

Computer can understand only machine language code.

- ▶ [True Pg 12](#)
- ▶ False

Which of the following is the correct syntax to print multiple values or variables in a single command using cout?

- ▶ cout <
- ▶ cout <
- ▶ cout <
- ▶ cout <

Question No: 14 (Marks: 1)

The compilers and interpreters also belong to the System Software category.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



▶ True Pg 11

▶ False

Question No: 15 (Marks: 1)

Editors are used to compile the code.

▶ True

▶ False

Compilers are used for compilation of source codes, However Editors are used to write the source codes.

Question No: 16 (Marks: 1)

The variables having a name, type and size are just like empty boxes.

▶ True

▶ False

Question No: 17 (Marks: 1)

What will be the result of the statement

`rand ( ) % 50`

When 50 divides any number, the remainder will always be less than 50.

Question

No 1



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



The statement `cout << yptr` will show the_____the `yptr` points to.

Value
Type
Address
Data
a

What will be the result of the
expression `k = ++m;`

0
5

Question No 4

`char name [] = "Hello World";`

in the given statement a memory of_____characters will be allocated.

Select Correct Option



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



13

11

12

10

A function's prototype is written__the function call.

Select Correct Option

52

50

51

57

Question No 7



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



In C\C++, by default argument are passed by_ to a function.

Select Correct Option

Reference

Value

Size

Question No 8

Correcting the errors from a program is termed as_.

Select Correct Option

Linkin

g

Loadin

g

Executi

ng

Debugging

Declaration of two-dimensional array of integers having 3 rows and 5 columns is following?

```
int arr [3][5];
```

To get the value stored at a memory address, we use the_.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Which of the following is the correct way to write a compound assignment operator?

`x += 4;`

`x + = 4;`

`x + = = 4;`

None of the above

Question No 12

We can say that a pointer is a variable that holds the address.

Select Correct Option

Byte

code

Source

code

What is the use of ios::trunc mode?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Select Correct Option

- To open a file in input mode
- To open a file in output mode
- To truncate an existing file to half
- To truncate an existing file to zero

Which of the following is the correct operator to compare the values of two variables?

:=

=

“=”

= = Ans

Question No 16

What will be the value of the variable output in the given piece of code? Double output = 0;

Output – $(2+2) * 4 + 2 / (4-2);$

15

17Ans

12



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



11

A variable of character data type occupies____bytes in memory.

2

4

8

According to c++ norms, the first character of a variable name must be an alphabet or

Select Correct Option

Underscore

Special
character

Digit

None of the given options



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question No 20

For breaking complex problems into smaller pieces we use_____.

Select Correct Option

If
se
Loo
ps

From the following which one is the range of Random number generator function rand()?

C++ is a_____language.

Select Correct Option



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Whenever some number is added in an array name, it will jump as many_____as the added number.

Rows

Value

Column

mn

None of the given

Question No 24

Array indexes start from_____.

Select Correct Option

0Ans

1

2

3



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



_____will explain the function of a program.

Select Correct Option

Comment

Which of the following will be the most appropriate data type to store the value 63.547?

Float

< and > both are___operations.

Select Correct Option

Relational
Logical
Mathemat
ical

6. By default, the starting index of an array in

c++ is _____

Output file stream



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



0

7. How we declare an array of integer data whose size is 20 with array name "count".

```
Int count [20];
```

8. Which of the following is a keyword for data type in C/C++? Int

9. C was developed with the help of language BCPL and B

10. An object of a class can be created for saving the current position of any opened file before reading from the file. Streampos

11. C++ is a language.
High level



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



12. In while loop, the loop counter is initialized at-----

Before entering the loop

13. What is the output of the following code if

the 3rd case is true

```
Switch(var)
```

```
{Case 'a';
```

```
Cout<<"apple"<<
```

```
endl;Mango
```

14.----- character is used to indicate the end of the

string

g.

Null

15. Which of the following is used to perform

bit-wise Exclusive OR operation?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



16. If $x = 11$, and $x \% 3$, then value of x will be----

2

17. A variable of character data type occupies _____ by testing
memory.

1 byte.

18. Null character is represented by _____ in C++?

`\0`

19. In computer system there are mainly _____ type of

Software.

2.

20. There is a pointer variable named `ptr` of type

float. Which type of variable address can be



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



store by ptr?

Float

21. A character is stored in the memory in -----

Byte

22. X is an integer

variable; what does `x++` mean, Add 1

in x value

23. When we call a function, its control -----

Transfers to its definition

24. `'\0'` takes - space in the memory.

1 byte



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



25----- will be used for enclosing function statements into

A block?

```
{}
```

26.How can we declare an array of characters

whose size is 12 with array name “country”?

```
Char country[12];
```

27.Following is the declaration of a 2d array,

how many Columns are declared for this

array.

```
Int arr[3][
```

```
2];2
```

28.If we assign 2.06721 to an integer variable x,

what will be The output if we print x using



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



cout<< statement?

2

29. We can access a global variable----

From anywhere in the program

30. We use to include all those functions which are

located in different

files.Linker



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



31. A character is stored in the memory in ----

Byte

32. Which is not true regarding
structure? We can declare array
of structure

33. Mr. Ahmad sleeps thirty hours everyday.

This sentence is ----

Grammatically correct but illogical

34. ---- will explain the function of a program.

Comments

35. Char **argv can be read as ----

Pointer to pointer to char



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



36. What will be the output of the

following code? `String name[4]=`

`{"ali", "bilal", "omer", "Ayesha"};`

`Cout<<name[0];`

Ali

37. The data type before a function name

represents its return type

37. The expression $((a+b) == 10) \vee ((x+y) == 20)$ is true only if?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Either((a+b) ==)OR((x+ y)==20) istrue

38. = operator is used for ----

Assigning values to variables

39. What is the use of ios::trunc

mode? To truncate an existing

file to zero

40. X is an integer variable; what does x

++ means, Add 1 in x value

41. Structures use allocation.

Heap

42. What will be the size of the following



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



character array? Char name[] = "adeel";

6

43. A -- is an array of characters that can store number of

Character

specified. String

44. --- statement is used to terminate the processing of a

particular case and exit from switch structure.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Break

45. If $y = 20$ and $z = y++$, then the value of z will be-----

2146. If

Int a=

17; int

b = 3;

double c = a/b;

what will be value of

variable c? 5

47. What will be the output of the following code?

String grade[3]=

{“a”, “b”, “c”}; Grade[2]=

“f”; Cout<<grade[2];

F



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



48. Declaration of two-dimensional array of integers having 3 rows and 5 columns is following?

`Intarr[3][5];`

49. $A = a + 1$; can be written as----

$A+ = 1$;

50. A record is a group of related



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Fields

51. What will be the result of arithmetic
expression $6 + 48 / 4 * 3$?

42

52-----construct is used to execute asset of instructions

When a condition is true and other set
when it is false? If\else

53. If an array has 50 elements, what is allow
able range of subscripts?

0 –49

54.If `int a= 50;` then the value of `a/=`

`3;` will be? 16



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



55. Which of the following options is/are correct about array? Only one type of elements can store in an array

56. Whenever some number is added in an array name, it will jump as many _____ as the added number?

Rows



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



7 -----return true if c is a digit or a letter and false otherwise.

int isalnum(int c)

58. Which of the following is the default mode of the opening using ofstream class?

ios::trunc

59. In which language the compiler of C++ language is written?

60. While loop executes at least how many times?

61. String are accessed by variable of type----

char

62. Which of the following is the correct operator to compare the values of two variables?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



==

63. Not operator is a-----

Single input operator

64. Pointer points to a particular-----

Memory address



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



65. A function is a block of statements that can be defined once and used-

---in the program.

As many times as user wants

66. ----- function is used to find the number of characters in a string?

Strlen()

67. != operator is used to check whether the operand on the left-hand side is not equal to the operand on the right-hand-side.

Not equal

68. A while loop may execute 0 or more times.

0

69. How we declare an array of integer data whose size is 20 with array name "count".

```
Int count[20];
```



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



70. A variable declared within a code block becomes a local variable for that block.

k.

Loc

al

71. If a file is opened with ios::out mode, then-----

We can write in this file



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



72. A function's prototype is written--- the
function call. Before

73---Loop is mostly used to perform repetition of a task for a known
Number of
times. For

74. In shifting operations if zero is inserted at the least
most bit, the Negative number will become a
number.

Positive

It is the job of to transfer the executable code from hard disk to
main

memory.

Loader

75. RAID stands for-----

Redundant array of inexpensive devices



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



76.Array indexes start from ----

0

77.Incallby reference,of a variable is passed to the called function.

Address

78.Howmany times the following do-while loop will execute?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Int k =

10; Do

{

Cout<<"statements"<<endl;?

6

79.The name of a location in memory is called----

Variable

81--- function is used to find the number of character in a string.

Strlen()

82.Which statement is used to

close a file? Myfile.close();

83----- allow us to have a memory location and use it a sint or char

Inter

changeably.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



None of the

given

84.While handling files, one can have options

All of the given

85-----function is used to determine then ext position to write a
Character while writing

into a file.Tellp()



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



86. Which is the correct syntax to define a structure named 'student'?

Structstudent{

//variables

};

87. <and> both are operators.

Logical

Identify the logical error in the following

if condition 88. If((i<5) &&(i>15))?

Condition is always false

89. Not operator is a----

Single input operator

90. The use of *sign in first and second statements is called--- and ---- of pointer.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



```
Int *ptr=
```

```
&x;
```

```
Cout<<*pt
```

```
r;?
```

Referencing,dereferencing

91. C is widely known as development language of operating system.

Linux



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



92.If x is declare as an integer, what will be result of the given expression?

$X = 2 + 3 * 5 \% 2 + 3 / 2$??

4

93.What will be the correct syntax of declaration of the following statements?

“ptr is a pointer to

constint”?? Constint*ptr

94.Afte revaluating the expression

95. $X = 10 + 3 * 4 / 2 - 1$, the value of

x will be? 15

96. We can read,write and manipulate the same file using----

Fstream.h

97.Return type of a function that does not return any value must be----



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Void

98. Pointers store the ----

Memory address

99. --- operator uses the sign[^].

Exclusive OR



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



100. To get the value stored at a memory address, we use the----

Dereferencing operator

101. Telling a computer what to do is called ----

Programming

102. Compiler translates high level language program into machine language code.

Machine

code

103. Each array declaration must provide the information about all these things except----

The location of the first element to be stored

104. EOF is used to check for the end of file when a file is being read.

End



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



105. The result of $4\%3$

will be? 1

106. When the logical operator AND(&&) combine two expression exp1 and exp2 then the result will be true only?

When both exp1 and exp2 are true



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



107. 'multi[3][3]' element can also be accessed by-----

$*(*(\text{multi}+3)+3)$

108. What is output of following code?

```
Int data[10]= { 10,20,30,40,50,60,70,80,90,100};
```

```
Int
```

```
*xptr=&data[4];
```

```
Int *xptr=&data
```

```
[6];
```

```
Cout<<xptr + yptr
```

```
++;??120
```

109. Which of the following is not the sub category of the system software? None of the above

110. We get $12|8 =$ where " $|$ " is (bit-wise OR)?

12



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



111 --- is a substitute of multiple if statement.

If..else if statement

112. Find out the logical error in following

lines of code. If(x= 10)

Cout<<"x is 10";?

Assignment operator should not be used for comparison

113. Which is not true regarding structure?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



c) we can't declare pointers to structure

114 ---- are used to compile the code.

Compiler

115. #include<iostre

am>

#include<cstring>

Using name

space std;

Intmain()

{

Char str1[10]=

“hello”; Char

str2[10]= “world”;?

10

116. A - structure specifies that an action is to be repeated while some



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Condition remains

true. Repetition

117. In which language the compiler of c

language is written? C

118. Characters string are terminated by-----

\0



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



119. A function is a block of statements that can be defined once and used-in the program.

As many times as user wants

120 ----- is used for output during the process of writing to the file.

Seekp()

In case of two-dimensional array, if you add some number in a two-dimensional name, it will jump to the next----

Row

121. In while loop the condition is checked the execution of loop.

Before

122. Array indexes start from ----

0



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



123. Pointers store the----

Memory address

124. Which step is not performed during a proper program design? Write details about the performance of program

125, We can say that a pointer is a variable that holds the address.

Memory



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



126. When accessing a structure memory, the identifier to the left of the Dot operator is the name of----

Structure variable

127. From the following; which one is the range of random number generator rand()?

0-32767

128. To read command-line arguments, the main () function itself must be given arguments.

2

129. Which operator has the highest

precedence? (*, -, /, +)?

* and / both have the same highest precedence

130. Suppose we have int y[10];

To access the 4th element of the array we write----

Y[3];



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



131. What will be the value of the variable output in the given piece of code? Double output= 0;

Output=(2+2)*4 +

/(4-2);17



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



132. What is the output of the following

```
statement?inti = 2.5; do {couti * 2; }
```

```
while(i>3 && i< 10); error
```

133. Searching is easier when an array is

already sortedTrue

134. If an array has 100 elements, what is allowable range of subscripts?

0 -99

While developing a program; should we think about the user interface?

//handouts

mainYes

A character is stored in the memory in

_String



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



These functions seekg() and seekp() requires an argument of type _____ to let them know how many bytes to move forward or backward.

int

dereferencing operator is represented by ____

*



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



_____transfers the executable code from main memory to harddisk.

Loader

When the logical operator OR (||) combine two expressions exp1 and exp2 then the result will be false only, //bit wise “or” applies here....

When both exp1 and exp2 are false

Suppose we have `inty[10]`; To _____ access the 4th element of the array we write

none of given

we have opened a file stream `my file` for reading (getting), `my file. tellg()` gives us the current get position of the file pointer. It returns a whole number of type

`int`



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



of

stre

am

is

use

d

for_____ Output file stream

A structure is a collection of_____under a single
name. Variables

In C/C++ the string constant is enclosed
.....correcte
d rued one

In curly braces

If the break statement is missed in
switch statement then, //a break



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Statement with no label always completes abruptly, the reason being a Break with no label. If no switch, while, do, or for statement in the Immediately enclosing method, constructor or initialize encloses the break statement, a compile-time error occurs?

This may cause a logical error

When we are using const keyword with a variable x then initializing it at the time of declaration is,

Optional

Which of the following is the correct way to assign an integer value 5 to

Element of a matrix say

‘m’ at second row and

third column? `m[2][3]=`

5 ;



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



1. Overflow condition occurs when we try to assign a value to a variable which is

_____.

Greater than its maximum size

Within its

range

Equal to

its size

Less than its maximum size

2. The `_break_` statement interrupts the flow of control.

Switch/

oop

continue

goto

break

3. Which of the following operators is used to access the value of variable pointed by a pointer?

* operator

-> operator

&& operator

& operator

4. Which of the following is not a reserve word for data types in standard C/C++?

float

real



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



double

5. To assign a value to a character type variable, _____ are used around the value.

parentheses ()
single quotes ' '
double quotes " "
curly braces { }

6. When $x = 7$; then the expression $x\% = 2$; will calculate the value of x as

_____.

1

3

7

2

7. What is the highest legal index for the following array? `int arr[4]`

4

3

2

1

8. For which array, the size of the array should be one more than the number of elements in an array?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



int
double
float
char



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



9.

I

In programming, comments are used to explain the functioning of the

___.Debugger

Editor

Program

Linker

10.

O

Operating System is a type of a/an

___.application software

system

software

computer

language

interpreter

11. ___are very good tools

for code reuse.operators

loops

function

s

variable

s

12. Identify the correct option which is used for calling the function `int square (int *)`.

`square(int`

`&num) ;`

`square(&nu`

`m) ;`

`square(*nu`

`m) ;`



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



```
square(num  
);
```

13. The `switch` statement allows us to select from multiple choices based on a set of fixed values for a given expression.

```
switch  
{  
    case 1:  
        break;  
    case 2:  
        continue;  
    case 3:  
        goto 4;  
}
```

14. The file-open mode `'a'` is used to open a file for output and move to the end of the file.

```
ios::out  
ios::app  
ios::trunc  
ios::binary
```

15. A function's single most important role is to `encapsulate` a block of code. It increases program size.

It accepts arguments and provides a return value.

It helps in organizing a program into conceptual units.

16. In C++, integer calculation occurs in `int` bytes. 1 byte.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



2 bytes

4 bytes

8 bytes

17. The
function write() takes _____ as
parameter(s). String of pointer type
String of variable lengths, no. of bytes to
be read and flags Pointer array of
characters and a delimiter

String and no. of bytes to be written

18. A ____ name includes a primary name and an
optional period with an extension.
File



SUBSCRIBE

AR Lucky Bahi





Disk Data
Database

19. In case of pass by reference, ____.

The values of the variables are passed to the function so that it can manipulate them

The location of variable in memory is passed to the function

The function declaration should contain ampersand (&) in its type declaration
Temporary variables are created to store the values of the variables passed

20. There is a pointer variable named *ptr* of type float then address of which type of variable the *ptr* will store in it?
int float char
double

21. If `char Array[7];` is a character array then write the statement which store a character at Fifth location of this array.02

Ans: `Array[4] = 'a';`

Question No: 1 (Marks: 1) - Please choose one

In order to get 256 from the number 2568 we divide this number by 10 and take,

- ▶ Its remainder
- ▶ The number





SUBSCRIBE

AR Lucky Bahi



► Its quotient

► Its divisor

Question No: 2 (Marks: 1) - Please choose one
The correct syntax of do-while loop is,

► (condition) while; do { statements; };

► { statements; } do-while ();

► while(condition); do { statements; };

► do { statements; } while

(condition); Question No: 3 (Marks: 1) - Please choose one

Which of the following function(s) is/are included in stdlib.h header file?

► double atof(const char *nptr)

► int atoi(const char *nptr)

► char *strcpy (char *s1, const char *s2)

► 1 and 2 only (Pg 191)

Question No: 4 (Marks: 1) - Please choose one

If the break statement is missed in switch statement then,

► The compiler will give error

► This may cause a logical error (Pg 76)

► No effect on program

► Program stops its execution

Question No: 5 (Marks: 1) - Please choose one

The data type before a function name represents its,

► Return Type (Pg 499)

► Function data

► Function arguments

► Function name

Question No: 6 (Marks: 1) - Please choose one

Member function tellg() returns the current location of the____pointer.

► tellptr()

► write()

► seekg()

► get() (Pg 215)



SUBSCRIBE

AR Lucky Bahi





Question No: 7 (Marks: 1) - Please choose one

What does $5 | 6$, evaluate to in decimal where ' $|$ ' is bitwise OR operator?

- ▶ 3
- ▶ 4
- ▶ 5

▶ 7



5 | 6 =
0 1 0 1
0 1 1 0

0 1 1 1 = 7

Question No: 8 (Marks: 1) - Please
choose one C is widely
known as development language of __operating system.

- ▶ Linux
- ▶ Windows
- ▶ **Unix (Pg 12)**
- ▶ Mac OS

Question No: 9 (Marks: 1) - Please
choose one What will be
the result of arithmetic expression $6 + 27/3 * 3$?

- ▶ 33
- ▶ 45
- ▶ **9**
- ▶ 30

Question No: 10 (Marks: 1) - Please
choose one How many
bytes are occupied by declaring following array of
characters? `char str[] = "programming";`

- ▶ 10
- ▶ 11
- ▶ **12**
- ▶ 13

Question No: 11 (Marks: 1) - Please
choose one What will be
the correct syntax for initialization of pointer ptr with string "programming"?

- ▶ `char ptr = 'programming' ;`
- ▶ `char *ptr = "programming" ;`
- ▶ `char *ptr = 'programming' ;`
- ▶ `*ptr =`
`"programming" ;`

pg 166

array element in each array initialized with a single character enclosed in single quote.

While assigning a character value to a char type variable single quotes are used around the character as 'a'.

Question No: 12 (Marks: 1) - Please choose one What will be the result of expression $x \% 2$, if $x = 7$?

- ▶ $x = 1$

- ▶ $x = 3$
- ▶ $x = 7$
- ▶ $x = 2$

Question No: 13 (Marks: 1) - Please choose one
 UNIX has been developed in _____ language

e.

- ▶ JAVA
- ▶ B
- ▶ **C (pg 12)**
- ▶ FORTRAN

Question No: 14 (Marks: 1) - Please choose one
 Declaring structures does not mean that memory is allocated.

- ▶ **True (Pg 229)**
- ▶ False

Question No: 15 (Marks: 1) - Please choose one
 What will be the value of i and j in the following

code segment?

```
int i, j ;
int x[5] = {2, 3, 4, 8, 9} ;
int *ptr
=&x[2]; i =
(*ptr)++ ;
j = *ptr++ ;
```

- ▶ $i = 5, j = 5$
- ▶ $i = 5, j = 8$
- ▶ **$i = 4, j = 8$**
- ▶ $i = 5, j = 9$

Question No: 16 (Marks: 1) - Please choose one
 When an array element is passed to a function, it is passed by --.

- ▶ **reference (Pg 266)**



- ▶ data type
- ▶ value
- ▶ data

When we pass ordinary variables to functions, they are passed by value because of the default behavior. But when an array is passed to a function, the default behavior changes and array is passed by reference

MIDTERM EXAMINATION 2010

Question No: 1 (Marks: 1) - Please choose one
What is the output of the following statement?

```
int i = 2.5; do { cout << i * 2; } while (i > 3 && i < 10);
```

(a) 510

(b) 5

(c) 48

(d) error

Question No: 2 (Marks: 1) - Please choose one





What does $!(7)$ evaluate to in decimal where $!$ is a NOT operator?

- (a) 7
- (b) 8
- (c) 9
- (d) 10

Question No: 3 (Marks: 1) - Please choose one

The condition in while loop may contain logical expression but not relational expression.

- (a) True
- (b) False

Question No: 4 (Marks: 1) - Please choose one
Searching is easier when an array is already sorted

- (a) True
- (b) False

Question No: 5 (Marks: 1) - Please choose one

If an array has 100 elements, what is allowable range of subscripts?

- (a) 0 - 99
- (b) 1 - 99
- (c) 0 - 100
- (d) 1 - 100

Question No: 6 (Marks: 1) - Please choose one

What will be the value of 'a' and 'b' after executing the following statements?

$a = 3;$
 $b = a++;$

- (a) 3, 4
- (b) 4, 4
- (c) 3, 3
- (d) 4, 3

Question No: 7 (Marks: 1) - Please choose one

What will be the correct syntax to initialize all elements of two-dimensional array to value 0?

- (a) `int arr[2][3] = {0,0} ;`
- (b) `int arr[2][3] = {{0},{0}} ;`





(c) `int arr[2][3] = {0},{0} ;`

(d) `int arr[2][3] = {0} ;`

Question No: 8 (Marks: 1) - Please choose one

Which of the following function returns the size of a string variable?

(a) `strlen()`

(b) `stringlen()`

(c) `strlen()`

(d) `strLength()`

When applied to a character array, the `strlen` function returns the length of the string stored there, not its allocated size.

Question No: 9 (Marks: 1) - Please choose one





What will be the range of numbers generated by function `rand () % 9`?

- (a) 0 to 9
- (b) 1 to 9
- (c) 0 to 8
- (d) 1 to 8

Question No: 11 (Marks: 1) - Please choose one
Computer can understand only machine language code.

- (c) True
- (d) False

Question No: 13 (Marks: 1) - Please choose one
What does $5 \wedge 6$, evaluate to in decimal where '^' is Exclusive OR operator?

- (a) True

(b) Fals

e

Detail:-

It

mean 5

= 0101

6 =

0110

$5 \wedge 6 = 0011$

If both input is same then the output is 0 and if different then

output is 1

Question No: 14 (Marks: 1) - Please choose one
If the file is not properly closed in the program, the program__.

- (a) Terminate normally
- (b) Indicate Runtime error
- (c) Indicate Compile time error

(d) Crashes

Eventually run out of file handles and/or memory space and crash.)

Question No: 15 (Marks: 1) - Please choose one

Which of the following header file include string conversion functions?





- (a) string.h
- (b) **stdlib.h** (Pg 190)
- (c) ctype.h
- (d) sconvert.h .

MIDTERM EXAMINATION2009

Question No: 1 (Marks: 1) - Please choose one
A precise sequence of steps to solve a
problem is calledØ Statement

Ø

Program

Ø

Utility

Ø Routine

Question No: 2 (Marks: 1) - Please
choose oneThe Compiler of C language
is written in
Ø Java Language





☐ UNIX
☐ FORTRON
Language ☐ C

Language

Question No: 3 (Marks: 1) - Please
choose one Initialization of variable at
the time of definition is, ☐ Must
☐ Necessary

☐ Good Programming

☐ None of the given options

Question No: 4 (Marks: 1) - Please choose one

In if structure the block of statements is
executed only, ☐ When the condition is false

☐ When it contain arithmetic
operators ☐ When it contain
logical operators

☐ When the condition is true

Question No: 6 (Marks: 1) - Please choose one

Dealing with structures and functions passing by reference is the most
economical method ☐ True

☐ False

Question No: 7 (Marks: 1) - Please
choose one Pointer is a variable which

store,

☐ Data

☐ Memory

Address ☐ Data

Type

☐ Values

Question No: 8 (Marks: 1) - Please choose one

Preprocessor program perform its function before phase takes





place.Ø Editing .

Ø Linking

Ø

Compilin

gØ

Loading

Question No: 9 (Marks: 1) - Please
choose one Which of the following can
not be a variable name?Ø area

Ø

_area

Ø

10area

Ø

area2

Question No: 10 (Marks: 1) - Please choose one
Which looping process is best, when the number of
iterations is known?Ø for

Ø while

Ø do-while

Ø all looping processes require that the iterations be known





Ø

Question No: 11 (Marks: 1) - Please choose one

Which character is inserted at the end of string to indicate the end of string?Ø new line

Ø

tab

Ø

null

Ø carriage return

Question No: 13 (Marks: 1) - Please choose one

Which of the following header file defines the rand() function?Ø iostream.h

Ø

conio.h

Ø

stdlib.h

Ø

stdio.h

Question No: 14 (Marks: 1) - Please choose one
Commenting the code _____

Ø Makes a program easy to understand for others.

Ø Make programs heavy, i.e. more space is needed for executable.Ø Makes it difficult to compile

Ø All of the given options.

Question No: 15 (Marks: 1) - Please choose one

What's wrong with this for loop?

for (int k = 2, k <=12, k++)

Ø the increment should always be ++k

Ø the variable must always be the letter i when using

a for loopØ there should be a semicolon at the end of





the statement

Ø the commas should be semicolons .

Question No: 16 (Marks: 1) - Please choose one

For which array, the size of the array should be one more than the number of elements in an array?

Ø int

Ø

double

Ø

float Ø

char

MIDTERM

EXAMINATION2009

Question No: 1 (Marks: 1) - Please choose one
The function of cin is

- ▶ To display message
- ▶ To read data from keyboard
- ▶ To display output on the screen
- ▶ To send data to printer

Question No: 2 (Marks: 1) - Please choose one

In C/C++ language the header file which is used to perform useful task and manipulation of



character data is

- ▶ cplex.h
- ▶ **ctype.h** (Pg 188)
- ▶ stdio.h
- ▶ delay.h

Question No: 3 (Marks: 1) - Please choose one How many parameter(s) function getline() takes?

- ▶ 0
- ▶ 1
- ▶ 2
- ▶ **3**

The member function getline() also takes three parameters: the buffer to fill, one more than the maximum number of characters to get, and the termination character. getline() functions exactly like get() does with these parameters, except getline() throws away the terminating character.

.

Question No: 4 (Marks: 1) - Please choose one Word processor is

- ▶ Operating system
- ▶ **Application software**
- ▶ Device driver .
- ▶ Utility software

Question No: 5 (Marks: 1) - Please choose one

For which values of the integer _value will the following code becomes an infinite loop?

```
int number=1;
while (true) {
    cout <<
    number;
```



if (number == 3) break;

number +=

integer_value; }

▶ any number other than 1 or 2

▶ **only 0**

▶ only 1

▶ on

ly 2

Ration

al:

number += integer_value... above line decide the fate of loop so any thing other than zero

leads

to value of 3 which will quite the loop. Only zero is the value which keeps the loop infinite.

Question No: 6 (Marks: 1) - Please choose one

Each pass through a loop is called a/an

▶ enumeration

▶ **Iteration**

▶ culmination





- ▶ pass through

Question No: 7 (Marks: 1) - Please choose one
A continue statement causes execution to skip to

- ▶ the return 0; statement
- ▶ the first statement after the loop
- ▶ the statements following the continue statement
- ▶ **the next iteration of the loop**

Continue statement is used, when at a certain stage, you don't want to execute the remaining statements inside your loop and want to go to the start of the loop.

Question No: 8 (Marks: 1) - Please choose one
What is the correct syntax to declare an array of size 10 of int data type?

- ▶ `int [10] name ;`
- ▶ `name[10] int ;`
- ▶ **`int name[10] ;`**
- ▶ `int name[] ;`

Question No: 9 (Marks: 1) - Please choose one
Consider the following code segment. What will the following code segment display?

```
int main(){  
    int age[10] =  
    {0};cout <<  
    age ;  
}
```

- ▶ Values of all elements of array
- ▶ **Value of first element of array**
- ▶ Starting address of array
- ▶ Address of last array element

Question No: 11 (Marks: 1) - Please choose one
How many bytes will the pointer intPtr of type int move in the following





statement?intPtr += 3 ;

- ▶ 3 bytes
- ▶ 6 bytes
- ▶ 12 bytes
- ▶ 24 bytes

one int is 4 bytes so $4 \times 3 = 12$ bytes

movement. Question No: 12 (Marks: 1) -

Please choose one

If there are $2(n+1)$ elements in an array then what would be the number of iterations required to search a number using binary search algorithm?

- ▶ n elements
- ▶ $(n+1)$ elements
- ▶ $2(n+1)$ elements
- ▶ $2(n+1)$ elements

Question No: 13 (Marks: 1) - Please choose one

Which of the following operator is used to access the value of variable pointed to by a pointer?





- ▶ * operator
- ▶ -> operator
- ▶ && operator
- ▶ & operator

Question No: 14 (Marks: 1) - Please choose one
The_____statement interrupts the flow of control.

- ▶ switch
- ▶ continue
- ▶ goto
- ▶ break

Question No: 15 (Marks: 1) - Please choose
one Analysis is the --- step in designing a
program

- ▶ Last
- ▶ Middle
- ▶ Post Design
- ▶ First

Analysis will be always followed by design and
then code. Question No: 16 (Marks: 1) - Please
choose one

Paying attention to detail in designing a program is _

- ▶ Time consuming .
- ▶ Redundant
- ▶ Necessary
- ▶ Somewhat Good

In programming, the details matter. This is a very important skill. A good
programmer always analyzes the problem statement very carefully and in
detail. You should pay attention to all the aspects of the problem.

MIDTERM EXAMINATION





Spring 2009

Question No: 1 (Marks: 1) - Please choose one _____ There are mainly _____types of software

- ▶ Two
- ▶ Three
- ▶ Four
- ▶ Five

Software is categorized into two main categories

- System Software
- Application Software

Question No: 2 (Marks: 1) - Please choose one _____

In C/C++ the #include is called,

- ▶ Header file
- ▶ Preprocessor Directive (Pg 15)
- ▶ Statement
- ▶ Function



Question No: 3 (Marks: 1) - Please choose one____

&& is ----- operator.

- ▶ An arithmetic
- ▶ **Logical**
- ▶ Relational
- ▶ Unary

we use logical operators (&& and ||) for AND and OR respectively with relational operators.

Question No: 4 (Marks: 1) - Please choose one____

In flow chart, the symbol used for decision making is,

- ▶ Rectangle
- ▶ Circle
- ▶ Arrow
- ▶ **Diamond (Pg 51)**

Question No: 6 (Marks: 1) - Please choose one____

C++ views each file as a sequential stream of_____.

- ▶ **Bytes .**
- ▶ Bits
- ▶ 0's or 1's
- ▶ Words

Question No: 7 (Marks: 1) - Please choose one_____

If the elements of an array are already sorted then the useful search algorithm is,

- ▶ Linear search
- ▶ **Binary search (Pg 188)**
- ▶ Quick search
- ▶ Random search

In binary search algorithm, the 'divide and conquer' strategy is applied. This plies only to sorted arrays in ascending or descending order.

Question No: 8 (Marks: 1) - Please choose one____

The address operator (&) can be used with,



- ▶ Statement
- ▶ Expression
- ▶ Variable
- ▶ Constant

Question No: 9 (Marks: 1) - Please choose one_____

When a pointer is incremented, it actually jumps the number of memory addresses

- ▶ According to data type (Pg 160)
- ▶ 1 byte exactly
- ▶ 1 bit exactly
- ▶ A pointer variable can not be incremented

Question No: 11 (Marks: 1) - Please choose one_____

Call by reference mechanism should be used in a program when there is

- i. large amount of data to be passed
- ii. small amount of data to be passed



iii. need to change the passed data

iv. no need to change the passed data

Choose the appropriate option for the above case.

- ▶ (i) and (ii) only
- ▶ **(i) and (iii) only**
- ▶ (ii) and (iii) only
- ▶ (ii) and (iv) only

Question No: 12 (Marks: 1) - Please choose one_

Which of the following is the starting index of an array in C++?

- ▶ **0**
- ▶ 1
- ▶ -1
- ▶ any number .

Question No: 13 (Marks: 1) - Please choose one_

The return type of a function that do not return any value must be _

- ▶ int
- ▶ **void**
- ▶ double
- ▶ float

Question No: 14 (Marks: 1) - Please choose one_

Which of the following is an extension of header file?

- ▶ .exe
- ▶ .txt
- ▶ **.h**
- ▶ .c

Question No: 15 (Marks: 1) - Please choose one__

We want to access array in random order which approach is better?

- ▶ Pointers



- ▶ **Array index (Pg 176)**
- ▶ Both pointers and array index are better
- ▶ None of the given options.

Question No: 16 (Marks: 1) - Please choose one_____

When we declare a multidimensional array the compiler store the elements of multidimensionalarray in the form of,

- ▶ Columns
- ▶ Rows
- ▶ **Contiguous memory location (Pg 174)**
- ▶ Matrix

MIDTERM EXAMINATION 2009

Question No: 1 (Marks: 1) - Please choose oneIn C/C++ the string constant is enclosed

- ▶ In curly braces



- ▶ In small braces
- ▶ In single quotes
- ▶ **In double quotes**

Question No: 2 (Marks: 1) - Please choose one
The size of int data type is .

- ▶ 1 bytes
- ▶ 2 bytes
- ▶ 3 bytes
- ▶ **4 bytes (Pg 257)**

Question No: 3 (Marks: 1) - Please choose one
In Flow chart process is represented by

- ▶ **Rectangle (Pg 51)**
- ▶ Arrow symbol
- ▶ Oval
- ▶ Circle

Question No: 5 (Marks: 1) - Please choose one
When we are using const keyword with a variable x then initializing it at the time of declaration is,

- ▶ **Must**
- ▶ Optional
- ▶ Not necessary
- ▶ A syntax error

Question No: 6 (Marks: 1) - Please choose one
Which of the following is the correct way to assign an integer value 5 to element of a matrix say 'm' at second row and third column?

- ▶ **m[2][3] = 5 ;**
- ▶ m[3][2] = 5 ;
- ▶ m[1][2] = 5 ;
- ▶ m[2][3] = '5' ;



Question No: 7 (Marks: 1) - Please choose one

How many total elements must be in two-dimensional array of 3 rows and 2 columns?

- ▶ 4
- ▶ 5
- ▶ 6 (3*2=6)
- ▶ 7

Question No: 8 (Marks: 1) - Please choose one

Which of the following is the correct statement for the following declaration? .
const int *ptr.

Ø ptr is a constant pointer

Ø ptr is constant integer

pointer Ø ptr is a constant

pointer to int Ø ptr is a

pointer to const int

Question No: 9 (Marks: 1) - Please choose one



Consider the following code segment. What will be the output of this code segment?

```
int arr[6] = {2, 3, 7, 4, 5, 6} ;
```

```
int *ptr1
```

```
=&arr[1] ; int
```

```
*ptr2 = &arr[4] ;
```

```
cout << (ptr2-
```

```
ptr1) ;
```

▶ 3

▶ 9

▶ 12

▶ 2

Question No: 10 (Marks: 1) - Please choose one

What will be the correct syntax to assign an array named arr of 5 elements to a pointer ptr?

▶ *ptr = arr ;

▶ ptr = arr ;

▶ *ptr = arr[5] ;

▶ ptr = arr[5] ;

Question No: 11 (Marks: 1) - Please

choose one C is a/an__language

▶ low level

▶ object based

▶ object oriented

▶ **function oriented** (Pg 77)

Question No: 13 (Marks: 1) - Please choose one

The variables having a name, type and size are just like empty boxes.

▶ False

▶ **True .**

Question No: 15 (Marks: 1) - Please choose one

Most efficient method of dealing with structure variables is to define the structure globally



- ▶ True
- ▶ False

Question No: 16 (Marks: 1) - Please
choose one Syntax of union is identical
to _____

- ▶ **Structure** (pg 242)
- ▶ Class
- ▶ Function
- ▶ None of the given options

MIDTERM EXAMINATION

2008

Question No: 16 (Marks: 1) - Please
choose one In Program
commenting the code liberally is

- ▶ **Useful.**
- ▶ Time consuming





SUBSCRIBE

AR Lucky Bahi



► Not necessary

Question :If we want to store a string “abc” in an array str then the size of this array must be atleast,

- (a) 2
- (b) 3
- (c) 4
- (d) 5

Question :How many bytes will the pointer intPtr of type int move in the following statement? `intPtr += 3 ;`

- (a) 3 bytes
- (b) 6 bytes
- (c) 12 bytes
- (d) 24 bytes

MIDTERM EXAMINATION

2007

Question :The remainder (%) operator is,

- An arithmetic operator (Pg 258)
- A logical operator
- A relational operator
- A division operator .

Question :When a call to function statement is encountered,

- The control is transfer to its Prototype
- The control is transfer to its definition
- The compiler stop execution of whole program
- The program hangs



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question # 1 of 10 (Start time: 06:31:50 PM) Total Marks: 1
if $(a > b \ \&\& \ a > c)$ then the condition will be true only if [Both \$a > b\$ and \$a > c\$ are true](#)

$a > b$ is false and $a > c$ is true
 $a > b$ is true and $a > c$ is false
Both $a > b$ and $a > c$ are false

Question # 2 of 10 (Start time: 06:32:48 PM) Total Marks: 1

In while loop the loop counter must be initialized,

With in the loop

[Before entering the](#)

[loop](#) At the end of the

loop None of the given options

Question # 3 of 10 (Start time: 06:33:15 PM) Total Marks: 1

_____ of a variable means the locations within a program from where it can be accessed.

Data
type
Visibility
Value

[Reference](#)



SUBSCRIBE

AR Lucky Bahi





Question # 4 of 10 (Start time: 06:33:49 PM) Total Marks: 1

Switch support_____data.

Integer

Charact

erFloat

Both integer and character

Question # 5 of 10 (Start time: 06:34:31 PM) Total Marks: 1

A function is a block of statements that can be defined once and used _____i
nthe program.

One time

Two

times

Three

times

[As many times as user wants](#)

Question # 6 of 10 (Start time: 06:35:13 PM) Total Marks: 1

_____statement is used to terminate the processing of a particular case and exit from switch structure.

if

goto

[break](#)

[continue](#)





SUBSCRIBE

AR Lucky Bahi



[Downloaded from internet \(vudigiacademy.com no copyright for this data\)](#)

Question # 7 of 10 (Start time: 06:35:32 PM) Total

Marks: 1 The most suitable data type for number

325.25 is _____.

char

int

short

float

[float](#)

Question # 8 of 10 (Start time: 06:35:51 PM) Total Marks: 1

X is an integer variable; what does X++ means,

Add 1 two times in X value

[Add 1 in X](#)

[value](#) Add 2 in

X value None

of these

Question # 9 of 10 (Start time: 06:36:12 PM) Total Marks: 1

The operators ++ and -- are used to increment or decrement the value of a variable by _

[1](#)



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question # 1 of 10 (Start time: 12:31:13 PM) Total Marks: 1

The result of $4\%3$ will be

2

1.5

1

1.33

Question # 2 of 10 (Start time: 12:31:34 PM) Total Marks: 1

While developing a program; should we think about the user interface? [Yes](#)

No

Question # 3 of 10 (Start time: 12:32:03 PM) Total Marks: 1

Which of the following is the right syntax to declare a variable in C++?

VariableName

Datatype;

Data Type =

VariableName;

[Data Type](#)

[VariableName;](#)

(Data Type)

VariableName;

Question # 4 of 10 (Start time: 12:32:30 PM

) Total Marks: 1 What will be the resultant

value of this expression $x = 17\%3$? 1



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



2

3

4

Question # 5 of 10 (Start time: 12:32:50 PM) Total Marks: 1

What will be the result of the expression $k = ++m$; if initially $k = 0$ and $m = 5$?

0

5

6

4

Question # 6 of 10 (Start time: 12:33:08 PM) Total Marks: 1

Function prototype is written,

Within main function

After the return

statement in main

Before the return

statement in main

Before call of that
function



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question # 7 of 10 (Start time: 12:34:02 PM)

Total Marks: 1 Switch statement can be used
in place of

_____stateme
nt.break

contin

ue

[Multip](#)

[le if](#)

goto

Question # 8 of 10 (Start time: 12:34:46 PM) Total Marks: 1

In while loop the loop counter must be initialized,

With in the loop

[Before entering](#)

[the loop](#) At the

end of the loop

None of the given

options

Question # 9 of 10 (Start time: 12:35:28 PM) Total Marks: 1

What logical error exists in the following arithmetic expression? $X = 50 / (2 \% 2) + 9$

() parenthesis are not allowed in
expressions [Division by zero will](#)

[occur in this expression](#) Order of

the expression is not according

to rules We can not use %

operator in expressions

Question # 10 of 10 (Start time: 12:36:06 PM) Total Marks: 1



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Loops are _____ Structure.

Decision

Sequential

[Repetition](#)

[pg 560](#)

None of the given options

1. Each pass through a loop is called a/an
 - [a] enumeration
 - [b] iteration
 - [c] culmination
 - [d] pass through

[Downloaded from internet \(vudigiacademy.com no copyright for this data\)](#)

2. Which looping process checks the test condition at the end of the loop?
 - [a] for
 - [b] while
 - [c] do-while
 - [d] no looping process checks the test

condition at the end [Downloaded from internet \(vudigiacademy.com no copyright for this data\)](#)

3. A continue statement causes execution to skip to
 - [a] the return 0; statement
 - [b] the first statement after the loop
 - [c] the statement following the continue statement
 - [d] the next iteration of the loop

[Downloaded from internet \(vudigiacademy.com no copyright for this data\)](#)



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



4. In a group of nested loops, which loop is executed the most number of times?
- [a] the outermost loop
 - [b] the innermost loop
 - [c] all loops are executed the same number of times
 - [d] cannot be determined without knowing the size of the loops
- Downloaded from internet
(vudigiacademy.com no copyright for this data)
5. The statement `i++;` is equivalent to
- [a] `i = i + i;`



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



[b] `i = i + 1;`

[c] `i = i - 1;`

[d] `i --;`

Downloaded from internet (vudigiacademy.com no copyright for this data)

6. Which looping process is best used when the number of iterations is known?

[a] `for`

[b] `while`

[c] `do-while`

[d] all looping processes require that the

iterations be known Downloaded from internet

(vudigiacademy.com no copyright for this data)

7. What's wrong? `for (int k = 2, k <= 12, k++)`

[a] the increment should always be `++k`

[b] the variable must always be the letter `i` when using a `for` loop

[c] there should be a semicolon at the end of the statement

[d] the commas should be semicolons

Downloaded from internet (vudigiacademy.com no copyright for this data)

8. What's wrong? `while( (i < 10) && (i > 24))`

[a] the logical operator `&&` cannot be used in a test condition

[b] the `while` loop is an exit-condition loop

[c] the test condition is always false

[d] the test condition is always true

Downloaded from internet (vudigiacademy.com no copyright for this data)

9. If there is more than one statement in the block of a `for` loop, which of the following must be placed at the beginning and the ending of the loop block?

[a] parentheses `( )`

[b] braces `{ }`

[c] brackets `[ ]`

[d] arrows `< >`

Downloaded from internet (vudigiacademy.com no copyright for this data)



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



10. What's wrong? $(x = 4 \ \&\& \ y = 5) ? (a = 5) ; (b = 6);$

- [a] the question mark should be an equal sign
- [b] the first semicolon should be a colon
- [c] there are too many variables in the statement
- [d] the conditional operator is only used with apstrings

Downloaded from internet (vudigiacademy.com no copyright for this data)

suppose we have `int y[10];` To access the 4th element of the array we write__

`y[4];`

`y[3];`

`y[2];`

none of given

From the following; which one is the range of Random number generator function `rand()`?

0 – 32768



SUBSCRIBE

AR Lucky Bahi





1 – 32768

0 – 32767

1 – 32767

From following; which one is the correct syntax of an array initialize:
Array size is 10 and it is of double data type to value 0?

`arr[10] = {0.0};`

`double arr[10]=`

`0.0; double arr[10]`

`= {0.0};double`

`arr[] = 0.0;`

The string in the array is terminated by a__

zer

o

nil

nul

l

one

In C/C++; by default arguments are passed by__to a function.





Referen
ce Value
Type
Data

1

char name [] = "Hello World" ; In the above statement, a
memory_of_characters will be allocated

13

11

12

10

_____Keyword is used to return some value from a function.

break
return
contin
uegoto





Which of the function call is call by value for the following function prototype? float add(int);





SUBSCRIBE

AR Lucky Bahi



add(&x);

add(x);

add(int

x);

add(*x);

The increment of a pointer depends on its_____.

variable

value

data

type

None of the given

The ASCII code of null character is_____

000

010

111

110

Pointers are a special type of_____in which a memory address is stored

variables



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Location

Character

rs

None of the
given just for
copy paste

1- Memory allocated from heap or free store

__.Select correct option:

can be returned back to the

system automatically can be

allocated to classes only

cannot be returned back unless freed explicitly using malloc and realloc

cannot be returned back unless freed explicitly using free and delete
operators

2- Once the_____are created, they exist for the life

time of the program Select correct option:

local variables

non static

variables

static

variables



SUBSCRIBE

AR Lucky Bahi





automatic

variables





SUBSCRIBE

AR Lucky Bahi



Once the static variables are created, they exist for the life of the program. They do not die. So returning their reference is all right.3- The members of a class declared with the keyword struct are__by default.

Select correct option:

static

privat

e

prote

cted

publi

c.

The members of a class declared with the keyword struct are public by default. A structure is inherited publicly by default.

Downloaded from internet (vudigiacademy.com no copyright for this data)

4- If the memory in the free store is not

sufficient

.Select correct option:

malloc

function



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



returns 1

malloc

function

returns 0

malloc functions returns NULL pointer

malloc function returns free space

if the memory in the free store is not sufficient enough to fulfill the request. malloc() function returns NULL pointer if the memory is not enough. In C++, 0 is returned instead of NULL pointer.

5. This reference to a variable can be obtained by preceding the identifier of a variable with

.Select correct option:

dot operator

ampersand sign &

^ sign

☐ operator

6- Once an object is declared as a friend,

__.Select correct option:



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



it has access to all non-public members as if they were public

it has access to public members only

it has no access to data

members of the class it has

to protected data members

only

- ☐ Friend declarations introduce extra coupling between classes
- ☐ Once an object is declared as a friend, it has access to all non-public members as if they were public
- ☐ Access is unidirectional If B is designated as friend of A, B can access A's non-public members; A cannot access B's
- ☐ A friend function of a class is defined outside of that class's scope



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



7- Reference variables must

___.Select correct option:

not be initialized after

they are declared be

initialized after they are

declared contain integer

value

contain zero value

8- If the request of new operator is not fulfilled due to insufficient memory in the

Select correct option:

the new operator

returns 2 the

new operator

returns 1

malloc functions returns NULL pointer

malloc function returns free space



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



9-

R

reference is not really an address it is

__. Select correct option:

a

synonym

memory an

antonym

memory a

value

a number

10-

I

If the request of new operator is not fulfilled due to insufficient memory

in

the

heap

__. Select correct option:

the new operator

returns 2 the

new operator

returns 1 the



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



operator returns

0

free operator returns nothing

11- Functions declared with the ___ specifier in a class member list are called friend functions of that class.
Select correct option:

protected

private

Public

friend



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Functions declared with the friend specifier in a class member list are called *friend functions* of that class. Classes declared with the friend specifier in the member list of another class are called *friend classes* of that class.

12- _____ p
public or private keywords can be ____
Select correct option:

written only for once in the class or
structure declaration **written multiple
times in the class or structure declaration**
written only twice in the class declaration
written outside the class

Section 11.1 Introduction

11.1 Q1: Which of the following is not an operator
overloaded by the C++ language? [Downloaded from
internet \(vudigiacademy.com no copyright for this
data\)](#)

pow.

>>.

+.<

<<.

Which of the following is true about streams?

- A. It is a sequence of bytes
- B. It is an ordered sequence
- c. All bytes can go through the stream simultaneously



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



D. Bytes that enters first into the stream will go out at last A only

C

only

A

and

B A

and

D

Stream is a sequence of bytes. It is an ordered sequence. Let's compare it with the door example. The person who enters first will go out of the door first. The person who enters behind someone will go out behind that person.

Similarly streams are also ordered sequence. The thing that enters first into the stream will go out first. You should think streams as ordered sequence of bytes. Byte is a unit of measure. A byte can store one character, so you can think of an ordered sequence of characters.

Section 11.2 Fundamentals of Operator Overloading

11.2 Q1: To use an operator on user-defined class objects, operator overloading:

Must never be used, with three exceptions. Must never be used.

Must always be used.

Must always be used, with three exceptions.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



11.2 Q2: The correct function name for overloading the addition (+) operator is:

operator_+.

operator

r:+.

operator

r+.

operator

r(+).

Downloaded from internet

(vudigiacademy.com no copyright for this

data) Section 11.3 Restrictions on Operator

Overloading

11.3 Q1: Which of the following operators cannot be overloaded?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



The .
operator.
The ->
operator.
The []
operator.
The &
operator.

11.3 Q2: Which statement about operator overloading is False?

New operators can never be created.
Certain overloaded operators can change the number of arguments they take.
The precedence of an operator cannot be changed by overloading. Overloading cannot change how an operator works on built-in types.

11.3 Q3: To implicitly overload the += operator:

Only the = operator needs to be overloaded. Only the + operator needs to be overloaded.
The += operator cannot be overloaded implicitly.
Both the + and = operators need to be overloaded.

Downloaded from internet
(vudigiacademy.com no copyright for this data)

Section 11.4 Operator Functions as

Class Members vs. Global Functions

11.4 Q1: Which of the following operators can be overloaded as a global function?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



0.
 ==.
 +
 =.
 []
 .

11.4 Q2: Which situation would require the operator to be overloaded as a global function?

The left most operand must be a class object (or a reference to a class object).
 The left operand is an int.
 The operator returns a reference. The overloaded operator is =.

11.4 Q3: An overloaded + operator takes a class object and a double as operands. For it to be commutative (i.e., a + b and b + a both work):

The + operator cannot be overloaded to be commutative. operator+ must be a non-member function.
 operator+ must be a member function of the class from which the objects are instantiated.

It must be overloaded twice; the operator+ function that takes the object as the left operand must be a member function, and the other operator+ function must be a global function.

Downloaded from internet (vudigiacademy.com
 no copyright for this data) Section 11.5
 Overloading Stream Insertion and Stream



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Extraction Operators

11.5 Q1: Suppose you have a programmer-defined data type `Data` and want to overload the `<<` operator to output your data type to the screen in the form `cout << dataToPrint;` and allow cascaded function calls.

The first line of the function definition would be:

```
ostream &operator<<( const Data &dataToPrint, ostream &output ).
    ostream &operator<<( ostream &output,
    const Data &dataToPrint ).ostream
    operator<<( ostream &output, const Data
    &dataToPrint ). ostream operator<<( const
    Data &dataToPrint, ostream &output ).
```

Section 11.6 Overloading Unary Operators

11.6 Q1: Suppose the unary `!` operator is an overloaded member function of class `String`. For a `String` object `s`, which function call is generated by the compiler when it finds the expression `!s`?

A compiler error results because no arguments are given.
`operator!( s ).`

`s.operator!( default_value1,`
`default_value2,...).s.operator!().`



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Section 11.7 Overloading Binary Operators

11.7 Q1: y and z are user-defined objects and the += operator is an overloaded member function. The operator is overloaded such that y += z adds z and y, then stores the result in y. Which of the following expressions is always equivalent to y += z?

y.operator

+=(z).y

= y + z.

y = y.operator+=(z).

y.operator+=(y + z).

11.7 Q2: For operators overloaded as non-static member functions:

Both binary and unary operators
take one argument. Neither binary
nor unary operators can have
arguments.

Binary operators can have two arguments and unary operators can
have one.

Binary operators can have one argument, and unary operators cannot
have any.

Section 11.8 Case Study: Array Class

11.8 Q1: Which of the following is False?

Two arrays cannot be meaningfully compared with equality or
relational operators.

C++ ensures that you cannot “walk off” either end of an array.

An entire non-char array cannot be input or output at once.

Arrays cannot be assigned to one another (i.e., array1 = array2;).

11.8 Q2: The array subscript operator [], when overloaded, cannot:

Take multiple values inside (e.g., [4 8]).



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Take a float as an operand.

Take user-defined

objects as operands. Be

used with linked list

classes.

Downloaded from internet (vudigiacademy.com no copyright for this data)

11.8 Q3: A copy constructor:

None of the above.

Is a constructor that takes no arguments.

Is a constructor with only default arguments.

Is a constructor that initializes a newly declared object to the value of an existing object of the same

clas

s.

11.8 Q4: Copy constructors must receive its argument by reference because:

The pointer needs to know the address of the original

data, not a temporary copy of it. The copy of the

argument passed by value has function scope.

Otherwise the constructor will only make a copy of a pointer to an object.

Otherwise infinite recursion occurs.

11.8 Q5: To prevent class objects

from being copied: Make

the copy constructor

private.

None of the above.

Make the overloaded assignment operator private.

Both (a) and (b).



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Section 11.9 Converting between Types

11.9 Q1: Conversion constructors:

Can convert between user-defined types.

Are implicitly defined by the compiler if not explicitly written by the programmer. Cannot convert built-in types to user defined types.

Can have multiple arguments.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



11.9 Q2: The prototypes of overloaded cast operator functions do not:

Specify the type they convert to.

Need to be defined inside the class whose objects are being converted. Specify the type that is being converted.

Specify a return type.

11.9 Q3: Which of the following lines would be the prototype for an overloaded cast operator function that converts an object of user-defined type Time into a double?

Time::operator_cast(d
ouble) const;.

Time::static_cast
double() const;.

Time::operator
double() const;.

d. Time::double() const;.

[Downloaded from internet](#)

[\(vudigiacademy.com no copyright for this data\)](#) Section 11.10 Case Study: String Class

11.10 Q1: Conversion constructors cannot:

Be used to convert the arguments for overloaded operators to the types needed by those overloaded operators.

Take exactly one argument.

Be used implicitly in series to match the needs of an overloaded operator.

Be applied implicitly.

11.10 Q2: Which of the following is not a disadvantage of default memberwise copy with objects containing pointers?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Having the possibility of leaving a dangling pointer.
Allowing both objects to point to the same dynamically allocated storage.

Requiring the explicit overloading of the assignment operator.

Allowing the destructor of one object to be called while leaving the second pointer, to the same memory location, intact.

11.10 Q3: Assume that the function call operator() is overloaded for data type String in the usual sense of selecting a substring from a larger string. For a String object string1 with the character string "ABCDEFGH", what string does string1(4 , 2) return?

"CDEF".

"EF".

"CD".

"EFGH".

Section 11.11 Overloading ++ and --

11.11 Q1: The conventional way to distinguish between the overloaded preincrement and postincrement operators(++) is:

To assign a dummy value to preincrement.

To make the argument list of postincrement include an int.

To have the postincrement operator call the preincrement operator. Implicitly done by the compiler.

11.11 Q2: Because the postfix increment operator returns objects by value and the prefix increment operator returns objects by reference:

The postfix increment operator returns the actual incremented object with its new value.

The postfix increment operator typically returns a temporary object



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



that contains the original value of the object before the increment occurred.

Prefix increment has slightly more overhead than postfix increment. Objects returned by postfix increment cannot be used in larger expressions.

Downloaded from internet
(vudigiacademy.com no copyright for this data) Section 11.12 Case Study: A Date Class



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



11.12 Q1: There exists a data type Date with member function Increment that increments the current Date object by one. The ++ operator is being overloaded to postincrement an object of type Date. Select the correct implementation:

```
Date Date::operator++( int )
{
    Date temp
    = *this;
    Increment(
    ); return
    *temp;
}
```

```
Date Date::operator++( int )
{
    Increment();
    Date temp
    = *this;
    return
    temp;
}
```

```
Date Date::operator++( int )
{
    Date temp
    = *this;
    return this;
    temp.Incre
    ment();
}
```



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



```

Date Date::operator++( int )
{

```

```

    Date temp = *this;
    Increment();
    return temp;

```

```

}.

```

Section 11.13 Standard Library Class string
 11.13 Q1: Which of the following is False?

- b. Class string provides bounds checking in its member function at.
- d. An exception is thrown, if the argument to string's at member function is an invalid subscript.

Class string's overloaded [] operator returns a vector element as an rvalue or an lvalue, depending on the context.

A string can be defined to store any data type.

yuzs

Section 11.14 explicit Constructors
 11.14 Q1: An explicit constructor:

Cannot be called outside of the class it is declared in. Does not initialize its class's data members.

Can be implicitly called by the compiler to perform a data type conversion.

Must take exactly one argument.

Section 10.2 const (Constant) Objects and const Member Functions

10.2 Q1: Which of the following statements will not produce a syntax error?

Defining a const member function that modifies a data member of the object.

Declaring an object to be const.

Declaring a constructor to be const.

Invoking a non-const member function on a const object.

10.2 Q2: The code fragment:



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



```
Increment::Increment(  
int c, int i )  
{ increment ( i )  
count = c;
```



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



}
does not cause any compilation errors. This tells you that:
increment must be a const
variable. count must be a
const variable. increment
must be a non-const
variable. count must be a
non-const variable.

Section 10.3 Composition: Objects as Members of Classes

10.3 Q1: When composition (one object having another object as a member) is used: Member objects are destructed last, in the order they are declared in the host's class. The host object is constructed first and then the member objects are placed into it.

Member objects are constructed first, in the order they are declared in the host's class.

Member objects are constructed first, in the order they appear in the host constructor's initializer list.

10.3 Q2: An error occurs if:

A non-reference, non-const, primitive data member is initialized in the member initialization list.

An object data member is not initialized in the member initialization list and does not have a default constructor.

An object data member is not initialized in the member initialization list. An object data member does not have a default constructor.

Section 10.4 friend Functions and friend Classes

10.4 Q1:

If the line:

friend class A;

appears in class B, and the line:

friend class B;

appears in class C, then:

Class A can access private variables of class B.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Class A is a friend of class C.

Class B can access class A's private variables.

Class C can call class A's private member functions.

10.4 Q2: Which of the following is not true about friend functions and friend classes?

A class can either grant friendship to or take friendship from another class using the friend keyword.

The friendship relationship is neither symmetric nor transitive.

A friend of a class can access all of its private data member and member functions. A friend declaration can appear anywhere in a class definition.

Section 10.5 Using the this Pointer

10.5 Q1: For a non-constant member function of class Test, the this pointer has type: const Test *.

Test * const.

const Test *

const.Test

const *.

10.5 Q2: Inside a function definition for a member function of an object with data element x, which of the following is not equivalent to this->x:

(* (& (*this)

)).x.

(*this).x.

*this

.x.x.

10.5 Q3: Assume that t is an object of class Test, which has member functions a(), b(), c() and d(). If the functions a(), b() and c() all return references to an object of class Test (using the dereferenced this pointer) and function d() is declared void, which of the following statements will not produce a syntax error:



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



t.a().b().d());



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



```
t.d().c();  
t.a().t.d();  
a().b().t;
```

Section 10.6 Dynamic Memory Management with Operators new and delete

10.6 Q1: Which of the following is False about the new operator and the object for which it allocates memory?

It automatically destroys the object after main is exited.

It returns a pointer.

It calls the object's constructor.

It does not require the size of the object to be explicitly specified in the new expression.

10.6 Q2: The delete operator:

Is called implicitly at the end of a program.

Must be told which destructor to call when

destroying an object. Can delete an entire

array of objects declared using new. Can

terminate the program.

Section 10.7 static Class Members

10.7 Q1: If Americans are objects of the same class, which of the following attributes would most likely be represented by a static variable of that class?

Age.

Favorite

food. Place

of birth.

The

President.

10.7 Q2: static data members of a certain class:

Cannot be changed, even by objects of the

same that class. Can be accessed only if an

object of that class exists.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Have class scope.

Can only be changed by static member functions.

10.7 Q3: static member functions:

Can be declared

const as well. Can use

the this pointer.

Cannot be called until an object of their class is instantiated.

Can only access other static member functions and static data members.

Section 10.8 Data Abstraction and Information Hiding

10.8 Q1: Which of the following is not an abstract data type? An ASCII character.

A for loop.

An int.

A user-defined class.

10.8 Q2: Which of the following are true about an abstract data type? I. Captures a data representation.

II. Defines the operations that are allowed on its data. III. Replaces structured programming.

I and II.

I and III.

I, II and III.

II and III.

Section 10.8.1 Example: Array Abstract Data Type

10.8.1 Q1: Which of the following capabilities do “raw”

C++ arrays not provide? Dynamic size expansion to accommodate more elements.

Array

comparison.

Subscript range

checking.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



“Raw” arrays do not provide any of the above capabilities.

Section 10.8.2 Example: String Abstract Data Type

10.8.2 Q1: Instead of including a string data type among C++’s built-in data types, C++: Was designed to include mechanisms for creating and implementing string abstract data types through classes.

Was designed to include mechanisms for creating and implementing string abstract data types through classes.

Forces the programmer to make do with char array strings. Chose to ignore the need for a string data type. None of the above.

Section 10.8.3 Example: Queue Abstract Data Type

10.8.3 Q1: The numbers 3, 2, 5, 7 are enqueued in a queue in that order, then three numbers are dequeued, and finally 3, 7, 9, 4 are enqueued in that order. What is the first number in the queue (the next number to be dequeued)?

- 3.
- 7.
- 9.
- 4.

Section 10.9 Container Classes and Iterators

10.9 Q1: Which of the following is not a type of container (collection) class?

floats.

Stacks.

Arrays.

Linked

lists.

Section 10.10 Proxy Classes

10.10 Q1: Proxy classes are best described as an example of:



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Structured programming.
Object-oriented programming (as used in the text).

Information hiding.

Utility functions.

10.10 Q2: In addition to hiding the implementation details that the ordinary method of “separating implementation from interface” would hide, using a proxy class also hides:

The definition of access

functions. The

definition of inline

functions.

The definition of constructors and the destructor.

The names of private data members.

Section 5.2 Essentials of Counter-Controlled Repetition

5.2 Q1: Which of the following does counter-controlled repetition require?

A condition that tests for the final value.

Counter-controlled repetition requires all of the above.

An increment or decrement by which the control variable is modified each time through the loop.

An initial value.

5.2 Q2: The

statement while (

--counter >= 1)

counter % 2 ? cout << "A" :

cout << "B"; cannot be

rewritten as:



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



```

while ( --counter >= 1 )
    if ( counter % 2 )
        cout << "A";
    else
        cout << "B";

```

```

while ( counter >= 1 )
    if ( counter % 2 )
        cout << "A";
    else

```

```

while ( --counter >= 1 )
    counter % 2 == 0 ? cout << "B" : cout << "A";

```

```

while ( counter > 1 )
{
    --counter;
    if ( counter % 2 )
        cout << "A";
    else
        cout << "B";
}

```

5.2 Q3: Which of the following is a bad programming practice?

Using floating-point values for counters in counter-controlled repetition.

Indenting the statements in the body of each control structure. Nesting multiple repetition structures one within another.

Placing vertical spacing above and below control structures.

Section 5.3 for Repetition Statement

5.3 Q1: If a variable is declared in the initialization expression of a for structure, then:



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



It can not be used in any structures that are nested in that for structure. It retains its final value after the loop is finished.

The scope of the variable is restricted to that particular for loop.

It is automatically reinitialized to zero once the loop is finished.

5.3 Q2: Which of the following is not true?

The initialization and increment expressions can be comma-separated lists.

You must declare the control variable outside of the for loop.

The three expressions in the for structure are optional.

A for loop can always be used to replace a while loop, and vice versa.

5.3 Q3: Consider the execution of the following for loop
`for (int x = 1; x < 5; increment )`

`cout << x + 1 << endl;`

If the last value printed is 5, which of the following might have been used for increment?

Any of the above.

`x += 1.`

a. `x++.`

`++x.`

Section 5.4 Examples Using the for Statement

5.4 Q1: Which of the following for headers is not valid?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



```
for ( int i = 0; i <
10; i++ ).int i = 0;
for ( ; i < 10; i++ ).
for ( int i = 0; int j = 5; ; i++ ).
for ( int i = 0; i < 10; ).
```

A Caution about Using Type double for Monetary Amounts

5.4 Q2: float and double variables should be used:

To perform monetary
calculations. To store
true/false values.

As imprecise representations of decimal numbers.

As counters.

Using Stream Manipulators to Format Numeric Output

5.4 Q3: Which of the following is a parameterized stream manipulator
used to format output?

set

w.

right

t.

left.

fixed

d.

Section 5.5 do...while Repetition Statement

5.5 Q1: If a do...while structure is used:

Counter-controlled repetition is not possible.

The body of the loop will execute at least once.

An infinite loop will not
take place. An off-by-



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



one error will not occur.

5.5 Q2: What will the following program segment do?

```
int counter = 1;  
do {  
    cout << counter << " ";  
} while ( ++counter <= 10 );
```

Cause a syntax error.
Print the numbers 1 through 11.
Print the numbers 1 through 9.
Print the numbers 1 through 10.

Section 5.6 switch Multiple-Selection Statement

5.6 Q1: A switch statement should be used:

As a multiple-selection structure.
As a single-selection structure.
To replace all if and if...else statements.
As a double-selection structure.

5.6 Q2: In a switch structure:

A default case is required.
A break is required after each case.
A break is required after the default case.
Multiple actions do not need to be enclosed in braces.

5.6 Q3: Which of the following is correct when labeling cases in a switch structure?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Case

1.

Case

1.

case1

. case

1.

5.6 Q4: switch can be
used to test:all
types of constants.

int

constants.

string

constants.

float

constants.

5.6 Q5: Which of the following data types can be used
to represent integers?long.

sho

rt.

char

.

All of the above.

Section 5.7 break and continue Statements

5.7 Q1: Which of the following is False?

break statements exit from the loop in which they are embedded.

continue statements skip the remaining statements in current

iteration of the body of the loop in which they are embedded.

continue and break statements may be embedded within all C++
structures.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



break and continue statements alter the flow of control.

5.7 Q2: Which of the following is False?

Many programmers feel that break and continue violate structured programming.

The effects of break and continue statements can be achieved by structured programming techniques.

You should always try to write the fastest, smallest code possible before attempting to make it simple and correct.

break and continue statements can perform faster than their corresponding structured techniques.

Section 5.8 Logical Operators

5.8 Q1: In C++, the condition (4 > y > 1):

Evaluates correctly and could be replaced by (4 > y && y > 1).
Does not evaluate correctly and should not be replaced by (4 > y && y > 1).

Does not evaluate correctly and should be replaced by (4 > y && y > 1). Evaluates correctly and could not be replaced by (4 > y && y > 1).

5.8 Q2: The OR (||) operator:

Stops evaluation upon finding one condition to be true.

Associates from right to left.

Has higher precedence than the

AND (&&) operator. Is a ternary operator.

5.8 Q3: An operator that associates

from right to left is:()

!=
?:

,,



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



5.8 Q4: The expression `if ( num != 65 )` cannot be replaced by:

`if ( !( num == 65 ) ).`
`if ( num > 65 || num < 65 ).`
`d. if ( !( num - 65 ) ).`
`if ( num - 65 ).`

5.8 Q5: An example of a unary

operator is: The <
 relational operator.
 The = assignment
 operator. The %
 arithmetic operator.

The ! logical
 operator.

Section 5.9 Confusing Equality (==) and Assignment (=) Operators

5.9 Q1: Variables are also known as:

rvalues, and cannot be used
 as lvalues. lvalues, but can
 be used as rvalues. Constant
 variables.

lvalues, and cannot be used as rvalues.

5.9 Q2: Consider the following code, assuming that x is an int with an initial value of 12

```

if( x = 6 )
    cout <<
x;

```

What is the
 output?

12.
 6.

A syntax error is



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



produced. Nothing.

5.9 Q3: Of the following, which is not a logic error?

Failing to initialize counter and total variables before the body of a loop. Not placing curly braces around the body of an if that contains two statements.

Using commas instead of the two required semicolons in a for header.

Using == to assign a value to a variable.

Section 5.10 Structured Programming Summary

5.10 Q1: The _____, _____ and _____ are the only three forms of control necessary.

break, continue,

if...else. sequence,

selection, repetition.

switch, if, else.

for, while, do...while.

5.10 Q2: Which of the following is not one of the

C++ control structures? if.

switch,
do...while.

main.

5.10 Q3: Which of the following is not one the rules for forming structured programs?

Any action state can be replaced by any control statement.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Any transition arrow can be reversed.

Begin with the “simplest activity diagram.”

Any action state can be replaced by two action states in sequence

Section 5.11 (Optional) Software Engineering Case Study: Identifying Objects' States and Activities in the ATM System

5.11 Q1: Which of the following is not a part of a UML state diagram?

A solid circle indicating the initial state.

Arrows with accompanying event description text representing transitions. Rounded rectangles representing states.

Fractions beside each state indicating the likelihood of entering that state.

5.11 Q2: An activity diagram for modeling the actions involved in executing a balance inquiry transaction using the BalanceInquiry object should not include:

Retrieving the user's balance information from the database of accounts. All of the above actions should be modeled in this activity diagram.

Receiving the user's main menu input indicating a desire to inquire the amount of his or her balance.

Displaying the user's balance information on the screen.

Question # 1 of 10 Total Marks: 1

< and > both are _____ operators.

Arithmetic

Relational

Logical PG

258

Mathematica

1



SUBSCRIBE

AR Lucky Bahi





Question # 2 of 10 Total Marks: 1

Find out the logical error in following lines of code. If (x = 10) cout << "x is 10";

10 should be enclosed in quotations

There is no semicolon at the end of if condition

[Assignment operator should not be used for comparison](#)

Variable x should not be inside parenthesis

Question # 3 of 10 Total Marks: 1

What will be the result of the expression $j = i++$; if initially $j = 0$ and $i = 5$?

0

[5](#)

6

4

Question # 4 of 10 Total Marks: 1

Default mechanism of calling a function by passing it array is call by __ and in case of passing variable is call by ____.

Reference, Reference

[Reference, value PG154,](#)

[119](#)Value, Reference

Value, Value

Question # 5 of 10 Total Marks: 1





When the break statement is encountered in a loop's body, it transfers the control

_____from the current loop.





SUBSCRIBE

AR Lucky Bahi



Inside

Outside

To break
statement

To continue
statement

Question # 6 of 10 Total Marks: 1

_____statement is used to terminate the processing of a particular case and exit from switch structure.

I
f
G
o
t
o
B
r
e
a
k

Continue

Downloaded from internet (vudigiacademy.com no copyright for this data)

Question # 7 of 10 Total Marks: 1



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



When the if statement consists of more than one statement then enclosing these statement in braces is__.

Compulsory

Opt
ion
al
Not
req
uir
ed
Rel
eva
nt

Question # 8 of 10 Total Marks: 1

What will be the value of the variable output in the given piece of code? `double output = 0; output = (2 + 2) * 4 + 2 / (4 - 2);`

15

17

12

1

Question # 9 of 10 Total Marks: 1



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



If we assign 2.06721 to an integer variable x, what will be the output if we print x using cout<< statement?

2

2.1

2.06

2.07

Question # 10 of 10 Total Marks: 1

_____ will be used for clarity and to force the order of evaluation in an expression.

'' ''

() PG32

' '

CS201- Introduction to Programming

What will be the correct syntax to declare two-dimensional array of float data type?

- ☐ float arr{2}{2} ;
- ☒ float arr[2][2] ;
- ☐ float arr[2,2] ;
- ☐ float[2][2] arr ;

The statement which cannot be used to increment the



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



variable x is

_____.

- ☐ $x = x + 1;$
- ☐ $x++;$
- ☒ $+x = 1;$
- ☐ $x += 1;$

Determine the output of the following while loop.

```
int counter = 0 ;
```

```
while(counter < 5)
```

```
    cout << counter
```

```
    << " ";counter++;
```

- ☐ 5 4 3 2 1
- ☒ Infinite loop
- ☐ 1 2 3 4
- ☐ 1 2 3 4 5

What will be the result of arithmetic expression

$6 + 27/3 * 3$?

- ☒ 33
- ☐ 45
- ☐ 9
- ☐ 30

The number 544.53 must be stored in_data type.

- ☐ int
- ☐ Short
- ☒ float
- ☐ char



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Which of the following is a correct way to initialize a variable x of inttype with value 10?

☐ `int x ; x = 10;`

☒ `int x = 10;`



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- ☐ `int x, x = 10;`
- ☐ `x = 10;`

In C, direction of expression evaluation is from_____.

- ☐ Right to Left
- ☐ Left to Left
- ☒ Left to Right
- ☐ Right to Right

What is the size of following array?

`char str[] = "abcd";`

- ☐ 2
- ☒ 3
- ☐ 4
- ☐ 5

Let ptr1 and ptr2 are pointer variables that points to integer datatypes then which one of the following arithmetic is allowed?

- ☒ `ptr1 + ptr2`
- ☐ `ptr1 - ptr2`
- ☐ `ptr1 * ptr2`
- ☐ `ptr1 / ptr2`

A variable declared inside a code block becomes ____ variable for that block.

- ☐ Global
- ☐ Static
- ☒ Local



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Inner

From the options given below, identify the correct output of following code segment.

```
main(){
int x = 5 ;
{
    int x = 4 ;
    cout << x << "," ;
}
cout << x ;
}
```

☐ 5 , 5

☐ 4 , 4



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- ☐ 4, 5
- ☐ 5, 4

What will be the correct syntax for initialization of a pointer ptr with string "programming"?

- ☐ `char *ptr = 'programming' ;`
- ☐ `*ptr = "programming" ;`
- ☐ `char ptr = 'programming' ;`
- ☒ `char *ptr = "programming" ;`

Correcting the errors from a program is termed as__ .

- ☐ Linking
- ☐ Loading
- ☒ Debugging
- ☐ Editing

In C/C++, when two programs a and b are trying to open a filexyz.txt at same time then__.

- ☐ Both programs will generate error
- ☐ Only one of them will succeed in opening that file and other will fail
- ☐ Both programs will open the file
- ☐ One of the program will re-start

A convenient way to implement random access files is by using only

_____.

- Fixed-length Records
- Variant-length Records



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- Variant-length Files
- Variant-length Files

The function write() takes _____ as parameter(s).

- ☐ String of pointer type
- ☐ String of variable lengths, no. of bytes to be read and flags
- ☐ Pointer array of characters and a delimiter
- ☐ String and no. of bytes to be written

_____ is the pointer which determines the position in a file from where the next read operation occurs.

- ☐ Put
- ☐ Seek
- ☐ Get
- ☐ Tell



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



The function `tellg()` returns the current location of the -
_____ pointer.

- ☐ Get
- ☐ Tellptr
- ☐ Write
- ☒ Seekg

Question No: 21 (Marks: 2)

Identify the error in the given code segment and give the reason of the error.

```
main()
{
    int num1[5] = {5,8,3,6,9};
    int *ptr;
    ptr = num1;
    num1++; (This is an increment operator and not use here)
    return 0;
}
```

Question No: 22 (Marks: 2)

Suppose there is a pointer `*sPtr` to structure 'student'. Write down two methods of accessing data member 'name' with `sPtr`.

`*sPtr=&student;`

`*sPtr="student";`



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question No: 23 (Marks: 3)

Explain the logic of the given program code and also determine its output.

```
#include
<iostream.h>
#include<string.h>
main()
{
    char name[10]=
    "Khaqan"; char
    msg[20] =
    "Welcome!";
    cout<<strncat(msg,
    name, 3);
    return 0;
}
```

Out Put (Welcome!Kha)



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question No: 24 (Marks: 3)

What will be the output of following code segment?

```
void func(int [], int);
```

```
main(){
```

```
int arr[3] = {2, 3, 5} ;
```

```
func(arr, 3) ;
```

```
for (int i = 0; i<3; i++)cout
```

```
<< arr[i] << "";
```

```
}
```

```
void func(int a[], int size){ for
```

```
(int i = 0; i<size; i++) a[i] =
```

```
2*a[i];
```

```
}
```

Is main har element ko 2 sy multiply kary ga. Output (2 4 10)



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question No: 1 (Marks: 1) - Please choose one
The function of cin is

- ▶ To display message
- ▶ To read data from keyboard
- ▶ To display output on the screen
- ▶ To send data to printer

Question No: 2 (Marks: 1) - Please choose one

In C/C++ language the header file which is used to perform useful task and manipulation of character data is

- ▶ cplex.h
- ▶ ctype.h
- ▶ stdio.h
- ▶ delay.h

The functions toupper and islower are part of the character handling library [<ctype.h>](#)

Question No: 3 (Marks: 1) - Please choose one
How many parameter(s) function getline() takes?

- ▶ 0
- ▶ 1
- ▶ 2
- ▶ 3

[infile.getLine\(name, maxChar, stopChar\);](#) The first argument is a character array, the array should be large enough to hold the complete line. The second argument is the maximum number of characters to be read. The third one is the character if we want to stop somewhere.

Question No: 4 (Marks: 1) - Please choose one
Word processor is

- ▶ Operating system
- ▶ Application software
- ▶ Device driver
- ▶ Utility software

Question No: 5 (Marks: 1) - Please choose one

For which values of the integer _value will the following code becomes an infiniteloop?

int number=1;



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



```
while (true) {  
    cout <<  
    number;  
    if (number == 3) break;
```



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



```
number += integer_value; }
```

- ▶ any number other than 1 or 2
- ▶ only 0
- ▶ only 1
- ▶ only 2

Ration

al:

```
number += integer_value
```

above line decide the fate of loop so any thing other then zero leads to value of 3 which will quite the loop. Only zero is the value which keeps the loop infinite.

<http://vustudents.ning.com>

Question No: 6 (Marks: 1) - Please choose one

Each pass through a loop is called a/an

- ▶ enumeration
- ▶ Iteration
- ▶ culmination
- ▶ pass through

Question No: 7 (Marks: 1) - Please choose one

A continue statement causes execution to skip to

- ▶ the return 0; statement
- ▶ the first statement after the loop
- ▶ the statements following the continue statement
- ▶ the next iteration of the loop

continue statement is used, when at a certain stage, you don't want to execute the remaining statements inside your loop and want to go to the start of the loop.

Question No: 8 (Marks: 1) - Please choose one



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



What is the correct syntax to declare an array of size 10 of int data type?

- ▶ `int [10] name ;`
- ▶ `name[10] int ;`
- ▶ `int name[10] ;`
- ▶ `int name[] ;`

Question No: 9 (Marks: 1) - Please choose one

Consider the following code segment. What will the following code segment display?

```
int main(){  
  
    int age[10] =  
    {0};cout <<  
    age ;  
  
}
```

- ▶ Values of all elements of array
- ▶ Value of first element of array
- ▶ Starting address of array
- ▶ Address of last array element

Question No: 10 (Marks: 1) - Please choose one

What will be the correct syntax to initialize all elements of two-dimensional array to value 0?

- ▶ `int arr[2][3] = {0,0} ;`
- ▶ `int arr[2][3] = {{0},{0}} ;`
- ▶ `int arr[2][3] = {0},{0} ;`



SUBSCRIBE

AR Lucky Bahi





► `int arr[2][3] = {0} ;`

Question No: 11 (Marks: 1) - Please choose one

How many bytes will the pointer *intPtr* of type `int` move in the following statement?

`intPtr += 3 ;`

- 3 bytes
- 6 bytes
- 12 bytes
- 24 bytes

one `int` is 4 bytes so $4 * 3 = 12$ bytes movement.

Question No: 12 (Marks: 1) - Please choose one

If there are $2^{(n+1)}$ elements in an array then what would be the number of iterations required to search a number using binary search algorithm?

- n elements
- (n+1) elements
- $2(n+1)$ elements
- $2^{(n+1)}$ elements

Question No: 13 (Marks: 1) - Please choose one

Which of the following operator is used to access the value of variable pointed to by a pointer?

- * operator
- -> operator
- && operator
- & operator

Question No: 14 (Marks: 1) - Please choose one





SUBSCRIBE

AR Lucky Bahi



The _____ statement interrupts the flow of control.

<http://vustudents.ning.com>

- ▶ switch
- ▶ continue
- ▶ goto
- ▶ break

Question No: 15 (Marks: 1) - Please choose one

Analysis is the -----step in designing a program

- ▶ Last
- ▶ Middle
- ▶ Post Design
- ▶ First

[analysis will be always followed by design and then code.](#)

Question No: 16 (Marks: 1) - Please choose one

Paying attention to detail in designing a program is ____

- ▶ Time consuming
- ▶ Redundant
- ▶ Necessary
- ▶ Somewhat Good

[In programming, the details matter. This is a very important skill. A good programmer always analyzes the problem statement very carefully and in detail. You should pay attention to all the aspects of the problem.](#)



SUBSCRIBE

AR Lucky Bahi





Question No: 1 (Marks: 1) - Please choose one

A precise sequence of steps to solve a problem is called

- ▶ Statement
- ▶ Program
- ▶ Utility
- ▶ Routine

Question No: 2 (Marks: 1) - Please choose one

The Compiler of C language is written in

- ▶ Java Language
- ▶ UNIX
- ▶ FORTRON Language
- ▶ C Language

The C language is so powerful that the compiler of C and other various operating systems are written in C.

Question No: 3 (Marks: 1) - Please choose one

Initialization of variable at the time of definition is,

- ▶ Must
- ▶ Necessary
- ▶ Good Programming
- ▶ None of the given options

Question No: 4 (Marks: 1) - Please choose one

In if structure the block of statements is executed only,

- ▶ When the condition is false
- ▶ When it contain arithmetic operators
- ▶ When it contain logical operators





SUBSCRIBE

AR Lucky Bahi



► When the condition is true



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question No: 5 (Marks: 1) - Please choose one

Which of the following function(s) is/are included in stdlib.h header file?

- ▶ double atof(const char *nptr)
- ▶ int atoi(const char *nptr)
- ▶ char *strcpy (char *s1, const char *s2)
- ▶ 1 and 2 only

Question No: 6 (Marks: 1) - Please choose one

Dealing with structures and functions passing by reference is the most economical method

- ▶ True
- ▶ False

Question No: 7 (Marks: 1) - Please choose one

Pointer is a variable which store,

- ▶ Data
 - ▶ Memory Address
- ▶ Data Type
- ▶ Values

Question No: 8 (Marks: 1) - Please choose one

Preprocessor program perform its function before ____phase takes place.

- ▶ Editing
- ▶ Linking



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- ▶ Compiling
- ▶ Loading

The C preprocessor modifies a source code file before handing it over to the compiler. You're most likely used to using the preprocessor to include files directly into other files,

Question No: 9 (Marks: 1) - Please choose one

Which of the following can not be a variable name?

- ▶ area
- ▶ _area
- ▶ 10area
- ▶ area2

Question No: 10 (Marks: 1) - Please choose one

Which looping process is best, when the number of iterations is known?

- ▶ for
- ▶ while



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- ▶ do-while
- ▶ all looping processes require that the iterations be known

Question No: 11 (Marks: 1) - Please choose one

Which character is inserted at the end of string to indicate the end of string?

- ▶ new line
- ▶ tab
- ▶ null
- ▶ carriage return

null character inserted at the end of the string by C automatically

Question No: 12 (Marks: 1) - Please choose one

How many bytes are occupied by declaring following array of characters?

```
char str[] = "programming";
```

- ▶ 10
- ▶ 11
- ▶ 12
- ▶ 13

11 plus one for null char (11+1= 12)

Question No: 13 (Marks: 1) - Please choose one

Which of the following header file defines the rand() function?

- ▶ iostream.h
- ▶ conio.h



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- ▶ `stdlib.h`
- ▶ `stdio.h`

The function is *rand()* and is in the standard library. To access this function, we need to include `<stdlib.h>` library in our program. This function will return a random number. The number can be between 0 and 32767.

Question No: 14 (Marks: 1) - Please choose one

Commenting the code _____

- ▶ Makes a program easy to understand for others.
- ▶ Make programs heavy, i.e. more space is needed for executable.
- ▶ Makes it difficult to compile
- ▶ All of the given options.

Question No: 15 (Marks: 1) - Please choose one

What's wrong with this for loop?
`for (int k = 2, k <= 12, k++)`



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- ▶ the increment should always be ++k
- ▶ the variable must always be the letter i when using a for loop
- ▶ there should be a semicolon at the end of the statement
- ▶ the commas should be semicolons

Question No: 16 (Marks: 1) - Please choose one

For which array, the size of the array should be one more than the number of elements in an array?

- ▶ int
- ▶ double
- ▶ float
- ▶ char

&& is ----- operator.

▶ An arithmetic

▶ Logical

▶ Relational

▶ Unary

we use logical operators (&& and ||) for AND and OR



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



respectively with relational operators.

Question No: 4
choose one____

(Marks: 1) - Please

In flow chart, the symbol used for decision making is,

- ▶ Rectangle
- ▶ Circle
- ▶ Arrow
- ▶ Diamond

http://www.ehow.com/about_5081911_symbols-used-flowchart.html

Question No: 5
one_____

(Marks: 1) - Please choose

The correct syntax of do-while loop is,

- ▶ (condition) while; do { statements; };
- ▶ { statements; } do-while ();
- ▶ while(condition); do { statements; };



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



► do { statements; } while (condition);

Question No: 6
choose one____

(Marks: 1) - Please



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



C++ views each file as a sequential stream of_____.

- ▶ Bytes
- ▶ Bits
- ▶ 0's or 1's
- ▶ Words

Question No: 7

(Marks: 1) -

Please choose one_____

If the elements of an array are already sorted then the useful search algorithm is,

- ▶ Linear search
- ▶ Binary search
- ▶ Quick search
- ▶ Random search



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



In binary search algorithm, the 'divide and conquer' strategy is applied. This applies only to sorted arrays in ascending or descending order.

Question No: 8
choose one____

(Marks: 1) - Please

The address operator (&) can be used with,

- ▶ Statement
- ▶ Expression
 - ▶ Variable
- ▶ Constant

Question No: 9
Please choose one_____

(Marks: 1) -

When a pointer is incremented, it actually jumps the number of memory addresses



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- ▶ According to data type
- ▶ 1 byte exactly
- ▶ 1 bit exactly
- ▶ A pointer variable can not be incremented

Question No: 10

(Marks: 1) -

Please choose one _____

Each pass through a loop is called a/an

- ▶ enumeration
- ▶ iteration
- ▶ culmination
- ▶ pass through

Question No: 11

(Marks: 1) - Please

choose one _____

Call by reference mechanism should be used in a program when there is



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- i. large amount of data to be passed
- ii. small amount of data to be passed
- iii. need to change the passed data
- iv. no need to change the passed data

Choose the appropriate option for the above case.

- ▶ (i) and (ii) only
 - ▶ (i) and (iii) only
- ▶ (ii) and (iii) only
- ▶ (ii) and (iv) only

Question No: 12
choose one_____

(Marks: 1) - Please



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Which of the following is the starting index of an array in C++?

▶ 0

▶ 1

▶ -1

▶ any number

Question No: 13
choose one_____

(Marks: 1) - Please

The return type of a function that do not return any value must be __

▶ int

▶ void

▶ double

▶ float

Question No: 14
choose one_____

(Marks: 1) - Please



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Which of the following is an extension of header file?

► .exe

► .txt

► .h

► .c

Question No: 15
choose one_____

(Marks: 1) - Please

We want to access array in random order which approach is better?

► Pointers

► Array index



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- ▶ Both pointers and array index are better
- ▶ None of the given options.

Question No: 16
choose one_____

(Marks: 1) - Please

When we declare a multidimensional array the compiler store the elements of multidimensional array in the form of,

- ▶ Columns
- ▶ Rows
- ▶ Contiguous memory location
- ▶ Matrix

CS201 Quiz No 1 Sahre by Eman November 24, 2014

Q1. The string in the array is terminated by a _____

zero
nil
null
one



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Q2. We can define a matrix as _____ array.

Sorted

Unsorted

Single dimensional

Multi dimensional *

Q3. _____ character is used to indicate the end of the string.

string

New line *

Blank space

Null

Q4. In call by reference, _____ of a variable is passed to the called function.

Name

Data type *

Value

Address

Q5. A function's prototype is written _____ the function call.

After

Before *

Q.6 Characters of a string stored in an array can be accessed directly using array _____.

Manipulation *

Superscript

Postscript

Subscript

Q7. Null character is used to indicate the _____ of string.

start

end *

begin

middle

Q8. If an array has 50 elements, what is allowable range of subscripts?

0 – 49 *



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



1 – 49

0 – 50

1 – 50

Q9. Return type of a function that does not return any value must be _____.

char

int

void *

Q.10. What is the output of the following code if the 3rd case is true
switch (var) { case 'a': cout<<"apple"<<endl; case 'b': cout<<"banana"<<endl; case 'm':
cout<<"mango"<<endl; default: cout<<"any fruit"<<endl; }

mango *

mango any fruit

apple

1: If we pass more than one arguments to a function then they are separated by _____.

Comma ,

2: Which of the following function call is “call by reference” for the following function prototype? int add (int *);

add(*x);

3: _____ statement is used to terminate the processing of a particular case and exit from switch structure.

if

4: What is the output of the following code if the 3rd case is true
switch (var) { case 'a': cout<<"apple"<<endl; case 'b': cout<<"banana"<<endl; case 'm': cout<<"mango"<<endl; default: cout<<"any fruit"<<endl; }

mango

any fruit



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



5: How many times the following do-while loop will execute? `int k = 10; do { cout << "Statements" << endl; k -= 2; } while(k>0);`

6: Using a segment of source code again by adding new functionalities with slight or no modification is termed as _____.
Code modification

7: While loop becomes infinite in which scenario _____.
When the condition is always False

8: _____ are used to compile the code.
compiler

9: In do while loop the condition is checked _____ one execution of loop.
after

1: Which of the following will be the most appropriate data type to store the value 63.547?

Float

2: The result of `4%3` will be
1

3: It is the job of _____ to transfer the executable code from hard disk to main memory.
Loader

4: Compiler translates high level language program into _____.
language code
Machine

5: In call by reference, _____ of a variable is passed to the called function.
address

6: What will be the output of the following while loop? `int counter = 0 ; while(counter < 15) cout << counter << " "; counter++;`
Compile time error



SUBSCRIBE

AR Lucky Bahi





7: _____ Loop executes atleast one times.

do while

8: In which language the compiler of C language is written?

C

9: According to c++ norms; the first character of a variable name must be an alphabet or

Special character

1. Base address is the memory address of _____ element of an array.

1st element (Not Sure)

2ad element

3rd element

none of above

2. In _____, we try to have a precise problem statement

Analysis

Desing

Coding

None of the given

3. Each array declaration must provide the information about all these things except

Name of the array

Type of data stored in the array

The location of the first element to be stored

Number of elements of the array

4. Pointers work by pointing to a particular _____

value

variable

data type

None of the given





SUBSCRIBE

AR Lucky Bahi



5. are conventional names of the command line parameters of the 'main()' function.

'argv' and 'argv'

'argc' and 'argv'

'argc' and 'argu'

None of above

6. Which header file must be included to use the functions tolower() and toupper()?

iostream.h

conio.h

ctype.h (Not Sure)

7. The statement cout << yptr will show the _____ the yptr points to.

Value

memory address

8. In Analysis, we try to have a _____

Determined the inputs

Break of problem

Precise problem statement

None of the given

9. Pointers are a special type of _____ in which a memory address is stored

Variable

10. _____ Returns true if c is a digit and false otherwise.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



int isalpha(int c)
int isalnum(int c)
int isxdigit(int c)
int isdigit(int c)

Question # 1 of 10 Total Marks: 1

< and > both are _____ operators.

Arithmetic

Relational

Logical = Correct Choice

Mathematical

Question # 2 of 10 Total Marks: 1

Find out the logical error in following lines of code. If (x = 10) cout "x is 10";

10 should be enclosed in quotations

There is no semicolon at the end of if condition

Assignment operator should not be used for Comparison = Correct Choice

Variable x should not be inside parenthesis

Question # 3 of 10 Total Marks: 1

What will be the result of the expression j = i++; if initially j = 0 and i = 5?

0

5 = Correct Choice

6

4

Question # 4 of 10 Total Marks: 1

Default mechanism of calling a function by passing it array is call by _____ and in case of passing variable is call by _____.

Reference, Reference

Reference,value = Correct Choice

Value, Reference



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Value, Value

Question # 5 of 10 Total Marks: 1

When the break statement is encountered in a loop's body, it transfers the control _____ from the current loop.

Inside

Outside = Correct Choice

To break statement

To continue statement

Question # 6 of 10 Total Marks: 1

_____ statement is used to terminate the processing of a particular case and exit from switch structure.

If

Goto

Break = Correct Choice

Continue

Question # 7 of 10 Total Marks: 1

When the if statement consists of more than one statement then enclosing these statement in braces is _____.

Compulsory = Correct Choice

Optional

Not required

Relevant

Question # 8 of 10 Total Marks: 1

What will be the value of the variable output in the given piece of code?

double output = 0; output = (2 + 2) * 4 + 2 / (4 - 2);

15

17 = Correct Choice

12

1



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question # 9 of 10 Total Marks: 1

If we assign 2.06721 to an integer variable x, what will be the output if we print x using cout statement?

2 = Correct Choice

2.1

2.06

2.07

Question # 10 of 10 Total Marks: 1

_____ will be used for clarity and to force the order of evaluation in an expression.

" "

()PG32

' '

[] = Correct Choice

1 - Application Softwares are use to

1. Type letters

2. Control computer hardware

3. Solve end user problems = Correct Choice

4. Develop Graphics

2 - Computer can do,

1. More than what we tell it

2. Less then what we tell it

3. Like human being

4. Exactly what we tell it = Correct Choice

3 - we can control our program while it is running by using

1. Debugger = Correct Choice

2. Linker

3. Loader



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



4. Editor

4 - _____ are part of system software

1. Linker and loaders = Correct Choice
2. Operating System and Linker
3. Drivers
4. None of the Given

5 - The remainder (%) operator is,

1. An arithmetic operator = Correct Choice
2. A logical operator
3. A relational operator
4. A division operator

6 - `int x = 2 * 3 + 4 * 5;` What value will x contain in the sample code above?

1. 22
2. 26 = Correct Choice
3. 46
4. 50

7 - What is the correct value to return to the operating system upon the successful completion of a program?

1. -1
2. 1
3. 0 = Correct Choice
4. Programs do not return a value.

8 - What is the only function all C++ programs must contain?

1. start()
2. system()
3. main() = Correct Choice



SUBSCRIBE

AR Lucky Bahi





4. program()

9 - What punctuation is used to signal the beginning and end of code blocks?

1. { } = Correct Choice
2. - > and < -
3. BEGIN and END
4. (and)

10 - What punctuation ends most lines of C++ code?

1. (dot)
2. (semi-colon) = Correct Choice
3. (colon)
4. (single quote)

Question No: 1 (Marks: 1) - Please choose one

A precise sequence of steps to solve a problem is called

- ▶ Statement
- ▶ Program
- ▶ Utility
- ▶ Routine

Question No: 2 (Marks: 1) - Please choose one

The Compiler of C language is written in





SUBSCRIBE

AR Lucky Bahi



- ▶ Java Language
- ▶ UNIX
- ▶ FORTRON Language
- ▶ C Language

The C language is so powerful that the compiler of C and other various operating systems are written in C.

Question No: 3 (Marks: 1) - Please choose one

Initialization of variable at the time of definition is,

- ▶ Must
- ▶ Necessary
- ▶ Good Programming
- ▶ None of the given options

Question No: 4 (Marks: 1) - Please choose one

In if structure the block of statements is executed only,

- ▶ When the condition is false
- ▶ When it contain arithmetic operators
- ▶ When it contain logical operators
- ▶ When the condition is true

Question No: 5 (Marks: 1) - Please choose one



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Which of the following function(s) is/are included in stdlib.h header file?

- ▶ double atof(const char *nptr)
- ▶ int atoi(const char *nptr)
- ▶ char *strcpy (char *s1, const char *s2)
- ▶ 1 and 2 only

Question No: 6 (Marks: 1) - Please choose one

Dealing with structures and functions passing by reference is the most economical method

- ▶ True
- ▶ False

Question No: 7 (Marks: 1) - Please choose one

Pointer is a variable which store,

- ▶ Data
- ▶ Memory Address
- ▶ Data Type
- ▶ Values

Question No: 8 (Marks: 1) - Please choose one



SUBSCRIBE

AR Lucky Bahi





Preprocessor program perform its function before _____ phase takes place.

- ▶ Editing
- ▶ Linking
- ▶ Compiling
- ▶ Loading

The C preprocessor modifies a source code file before handing it over to the compiler. You're most likely used to using the preprocessor to include files directly into other files,

Question No: 9 (Marks: 1) - Please choose one

Which of the following can not be a variable name?

- ▶ area
- ▶ _area
- ▶ 10area
- ▶ area2

Question No: 10 (Marks: 1) - Please choose one

Which looping process is best, when the number of iterations is known?

- ▶ for
- ▶ while
- ▶ do-while
- ▶ all looping processes require that the iterations be known





Question No: 11 (Marks: 1) - Please choose one

Which character is inserted at the end of string to indicate the end of string?

- ▶ new line
- ▶ tab
- ▶ null
- ▶ carriage return

null character inserted at the end of the string by C automatically

Question No: 12 (Marks: 1) - Please choose one

How many bytes are occupied by declaring following array of characters?

`char str[] = "programming";`

- ▶ 10
- ▶ 11
- ▶ 12
- ▶ 13

11 plus one for null char (11+1= 12)

Question No: 13 (Marks: 1) - Please choose one

Which of the following header file defines the `rand()` function?

- ▶ `iostream.h`
- ▶ `conio.h`





► `stdlib.h`

► `stdio.h`

The function is *rand()* and is in the standard library. To access this function, we need to include `<stdlib.h>` library in our program. This function will return a random number. The number can be between 0 and 32767.

Question No: 14 (Marks: 1) - Please choose one

Commenting the code _____

- Makes a program easy to understand for others.
- Make programs heavy, i.e. more space is needed for executable.
- Makes it difficult to compile
- All of the given options.

Question No: 15 (Marks: 1) - Please choose one

What's wrong with this for loop?

`for (int k = 2, k <=12, k++)`

- the increment should always be `++k`
- the variable must always be the letter `i` when using a for loop
- there should be a semicolon at the end of the statement
- the commas should be semicolons

Question No: 16 (Marks: 1) - Please choose one





For which array, the size of the array should be one more than the number of elements in an array?

- ▶ int
- ▶ double
- ▶ float
- ▶ char

Question No: 1 (Marks: 1) - Please choose one

In C/C++ the #include is called,

Header file

[Preprocessor](#) Directive

Statement

Function

Question No: 2 (Marks: 1) - Please choose one

To access the element of two dimensional array we use,

Single referencing

Single dereferencing

Double [dereferencing](#)

Double referencing

Question No: 3 (Marks: 1) - Please choose one

Data Size of the file is always _____ the actual size of the file.

[Greater](#) than





SUBSCRIBE

AR Lucky Bahi



Equal to

Less than or equal to

None of the above

Question No: 4 (Marks: 1) - Please choose one

When an identifier is declared with keyword const then,

Its value can be changed during execution.

[Its value can not be changed](#)

Its value can be changed with arithmetic operator

Its value can be overwritten

Question No: 5 (Marks: 1) - Please choose one

In C/C++ if we define an array of size eight (8) i.e. `int Arr [8];` then the last element of this array will be stored at,

`Arr[0]`

`Arr[8]`

[Arr\[7\]](#)

`Arr[-1]`

Question No: 6 (Marks: 1) - Please choose one

If it is required to copy an array to another array then,

[Both arrays must be of the same size and data type](#)

Both arrays may be of different size

Both arrays may be of different data type



SUBSCRIBE

AR Lucky Bahi





Both arrays may be of different size and type

Question No: 7 (Marks: 1) - Please choose one

In C/C++ all character strings are terminated with,

[Null character](#)

String

Zero

Full stop

Question No: 8 (Marks: 1) - Please choose one

Let suppose

```
struct intorDouble{
```

```
Int ival;
```

```
Double charvar;
```

```
};
```

```
main(){
```

```
intorDouble VAZ;
```

```
int size ;
```

```
size = sizeof(VAZ);
```

```
}
```

What will be the value of variable size, if int occupies 4 bytes and double occupies 8

bytes?





SUBSCRIBE

AR Lucky Bahi



2

4

8

12

Question No: 9 (Marks: 1) - Please choose one

When a pointer is incremented, it actually jumps the number of memory addresses

[According to data type](#)

1 byte exactly

1 bit exactly

A pointer variable can not be incremented

Question No: 10 (Marks: 1) - Please choose one

Do-while loop executes at least,

Zero Time

[One Time](#)

Two Times

N Times

Question No: 11 (Marks: 1) - Please choose one

$+=$, $*=$, $/=$, etc are called,

Assignment operators

Logical operator



SUBSCRIBE

AR Lucky Bahi





Compound assignment operator

Unary operator

Question No: 12 (Marks: 1) - Please choose one

Computer can understand only machine language code.

True

False

Question No: 13 (Marks: 1) - Please choose one

Which of the following is the correct syntax to print multiple values or variables in

a single command using cout?

`cout << "Hello" + x + "\n";`

`cout << "H" << x << "\n";`

`cout << "H", x, "\n";`

`cout << ("H" & x & "\n");`

Question No: 14 (Marks: 1) - Please choose one

The compilers and interpreters also belong to the System Software category.

True

False

Question No: 15 (Marks: 1) - Please choose one

Editors are used to compile the code.

True





False

Question No: 16 (Marks: 1) - Please choose one

The variables having a name, type and size are just like empty boxes.

True

1) Return type of a function that does not return any value must be _____. Select correct option:

char

int

void

doub

le

2) _____ A
function's prototype is written _____ the
function call. Select correct option:

After

Befo

re

With

At the end of

3) What will be the size of the following character
array? `char name[] = "Adeel";` Select correct option:

5





SUBSCRIBE

AR Lucky Bahi



6

4

7

4) _____ In

switch statement there can be
__default statements. Select correct
option:

1

2

3

4

5) _____ will be used for enclosing function
statements into a block. Select correct option:

" "

()



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



[]

{}

6) From following; which one is the correct syntax of an array initialize: Array size is 10 and it is of double data type to value 0? Select correct option:

`arr[10] = {0.0};`

`double arr[10]=`

`0.0; double`

`arr[10] = {0.0};`

`double arr[] =`

`0.0;`

7) Which of the function call is call by value for the following function prototype? `floatadd(int);` Select correct option:

`add(&x);`

`add(x);`

`add(int`

`x);`

`add(*x)`

`;`

8) A function is a block of statements that can be defined once and used in the program.

one

time 2

time

three



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



time

as many times as user wants

9) What will be the size of following

array? `int arr[29]0`

30

29

18

10) Which of the following function call is “call by reference” for the following function prototype? `int add (int *)`

`add(&x`

`);`

`add(int`

`x);`

`add(x);`

`add(*x); *`

11) The string in the array is terminated by a _____



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



0

nil

null

*on

12) If statement is used to terminate the processing of a particular case and exit from switch structure.

if

goto

break

continue

break i

think

13) will be used for enclosing function statements into a block. ""

()

[]

{ } *

14) Default mechanism of calling a function by passing it array is call by __ and in case of passing variable is call by __

Reference,

Reference

Reference,

value * Value,

Reference

Value, Value



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



15) What is the output of the following code, if the first case is true
switch (var) { case 'a': cout<<"apple"<<endl; case 'b':
cout<<"banana"<<endl; case 'm': cout<<"mango"<<endl; default: cout<<"any
fruit"<<endl; }

apple

apple anyfruit

apple banana mango *

none of above

16) Null character is represented by__in C++.

/0

\0 *

\n

\t



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



17) The string in the array is terminated by a _____

zer

o

nil

nul

l

on

e

18) We can define a matrix as_array.

Sorted

Unsort

ed

Single dimensional

Multi dimensional *

19) _____character is used to indicate the end of the string.

string

New line

* Blank

space

Null

20) In call by reference,_____of a variable is passed to the called function.

Name

Data

type *



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Value

Address

21) _____
the function call.

A function's prototype is written

After

Before *

22) _____ C

characters of a string stored in an array can be accessed directly using
array

____.Manipulation *

Superscript

Postscr

ipt

Subscri

pt

23) _____ Null character is used to indicate
the _____ of string.

start

end

*

begi

n



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



midd
le

24) If an array has 50 elements, what is
allowable range of subscripts? $0 - 49$ *

$1 - 49$



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



0 – 50

1 – 50

25) _____ Return type
of a function that does not return any value must be_____.

char

int

void

*

26) What is the output of the following code if the 3rd case is true
switch (var) { case 'a': cout<<"apple"<<endl; case 'b': cout<<"banana"<<endl;
case 'm': cout<<"mango"<<endl; default: cout<<"any fruit"<<endl; }

mango *

mango any

fruitapple

1. What is the correct syntax to declare an array of 15 elements of type float?
2. From the following; which one is the range of Random number generator function rand()? (0 and 32767) Ans
3. When No. of repetition is known then we use the __structure to perform repetition tasks (while loop)
Ans
4. Loops are _____ Structure (Repetition) Ans



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- 5 When the break statement is encountered in a loop's body, it transfers the control _____ from the current loop.

(When a break statement is encountered in a loop, the loop terminates immediately. The control exits the inner most loop if there are nested loop) ans

6. By default, the starting index of an array in C++ is (zero) Ans
(starting point is zero and ending point is less than one)
7. A while loop may execute _____ or more times. (Zero) Ans
8. In C/C++, by default arguments are passed by _____ to a function
(value) I think value but not confirmed
- 9: If we pass more than one arguments to a function then they are separated by _____.
- Comma ,



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



10: Which of the following function call is “call by reference” for the following function prototype? `int add (int *);`

`add(*x);`

11: _____ statement is used to terminate the processing of a particular case and exit from switch structure.

`if`

12: What is the output of the following code if the 3rd case is true
`switch (var) { case 'a': cout<<"apple"<<endl; case 'b': cout<<"banana"<<endl; case 'm': cout<<"mango"<<endl; default: cout<<"any fruit"<<endl; }`

`mang`

`o any`

`fruit`

13: How many times the following do-while loop will execute?
`int k = 10; do { cout<<"Statements"<<endl; k -= 2; } while(k>0);`

14: Using a segment of source code again by adding new functionalities with slight or no modification is termed as_____.

`Code modification`

15: While loop becomes infinite in which scenario_____.

`When the condition is always False`

16: _____ are used to compile the code.

`compiler`



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



17: In do while loop the condition is checked__one execution of loop.

after

18: Which of the following will be the most appropriate data type to store the value 63.547?

Float

19: The result of $4\%3$ will be

20: It is the job of__to transfer the executable code from hard disk to mainmemory.

Loader

21: Compiler translates high level language program into__language code

Machine

2
2: In call by reference,____of a variable is passed to the called function.

address

23

What will be the output of the following while loop? `int counter = 0 ; while(counter < 15)`



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



cout counter “ ”; counter++;

Compile time error

24: _____ Loop executes atleast one times.

do while

2 In which language the compiler of C language is written? C
5:



SUBSCRIBE

AR Lucky Bahi





26: According to c++ norms; the first character of a variable name must be an alphabet or

Special character

Functions declared with the _____ specifier in a class member list are called friend functions of that class.

protected

private

public

friend

Functions declared with the friend specifier in a class member list are called *friend functions* of that class. Classes declared with the friend specifier in the member list of another class are called *friend classes* of that class.

Public or private keywords can be _____

written only for once in the class or structure declaration

written multiple times in the class or structure declaration

written only twice in the class declaration

written outside the class

good practice is to write public or private keywords only once in the class or structure declaration, though there is no syntactical or logical problem in writing them multiple times.

The friend keyword provides access _____.

in one direction only

in two directions

to all classes

to the data members of the friend class only





The *friend* keyword provides access in one direction only. This means that while *OtherClass* is a friend of *ClassOne*, the reverse is not true.

References cannot be uninitialized. Because it is impossible to _____

reinitialize a pointer

reinitialize a reference

initialize a NULL pointer

cast a pointer

References cannot be uninitialized. Because it is impossible to reinitialize a reference, new operator can be used for _____.

only integer data type

only char and integer data types

integer , float, char and double data types

dot operator

Similarly, new operator can be used for other data types like char, float and double etc.

The destructor is used to _____.

allocate memory

deallocate memory

create objects

allocate static memory

Reference is not really an address it is _____.

a synonym

an antonym

a value

a number

Difference Between References and Pointers

The reference in a way keeps the address of the data entity. But it is not really an address it is a synonym,

If we want to allocate memory to an array of 5 integers dynamically, the syntax will be _____.

```
int *iptr ; iptr = new int[5] ;
```

```
integer iptr** ; iptr= new int[5]
```





```
int iptr ; iptr= int [5]
```

```
iptr= new[5]
```

Memory allocated from heap or free store _____.

can be returned back to the system automatically

can be allocated to classes only

cannot be returned back unless freed explicitly using malloc and realloc

cannot be returned back unless freed explicitly using free and delete operators

The memory allocated from free store or heap is a system resource and is not returned back to the system unless explicitly freed using delete or free operators.

Operator overloading is to allow the same operator to be bound to more than one implementation, depending on the types of the _____.

Compilers

Operands

Function names

Applications

Operator overloading is to allow the same operator to be bound to more than one implementation, depending on the types of the operands.

The operator to free the allocated memory using new operator is _____.

free

del

delete

remove

The operator to free the allocated memory using new operator is delete. So whenever, we use new to allocate memory, it will be necessary to make use of 'delete' to deallocate the allocated memory

Question # 1 of 10 (Start time: 02:17:54 PM) Total Marks: 1

By default, the starting index of an array in C++ is _____.

Select correct option:





SUBSCRIBE

AR Lucky Bahi



2

-1

0

1

Question # 2 of 10 (Start time: 02:19:01 PM)

Total Marks: 1

We can define a matrix as _____ array.

Select correct option:

Sorted

Unsorted

Single dimensional

Multi dimensional

Question # 3 of 10 (Start time: 02:19:52 PM)

Total Marks: 1

We can access a global variable _____

Select correct option:

From the functions only

From the loops only

From the main() function only

From anywhere in the program

Question # 4 of 10 (Start time: 02:21:00 PM)

Total Marks: 1

A function's prototype is written _____ the function call.

Select correct option:

After

Before

With



SUBSCRIBE

AR Lucky Bahi





At the end of

Question # 5 of 10 (Start time: 02:22:23 PM) Total Marks: 1

Which of the function call is call by value for the following function prototype? float add(int);

Select correct option:

add(&x);

add(x);

add(int x);

add(*x);

Question # 6 of 10 (Start time: 02:23:22 PM) Total Marks: 1

+= , *= , /= , etc are called,

Select correct option:

Assignment operators

Logical operator

Compound assignment operator

Unary operator

Question # 7 of 10 (Start time: 02:24:02 PM) Total Marks: 1

What is the output of the following code if the 2nd case is true switch (var) { case 'a': cout<<"apple"<<endl; case 'b': cout<<"banana"<<endl; case 'm': cout<<"mango"<<endl; default: cout<<"any fruit"<<endl; }

Select correct option:

banana

banana any fruit





banana mango anyfruit

none of the above

Question # 8 of 10 (Start time: 02:25:00 PM) Total Marks: 1

In C/C++, by default arguments are passed by _____ to a function.

Select correct option:

Reference

Value

Size

Data

Question # 9 of 10 (Start time: 02:25:19 PM) Total Marks: 1

What will be the value of 'a' and 'b' after executing the following statements? `int a = 9; int b = a++; cout/p>`

Select correct option:

10,9

9,10

9,9

10,10

Question # 10 of 10 (Start time: 02:26:43 PM) Total Marks: 1

What is the output of the following code if the 3rd case is true `switch (var) { case 'a': cout<<"apple"<<endl; case 'b': cout<<"banana"<<endl; case 'm': cout<<"mango"<<endl; default: cout<<"any fruit"<<endl; }`

Select correct option:

mango

mango any fruit





apple

none of the above

_____ operator is used to pass the address of a variable in call by reference method.

&

In C++, what will be the highest index of the following array? `int array[15];`

15

For breaking complex problems into smaller pieces we use _____.

Functions

Function prototype is written,

Before the return statement in main

When we call a function, its control

The compiler stops execution of whole program

`+=` , `*=` , `/=` , etc are called,

Compound assignment operator

What will be the result of the expression `k = ++m;` if initially `k = 0` and `m = 5`?

0

By default, the starting index of an array in C++ is _____.

0

What will be the size of the following character array? `char name[] = "Adeel";`

5

_____ statement is used to terminate the processing of a particular case and exit from switch structure.

continue





SUBSCRIBE

AR Lucky Bahi



Question No:1 (Marks: 1) - Please choose one
The first instruction of “COM” file must be at offset:

- ▶ 0x0010
- ▶ 0x0100 (Page 19)
- ▶ 0x1000
- ▶ 0x0000

Question No:2 (Marks: 1) - Please choose one

The execution of the instruction “mov word [ES : 0], 0x0741” will print character “A” on screen , backgroundcolor of the screen will be

- ▶ Black (Page 81)
- ▶ White
- ▶ Red
- ▶ Blue

Question No:3 (Marks: 1) - Please choose one

The iAPX888 architecture consists of__register.

- ▶ 12
- ▶ 14
- ▶ 16 (Page 15)
- ▶ 18

Question No:4 (Marks: 1) - Please choose one

The execution of the instruction “mov word [ES: 0], 0x0741” will print “A” on the screen, color of the character will be

- ▶ Black
- ▶ White (Page 81)
- ▶ Red
- ▶ Blue



SUBSCRIBE

AR Lucky Bahi





Question No:5 (Marks: 1) - Please choose one

One screen location corresponds to a

► Byte

► Word (Page 80)

► Double

byte

Double

word

Question No:6 (Marks: 1) - Please choose one

When an item is pushed on the decrementing stack, the top of the stack is

► First decremented and then element copied on to the stack (Page 68)

► First incremented and then element copied on to the stack

► Decrement after the element copied on to the stack

► Incremented after the element copied on to the stack

Question No:7 (Marks: 1) - Please choose one

Each screen location corresponds to a word, the lower byte of this word contains _

► The character code (Page 81)

► The attribute byte

► The parameters





- ▶ The dimensions

Question No:8 (Marks: 1) - Please choose one

if ax contains decimal -2 and BX contains decimal 2 then
after the execution of instructions: `CMP AX, BX ,JA label`

- ▶ Jump will be taken
- ▶ Zero flag will set
- ▶ ZF will contain value -4
- ▶ Jump will not be taken

Question No:9 (Marks: 1) - Please choose one

If D is “35” is shift to left 2 bits the new value

- ▶ 35
- ▶ 70
- ▶ 140
- ▶ 17





Question No:10 (Marks: 1) - Please choose one

When two 16bit numbers are added the answer can be 17 bits long, this extra bit that won't fit in the target register is placed in the where it can be used and tested

▶ carry flag (Page 16)

- ▶ Parity Flag
- ▶ Auxiliary Carry
- ▶ Zero Flag

Question No: 11(Marks: 1) - Please choose one

Only instructions allow moving data from memory to memory.

▶ string (Page 29)

- ▶ word
- ▶ indirect
- ▶ stack

Question No:12 (Marks: 1) - Please choose one

When a 16 bit number is divided by an 8 bit number, the quotient will be in

▶ AL (Page 85)

- ▶ AX
- ▶ AH
- ▶ DX

Question No:13 (Marks: 1) - Please choose one





Which bit of the attributes byte represents the red component of background color ?

- ▶ 3
- ▶ 4
- ▶ 5

▶ 6 (Page 81)

Question No:14 (Marks: 1) - Please choose one

| 0 |-->| 1 | 1 | 0 | 1 | 0 | 0 | 0 |-->| C | is a example of ____

- ▶ Shl
- ▶ sar

▶ Shr (Page 52)

- ▶ Sal

Question No:15 (Marks: 1) - Please choose one

allow changing specific processor behaviors and are used to play with it.

▶ Special Instructions (Page 14)

- ▶ Data Movement Instructions
- ▶ Program Control Instructions
- ▶ Arithmetic and Logic Instructions





Question No:16 (Marks: 1) - Please choose one

8088 is a 16bit processor with its accumulator and all registers of_.

- ▶ 32 bits
- ▶ 6 bits
- ▶ 16 bits (Page 14)
- ▶ 64 bits

Question No:17 (Marks: 1) - Please choose one

decrements SP (the stack pointer) by two and then transfers a word from the source operand to the top of stack

- ▶ PUSH (Page 71)
- ▶ POP
- ▶ CALL
- ▶ RET

MIDTERM 2011

CS401 Assembly Language

1. In instruction ADC the operands can be
 - o Two register only
 - o Two register and one memory location
 - o CF and two other operands (Page 57)
 - o ZF and two other operands





SUBSCRIBE

AR Lucky Bahi



2. After the execution of instruction “RET”
 - o SP is incremented by 2 (Page 66)
 - o SP is decremented by 2
 - o SP is incremented by 1
 - o SP is decremented by 1

3. The extended ASCII has
 - o 64 characters
 - o 128 characters (Page 79)
 - o 256 characters
 - o 502 characters



SUBSCRIBE

AR Lucky Bahi





4. The second byte in the word designated for screen location holds
 - o The dimension of the screen
 - o Character position on the screen
 - o **Character color on the screen** (Page 81)
 - o ACSII code of the character

5. REP will always
 - o Incremented CX by 1
 - o Incremented CX by 2
 - o **Decrement CX by 1** (Page 92)
 - o Decrement CX by 2

6. The routine that executes in response to an INT instruction is called
 - o **ISR** (Page 103)
 - o IRS
 - o ISP
 - o IRT

7. The iAPX888 architecture consists of _register.
 - o 12
 - o 14
 - o **16** (Page 15) Rep
 - o 18

8. In the instruction “CMP AX,BX” the contents of
 - o AX are changed
 - o BX are changed
 - o CX are changed
 - o **Flag register are changed** (Page 39)

9. All the addressing mechanisms in iAPX88 return a number called _address.
 - o **Effective** (Page 33)





SUBSCRIBE

AR Lucky Bahi



- o faulty
- o indirect
- o direct

10. The execution of the instruction “mov word [ES: DI], 0x0720”

- o [will clear next character on screen \(Page 82\)](#)
- o will print “20” at top left of the screen
- o will print “20” at top right of the screen
- o will move DI at location 0720 on the screen



SUBSCRIBE

AR Lucky Bahi





11. “mov byte [num1],5” is ___ instruction.
- ☐ legal (Page 30)
 - ☐ illegal
 - ☐ stack based
 - ☐ memory indirect
12. MOV instruction transfers a byte or word from which of the following source location.
- ☐ DS:DI
 - ☐ ES:SI
 - ☐ ES:DI
 - ☐ DS:SI (Page 92)
13. The execution of the instruction “mov word [ES: 0], 0x0741” will print “A” on the screen, color of the character will be
- ☐ Black
 - ☐ White (Page 81) rep
 - ☐ Red
 - ☐ Blue
14. If AX contains FFFFh, then after execution of instruction “SAL ax, 3”, the result will be
- ☐ -3
 - ☐ +3
 - ☐ -8
 - ☐ +8
15. If the decimal number “35” is shifted by two bit to left, the new value will be
- ☐ 35
 - ☐ 70
 - ☐ 140 (00100011 = 35 , 10001100=140)
 - ☐ 17





SUBSCRIBE

AR Lucky Bahi



16. While using STOSB, if DF=1 then

- o The value of SI will be incremented by one
- o The value of SI will be incremented by two
- o The value of SI will be decremented by one
- o The value of SI will be decremented by two

[click here for detail](#)

17. After the execution of STOSW, the CX will be

- o Decrement by 1
- o Decrement by 2 (Page 92)
- o Increment by 1
- o Increment by 2



SUBSCRIBE

AR Lucky Bahi





18. The memory address always move from
- ☐ [processor to memory](#)
 - ☐ memory to processor
 - ☐ memory to peripheral
 - ☐ peripheral to processor
19. An offset alone is not complete without
- ☐ [Segment](#) (Page 34)
 - ☐ code label
 - ☐ index register
 - ☐ data label
20. Code Segment is associated to__register by default.
- ☐ [IP](#) (Page 34)
 - ☐ SS
 - ☐ BP
 - ☐ CX

MIDTERM SPRING 2011

CS401 Assembly Language

Question No:1 (Marks: 1) - Please choose one

After the execution of SAR instruction:

- ▶ MSB remain as it is
- ▶ MSB Will change
- ▶ [MSB move to left](#) (Page 52)
- ▶ No change will occur.



Question No:2 (Marks: 1) - Please choose one

ASCII stands for_____.

The screen is two dimensional space having:

- ▶ 25 Rows and 25 Columns
- ▶ 25 Rows and 80 Columns
- ▶ 80 Rows and 80 Columns



80 Rows and 25 Columns (Page 80)



Question No:3 (Marks: 1) - Please choose one

In the Rotate Right Operation every bit moves one position to right and the bit dropped from the right is inserted at the left and:

► Dropped in CF (Page 53)

- moves to AL
- Don't go anywhere.

Question No:4 (Marks: 1) - Please choose one

_____ of the following flags will be affected by MOVSB?

► DF [Click here for detail](#)

- ZF
- PF
- No effect on flags.

Question No:5 (Marks: 1) - Please choose one

The iAPX88 processor supports ___ modes of memory access.

- 5
- 6
- 7 (Page 35)
- 8

Midterm Spring 2010 CS401
Assembly Language





Question No:1 (Marks: 1) - Please choose one

Stack is a____that behaves in a first in last out manner.

► Program

► data structure (Page 67)

► Heap

► None of the Given

Question No:2 (Marks: 1) - Please choose one

The physical address of the stack is obtained by

► SS:SI combination

► SS:SP combination (Page 68)

► ES:BP combination

► ES:SP combination





Question No:3 (Marks: 1) - Please choose one

Foreground and background parameter will be

▶ 32bits

▶ 16bits

▶ 8bits

▶ 4bits

Question No:4 (Marks: 1) - Please choose one

The clear screen operation initialize whole block of memory

▶ 0741

▶ 0417

▶ 0714

▶ 0174, 0720 (Page 91)

Question No:5 (Marks: 1) - Please choose one

In STOSB instruction, when DF is Set, SI is

▶ Incremented by 1

▶ Incremented by 2

▶ Decrement by 1 [Click here for detail](#)

▶ Decrement by 2

Question No:6 (Marks: 1) - Please choose one

Assembly language is:

▶ Low-level programming language [Click here for detail](#)

▶ High-level programming language





- ▶ Also known as machine language
- ▶ Not considered closer to the computer

Question No:7 (Marks: 1) - Please choose one

A 32 Bit processor has accumulator of -----

- ▶ 8 bit
- ▶ 16 bit
- ▶ 32 bit (Page 12)
- ▶ 64 bit

Question No:8 (Marks: 1) - Please choose one

To transfer control back the RET instruction take

- ▶ 1 argument
- ▶ 1 argument
- ▶ 3 arguments (Page 72) (Not sure)
- ▶ No arguments





Question No:9 (Marks: 1) - Please choose one

RET is executed, it recovers the values from

- ▶ Register
- ▶ [Stack \(Page 71\)](#)
- ▶ Data segment
- ▶ Code segment

Question No:10 (Marks: 1) - Please choose one

To convert any digit to its ASCII representation

- ▶ [Add 0x30 in the digit \(Page 80\)](#)
- ▶ Subtract 0x30 from the digit
- ▶ Add 0x61 in the digit
- ▶ Subtract 0x61 from the digit

Question No:11 (Marks: 1) - Please choose one

The prevalent convention in most high level languages is stack clearing by the

- ▶ Caller
- ▶ [Callee \(Page 74\)](#)
- ▶ RET
- ▶ Stack



Question No:12 (Marks: 1) - Please choose one

After execution of JCXZ instruction CX will changed with flag affect.

- ▶ CF
- ▶ OF
- ▶ DF

▶ None of Above (Page 43)

Question No:13 (Marks: 1) - Please choose one

Execution of the instruction “mov word [ES : 0], 0x0741” will print

- ▶ “A” appear on the top left of screen (Page 81)
- ▶ “A” appear on the top right of screen
- ▶ “A” appear on the center of screen
- ▶ “A” appear on the bottom left of screen

Question No:14 (Marks: 1) - Please choose one

if contains decimal -2 and BX contains decimal 2 then after the execution of instructions: CMP AX, BX
JA label

▶ Jump will be taken



- ▶ Zero flag will set
- ▶ ZF will contain value -4
- ▶ Jump will not be taken

Question No:15 (Marks: 1) - Please choose one

Which of the following options contain the set of instructions to open a window to the video memory?

- ▶ mov AX,
0xb008mov
ES, AX

▶ mov AX, 0xb800

mov ES, AX (Page 81) rep

- ▶ mov AX,
0x8b00mov
ES, AX
- ▶ mov AX,
0x800bmov
ES, AX

Question No:16 (Marks: 1) - Please choose one

If D is “35” is shift to left 2 bits the new value

- ▶ 35
- ▶ 70

▶ 140

- ▶ 17

Question No:17 (Marks: 1) - Please choose one





Execution of the instruction “mov word [ES : 0], 0x1230” will print the character color will

- ▶ Green
- ▶ White
- ▶ Red
- ▶ Black

MIDTERM EXAMINATION

Spring 2010

Question No: 1 (Marks: 1) - Please choose one

After the execution of SAR instruction

- ▶ The msb is replaced by a 0
- ▶ The msb is replaced by 1
- ▶ The msb retains its original value
- ▶ The msb is replaced by the value of CF (Page 52)





Question No: 2 (Marks: 1) - Please choose one

RETF will pop the offset in the

► BP

► IP (Page 69)

► SP

► SI

Question No: 3 (Marks: 1) - Please choose one

The routine that executes in response to an INT instruction is called

► ISR (Page 103) rep

► IRS

► ISP

► IRT

Question No: 4 (Marks: 1) - Please choose one

The first instruction of “COM” file must be at offset:

► 0x0010

► 0x0100 (Page 19) rep

► 0x1000

► 0x0000

Question No: 5 (Marks: 1) - Please choose one

“Far” jump is not position relative but is ____





► memory dependent

► Absolute (Page 46)

► Temporary

► indirect

Question No: 6 (Marks: 1) - Please choose one

Only_____instructions allow moving data from memory to memory.

► string (Page 29) rep

► word

► indirect

► stack

Question No: 7 (Marks: 1) - Please choose one

After the execution of instruction “RET 2”

► SP is incremented by 2

► SP is decremented by 2





- ▶ SP is incremented by 4 (Page 66)
- ▶ SP is decremented by 4

Question No: 8 (Marks: 1) - Please choose one

DIV instruction has

- ▶ Two forms (Page 85)
- ▶ Three forms
- ▶ Four forms
- ▶ Five forms

Question No: 9 (Marks: 1) - Please choose one

When the operand of DIV instruction is of 16 bits then implied dividend will be of

- ▶ 8 bits (Page 85)
- ▶ 16 bits
- ▶ 32 bits
- ▶ 64 bits

Question No: 10 (Marks: 1) - Please choose one

After the execution of MOVS instruction which of the following registers are updated

- ▶ SI only
- ▶ DI only





- ▶ SI and DI only (Page 92)
- ▶ SI, DI and BP only

Question No: 11 (Marks: 1) - Please choose one

In 8088 architecture, whenever an element is pushed on the stack

- ▶ SP is decremented by 1
- ▶ SP is decremented by 2 (Page 68)
- ▶ SP is decremented by 3
- ▶ SP is decremented by 4

Question No: 12 (Marks: 1) - Please choose one

When a very large number is divided by very small number so that the quotient is larger than the space provided, this is called

- ▶ Divide logical error





► Divide overflow error (Page 85)

- Divide syntax error
- An illegal instruction

Question No: 13 (Marks: 1) - Please choose one

In the word designated for one screen location, the higher address contains

- The character code
- The attribute byte (Page 81)
- The parameters
- The dimensions

Question No: 14 (Marks: 1) - Please choose one

Which of the following options contain the set of instructions to open a window to the video memory?

► mov AX,
0xb008mov
ES, AX

► mov AX, 0xb800

mov ES, AX (Page 81) rep

► mov AX,
0x8b00mov
ES, AX

► mov AX,
0x800bmov
ES, AX





Question No: 15 (Marks: 1) - Please choose one

In a video memory, each screen location corresponds to

- ▶ One byte
- ▶ Two bytes (Page 80)
- ▶ Four bytes
- ▶ Eight bytes

Question No: 16 (Marks: 1) - Please choose one

The execution of the instruction “mov word [ES : 0], 0x0741” will print character “A” on screen , backgroundcolor of the screen will be

- ▶ Black (Page 81) rep
- ▶ White
- ▶ Red
- ▶ Blue





MIDTERM Fall 2011

CS401 Assembly Language

Question No:1 (Marks: 1) - Please choose one

One screen location corresponds to a

► Byte

► Word (Page 80) rep

► Double byte

► Double word

Question No:2 (Marks: 1) - Please choose one

After the execution of “PUSH AX” statement

► AX register will reside on the stack

► A copy of AX will go on the stack (Page 69)

► The value of AX disappear after moving on stack

► Stack will send an acceptance message

Question No:3 (Marks: 1) - Please choose one

physical address of the stack is obtained by

► SS:SP combination

► SS:SI combination

► SS:SP combination (Page 68) rep

► ES:BP combination

► ES:SP combination



Question No:4 (Marks: 1) - Please choose one

If the address of memory location Num1 is 0117 and its content is 0005 then after execution of the instruction“ mov bx, Num1” bx will contain

► 0005

► 0117 (Page 30)

► Num1

► 1701

Question No:5 (Marks: 1) - Please choose one

In STOS instruction, the implied source will always be in

► AL or AX registers (Page 92)

► DL or DX registers

► BL or BX registers

► CL or CX registers



Question No:6 (Marks: 1) - Please choose one

The shift logical right
operation inserts A zero at
right

A zero at left (Page 52)

A one at
right A
one at
right

Question No:7 (Marks: 1) - Please choose one

REP will
always
Increment CX
by 1
Increment CX
by 2

Decrement CX by 1 (Page 92) rep

Decrement CX by 2

Question No:8 (Marks: 1) - Please choose one

When an item is pushed on the decrementing stack, the top of the stack is

► First decremented and then element copied on to the stack (Page 68) rep



- ▶ First incremented and then element copied on to the stack
- ▶ Decrement after the element copied on to the stack
- ▶ Incremented after the element copied on to the stack

Question No:9 (Marks: 1) - Please choose one

assembly the CX register is used normally as a__register.

- ▶ source
- ▶ counter (Page 32)
- ▶ index
- ▶ pointer

Which is the unidirectional bus ?

- (I) Control Bus
- (II) Data Bus
- (III) Address Bus
- ▶ I only
- ▶ II only

- ▶ III only (Page 9)
- ▶ I and II only

Question No:10 (Marks: 1) - Please choose one

The basic function of SCAS instruction is to

- ▶ Compare (Page 92)
- ▶ Scan



- ▶ Sort
- ▶ Move data

Question No:11 (Marks: 1) - Please choose one

_____ register holds the address of next instruction is to be executed

- ▶ Base pointer
- ▶ Code segment
- ▶ Source index

▶ Program counter (Page 13)

Question No:12 (Marks: 1) - Please choose one

JC and JNC test the_____flag.

▶ carry (Page 41)

- ▶ parity
- ▶ zero
- ▶ sign

Question No:13 (Marks: 1) - Please choose one

After the execution of REP instruction CX will be decremented then which of the following flags will be affected?

- ▶ CF
- ▶ OF
- ▶ DF

▶ No flags will be affected (Page 93)

Question No:14 (Marks: 1) - Please choose one



In string manipulation whenever an instruction needs a memory source, which of the following will hold the pointer to it?

- ▶ ES: DI
- ▶ ES: BP
- ▶ DS:BP
- ▶ DS:SI (Page 91)

Question No:15 (Marks: 1) - Please choose one which bit sets the character "blinking" on the screen?

- ▶ 5
- ▶ 6
- ▶ 7 (Page 7)
- ▶ 8



Question No:16 (Marks: 1) - Please choose one

If we want to divide a signed number by 2, this operation can better be accomplished by

► SHR

► SAR (Page 52)

► SHL

► SAL

Question No:17 (Marks: 1) - Please choose one

After the execution of STOSB, the CX will be.....

► Incremented by 1

► Incremented by 2

► Decrement by 1 (Page 92)

► Decrement by 2

Question No:18 (Marks: 1) - Please choose one

Each screen location corresponds to a word, the lower byte of this word contains _

► The character code (Page 81) rep

► The attribute byte

► The parameters

► The dimensions

Question No:19 (Marks: 1) - Please choose one

In a video memory, each screen location corresponds to





► One byte

► Two bytes (Page 86)

► Four bytes

► Eight bytes

MIDTERM EXAMINATION

Spring 2010

Question No:1 (Marks: 1) - Please choose one

Execution of the instruction “mov word [ES : 0], 0x0741” will print

- “A” appear on the top left of screen (Page 81) rep
- “A” appear on the top right of screen
- “A” appear on the center of screen
- “A” appear on the bottom left of screen





Question No:2 (Marks: 1) - Please choose one

After the execution of “PUSH AX” statement

- ▶ **AX register will reside on the stack (Page 69) rep**
- ▶ A copy of AX will go on the stack
- ▶ The value of AX disappear after moving on stack
- ▶ Stack will send an acceptance message

Question No:3 (Marks: 1) - Please choose one

If D is “35” is shift to left 2 bits the new value

- ▶ 35
- ▶ 70
- ▶ **140**
- ▶ 17

Question No:4 (Marks: 1) - Please choose one

When an item is pushed on the decrementing stack, the top of the stack is

- ▶ **First decremented and then element copied on to the stack (Page 68) rep**
- ▶ First incremented and then element copied on to the stack
- ▶ Decrement after the element copied on to the stack
- ▶ Incremented after the element copied on to the stack

Question No:5 (Marks: 1) - Please choose one

After the execution of REP instruction CX will be decremented then which of the following flags will be affected?





- ▶ CF
- ▶ OF
- ▶ DF

▶ No flags will be affected (Page 93) rep

Question No:6 (Marks: 1) - Please choose one

In a video memory, each screen location corresponds to

- ▶ One byte
- ▶ Two bytes (Page 66)
- ▶ Four bytes
- ▶ Eight bytes

Question No:7 (Marks: 1) - Please choose one

shifting the -15 two bit sAR

- ▶ -7
- ▶ -8
- ▶ 7
- ▶ 8



Question No:8 (Marks: 1) - Please choose one

mov ax,5 has

► 1 operand

► 2 opeand (Page 25)

► 3 operand

► 4 opeand

MIDTERM EXAMINATION

Spring 2010

Question No: 1 (Marks: 1) - Please choose one

The physical address of the stack is obtained by

- SS:SP combination
- SS:SI combination

► SS:SP combination (Page 68) rep

- ES:BP combination
- ES:SP combination

Question No: 2 (Marks: 1) - Please choose one

After the execution of instruction “RET ”

- SP is incremented by 2



SP is incremented by 2 (Page 66) rep



- ▶ SP is decremented by 2
- ▶ SP is incremented by 1
- ▶ SP is decremented by 1

Question No: 3 (Marks: 1) - Please choose one

The second byte in the word designated for one screen location holds

- ▶ Character color on the screen
 - ▶ The dimensions of the screen
 - ▶ Character position on the screen
- ▶ Character color on the screen (Page 81) rep
- ▶ ASCII code of the character





Question No: 4 (Marks: 1) - Please choose one

REP will always

- ▶ Increment CX by 1
- ▶ Increment CX by 2
- ▶ Decrement CX by 1 (Page 92)
- ▶ Decrement CX by 2

Question No: 5 (Marks: 1) - Please choose one

The basic function of SCAS instruction is to

- ▶ Compare (Page 92) rep
- ▶ Scan
- ▶ Sort
- ▶ Move data

Question No: 6 (Marks: 1) - Please choose one

Index registers are used to store __

- ▶ Data
- ▶ Intermediate result
- ▶ Address (Page 16)
- ▶ Both data and addresses



Question No: 7 (Marks: 1) - Please choose one

The bits of the_____work independently and individually

- ▶ index register
- ▶ base register
- ▶ flags register (Page 12)
- ▶ accumulator

Question No: 8 (Marks: 1) - Please choose one

To convert any digit to its ASCII representation

- ▶ Add 0x30 in the digit (Page 80) rep
 - ▶ Subtract 0x30 from the digit
 - ▶ Add 0x61 in the digit
 - ▶ Subtract 0x61 from the digit



Question No: 9 (Marks: 1) - Please choose one

When a 32 bit number is divided by a 16 bit number, the quotient is of

- ▶ 32 bits
- ▶ 16 bits (Page 85)
- ▶ 8 bits
- ▶ 4 bits

Question No: 10 (Marks: 1) - Please choose one

When a 16 bit number is divided by an 8 bit number, the quotient will be in

- ▶ AX
- ▶ AL (Page 85) rep
- ▶ AH
- ▶ DX

Question No: 11 (Marks: 1) - Please choose one

Which mathematical operation is dominant during the execution of SCAS instruction

- ▶ Division
- ▶ Multiplication
- ▶ Addition
- ▶ Subtraction (Page 92)

Question No: 12 (Marks: 1) - Please choose one





If AX contains decimal -2 and BX contains decimal 2 then after the execution of instructions: CMP AX, BX
JA label

► Jump will be taken

- Zero flag will set
- ZF will contain value -4
- Jump will not be taken

Question No: 13(Marks: 1) - Please choose one

The execution of the instruction “mov word [ES : 160], 0x1230” will print a character “0” on the screen at

► Second column of first row

► First column of second row (Page 81)

- Second column of second row
- First column of third row





Question No: 14(Marks: 1) - Please choose one

If the direction of the processing of a string is from higher addresses towards lower addresses then

- ▶ ZF is cleared
- ▶ DF is cleared
- ▶ ZF is set
- ▶ DF is set (Page 91)

Question No: 15 (Marks: 1) - Please choose one

The instruction ADC has__Operand(s)

- ▶ 0
- ▶ 1
- ▶ 2
- ▶ 3 (Page 56)

Question No: 16 (Marks: 1) - Please choose one

Which bit of the attributes byte represents the red component of background color ?

- ▶ 3
- ▶ 4
- ▶ 5
- ▶ 6 (Page 81)





MIDTERM EXAMINATION

Spring 2010

Question No: 1 (Marks: 1) - Please choose one

Suppose AL contains 5 decimal then after two left shifts produces the value as

- ▶ 5
- ▶ 10
- ▶ 15
- ▶ 20

Question No: 2 (Marks: 1) - Please choose one

In STOS instruction, the implied source will always be in

- ▶ AL or AX registers (Page 92) rep





- ▶ DL or DX registers
- ▶ BL or BX registers
- ▶ CL or CX registers

Question No: 3(Marks: 1) - Please choose one

After the execution of STOSW the CX will be

- ▶ Decrement by 1
- ▶ Decrement by 2 (Page 92) rep
- ▶ Increment by 1
- ▶ Increment by 2

Question No: 4(Marks: 1) - Please choose one

The basic function of SCAS instruction is to

- ▶ Compare (Page 92) rep
- ▶ Scan
- ▶ Sort
- ▶ Move data

Question No: 5(Marks: 1) - Please choose one

Which is the unidirectional bus ?

- (I) Control Bus
- (II) Data Bus
- (III) Address Bus
- ▶ I only





Question No: 8(Marks: 1) - Please choose one

In assembly the CX register is used normally as a_register.

- ▶ source
- ▶ counter (Page 92)
- ▶ index
- ▶ pointer

Question No: 9(Marks: 1) - Please choose one

All the addressing mechanisms in iAPX88 return a number called *address*.

- ▶ effective (Page 33)
- ▶ faulty
- ▶ indirect
- ▶ direct

Question No: 10(Marks: 1) - Please choose one

Which bit of the attributes byte represents the blue component of foreground color

- ▶ 3
- ▶ 2
- ▶ 1
- ▶ 0 (Page 81)

Question No: 11 (Marks: 1) - Please choose one





When a 32 bit number is divided by a 16 bit number, the quotient will be stored in

► AX (Page 85)

- BX
- CX
- DX

Question No: 12(Marks: 1) - Please choose one

“mov byte [num1], 5” is__instruction.

► legal (Page 30) rep

- illegal
- stack based
- memory indirect

Question No: 13(Marks: 1) - Please choose one

Which of the following options contain the set of instructions to open a window to the video memory?

► mov AX,
0xb008
mov ES,
AX





► mov AX, 0xb800

mov ES, AX (Page 81) rep

► mov AX,
0x8b00
mov ES,
AX

► mov AX,
0x800b
mov ES,
AX

Question No: 14(Marks: 1) - Please choose one

The execution of the instruction “mov word [ES : 0], 0x0741” will print character “A” on screen, color of the character will be

► Black

► White (Page 81) rep

► Red

► Blue

Question No: 15(Marks: 1) - Please choose one

Which of the following flags will be affected by MOVSW?

► DF

► PF

► ZF

► No effect on flags





Question No: 16 (Marks: 1) - Please choose one

Which bit of the attributes byte represents the blue component of background color ?

- ▶ 3
- ▶ 4 (Page 81)
- ▶ 5
- ▶ 6

MIDTERM EXAMINATION

Spring 2009

Question No: 1 (Marks: 1) - Please choose one

To transfer control back the RET instruction take

- ▶ 1 argument
- ▶ 1 argument
- ▶ 3 arguments (Page 72) rep
- ▶ No arguments





Question No: 2 (Marks: 1) - Please choose one

In STOSB instruction SI is decremented or incremented by

► 4

► 1 (Page 92) SI and DI both are Index registers

► 2

► 3

Question No: 3 (Marks: 1) - Please choose one

CMPS instruction subtracts the source location to the destination location. Destination location always lies in

► DS:SI

► DS:DI

► ES:SI

► ES:DI (Page 93)

Question No: 4 (Marks: 1) - Please choose one

Regarding assembler, which statement is true:

► mnemonics to the corresponding OPCODE Assembler converts (Page 13)

► Assembler converts OPCODE to the corresponding mnemonics

► Assembler executes the assembly code all at once

► Assembler executes the assembly code step by step

Question No: 5 (Marks: 1) - Please choose one

If “BB” is the OPCODE of the instruction which states to “move a



constant value to AX register”, the hexadecimal representation (Using little Endian notation) of the instruction “Mov AX,336” (“150” in hexadecimal number system) will be:

- ▶ 0xBB0150
- ▶ 0x5001BB
- ▶ 0x01BB50
- ▶ 0xBB5001 (Page 19)

Question No: 6 (Marks: 1) - Please choose one

In the instruction MOV AX, 5 the number of operands are

- ▶ 1
- ▶ 2 (Page 25) rep
- ▶ 3
- ▶ 4

Question No: 7 (Marks: 1) - Please choose one

The maximum parameters a subroutine can receive (with the help of registers) are

- ▶ 6
- ▶ 7 (Page 72)
- ▶ 8



► 9

Question No: 8 (Marks: 1) - Please choose one

In assembly the CX register is used normally as a_register.

► source

► counter (Page 92) rep

► index

► pointer

Question No: 9 (Marks: 1) - Please choose one

All the addressing mechanisms in iAPX88 return a number calledaddress.

► effective (Page 33) rep

► faulty

► indirect

► direct

Question No: 10 (Marks: 1) - Please choose one

When a 16 bit number is divided by an 8 bit number, the dividend will be in

► AX (Page 85)

► BX

► CX





► DX

Question No: 11 (Marks: 1) - Please choose one

in Left-Shift-Operation the left most bit ____

► will drop

► will go into CF (Page 52)

► Will come to the right most

► will be always 1

Question No: 12 (Marks: 1) - Please choose one

Suppose the decimal number "35" after shifting its binary two bits to left, the new value becomes ____

► 35

► 70

► 140

► 17





SUBSCRIBE

AR Lucky Bahi



Question No: 13 (Marks: 1) - Please choose one

When divide overflow occurs processor will be interrupted this type of interrupt is called

- ▶ [Hardware interrupt](#) [Click here for detail](#)
- ▶ Software interrupt
- ▶ Processor exception
- ▶ Logical interrupts

Question No: 14 (Marks: 1) - Please choose one

Which mathematical operation is dominant during the execution of SCAS instruction

- ▶ Division
- ▶ Multiplication
- ▶ Addition
- ▶ [Subtraction](#) (Page 92) rep

Question No: 15 (Marks: 1) - Please choose one

After the execution of REP instruction CX will be decremented then which of the following flags will be affected?

- ▶ CF
- ▶ OF
- ▶ DF
- ▶ [No flags will be affected](#) (Page 93) rep

Question No: 16 (Marks: 1) - Please choose one



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



_____ is one of the reasons due to which string instructions are used in 8088

- ▶ Efficiency and accuracy
- ▶ Reduction in code size and accuracy
- ▶ Reduction in code size and speed (Page 91)
- ▶ Reduction in code size and efficiency

Question No: 1 (Marks: 1) - Please choose one__

There are mainly----- types of software

- Two
- Three
- Four
- Five

Question No: 2 (Marks: 1) - Please choose one_____

In C/C++ the #include is called,

- Header file
- Preprocessor Directive
- Statement
- Function

Question No: 3 (Marks: 1) - Please choose one_____

&& is ----- operator.

- An arithmetic
- Logical
- Relational
- Unary

Question No: 4 (Marks: 1) - Please choose one__

In flow chart, the symbol used for decision making is,

- Rectangle
- Circle
- Arrow



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- **Diamond**

Question No: 5 (Marks: 1) - Please choose one_

The correct syntax of do-while loop is,

- (condition) while; do { statements; };
- { statements; } do-while ();
- while(condition); do { statements; };
- **do { statements; } while (condition);**

Question No: 6 (Marks: 1) - Please choose one_____

C++ views each file as a sequential stream of_____.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- **Bytes**
- Bits
- 0's or 1's
- Words

Question No: 7 (Marks: 1) - Please choose one_____

If the elements of an array are already sorted then the useful search algorithm is,

- Linear search
- **Binary search**
- Quick search
- Random search

Question No: 8 (Marks: 1) - Please choose one_____

The address operator (&) can be used with,

- Statement
- Expression
- **Variable**
- Constant

Question No: 9 (Marks: 1) - Please choose one_____

When a pointer is incremented, it actually jumps the number of memory addresses

- **According to data type**
- 1 byte exactly
- 1 bit exactly
- A pointer variable can not be incremented

Question No: 10 (Marks: 1) - Please choose one_____

Each pass through a loop is called a/an

- enumeration
- **iteration**
- culmination
- pass through

Question No: 11 (Marks: 1) - Please choose one_____



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Call by reference mechanism should be used in a program when there is

- i. large amount of data to be passed
- ii. small amount of data to be passed
- iii. need to change the passed data
- iv. no need to change the passed data

Choose the appropriate option for the above case.

- (i) and (ii) only
- (i) and (iii) only
- (ii) and (iii) only



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- (ii) and (iv) only

Question No: 12 (Marks: 1) - Please choose one__

Which of the following is the starting index of an array in C++?

- **0**
- 1
- -1
- any number

Question No: 13 (Marks: 1) - Please choose one__

The return type of a function that do not return any value must be

-
- int
 - **void**
 - double
 - float

Question No: 14 (Marks: 1) - Please choose one__

Which of the following is an extension of header file?

- .exe
- .txt
- **.h**
- .c

Question No: 15 (Marks: 1) - Please choose one__

We want to access array in random order which approach is better?

- **Pointers**
- Array index
- Both pointers and array index are better
- None of the given options.

Question No: 16 (Marks: 1) - Please choose one__

When we declare a multidimensional array the compiler store the elements of multidimensional array in the form of,



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- Columns
- Rows
 - Contiguous memory location
- Matrix

Question No: 1 (Marks: 1) - Please choose one

The function of cin is

- To display message
- To read data from keyboard
- To display output on the screen
- To send data to printer

Question No: 2 (Marks: 1) - Please choose one

In C/C++ language the header file which is used to perform useful task and manipulation of character data is

- cplex.h
- ctype.h
- stdio.h
- delay.h

Question No: 3 (Marks: 1) - Please choose one

How many parameter(s) function getline() takes?

- 0
- 1
- 2
- 3

Question No: 4 (Marks: 1) - Please choose one

Word processor is

- Operating system
- Application software
- Device driver
- Utility software

Question No: 5 (Marks: 1) - Please choose one

For which values of the integer _value will the following code becomes an infiniteloop?

```
int
number=1;
while (true)
```



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



```
{ cout <<
number;
if (number == 3) break;
http://vustudents.ning.com
http://vustudents.ning.com
number += integer_value; }
➤ any number other than 1 or 2
➤ only 0
➤ only 1
➤ only 2
```



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question No: 6 (Marks: 1) - Please choose one

Each pass through a loop is called a/an

- enumeration
 - **Iteration**
- culmination
- pass through

Question No: 7 (Marks: 1) - Please choose one

A continue statement causes execution to skip to

- the return 0; statement
- the first statement after the loop
- the statements following the continue statement
 - **the next iteration of the loop**

Question No: 8 (Marks: 1) - Please choose one

What is the correct syntax to declare an array of size 10 of int data type?

- int [10] name ;
- name[10] int ;
 - **int name[10] ;**
- int name[] ;

Question No: 9 (Marks: 1) - Please choose one

Consider the following code segment. What will the following code segment display?

```
int main(){
int age[10] =
{0};cout <<
age ;
}
```

- Values of all elements of array
- Value of first element of array
 - **Starting address of array**
- Address of last array element

Question No: 10 (Marks: 1) - Please choose one

What will be the correct syntax to initialize all elements of two-dimensional array to value 0?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- `int arr[2][3] = {0,0} ;`
- `int arr[2][3] = {{0},{0}} ;`
- `int arr[2][3] = {0},{0} ;` <http://vustudents.ning.com>
- `int arr[2][3] = {0} ;`

Question No: 11 (Marks: 1) - Please choose one

How many bytes will the pointer *intPtr* of type `int` move in the following statement?

`intPtr += 3 ;`

- 3 bytes
- 6 bytes
- 12 bytes
- 24 bytes

Question No: 12 (Marks: 1) - Please choose one



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



If there are $2(n+1)$ elements in an array then what would be the number of iterations required to search a number using binary search algorithm?

- n elements
- $(n+1)$ elements
- $2(n+1)$ elements
- $2(n+1)$ elements

Question No: 13 (Marks: 1) - Please choose one

Which of the following operator is used to access the value of variable pointed to by a pointer?

- * operator
- -> operator
- && operator
- & operator

Question No: 14 (Marks: 1) - Please choose one

The _____ statement interrupts the flow of control.

- switch
- continue
- goto
- break

Question No: 15 (Marks: 1) - Please choose one

Analysis is the-----step in designing a program

- Last
- Middle
- Post Design
- First

Question No: 16 (Marks: 1) - Please choose one

Paying attention to detail in designing a program is ____

- Time consuming
- Redundant
- Necessary
- Somewhat Good

Question No: 1 _____ (



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Marks: 1) - Please choose one

The function of cin is

- ▶ To display message
- ▶ To read data from keyboard
- ▶ To display output on the screen
- ▶ To send data to printer

Question No: 2

(

Marks: 1) - Please choose one

In C/C++ language the header file which is used to perform useful task and manipulation of character data is

- ▶ cplex.h
- ▶ ctype.h
- ▶ stdio.h
- ▶ delay.h

Question No: 3

(



SUBSCRIBE

AR Lucky Bahi





Marks: 1) - Please choose one

How many parameter(s) function `getline()` takes?





SUBSCRIBE

AR Lucky Bahi



▶ 0

▶ 1

▶ 2

▶ 3

Question No: 4 _____ (

Marks: 1) - Please choose one _____

Word processor is

- ▶ Operating system
- ▶ Application software
- ▶ Device driver
- ▶ Utility software

Question No: 5 _____ (

Marks: 1) - Please choose one _____



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



For which values of the integer `_value` will the following code becomes an infiniteloop?

```
int  
number=1  
;while  
(true) {  
    cout << number;  
    if (number == 3)  
        break; number +=  
        integer_value; }
```

- ▶ any number other than 1 or 2
- ▶ only 0
- ▶ only 1



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



► only 2

Question No: 6 _____ (
Marks: 1) - Please choose one _____

Each pass through a loop is called a/an

- enumeration
- Iteration
- culmination
- pass through

Question No: 7 _____ (
Marks: 1) - Please choose one _____

A continue statement causes execution to skip to

- the return 0; statement
- the first statement after the loop
- the statements following the continue statement
- the next iteration of the loop



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question No: 8 _____ (
Marks: 1) - Please choose one _____

What is the correct syntax to declare an array of size 10 of int data type?

► `int [10] name ;`

► `name[10] int ;`



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



► `int name[10] ;`

► `int name[] ;`

Question No: 9 _____ ()
Marks: 1) - Please choose one _____

Consider the following code segment. What will the following code segment display?

```
int main(){  
int age[10] =  
{0};cout <<  
age ;  
}
```

- Values of all elements of array
- Value of first element of array
- Starting address of array
- Address of last array element



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question No: 10 _____ (
Marks: 1) - Please choose one _____

What will be the correct syntax to initialize all elements of two-dimensional array to value 0?

- ▶ `int arr[2][3] = {0,0} ;`
- ▶ `int arr[2][3] = {{0},{0}} ;`
- ▶ `int arr[2][3] = {0},{0} ;`



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



► `int arr[2][3] = {0} ;`

Question No: 11 _____ (

Marks: 1) - Please choose one _____

How many bytes will the pointer *intPtr* of type `int` move in the following statement?

`intPtr += 3 ;`

► 3 bytes

► 6 bytes

► 12 bytes

► 24 bytes

Question No: 12 _____ (

Marks: 1) - Please choose one _____

If there are $2^{(n+1)}$ elements in an array then what would be the number of iterations required to search a number using binary



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



search algorithm?

- ▶ n elements
- ▶ (n+1) elements
- ▶ $2(n+1)$ elements
- ▶ $2^{(n+1)}$ elements

Question No: 13 _____ (

Marks: 1) - Please choose one _____



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Which of the following operator is used to access the value of variable pointed to by a pointer?

- ▶ * operator
- ▶ -> operator
- ▶ && operator
- ▶ & operator

Question No: 14 _____ (Marks: 1) - Please choose one _____

The _____ statement interrupts the flow of control.

- ▶ switch
- ▶ continue
- ▶ goto
- ▶ break

Question No: 15 _____ (Marks: 1) - Please choose one _____



SUBSCRIBE

AR Lucky Bahi





Analysis is the-----step in designing a program

- ▶ Last
- ▶ Middle
- ▶ Post Design
- ▶ First





SUBSCRIBE

AR Lucky Bahi



Question No: 16 _____ (

Marks: 1) - Please choose one _____

Paying attention to detail in designing a program is ____

- ▶ Time consuming
- ▶ Redundant
- ▶ Necessary
- ▶ Somewhat Good

Question No: 1 _____ (

Marks: 1) - Please choose one _____

A precise sequence of steps to solve a problem is called

- ▶ Statement
- ▶ Program
- ▶ Utility
- ▶ Routine



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question No: 2 _____ (

Marks: 1) - Please choose one _____

The Compiler of C language is written in



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- ▶ Java Language
- ▶ UNIX
- ▶ FORTRON Language
- ▶ C Language

Question No: 3 _____ (

Marks: 1) - Please choose one _____

Initialization of variable at the time of definition is,

- ▶ Must
- ▶ Necessary
- ▶ Good Programming
- ▶ None of the given options

Question No: 4 _____ (

Marks: 1) - Please choose one _____

In if structure the block of statements is executed only,



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- ▶ When the condition is false
- ▶ When it contain arithmetic operators
- ▶ When it contain logical operators
- ▶ When the condition is true

Question No: 5 _____ (

Marks: 1) - Please choose one _____

Which of the following function(s) is/are included in stdlib.h header file?

- ▶ double atof(const char *nptr)



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- ▶ `int atoi(const char *nptr)`
- ▶ `char *strcpy ( char *s1, const char *s2)`
- ▶ 1 and 2 only

Question No: 6 _____ (

Marks: 1) - Please choose one _____

Dealing with structures and functions passing by reference is the most economical method

- ▶ True
- ▶ False

Question No: 7 _____ (

Marks: 1) - Please choose one _____

Pointer is a variable which store,

- ▶ Data
- ▶ Memory Address



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- ▶ Data Type
- ▶ Values

Question No: 8 _____ (_____
Marks: 1) - Please choose one _____

Preprocessor program perform its function before phase takes place.

- ▶ Editing
- ▶ Linking
- ▶ Compiling



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



► Loading

Question No: 9 _____ ()
Marks: 1) - Please choose one _____

Which of the following can not be a variable name?

- area
- _area
- 10area
- area2

Question No: 10 _____ ()
Marks: 1) - Please choose one _____

Which looping process is best, when the number of iterations is known?

- for
- while
- do-while



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- ▶ all looping processes require that the iterations be known

Question No: 11 _____ ()
Marks: 1) - Please choose one _____

Which character is inserted at the end of string to indicate the end of string?

- ▶ new line
- ▶ tab
- ▶ null



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



► carriage return

Question No: 12 _____ ()
Marks: 1) - Please choose one _____

How many bytes are occupied by declaring following array of characters?

`char str[] = "programming";`

► 10

► 11

► 12

► 13

Question No: 13 _____ ()
Marks: 1) - Please choose one _____

Which of the following header file defines the rand() function?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



► `iostream.h`

► `conio.h`

► `stdlib.h`

► `stdio.h`

Question No: 14 _____ (

Marks: 1) - Please choose one _____

Commenting the code _____



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- ▶ Makes a program easy to understand for others.
- ▶ Make programs heavy, i.e. more space is needed for executable.
- ▶ Makes it difficult to compile
- ▶ All of the given options.

Question No: 15 _____ (Marks: 1) - Please choose one

What's wrong with this
for loop?for (int k = 2, k
<=12, k++)

- ▶ the increment should always be ++k
- ▶ the variable must always be the letter i when using a for loop
- ▶ there should be a semicolon at the end of the statement
- ▶ the commas should be semicolons

Question No: 16 _____ (Marks: 1) - Please choose one

For which array, the size of the array should be one more than the



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



number of elements in an array?

► int

► double

► float

► char



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question No: 1 (Marks: 1) - Please choose one

A precise sequence of steps to solve a problem is called

- Statement
- Program
- Utility
- Routine

Question No: 2 (Marks: 1) - Please choose one

The Compiler of C language is written in

- Java Language
- UNIX
- FORTRON Language
- C Language

Question No: 3 (Marks: 1) - Please choose one



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Initialization of variable at the time of definition is,

- Must
- Necessary
 - **Good Programming**
- None of the given options

Question No: 4 (Marks: 1) - Please choose one

In if structure the block of statements is executed only,

- When the condition is false
- When it contain arithmetic operators
- When it contain logical operators
 - **When the condition is true**

Question No: 5 (Marks: 1) - Please choose one

Which of the following function(s) is/are included in stdlib.h header file?

- double atof(const char *nptr)
- int atoi(const char *nptr)
- char *strcpy (char *s1, const char *s2)
 - **1 and 2 only**

Question No: 6 (Marks: 1) - Please choose one

Dealing with structures and functions passing by reference is the most economical method

- **True**
- False

Question No: 7 (Marks: 1) - Please choose one

Pointer is a variable which store,

- Data
 - **Memory Address**
- Data Type
- Values

Question No: 8 (Marks: 1) - Please choose one



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Preprocessor program perform its function before phase takes place.

- Editing
- Linking
- **Compiling**
- Loading

Question No: 9 (Marks: 1) - Please choose one

Which of the following can not be a variable name?

- area
- _area



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



> 10area

> area2

Question No: 10 (Marks: 1) - Please choose one

Which looping process is best, when the number of iterations is known?

> for

> while

> do-while

> all looping processes require that the iterations be known

Question No: 11 (Marks: 1) - Please choose one

Which character is inserted at the end of string to indicate the end of string?

> new line

> tab

> null

> carriage return

Question No: 12 (Marks: 1) - Please choose one

How many bytes are occupied by declaring following array of characters?

```
char str[] = "programming";
```

> 10

> 11

> 12

> 13

11 plus one for null char (11+1= 12)

Question No: 13 (Marks: 1) - Please choose one

Which of the following header file defines the rand() function?

> iostream.h

> conio.h

> stdlib.h



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



➤ stdio.h

Question No: 14 (Marks: 1) - Please choose one

Commenting the code _____

- Makes a program easy to understand for others.
- Make programs heavy, i.e. more space is needed for executable.
- Makes it difficult to compile
- All of the given options.

Question No: 15 (Marks: 1) - Please choose one

What's wrong with this

for loop? for (int k = 2, k
<=12, k++)

- the increment should always be ++k



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- the variable must always be the letter i when using a for loop
- there should be a semicolon at the end of the statement
 - the commas should be semicolons

(Marks: 1) - Please choose one

For which array, the size of the array should be one more than the number of elements in

an array?

- int
- double
- float
- char

The ASCII code of null character is -----

000

Which step is not performed during a proper
program design?

Write details about the performed of program

How many elements are stored stored in the following? In

matrix[4][5]

20



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Which of the following is not a valid variable

name inc++?

@student name

If an array has 50 elements what is allowable

range of subscripts

0-49

Compiler is a



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



System

softwar

e

If Num is an integer variable then

Num++ means,

Add 1 with Num

For one byte there are combinations of values that can be stored in computer

2^8

In C/C++ language the header file which is used to perform useful task and manipulation of character data is

ctype.h

Default case in

switch statement is,

Optional



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



When break statement is encountered in switch statement, it

Exits from switch statement

What will be the result of arithmetic expression

$6 + 27 / 3 * 3$?

33

What is the correct syntax to declare an array of size 10 of int datatype?

`int name[10] ;`

How many dimensions does n-dimensional array



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



has?

n dimensions

What will be the correct syntax to access the value of fourth element of an array using pointer ptr?

ptr[3]

Which of the following values C++ use to represent true and false?

1 and 0

Declaring structures does not mean that memory is allocated.

True

For which array, the size of the array should be one more than the number of elements in an array?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



If a variable is passed by value to a function and the function makes some changes to that variable then it

Does not affect the
original variable

In C/C++ the #include is
called, Preprocessor

Directive

Loops are ----- Structure.

Repetition

In C/C++ the string
constant is enclosed

In double quotes

Switch statement

deals with,

Integer and
character data



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



A record is a group of related

.Fields

C++ views each file as a sequential stream of_____.

Bytes

To access the element of two dimensional
array we use,

Double referencin

If it is required to copy an array to another
array then,



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Both arrays must be of the same size and
datatype

The precedence of * is higher than dot

operator False

Pointers works by pointing to a data type, which can be
of the form,

All of the given options

Which of the following data type(s) can operate on modulus
operator '%'?

Int

What will be the output of
following code? `int x = 10 ;`

`cout << "x =" << x`



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



;

x=1

0

Which looping process checks the test condition at the end of the loop?

do while

What will be the correct syntax of the following statement?

int *constptr ;

A function must always return a value.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



False

C is a/an

_____ langug

uae

function oriented

Assignment operator is used for

.assigning value to variables

When the logical operator AND (&&) combine two expressions exp1 and exp2 then the result will be true only,

When both exp1 and exp2 are true

Which of the following function(s) is/are included in

ctype.h header file?

All of the above

To access the data members of structure

_____ i

sused.



SUBSCRIBE

AR Lucky Bahi





dot operator (.)





SUBSCRIBE

AR Lucky Bahi



The address operator (&) can be used with,

Variable

Both compiler and interpreter are used to translate program into machine language code.

True

Missing semicolon ';' at the end of C++ statement is

Syntax error

Switch statement is an alternative of

Multiple if

Array is passed by value to a function by default.

False

Which of the following is the correct function call having array named student of 10 elements as a parameter.

Add Record (student [])

What will be the result of expression $x\% = 2$, if x



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



= 7?

$x = 1$

What will be the output of following

code segment? `main(){`

`int x = 5 ;`

`{`



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



```
int x
```

```
=4;
```

```
cout<x
```

```
}
```

```
Cout<x;
```

```
}
```

```
4, 5
```

Which of the following operator is used to access the value of variable pointed to by a pointer?

For loop

The object _____ may be used both for file input and

file fstream

What's wrong with this

forloop? for (int k = 2, k

<=12,k++)

The commas should be
semicolons

Union intorDouble{ntival;



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Double charvar;

};

main()

{

intorDouble

VAZ; int size ;

size = sizeof(VAZ); }

What will be the value of variable "size", if int occupies 4 bytes anddouble occupies 8 bytes?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



C language

is developed

by

Dennis Ritchie

Which of the following choice is not an example of an int datatype?

-4.0

In flow chart, the symbol used for

decision making is,

Diamond

Switch statement

deals with,

Integer and

character data

*doc is _____ by

Sequential File



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Member function tellg() returns the current location of the pointer.

get()

Dealing with structures and functions passing by reference is the most economical method

True

In C/C++ all character strings are terminated with,

Zero

Word processor



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



is

Applicati

on

software

Which of the following cannot be a

variablename?

10area

Which looping process is best, when the number of

iterations is known?

For

By default an array of characters is passed by value

to a function.

False

Which of the following operator is used to access the

address of a variable?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



& operator

**The name of an array represents address of first location
of array element.**

True

Data Size of the file is always _____ the actual size of the

None of the above

**When an identifier is declared with
keyword const then,**

Its value can not be changed



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



In C/C++ if we define an array of size eight (8) i.e. `intArr[8]`; then the last element of this array will be stored at,

`Arr[7]`

If it is required to copy an array to another array then,

Both arrays must be of the same size and datatype

In C/C++ all character strings are terminated with,

Null character

When a pointer is incremented, it actually jumps the number of memory addresses

According to data type



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



`+= , *= , /= , etc` are

called Compound

assignment operator

Computer can understand only machine

language code.

True

The compilers and interpreters also belong to the System

Software category.

True

Editors are used to

compile the code.

False

The variables having a name, type and size are just like

empty boxes.

True

What will be the result of the statement `rand ( )`



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



% 50

Less than 50.

if ($a > b$ && $a > c$) then the condition will be
true only if

Both $a > b$ and $a > c$ are true

In while loop the loop counter must be

initialized, Before entering the loop

of a variable means the locations within a program from
where it can be



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



accessed.

**Referen
ce**

Switch support

Character



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



A function is a block of statements that can be defined once and used

in the program.

As many times as user wants

statement is used to terminate the processing of a particular case and exit from switch structure.

break

The most suitable data type for number

325.25 is

float

X is an integer variable; what does X++

means, Add 1 in X value

The operators ++ and -- are used to increment or decrement the value of a variable by



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



1

Which of the following loops checks the test condition at the end of the loop? Do-While

What is the output of the following statement?
`int i = 2.5; do { cout << i * 2; } while (i > 3 && i <`

10); Error

What does `!(7)` evaluate to in decimal where `!` is a NOT operator? 7

The condition in while loop may contain logical expression but not relational expression.

False



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Searching is easier when an array is already sorted True

If an array has 100 elements, what is allowable range of subscripts?

0 – 99

What will be the value of ‘a’ and ‘b’ after executing the following statement

s?a = 3;

b=a+

4,3

What will be the correct syntax to initialize all elements of two-dimensional array to value 0?

intarr[2][3] = {{0},{0}} ;

Which of the following function returns the size of a string variable?

strlen()

What will be the range of numbers generated by function rand () % 9?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



0 to 8

Computer can understand only machine languagecode. True

What does $5 \wedge 6$, evaluate to in decimal where ‘^’ is Exclusive OR operator?

False

If the file is not properly closed in the program, the program.

Crashes

Which of the following header file include string conversionfunctions? stdlib.h

The function of cin is



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



To read data from keyboard

In C/C++ language the header file which is used to perform useful task and manipulation of character data is ctype.h

How many parameter(s) function getline() takes?

3

Word processor is

Application software

For which values of the integer _value will the following code becomes an infinite loop?

```
int  
number=1;  
while  
(true) {  
cout<<  
number;
```



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



```
if (number == 3)
```

```
break; number
```

```
+=integer_value
```

```
; } only 0
```

Each pass through a loop is
called a/an

Iteration

A continue statement causes execution
to skip to

the next iteration of the loop

What is the correct syntax to declare an array of size 10 of
int datatype?

```
Int name[10] ;
```

Consider the following code segment. What will the following code



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



segment display?

```
int main(){  
int age[10]  
=  
{0};  
cout<<  
age ;  
}
```

Value of first element of array

What will be the correct syntax to initialize all elements of two-dimensional array to value 0?

```
intarr[2][3] = {0,0} ;
```

How many bytes will the pointer intPtr of type int move in the following statement?

```
intPtr +=  
3 ;12 bytes
```



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



If there are $2(n+1)$ elements in an array then what would be the number of iterations required to search a number using binary search algorithm?

$(n+1)$ elements

Which of the following operator is used to access the value of variable pointed to by a pointer?

Operator

The _____ statement interrupts the flow of Break

Analysis is the ----- step in designing a program

First

Paying attention to detail in designing a program is

Necessary

Application Software's are

sed to

Solve end user problems



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Computer can do,

Exactly what we

tell it

We can control our program while it is running

by using

Debugger

are part of system

software Linker and

loaders

The remainder (%) operator is,

An arithmetic operator

`int x = 2 * 3 + 4 * 5;` What value will x contain in the

sample code above?

26

What is the correct value to return to the operating system upon the successful completion of a program?

0



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



What is the only function all C++ programs must contain?

main()

What punctuation is used to signal the beginning and end of code blocks?

{ }

What punctuation ends most lines of C++ code?

(Semi-colon)



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Which of the following is a correct comment?

`/* Comment */`

Which of the following is not a correct
variable type?

Real

Which of the following is the correct operator to compare two variables?

`==`

Identify the correct statement

All lines beginning with two slash signs are considered comments.

There is a unique function in C++ program by where all
C++ programs start their

Main ()

Every statement in C++ program should
end with

A Semicolon

`(;)` A variable

is/are



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Those numbers that is frequently required in
programs

The value of

$2*15/3*7+3*2$ is 76



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



The size of a

double variable is

8 bytes

Which of the following are NOT relational operators?

==

Which of the following cannot be

used as identifiers?

Spaces

Result of " number = number / 10; " will be equal to The " number = number % 10; "

FALSE

int x, y = 10; cout << x << endl; The value of the x will be in the above code

Unknown Value

In flow chart

process is



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



represented by

Rectangle

Which of the following is the boolean operator for logical-and?

&&

Evaluate! (1

&&! (0 || 1)).

TRUE

operator?

Logical NOT

(!)

Which of the following shows the correct syntax for an if statement?

if (expression)

In if structure the block of statements

is executed only,



SUBSCRIBE

AR Lucky Bahi





When the condition is true





SUBSCRIBE

AR Lucky Bahi



Loader transfers the executable code from main memory to hard disk.

FALSE

What is the final value of x when the code `int x; for(x=0; x < 10; x++) {}` is run?

10

When does the code block following `while(x < 100)` execute?

When x is greater than one hundred
Which is not a loop structure?

Repeat Until

`for (int n=10; n >0; n++) { cout<< n << ", "; }` How many Time Loop will run
Infinite Time

When break statement is encountered in switch statement, it

Exits from switch statement



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



A for loop usually consist of

2

How many times is a do while loop guaranteed to loop?

1

41- $x = x + 4$; Is

Equal to



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



`x += 4;`

The first expression in a for loop is

The first value of our countervariable

What is the break statement used for?

To quit the current iteration



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



What is the continue statement used for?

To stop the current iteration and begin the next iteration from the beginning

What is the output of the following code? for (int a = 1; a <= 1; a++) cout<<a+

+

;

1

2

Every case statement is follows by?

:

What is required to avoid falling through from one case to theext?

Break;

What keyword covers unhandled possibilities in switchcase?

Default

What is the result of the following code? x=0; switch(x) { case 1: cout<<"One"; case



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Hello World

Which of the

following is true?

1

Every function in C++ are



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



followed

by

Parenthes

is

Which is not a

proper prototype?

double funct(char

x)

What is the return type of the function with prototype: "

int funct(char x, float v, double

t);"

int

Which of the following is a valid function call (assuming the

function exists)?

funct();



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Which of the following is a complete function?

`int funct(int x) {return x=x+1;}` Function prototypes are useful

All of the above

A function that calls itself is

known as

Recursive

function

A preprocessor directive is identified by

#



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



When a call to function
statement is encountered,

The control is transfer to its
Prototype The directives for the
preprocessors begin with

Two Slashes (//)

The file iostream includes

The declarations of the basic standard input-
output library

Which of the following is
false? None of above

Which of the following statement is true about
preprocessor directives?

They end with a semicolon

If the statements `int j, k; j = 123; k = 234; int* q, * r; r = &j; q = &k; cout <<`
`*q << ' ' << *r;` are executed, what will be displayed?

132, 234



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



If the statements `int j,k; j = 123; k= 234; int* q, * r; cout<< *q<< ' << *r;` are executed,

What will be

displayed? Garbage

values



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Which of the following correctly declares an array?

`int anarray[10];`

Which of the following correctly accesses the seventh element stored in `foo`, an array with 100 elements?

`foo[6];`

Which of the following gives the memory address of the first element in array `foo`, an array with 100 elements?

`Foo;`

Consider the following statement: `int age [ ] = { 0, 2, 1, 3, 4, 5, 6, 7, 8, 9 };` Array Length is

10

`c [ 3 ] = 33;` by this Code we are assigning the value to

4th element



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



for (i = 0; i < 10 ; i ++) { b[i] = a[i]; } by given loop we

are

Copying the two arrays

```
int z, i ; int a [ 100 ] ; z=5; for ( i =0 ; i < 100 ; i ++ ) { a [ i ] = i ; } for ( i = 0 ; i < 100 ; i ++ ) { if ( z == a [ i ] ) { found = 1 ; break ; } } Loop will be executed
```

for

6 Times



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Given that #define sum(a,b) a+b what is the

value of: sum(3+1,2);

6

int m=0,v=0; for(m=5;m < 8;m++){ v=v+(m++)+(++m); } cout<< v<<endl; output of the V will be ?

11

Because of variable scope

Variables created in a function cannot be used another function

When we are using const keyword with a variable x then initializing it at the time of declaration is

Must

void allocateme(int* p){ p = new int; *p = 2; } int main(){ int i = 1; allocateme(&i); std::cout<< i; return 0; }

What is displayed?

Outputs '1'

int numarray[4][4] = {1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12};

What value does numarray [0][3] in the sample code above contain?

4



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



If the statements `<br>int j,k;<br>j = 123;<br>k= 234;<br>int* q, *r;<br>cout<< *q << ' ' << *r ;<br>`are executed, what will be displayed?

garbage values

Which one of the following will declare a pointer to an integer at address `0x22ff74` in memory?

`int *x; *x =`

`0x22ff74; An`

`array` is also

`called` Constant

pointer



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Which of the following is the proper declaration of a pointer?

`int *x;`

Which of the following gives the memory address of integer variable `a`(`inta;`)?

`&a;`

Which of the following is the proper Operator to allocate memory?

`New`

Which of the following is the proper keyword to deallocate memory?

`Delete`

When we are calling function i.e. `swap (&x, &y);` then it is a call by

`Reference`



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Which symbol is used to declare a pointer?

*

Which symbol is used to

reference a pointer?

&

In the given code `inty[10]; int *x ; x=`

`y; y is giving`

Address of the first element of the array

Adding to a pointer that points to an

array will

Cause the pointer to point to the next element in the



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



array.

Which one of the following operators is a unary operator?

Complement operator

(~)The statement `i++;`

is equivalent to

`i = i + 1;`

A variable which is defined inside a function is called

Functional variable

Which of the following is a two-dimensional array?

`intanarray[20][20];`

`inttwoDArray[2][2] = {0,1,2,3,4,5,6};` the 1st row and 3rd element is;



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



2

An array of pointers is the same

as

.Pointers to pointers

Pointers may be _____ like any other data

Arrayed (stored in an array)

In C/C++ language when an array is passed to a function then by default its passing Mechanism is,

Call by Reference

intisdigit(int c) Returns true if c

is a

Digit

intisupper(int c) Returns true if c

is a

Uppercase letter



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



**doubleatof(const char *nPtr) Converts the
stringnPtr to**

double

The basic steps of file handling are:

Open the file, Read and write, Close the file

ofstreamoutFile; char outputFileName[] = "myFileOut.txt"; char

ouputText[100]

= "Welcome to VU"; outFile.open(outputFileName); at the end of the code

file is opened for Writing

**If we open a file stream myfile for reading, what will give us the
currentposition of the file pointer?**

tellg()

**If we open a file stream myfile for reading, what will give us the
currentposition of the file pointer?**

tellp()

Which of the following classes

handlers fileinput?

Ifstream



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



By writing: `aFile.seekg (10L, ios::beg)` We are asking to move

10 bytes

forward from the beginning

By using `seekg ()` function, we can know the actual

data length

we will call `tellg ()` to give the current position in

number.

This number is the actual data bytes inside the file.

Long

We can use `inputFile.getc ()` to get a _____ and `outputFile.putc
()` write

a _____ into a

file.

Character,

character

will return the number of bytes reserved for a variable or

data type. `sizeof` operator

To access the members of a structure, which symbol is used ?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



A member is

a Variable in

a structure

Which of the following is a properly defined

struct? structa_struct {int a;};

Which properly declares a variable of

struct Student?

struct Student;

Using structures we can declare:

Simple variables, Pointers and Arrays of structure

During compilation compiler looks for the _____ and process it

Preprocessor directives

When we write a class template the first line must be:

template< class T >, Here T can be replaced with any name

but it is preferable

What does 5 | 6 evaluate to in decimal?

5 | 6 =
 0 1 0 1
 0 1 1 0
 0 1 1 1 = 7



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



What does $5 \& 6$ evaluate to in decimal?

$5 \& 6 = 0101 \text{ } 0110 \text{ } 0100 = 4$

What does $5 \wedge 6$ evaluate to in

decimal? $5 \wedge 6 = 01010110 \text{ } 0011 = 3$

In order to get 256 from the number 2568 we divide this

number by 10 and take,

Its quotient

The correct syntax of do-

while loop is,

While (condition); do {statements

};

Which of the following function(s) is/are included in stdlib.h header file?

1 and 2 only

If the break statement is missed in

switch statement then,

No effect on program



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



The data type before a function

name represents its,

Return Type

What does $5 \mid 6$, evaluate to in decimal where $\mid$ is bitwise OR operator

?5

What will be the correct syntax for initialization of pointer ptr with string "programming?" $\% = 2$, if x problem is written in UNIX

Initialization of variable at the time of definition is,



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Good Programming

In if structure the block of statements is executed only,

When the condition is true Pointer is a variable which store,

Memory Address

Preprocessor program perform its function before __phase takes place.

Compiling

Which character is inserted at the end of string to indicate the end of string?

Null

How many bytes are occupied by declaring following array of characters? `charstr[] = "programming";`

12

Which of the following header file defines the `rand()` function?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



stdlib.h

Commenting the code

**Makes a program easy to understand
for others**

**What's wrong with this
forloop? for (int k = 2, k
<=12,k++)**

The commas should be semicolons

**For which array, the size of the array should be one more
than the number of elements in an array?**

Char

**To Which category of the software “Compiler and Interpreter”
belongs?**

System Software

**In C/C++ the string
constant is enclosed**

In double

quotes The size



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



of int datatype

is

4 bytes

In Flow chart

process is

represented by

Rectangle

If the break statement is missed in

switch statement then,

No effect on program

Which of the following is the correct way to assign an integer value 5 to element of a matrix say 'm' at second row and third column?

$m[2][3] = 5 ;$

How many total elements must be in two-dimensional array of 3 rows and 2 columns?

6



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Consider the following code segment. What will be the output of this code segment? `intarr[6] = {2, 3, 7, 4, 5, 6} ;`
`int *ptr1 =&arr[1]`

`int *ptr2 =`

`&arr[4] ;`

`cout<<(ptr2-`

`ptr1) ;`

ptr is a pointer to constint

What will be the correct syntax to assign an array named arr of 5elements to a pointer ptr?

C is a/an ____language

function oriented

Syntax of union is identical

to

Structure

Most efficient method of dealing with structure variables is to define thestructure globally.

False

In order to get 256 from the number 2568 we divide this number by 10 andtake,



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Its quotient

There are mainly ----- types of software

Two

In C/C++ the #include is called,

Preprocessor Directive

&& is

----- operato

r

Logical

In flow chart, the symbol used for

decisionmaking is,

Diamond

The correct syntax of do-

whileloop is,

do { statements; }

while(condition);



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



C++ views each file as a sequential stream of _____.

Bytes

If the elements of an array are already sorted then the useful search algorithm is,

Binary search

The address operator (&) can be used with,

Variable

When a pointer is incremented, it actually jumps the number of memory addresses

,

According to data type

Each pass through a loop is called a/an

Iteration

Call by reference mechanism should be used in a program when there is
i. large amount of data to be passed
ii. small amount of data



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



to be passed iii. need to change
the passed data

iv. no need to change the passed data Choose the appropriate
option for the above case.

and (iii) only

Which of the following is the starting index of an array in



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



C++?

0

The return type of a function that do not return any value must be

Void

Which of the following is an extension of header file?

.h

We want to access array in random order which approach is better?

Pointers

When we declare a multidimensional array the compiler store the elements of multidimensional array in the form of,

Pointers

When we declare a multidimensional array the compiler store the elements of multidimensional array in the form of,

Contiguous

memory location



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



The function of cin is

To read data from keyboard

Care must be taken about the correct _____ of operator overloading. (Choose the most appropriate).

In functions, that returns reference use _____.

Both Semantic and Complexity

Global or static variables

In overloading the assignment (=) operator, which object(s) will call the



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



operator function?

Right object of the assignment operator

Friend functions are_____.

Unidirectional (not confirm)

We cannot increment_____.

References

A pointer is

**.The address of a
variable**

Overloaded assignment operator must

be Non-member function of class (not

The concept of friend function negates the concept of

.confirm)

Encapsulation



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



If class A is a friend of class B, and
class B is class C to be a friend,

It has to declare, class C as a friend

The difference between pointers and references is that_____.

We can do arithmetic with pointer

A reference cannot be

.NULL

An address is a_____, while a pointer is a_____.

Variable, constant

The reference data types are used as_____variables without

operator

Local, &



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



The syntax of declaration of a function that returns the reference to an

integer is

int&myfunc()

;

References cannot be uninitialized. Because it is impossible to

Initialize a NULL pointer

<and> both are

Logical

Find out the logical error in following lines of code. If (x = 10) cout

<< "x is 10"; 10 should be enclosed in quotations

There is no semicolon at the end of if condition

What will be the result of the expression j = i++; if initially j = 0 and i = 5? 5

Default mechanism of calling a function by passing it array is

call by and in case of passing

variable is call by.

Reference, value

When the break statement is encountered in a loop's body, it transfers the

from the current loop.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



contro

l

Outsid

e

statement is used to terminate the processing of a particular case and exit from switch structure.

Break

When the if statement consists of more than one statement then enclosing statement in braces is _____.

these

Compulso

ry

What will be the value of the variable output in the given piece of code? `double output = 0; output = (2 + 2) * 4 + 2 / (4 - 2);`

17

If we assign 2.06721 to an integer variable x, what will be the output if we print x using `cout<< statement?`

2



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



will be used for clarity and to force the order of evaluation in an expression. ()

What does STL

stand for?

Standard template

library

Skill(s) that is/are needed by programmers_____.

All of the given options

For which array, the size of the array should be one more than the number of elements in an array?

char

new and delete are_____ whereas malloc and free are__.

Operators, functions

Friend functions are_of a

class. Non-member functions

If overloaded plus operator is implemented as non-member function then which of the following statement will be true for the statement given below?

obj3 = obj1 + obj2 ;

obj2 will be passed as an argument to + operator whereas obj1 will drive the + operator



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Which one of the following is the declaration of overloaded pre-increment operator implemented as member function?

Class-name operator ++(int) ;

For cin, the source is normally a ___ and destination can be ___.

Keyboard, variable

We can also do conditional compilation with preprocessor directives. True

The programs, in which we allocate static memory, run essentially on

Stack



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



The default value of a parameter can be provided inside the function definition

While calling function, the arguments are assigned to the parameters from no specific order is followed

When an operator function is defined as member function for a binary Plus (+) operator then the number of argument it take is/are.

N arguments

With user-defined data type variables (Objects), self-assignment can

produce

Logical
error

Assignment operator is used to initialize a newly declared object from existing object.

True

When an object of a class is defined inside another class then, Constructor of inner object will be called first



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



In the member initializer list, the data members are

initialized, In the order in which they are defined

within class

new operator allocates memory from free store and return _.

A pointer

"new" and "delete" keywords are _____ in C++ language.

Memory Allocation Function

Return type of a function that does not return any value
must be .void



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



A function's prototype is written _____ the function

Before

What will be the size of the following character array? `char name[] = "Adeel";` 5

From following; which one is the correct syntax of an array initialize: Array size is 10 and it is of double data type to value 0? `double arr[10] = {0.0};`

Which of the function call is call by value for the following function prototype? `float add(int);`

`add(x);`

Null character is represented by _____ in C++.

`\0`

What is the output of the following code, if the first case is true
`switch (var) { case 'a': cout<<"apple"<<endl; case 'b': cout<<"banana"<<endl; case 'm': cout<<"mango"<<endl; default: cout<<"anyfruit"<<endl; }`

apple banana mango

Which of the following function call is "call by reference" for the following function prototype? `int add (int )add(x);`

The string in the array is terminated by a

null



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Default mechanism of calling a function by passing it array is call by variable is call by and in case of passing

Reference, value

$\langle . \langle = \rangle . \rangle$ = are called

operat

ors Relational

Why the use “cin”?

To read data from keyboard

!(x<3) means in

c++ that X is

greater than 3

The data in the memory is

Volatile



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Each array declaration must provide the information about all these things except.

The location of the first element to be stored

What will be the output of the program

```
if(x=10? If(x!=0&&  
x<=10)
```

```
{
```

```
cout<<"condition 1 is true";
```

```
}
```

```
{
```

```
If(x>=10&& x<20)
```

```
}
```

Condition 1 is true condition 2 is true

C is widely known as development

language of _____ operating system.

Window

A repetition statement specifies that an action is to be continued while some remains true



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Condition

1 -----is used for input file or for reading from the file.

Tellg()

2. Following is the declaration a ----- array. `Int arr[2][2][2]`

3-dimensional

3. `!( x < 3 )` means in c++ that

X is greater than 3

4. Which of the following option is correct to compare the declaration of the function?

----- (parameter1, parameter2)

{

// code to be executed



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



}

Void functionNAME

5. Ofstream is used for -----

Output file stream

6. By default, the starting index of an array in c++ is ____

0

7. How we declare an array of integer data whose size is 20 with array name "count".

Int count [20];

8. Which of the following is a reserve word for data types in c/c++?

Int

9. C was developed with the help of ----- language

BCPL and B

10. An object of-----class can be created for saving the current position of any opened file before reading from the file.

Streampos

11. C ++ is a ----- language.



SUBSCRIBE

AR Lucky Bahi





High level





SUBSCRIBE

AR Lucky Bahi



12. In while loop, the loop counter is initialized at -----

Before entering the loop

13. What is the output of the following code if the 3rd case is true

Switch (var)

{Case 'a';

Cout<<"apple"<<endl;

Mango

14.-----character is used to indicate the end of the string.

Null

15. Which of the following is used to perform bitwise exclusive OR operation?

|

16. If $x = 11$, and $x \% 3 = 2$, then value of x will be----

2

17. A variable of character data type occupies --- bytes in memory.



SUBSCRIBE

AR Lucky Bahi





1





SUBSCRIBE

AR Lucky Bahi



18. Null character is represented by-----in c ++?

\0

19. In computer system there are mainly---- type of softwares.

2

20. There is pointer variable named ptr of type float.

Which type of variable address can be store by ptr?

Float

21. A character is stored in the memory in -----

Byte

22. X is an integer variable; what does x++ means,

Add 1 in x value

23. When we call a function, its control-----

Transfers to its definition

24. '\0' takes ---- space in the memory.

1 byte



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



25----- will be used for enclosing function statements into a block?

{ }

26. How can we declare an array of characters whose size is 12 with array name “country”?

Char country[12];

27. Following is the declaration of a 2d array, how many columns are declared for this array.

Int arr[3][2];

2

28. If we assign 2.06721 to an integer variable x, what will be the output if we print x using cout<< statement?

2

29. We can access a global variable ----

From anywhere in the program

30. We use ---- to include all those functions which are located in different files.

Linker



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



31. A character is stored in the memory in ----

Byte

32. Which is not true regarding structure?

We can declare array of structure

33. Mr. ahmad sleeps thirty hours every day. This sentence is ____

Grammatically correct but illogical

34.----- will explain the function of a program.

Comments

35. Char **argv can be read as ----

Pointer to pointer to char

36. What will be output of the following

code? String name [4] = {"ali",
"bilal","omer", "Ayesha"}; Cout<< name [0];

Ali

37. The data type before a function name represents its,

Return type



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



37. The expression $((a+b) = 10) \parallel ((x+y) = 20)$ is true only if?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Either $((a+b) =)$ OR $((x + y) = 20)$ is true

38. = operator is used for ----

Assigning values to variables

39. What is the use of `ios::trunc` mode?

To truncate an existing file to zero

40. X is an integer variable; what does `x ++` means,

Add 1 in x value

41. Structures use ----- allocation.

Heap

42. What will be the size of the following character array?

`Char name[] = "adeel";`

6

43. A -----is an array of characters that can store number of character specified.

String

44 -----statement is used to terminate the processing of a particular case and exit from switch structure.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Break

45. If $y = 20$ and $z = y ++$, then the value of z will be-----

2146. If

Int a =

17; int b

= 3;

double c = a/b;

what will be value of variable c?

5

47. What will be the output of the following code?

String grade [3] = {"a", "b",

"c"}; Grade[2] = "f";

Cout<< grade[2];

F

48. Declaration of two-dimensional array of integers

having 3 rows and 5 columns is following?

Int arr [3][5];

49. $A = a + 1$; can be written as ----

$A++ = 1$;



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



50. A record is a group of related



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Fields

51. What will be the result of arithmetic expression $6 + 48 / 4 * 3$?

42

52. -----construct is used to execute a set of instructions when a condition is true and other set when it is false?

If\else

53. If an array has 50 elements, what is allowable range of subscripts?

0 – 49

54. If `int a = 50`; then the value of `a/= 3`; will be?

16

55. Which of the following option is/are correct about array?

Only one type of elements can store in an array

56. Whenever some number is added in an array name, it will jump as many as the added number?

Rows



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



57.----- returns true if c is a digit or a letter and false otherwise.

Int isalnum(int c)

58. which of the following is the default mode of the opening using ofstream class?

Ios::trunc

59. In which language the compiler of c language is written?

C

60. While loop executes at least?

One time

61. String are accessed by variable of type----

Char

62. Which of the following is the correct operator to compare the values of two variables?

= =

63. Not operator is a -----

Single input operator

64. Pointer points to a particular-----

Memory address



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



65. A function is a block of statements that can be defined once and used-

---in the program.

As many times as user wants

66----- function is used to find the number of characters in a string?

Strlen()

67. != operator is used to check whether the operand on the left-hand side is--to the operand on the right-hand-side.

Not equal

68. A while loop may execute ---- or more times.

0

69. How we declare an array of integer data whose size is 20 with array name "count".

Int count[20];

70. A variable declared within a code block becomes --variable for that block.

Local

71. If a file is opened with ios::out mode, then -----



SUBSCRIBE

AR Lucky Bahi





We can write in this file





SUBSCRIBE

AR Lucky Bahi



72. A function's prototype is written --- the function call.

Before

73. ---- Loop is mostly used to perform repetition of a tasks for a known number of times.

For

74. In shifting operations if zero is inserted at the left most bit, the negative number will become a number.

Positive

75. It is the job of ---- to transfer the executable code from hard disk to main memory.

Loader

76. RAID stands for-----

Redundant array of inexpensive devices

77. Array indexes start from ----

0

78. In call by reference, ----- of a variable is passed to the called function.

Address



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



79. How many times the following do-while loop will execute?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Int k =

10; Do

{

Cout << "statements" << endl; ?

6

80. The name of a location in memory is called ----

Variable

81. ----- function is used to find the number of character in a string.

Strlen()

82. Which statement is used to close a file?

Myfile.close();

83. ----- allow us to have a memory location and use it as int or char interchangeably.

None of the given

84. While handling files, one can have -- options

All of the given

85. ----- function is used to determine the next position to write a character while writing into a file.

Tellp()



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



86. Which is the correct syntax to define a structure named 'student'?

```
Struct student{
```

```
//variables
```

```
};
```

87. < and > both are --- operators.

Logical

Identify the logical error in the following if

condition 88. If ((i<5) & & (i>15)) ?

Condition is always false

89. Not operator is a ----

Single input operator

90. The use of *sign in first and second statements is called --- and ---- of pointer.

```
Int *ptr =
```

```
&x;
```

```
Cout<<*ptr
```

```
; ?
```

Referencing, dereferencing



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



91. C is widely known as development language of --operating system.

Linux



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



92. If x is declare as an integer, what will be result of the given expression?

$X = 2 + 3 * 5 \% 2 + 3 / 2$??

4

93. What will be the correct syntax of declaration of the following statements?

“ptr is a pointer to const int” ??

Const int *ptr

94. After evaluating the expression

95. $X = 10 + 3 * 4 / 2 - 1$, the value of x will be?

15

96. We can read, write and manipulate the same file using ----

Fstream.h

97. Return type of a function that does not return any value must be ----

Void

98. Pointers store the ----

Memory address

99----- operator uses the sign ^.



SUBSCRIBE

AR Lucky Bahi





Exclusive OR





SUBSCRIBE

AR Lucky Bahi



100. To get the value stored at a memory address, we use the ----
Dereferencing operator

101. Telling a computer what to do is called ----
Programming

102. Compiler translates high level language program into --- language
code.
Machine

103. Each array declaration must provide the information about all
these things except ----
The location of the first element to be stored

104. Eof is used to check for the -- of file when a file is being read.
End

105. The result of $4\%3$ will be?
1

106. When the logical operator AND (&&) combine two expression
exp1 and exp2 then the result will be true only?
When both exp1 and exp2 are true



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



107. 'multi[3][3]' element can also be accessed by -----

$*(*(\text{multi} + 3) + 3)$

108. What is output of following code?

```
Int data [10] = {10,20,30,40,50,60,70,80,90,100};
```

```
Int *xptr =&data
```

```
[4]; Int *xptr
```

```
=&data [6];
```

```
Cout<<xptr + yptr ++; ??
```

120

109. Which of the following is not the subcategory of the system software?

None of the above

110. We get $12 \mid 8 = \text{----}$ where “|” is (bit-wise OR) ?

12

111 ----- is a substitute of multiple if statement.

If..elseif statement

112. Find out the logical error in following lines of code. If (x = 10)

```
Cout << “x is 10”; ?
```



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Assignment operator should not be used for comparison

113. Which is not true regarding structure?



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



c) we can't declare pointers to structure

114 -----are used to compile the code.

Compiler

115. #include

#<iostream> include

<cstring>

Using namespace

std; Int main ()

{

Char str1[10] =

“hello”; Char str2[10]

= “world”; ? 10

116. A ----structure specifies that an action is to be repeated while some condition remains true.

Repetition

117. In which language the compiler of c language is written?

C

118. Characters string are terminated by -----

\0



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



119. A function is a block of statements that can be defined once and used -
-- in the program.

As many times as user wants

120 ----- is used for output during the process of writing to the file.
Seekp()

In case of two-dimensional array, if you add some number in a two-dimensional name, it will jump to the next----

Row

121. In while loop the condition is checked-- the execution of loop.

Before

122. Array indexes start from ----

0

123. Pointers store the ----

Memory address

124. Which step is not performed during a proper program design?

Write details about the performance of program

125, We can say that a pointer is a variable that holds the address.

Memory



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



126. When accessing a structure memory, the identifier to the left of the dot operator is the name of ----

Structure variable

127. From the following; which one is the range of random number generator rand() ?

0 – 32767

128.----- To read command-line arguments, the main () function itself must be given arguments.

2

129. Which operator has the highest precedence? (*, -, /, +) ?

* and / both have the same highest precedence

130. Suppose we have int y[10];

To access the 4th element of the array we write----

Y[3];

131. What will be the value of the variable output in the given piece of code? Double output = 0;

Output = (2 + 2) * 4 + / (4 – 2);

17



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



132. What is the output of the following statement?

```
int i = 2.5; do { cout << i * 2; } while (i > 3 && i < 10);
```

error

133. Searching is easier when an array is already sorted
True

134. If an array has 100 elements, what is allowable range of subscripts?

0 - 99

While developing a program; should we think about the user interface?
//handouts

main Yes

A character is stored in the memory in _____

String

These functions seekg() and seekp() requires an argument of type _____ to let them how many bytes to move forward or backward.

Int



SUBSCRIBE

AR Lucky Bahi





dereferencing operator is represented by _____

*





SUBSCRIBE

AR Lucky Bahi



_____ transfers the executable code from main memory to hard disk.

Loader

When the logical operator OR (||) combine two expressions exp1 and exp2

then the result will be false only, //bitwise “or” applies here....

When both exp1 and exp2 are false

suppose we have `int y[10]`; To access the 4th element of the array we write_____

none of given

we have opened a file stream `myfile` for reading (getting), `myfile.tellg()` gives us the current get position of the file pointer. It returns a whole number of type_____

int

`ofstream` is used for_____

Output file stream

A structure is a collection of _____ under a single name.

Variables



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



In C/C++ the string constant is enclosedcorrected r red one

In curly braces



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



The size of int data type
is 4 bytes

In Flow chart process is represented
by Rectangle

If the break statement is missed in switch statement then, // a break statement with no label always completes abruptly, the reason being a break with no label. If no switch, while, do, or for statement in the immediately enclosing method, constructor or initializer encloses the break statement, a compile-time error occurs?

This may cause a logical error

When we are using const keyword with a variable x then initializing it at the time of declaration is, ?

Optional

Which of the following is the correct way to assign an integer value 5 to element of a matrix say 'm' at second row and third column?

$m[2][3] = 5 ;$

How many total elements must be in two-dimensional array of 3 rows and 2 columns?

6



SUBSCRIBE

AR Lucky Bahi





Which of the following is the correct statement for the following declaration?





SUBSCRIBE

AR Lucky Bahi



*ptr is a pointer to const int

What will be the correct syntax to assign an array named arr of 5 elements to a pointer

ptr?

*ptr = arr[5] ;

C is a/an ____ language
object oriented

The variables having a name, type and size are just like empty boxes. True

What's wrong with this for
loop? for (int k = 2, k <= 12,
k++)
the commas should be semicolons

Most efficient method of dealing with structure variables is to define the structure globally
True

There are mainly----- types of software.//



SUBSCRIBE

AR Lucky Bahi





Two

When a pointer is incremented, it actually jumps the number of memory addresses ?





SUBSCRIBE

AR Lucky Bahi



According to data type

setw is a parameterized manipulator.

True

if ($a > b$ && $a > c$) then the condition will be true

only if Both $a > b$ and $a > c$ are true

In while loop the loop counter must be initialized, Before entering the loop

_____ of a variable means the locations within a program from where it can be accessed.

Reference

Switch support _____ data.

Integer

Character

Float



SUBSCRIBE

AR Lucky Bahi





Both integer and character





SUBSCRIBE

AR Lucky Bahi



A function is a block of statements that can be defined once and used _____ in the program.

As many times as user wants

_____statement is used to terminate the processing of a particular case and exit from switch structure.

break

The most suitable data type for number 325.25 is ____.

float

X is an integer variable; what does X++

means, Add 1 in X value

The operators ++ and -- are used to increment or decrement the value of a variable by _____

1

Which of the following loops checks the test condition at the end of the loop?

Do-While

The operator to free the allocated memory using new operator is



SUBSCRIBE

AR Lucky Bahi





____.delete





SUBSCRIBE

AR Lucky Bahi



suppose we have `int y[10]`; To access the 4th element of the array we write_____

`y[3];`

From the following; which one is the range of Random number generator function `rand()`?

0 – 32767

From following; which one is the correct syntax of an array initialize: Array size is 10 and it is of double data type to value 0?

`double arr[10] = {0.0};`

The string in the array is terminated by a_____

null

In C/C++; by default arguments are passed by _to a function.

Value

`char name [] = "Hello World"` ; In the above statement, a memory of ____ characters will be



SUBSCRIBE

AR Lucky Bahi





allocated 12

_____Keyword is used to return some value from a function.





SUBSCRIBE

AR Lucky Bahi



return

Which of the function call is call by value for the following function prototype? float add(int);

add(x);

The increment of a pointer depends on its ____.

data type

The ASCII code of null character is_____

000

Pointers are a special type of _____ in which a memory address is stored

variables

Transpose of a matrix means that when we interchange rows and columns_____

the first row becomes the first column

Pointers store the _____

value of a variable



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Which of the following function call is “call by reference” for the following function prototype? `int add (int *); add(&x);`

The name of the array is a constant pointer which contains the memory address of the `_` of the array.
first element

array name always contains the memory address of the `_____` of the array
first element

At the `_____` , we try to break up the problem into functional units
design phase

Syntax of a union is identical to `_____` .
structure

A union is a user-defined data type that contains only `_____` from its list of members at



SUBSCRIBE

AR Lucky Bahi





a time.

one object





SUBSCRIBE

AR Lucky Bahi



Which of the given file handling modes are similar in their functionality ? `ios::trunc`, `ios::ate`

Which one of the given option is not a mode for reading/writing the data from a file?

Trunk

In C/C++, the header file used for string manipulation is _____.
`string.h`

A 2D array `multi[5][10]` can be accessed using the array name as `**multi`, this technique is called _____.
Double dereferencing

C language was evolved from ___ language(s).

B and BCPL

The _____ statement forces the immediate next iteration of the loop.

Continue

_____ are very good tools for code reuse.



SUBSCRIBE

AR Lucky Bahi





Functions





When an argument is passed by reference, _____
the function accesses the argument's original value in the calling
program.

_____ executes all the lines before error and stops at the line
which contains the error.

Intrepreter

Analysis is the-----step in designing a program.

First

Which of the following is the correct function call, having array named
student of 10

elements as a parameter?

`addRecord(student);`

When an array element is passed to a function, it is passed by

_____.

Reference

What is the correct syntax to declare an array of size 10 of int data





SUBSCRIBE

AR Lucky Bahi



type? int name[10] ;

If we want to copy an array, both arrays need to be of same ____ _.

Data type and size



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Which of the following is the correct syntax to print multiple values or variables in a single command using cout?

`cout << "H" << x << "\n";`

Which one of the statements given below is equivalent to x

`%= 5? x = x % 5`

The condition in loop should be a(n)_____.

Boolean Expression

Which structure is represented by following flow

chart ?if structure

Stream which sends data to the program is called _____.

Input stream

Syntax of a union is identical to _____.

Structure

When accessing a structure member, the identifier to the left of the dot operator is the

name of _____.

a structure variable



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



The parameter passed to isdigit() function is _____.

a character variable

TWAIN stands for _____ .

Technology Without An Interesting Name

_____ translates high level language program into machine language code.

Compiler

From the option given below, what will be the correct output of the code? for (int a = 1; a <= 3; a++)

cout<<a*3-

1<<" ";2 5 8

If the return type of a function is void then it means that it will____ _.

return any type of

data return no data

The functions that have already been defined as a part of the language are called

_____.

built-in functions



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Given that doubleArray is an array of 7 integers. Which of the below is the correct statement to access the 5th element of the array?

doubleArray[4]

The symbol which is used to represent a process in a flow chart is

____.

Rectangle

When an array is passed to a function, by default it will be passed by ____.

Reference

What is the range of Random number generator function

rand()? 0 – 32767

The first character of a variable name must be an alphabet or

____.

Underscore

In _____, the first pointer stores the address of the some other pointer, which contains the address of any variable.



SUBSCRIBE

AR Lucky Bahi





single dereference





Initialization of variable at the time of definition is----- practice.

Good Programming

Which looping process checks the test condition at the end of the loop? do-while

You can use a _____ statement to transfer control elsewhere out of the nested structure.

Goto

Which of the following array is the most suitable for storing a matrix structure?

Single-dimensional array

The microsoft word document(.doc) is a kind of ____ _ .

Random Access File

A union is a user-defined data type that contains only ____ from its list of members at a

time. one object

In C/C++, _____ are the doors through which data can enter and come

out of a





program.

Streams





SUBSCRIBE

AR Lucky Bahi



Which one of the given option is not a mode for reading/writing the data from a file?

Trunk

C++ views each file as a sequential stream of _____.

Bytes

In 2D array, the technique used to access the array elements is called _____

Double dereferencing

From the options given below, identify the correct option which is used for calling the function float square (int &);

square (num);

Identify the correct option which is used for calling the function float area(int).

area(num) ;

Which kind of error occurs in the code below to access the variable num in the main

function?

int num

=10;int



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



```
main(){ int
```

```
x ;
```

```
x = num ;
```



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



}

No error

program statement that invokes a function is called _____.
function call

What will be the output of the following code

```
segment? main(){
```

```
int a = 10
```

```
;int b =0;
```

```
int *x =
```

```
&a; b =
```

```
(*x)+3 ;
```

```
cout << a << " , " << b ;
```

```
}
```

10,1

3

When the logical operator AND (&&) combines two expressions exp1 and exp2 then the result will be true only _____

When both exp1 and exp2 are true



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



For which array, the size of the array should be one more than the number of elements in an array?

char



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



What is the range of Random number generator function
rand()? 0 – 32767

To assigned a value to a character type variable, ____ are used around
the value.

single quotes '
'

In C/C++, the #include is called _____.
Preprocessor Directive

The number 544.53 must be stored in ____ data type.
Float

Use of the _____ statement violates the rules of structured
programming
.Goto

In Flow Chart, flow of control is represented by _____.
Arrow

What will be the correct syntax for initialization of pointer ptr of
type int with variable x?
int *ptr = &x ;



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Syntax of a union is identical to ____ _ .

structure

A union is a user-defined data type that contains only ____ from its list of members at a

time. one object

Which of the given file handling modes are similar in their functionality ? ios::trunc, ios::ate

Which one of the given option is not a mode for reading/writing the data from a file?

Trunk

Stream which sends data to the program is called ____ _.

Input stream

Syntax of a union is identical to ____ _ .

Structure

When accessing a structure member, the identifier to the left of the dot operator is the name of ____ _ .

a structure variable



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



The parameter passed to isdigit() function is _____.
a character variable

TWAIN stands for _____ .

Technology Without An Interesting Name

_____ translates high level language program into machine language code.

Compiler

From the option given below, what will be the correct output of the code?
for (int a = 1; a <= 3; a++)

cout<<a*3-

1<<" ";2 5 8

If the return type of a function is void then it means that it will_____.
return no data

The functions that have already been defined as a part of the language are called

_____.



SUBSCRIBE

AR Lucky Bahi





built-in functions





SUBSCRIBE

AR Lucky Bahi



Given that doubleArray is an array of 7 integers. Which of the below is the correct

statement to access the 5th element of the array?

doubleArray[4]

The symbol which is used to represent a process in a flow chart is

____.

Rectangle

When an array is passed to a function, by default it will be passed by ____.

Reference

The first character of a variable name must be an alphabet or

____.

Underscore

In _____, the first pointer stores the address of the some other pointer, which contains the address of any variable.

single dereference

Initialization of variable at the time of definition is----- practice.



SUBSCRIBE

AR Lucky Bahi





Good Programming





SUBSCRIBE

AR Lucky Bahi



Which looping process checks the test condition at the end of the loop? do-while

You can use a _____ statement to transfer control elsewhere out of the nested structure.

Goto

An object of _____ class can be created for saving the current position of any opened file

before reading from the
file Stream

The value returned by the eof() function is of _____ type.

Character

If a file is not properly closed in a program then what is the status of the program ?

The program will terminate normally

The parameter passed to isdigit() function is _____.
a character variable



SUBSCRIBE

AR Lucky Bahi





In C/C++, the header file used for string manipulation is _____.
string.h

Arrays are best data structures _____.
for relatively permanent collections of data

Each array declaration must provide the information about all these things except

_____.

Number of elements of the array

The First step for developing a program is _____.

Linking

Analysi

s

_____ transfers the executable code from hard disk to main
memory. Loader

_____ operator is used to pass the address of a variable to the
called function.





&





SUBSCRIBE

AR Lucky Bahi



In call by reference, _____ of a variable is passed to the called function

.

Address

_____ of a function is also known as signature of a function.

Declaration

Preprocessor program performs its function before _____ phase takes place.

Compilin

g

Which of the following is the correct function call, having array named student of 10 elements as a parameter?

addRecord(student[10]);

The remainder (%) operator is a _____ operator.

Arithmetic

Which of the following array is the most suitable for storing a matrix structure?

Two-dimensional array



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



*.doc is _____ by type.

- Random Access File



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Which of the following is NOT a preprocessor directive?

- #define

The return type of operator function must always be void.

- False

Question No: 4 (Marks: 1) - Please choose one

What does (*this) represents?

- A value of the data member

The statement cin.get (); is used to,

- Read a character from keyboard

When we do dynamic memory allocation in the constructor of a class, then it is necessary to provide a destructor.

- True

Overloaded new operator function takes parameter of type size_t and returns

- void pointer

The second parameter of operator functions for << and >> are objects of the class for which we are overloading these operators.

- True

C++ is a case-sensitive language



SUBSCRIBE

AR Lucky Bahi





► True





SUBSCRIBE

AR Lucky Bahi



o include code from the library in the program, such as `iostream`, a directive would be called up using this command.

- `#include <iostream.h>`

A template function must have only generic data types.

- True

Template class can not have static variables.

- False

What will be the correct syntax to assign an array named `arr` of 5 elements to a pointer

`ptr`?

- `*ptr = arr[5] ;`

What will be the correct syntax to access the value of fourth element of an array using pointer `ptr`?

- Both 1 and 3

If most significant bit of un-signed number is 1 then it represents a positive number.

- True



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



If there is a symbol (& sign) used with the variable name followed by datatype then it

refers to _____ and if & is being used with variable name then it refers to

_____.

- Reference variable, address of variable

We can also do conditional compilation with preprocessor directives.

- True

The default value of a parameter can be provided inside the

- function definition

Classes defined inside other classes are called _____ classe

- nested

What purpose do classes serve?

- All of the given options

Every class contains _____.

- Constructor

new operator is used to allocate memory from the free store during

- None of the given options



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



When an object of a class is defined inside another class then,

- Destructor of inner object will be called first

It is possible to define a class within another class.

- True

New and Delete are also used with _____ and data types as well.

- Class, Objects

With New keyword, data types and class members are initialized with meaningful values instead of garbage.

- True

C language is developed by

- Dennis Ritchie

Which of the following choice is not an example of an int data type?

- -4.0

In flow chart, the symbol used for decision making is,

- Diamond



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Switch statement deals with,

- Integer and character data

Default case in switch statement is,

- Optional

*.doc is _____ by type.

- Sequential File

Member function tellg() returns the current location of the

pointer.

- tellptr()

Dealing with structures and functions passing by reference is the most economical method

- True

In C/C++ all character strings are terminated with,

- Null character

Word processor is <http://vustudents.ning.com>

- Application software



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Which of the following can not be a variable

name? 10area

Which looping process is best, when the number of iterations is known?

► while

By default an array of characters is passed by value to a function

► False

Which of the following operator is used to access the address of a variable?

► & operator

The name of an array represents address of first location of array element.

► False

Compiler is a

► Application Software

If Num is an integer variable then Num++ means,

► Add 1 with Num



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



For one byte there are ____ combinations of values that can be stored in computer.

- 2^8

In C/C++ language the header file which is used to perform useful task and manipulation of character data is

- `ctype.h`

Default case in switch statement is,

- Optional

When break statement is encountered in switch statement, it

- Exits from switch statement

What will be the result of arithmetic expression $6 + 27/3 * 3$?

- 33

What is the correct syntax to declare an array of size 10 of int data type?

- `int name[10] ;`

How many dimensions does n-dimensional array has?

- n dimensions



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



What will be the correct syntax to access the value of fourth element of an array using pointer ptr?

- ptr[3]

Which of the following values C++ use to represent true and false?

- 1 and 0

Declaring structures does not mean that memory is allocated.

- True

For which array, the size of the array should be one more than the number of elements in an array?

- char

If a variable is passed by value to a function and the function makes some changes to that variable then it

- does not affect the original variable

In C/C++ the #include is called,

- Preprocessor Directive

Loops are _____ Structure.

- Repetition



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



the sizeof operator is used to determine the size of _____.
data type

Structures use _____ allocation.

Stack

Which header file must be included to use the functions to lower() and toupper()?

ctype.h

In Analysis, we try to have a _____

Precise problem statement

Pointers store the _____

memory address

_____ Returns true if c is a digit and false

otherwise. int isdigit(int c)

eof is used to check for the _____ of file when a file is being read.

End



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



The statement `cout << yptr` will show the _____ the `yptr` points to.
memory address

Which of the following is true about
streams? A & B

While handling files, one can have _____ options
All of the given

If an array has 50 elements, what is allowable range of
subscripts? 0 – 49

A structure is a collection of _____ under a single name.
variables

`Ifstream` is used for _____
Input file stream

The ASCII code of null character is _____
000

dereferencing operator is represented by _____
*



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Whenever some number is added in an array name, it will jump as many

_____ as the added

number.rows

To access the data members of structure, _____ is used.

Dot operator

Which of the following is true about streams? A. It is a sequence of bytes

B. It is an ordered sequence C. All bytes can

go through the stream simultaneously D. Bytes that enters first into the stream will go out at last

A and B

We use _____ to open a file or stream for extraction

in

char **argv can be read as _____ _.

pointer to pointer to char

From following; which one is the correct syntax of an array

initialize: Array size is 10 and it is of double data type to value 0?

double arr[10] = {0.0};



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Pointers work by pointing to a particular _____
data type

_____ function give the position of the next character to
be read from that file.

tellg()

aFile. seekg (-10L,
ios:cur)backward
direction

An object of _____ class can be created for saving the current position
of any opened file before reading from the file.

Stream

Structures are syntactically defined with the word _____.
struct

_____ allow us to have a memory location and use it as int or



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



char interchangeably

union



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Question# 9 of 10 (Start time: 12:25:41 PM) Total Marks: 1

A hierarchy of classes which are used to deal with console and disk files are called ____.

IO classes

_____function is used to determine the next position to write a character while writing into a file.

tellp()

For binary member operators, operands on the _____ drives (calls) the operation.

Left

We cannot increment ____.

references

We can _____ pointer.

all of the given

We can _____ references.

None of the given



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



What will be the correct syntax for the following function call?
`add(x);`



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



An instance of a class is called _____.
object

The _____ is called automatically when an object destroys
destructor

The destructor is used to _____.
deallocate memory

_____ data isn't accessible by non-member functions or outside
classes. private

Member functions of the class _____ main program.
are accessible from

Overloading means :

Using the same name to perform multiple tasks or different tasks
depending on the situation.

The main advantage of function overloading is _____.
The program becomes more readable

You cannot overload the _____ operator.



SUBSCRIBE

AR Lucky Bahi





? :





SUBSCRIBE

AR Lucky Bahi



In C++, a variable can be declared anywhere in the program this will increase __ _.

efficiency

Memory allocated from heap or free store ____ _.

cannot be returned back unless freed explicitly using free and delete operators

We cannot use _____ pointer for storing and reading data from it.

'NULL

The dynamic memory allocation uses ____ whereas static memory allocation uses _____ _.

heap , stack

What will be the output of the given code?

```
#include <iostream>
#define MAX( A, B ) ((A) > (B) ?
```

```
(A) : (B))
```

```
void main()
```

```
{ int i, x, y;
```

```
x = 23;
```

```
y = 45;
```

```
i = MAX( x++, y++ );
```



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



```
// Side-effect: // larger value incremented twice
```

```
cout << "x = " << x << " y = " << y << "\n";
```

```
}
```



SUBSCRIBE

AR Lucky Bahi





x=24 y=47

NULL has been defined in ____ header file.

Stdlib.h

Symbolic constant PI can be defined as:

```
#define PI 3.14
```

The friend function of a class can have access _____.
to the private data members

C++ was developed by ____.

Bejarne Stroustrup

Once the _____ are created, they exist for the life time of the program.
static variables

Encapsulation means ____.

that the data of a class can be accessed from outside

An address is a _____, while a pointer is a ____.
constant, variable





SUBSCRIBE

AR Lucky Bahi



The syntax of declaration of a function that returns the reference to an integer is__.

int & myfunc();

Which one of the following is mandatory preprocessor directive for #c++?include

The members of a class declared with the keyword struct are_____ by default.

Public

getche() is a _____ function and defined in __header file.

built-in function , conio.h

_____ operators are the ones that require two operands on both sides ofthe operator.

Binary

_____ will return the number of bytes reserved for a variable or datatype.

sizeof operator



SUBSCRIBE

AR Lucky Bahi





_____ are not available in C
language. Library functions





SUBSCRIBE

AR Lucky Bahi



The members of a class declared without any keyword are ____ by default

.

private

For console input and output we use ____.

conio.h header file

The name of the destructor is the same as that of a class proceeding with a _ _.

~ sign

A reference cannot be NULL it has to point a data type. True

A pointer is ____ _.

a variable for storing address

Constructor is a special function, called whenever we ____ _.

instantiate an object of a class

Symbolic constant PI can be defined

```
#as:define PI 3.14
```



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Object code is machine code but it is not _____ and _____.
relocatable, executable

The default visibility for the data members of the
class is private

accessible outside the class

The _____ is called automatically when an object destroys.
destructor

Constructor is special type of
function : which has no return type

_____ variables are those that are defined outside of
main. Global

Within the statement `obj1=obj2`; `obj1` will call the assignment operator
function and `obj2` will be passed as an argument to function.

True

When the compiler overload the assignment (=) operator by default
then Compiler does member wise assignment.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



It is possible to return an object from function using this pointer. True

Overloaded assignment operator must be Member function of class

Let suppose

int a, b, c, d,

e;

a = b = c = d = e = 42;

This can be interpreted by the compiler

as a = (b = (c = (d = (e = 42))));

In statement a+b+c, at first b+c is executed first

Suppose int i = 10; then what is the output of

cout<<oct<<i;12

ostream is a _____ operator.

Standalone

_____ must be included to use stream manipulation in your code.



SUBSCRIBE

AR Lucky Bahi





Iomanip





SUBSCRIBE

AR Lucky Bahi



_____ operators are the ones that require only one operator to work.

Unary

The endl and flush are _____.

Manipulators

When operator function is implemented as member function then return type of function ____.

Can be any data type

When a variable is defined as static in a class then _____.

Only one copy is created for all objects of this class

Automatic variables are created on _____.

Stack

```
cout << i << "
```

```
"; cout << d
```

```
<< " "; cout
```

```
<< f;
```

Above statements can be written within statement of one line as:

```
cout << i << " "<< d << " "<< f;
```



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



dec, hex, oct are all ____ _.

Non-parameterized manipulators

What will be the output of following statement?

```
cout<<setfill('0')<<setw(7)<< 128;
```

0000128

Which of the following syntax is best used to delete an array of 5 objects named 'string' allocated using new operator.

```
delete []string;
```

If we have a program that writes the output data(numbers) to the disc, and if we collect the output data and write it on the disc in one write operation instead of writing the numbers one by one.

In the above situation the area where we will gather the number is called Buffer

The first parameter of operator function for << operator ____ _.

Must be passed by reference

The second parameter of operator function for >> operator must always be passed

By reference



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



The only operator that the compiler overloads for user define data type by default is-----

Assignment (=) operator

Consider the following code, the printed value will be converted

into: int n=10;

cout

<<oct<<n;

Base 8

_____ variables are defined in the main.

Local

ostream class is _____ and not under our control.

built-in

The memory allocation in C++ is carried out with the help of ____.

new operator

If B is designated as friend of A, B can access A's non-public members. A can access non-public members of B

If the request of new operator is not fulfilled due to insufficient



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



memory in the heap _.

the operator returns 0



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



We should not use such variable names that are starting with _____ because in C++, there are lots of internal constants and symbolic names that start with it.

double underscore

The friend keyword provides access _____.
in one direction only

The malloc function takes _____ argument(s).
one

The constructor contains_____.
no return type

What will be the output of the following c++

```
#code?include<iostream.h>
```

```
#define max
```

```
100main()
```

```
{
```

```
#ifdef max
```

```
Cout<<"Hello
```

```
w;
```



SUBSCRIBE

AR Lucky Bahi





}

Error





SUBSCRIBE

AR Lucky Bahi



Once we have defined a symbolic constant value using `#define`, that value

_____ during program
execution cannot be changed

The memory allocation functions return a chunk of memory with a pointer of type `void*`.

ptr

A class can be declared as a _____ of other class.
member

To avoid dangling reference, don't return _____.
the reference of a local variable from the function

Constructor is itself a _____ of C++ and _____.
function, can be overloaded

The parameter passed to `isdigit()` function is _____ variable.
Integer

`char **argv` can be read as _____.
pointer to pointer to char



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



To read command-line arguments, the `main()` function itself must be given

arguments.2



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



How many bytes an integer type pointer intPtr will jump in memory if the statement below is executed?

```
intPtr += 2;
```

8

The increment of a pointer depends on its ____.

data type

The statement `cout << yptr` will show the ____ the yptr points to.
memory address

_____ is used as a dereferencing operator.

*

Transpose of a matrix means that when we interchange rows and columns ____.

the first row becomes the first column

Individual characters in a string stored in an array can be accessed directly using array ____.

subscript

We can define a matrix as ____ array.



SUBSCRIBE

AR Lucky Bahi





Multi dimensional





SUBSCRIBE

AR Lucky Bahi



A _____ is an array of characters that can store number of character specified

.String

Given a two dimensional array of integers, what would be the correct way of assigning the value 6 to the element at third row and fourth column?

`array[2][3] = 6;`

_____ of a variable means the locations within a program from where it can be accessed.

Visibility

Which of the following function call is "call by reference" for the following function prototype? `int add (int *);`

`add(&x);`

Which of the following function call is "call by reference" for the following function prototype? `float add (float *);`

`add(&x);`

Which of the function call is call by value for the following function prototype? `float add(float);`

`add(x);`



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Which of the function call is "call by value" for the following function prototype? float add(int);

add(x);

Return type of a function that does not return any value must be __ _.

void

_____ will be used for enclosing function statements into a block.

{ }

What is the output of the following code if the 2nd case is

true switch (var) {

case 'a': cout<<"apple"<<endl;

case

'b':cout<<"banana"<<endl;

case

'm':cout<<"mango"<<endl;

default: cout<<"any

fruit"<<endl;

}

Banana mango any fruit

When the break statement is encountered in a loop's body, it transfers



SUBSCRIBE

AR Lucky Bahi





the control ____ from the current loop.

Outside

What is the output of the following code if the 3rd case is true

```
switch (var) {
```





SUBSCRIBE

AR Lucky Bahi



```
case 'a':cout<<"apple"<<endl;
```

```
case
```

```
'b':cout<<"banana"<<endl;
```

```
case
```

```
'm':cout<<"mango"<<endl;
```

```
default: cout<<"any
```

```
fruit"<<endl;
```

```
}
```

Mango any fruit

What is the output of the following code, if the first case is

true

```
switch (var) {
```

```
case 'a':cout<<"apple"<<endl;
```

```
case
```

```
'b':cout<<"banana"<<endl;
```

```
case
```

```
'm':cout<<"mango"<<endl;
```

```
default: cout<<"any
```

```
fruit"<<endl;
```

```
}
```

Apple banana mango any fruit



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



What will be the output of following code

```
segment? for (int i = 2; i<10; i++) {
```

```
if ( i == 5)
```

```
continue; cout <<
```

```
i << ", " ;
```

```
}
```

```
2,3,4,6,7,8
```

```
,9
```



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



_____ statement is used to terminate the processing of a particular case and exit from switch structure.

break

What will be the result of the expression $j = i++$; if initially $j = 0$ and $i = 5$? 5

What will be the result of the expression $k = ++m$; if initially $k = 0$ and $m = 5$

What will be the result of the expression $k = ++m$; if initially $k = 0$ and $m = 5$?

6

How many times the following do-while loop will execute?

```
int k = 10; do { cout << "Statements" << endl; k -= 2; }
```

```
while(k>0); 6
```

Which of the following loops checks the test condition at the end of the loop?

Do-While

The operators $++$ and $--$ are used to increment or decrement the value of a variable by $__$.



SUBSCRIBE

AR Lucky Bahi





1





SUBSCRIBE

AR Lucky Bahi



How many times the following loop will execute?

```
int j = 3; while(j > 0) { cout << "Statements" <<  
endl; j -= 2; } 2
```

A _____ structure specifies that an action is to be repeated while some condition remains

true. Control

!(x > 3) means in C++

that x is less than or

equal to 3

When the logical operator && combines two expressions then the result will be true only when the both expressions are _.

true

< and > both are _____ operators.

Relational

What will be the value of variable “input” if the initial value of input is 67?

```
if(input >= 50)
```



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



input = input +

1; if(input <=

75) input =

input + 2;



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



else

input = input - 1;

70

!(x < 3) means in C++ that

x is greater than or equal to 3

!= operator is used to check whether the operand on the left-hand-side is

_____ to the operand on the right-hand-

side. Not equal

When the if statement consists more than one statement then enclosing these statement in curly braces is,

Must

The most suitable data type for number 325.25 is __ _.

Float

What will be the result of arithmetic expression

$6 + 48 / 4 * 3$? 42

Which of the following will be the most appropriate data type to store the value 63.547?



SUBSCRIBE

AR Lucky Bahi





Float





SUBSCRIBE

AR Lucky Bahi



In the given expression which operator will be evaluated first? $10 + (6 / 2) - 2 * 3$?

/

What will be the value of the variable output in the given piece of code? `double output = 0;`

`output = (2 + 2) * 4 + 2 / (4 - 2);`

17

It is the job of _____ to transfer the executable code from hard disk to main

memory.

Loader

In computer systems there are mainly _____ type of softwares.

2

_____ will explain the function of a program.

Comments

if $(a > b \ \&\& \ a > c)$ then the condition will be true

only if Both $a > b$ and $a > c$ are true



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



A variable of character data type occupies ____ byte(s) in memory.

1



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



We must include the header file _____ to convert the value of one type into another type using built-in

functions.string.h

A function is a block of statements that can be defined once and used _____ in the program.

As many times as user wants

Select the correct way to assign the address of first element of array to pointer?

int *ptr = &data;

Consider the following code segment. What will be the output of following code?

```
int addValue (int
*a){ int b = (*a) +
2; return b;
}
main() {
int x =
6;
cout<<addValue(&x)<
<" "; cout<<x;
```



SUBSCRIBE

AR Lucky Bahi





}

6,8,6





SUBSCRIBE

AR Lucky Bahi



Here the code is given below. You have to identify the problem in the code. `while(i < 10) && (i > 24))`

the test condition is always false

The correct syntax of do-while loop is ____.

`do {statements;} while (condition);`

Matrix is defined as ____.

Multi-dimensional array

In programming, comments are used to explain the functioning of the

—.

Program

Operating System is a type of a/an ____.

system software

From the options given, you need to choose the option which is true for the given code.

```
for (int i = 1; i>0; i++) {
```



SUBSCRIBE

AR Lucky Bahi





`/*loop code*/`

`}`

the test condition is always true





SUBSCRIBE

AR Lucky Bahi



Which of the following values are used in C/C++ to represent true and false?

1 and 0

'While' loop may execute _____ or more times.

zero

Body of any function is enclosed within__ _.

{ }

What will be the correct syntax for initialization of a pointer ptr with string "programming"?

```
char *ptr = "programming";
```

Which one of the given option is not a mode for reading/writing the data from a file?

Get

Which of the following operators is used to access the value of variable pointed by a pointer?

* operator



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



In case of single dereferencing, the value of the _____ is the address of the _____.

pointer, variable

The remainder (%) operator is a _____ operator.

Arithmetic

What will be the output of following

code? `int x = 10;`

`cout<<"x="<`

`<x;x=10`

The purpose of using `cout<<` is to _____.

Display information on the screen

Which of the following data types will be assumed if no data type is specified with constant?

short

When an array element is passed to a function, it is passed by _____.

reference

While programming, it is good to provide an easy to understand and easy to use interface; this programming skill is called _____.



SUBSCRIBE

AR Lucky Bahi





usability





SUBSCRIBE

AR Lucky Bahi



_____ executes all the lines before error and stops at the line which contains the error.

Intrepreter

Which of the following is the correct syntax to access the value of first element of an array using pointer ptr?

*ptr[0]

C is a/an _____ language.

function oriented

_____ of a function is also known as signature of a function. Declaration

_____ are very good tools for code reuse.

functions

If any break statement is missed in switch statement then _____.
this may cause a logical error

A 2D array multi[5][10] can be accessed using the array name as
**multi, this technique is called _.



SUBSCRIBE

AR Lucky Bahi





Double dereferencing





SUBSCRIBE

AR Lucky Bahi



In C/C++, the default command line arguments passed to the main function are ____.

int argc, char **argv

A record is a group of related ____.

Fields

The Microsoft Word document (.doc) is a kind of ____.

Random Access File

NULL character is used to indicate the ____ of string.

End

How many dimensions does an n-dimensional array

have? n dimensions

Which of the following function calls is "call by reference" for the following function prototype?

func(&num);

The loop which is most suitable to be used when the number of iterations is known is called ____.

for



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



In C/C++, the string constant is enclosed in ____.

double quotes " "



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



In order to get the right most digit of a number, we divide this number by 10 and take ____.

Its remainder

What is the correct syntax to declare an array of size 10 of int data type? `int name[10];`

How many bytes of memory are occupied by array

`'str'?char str[] = "programming";`

11

Suppose that an integer type pointer contains a memory address 0x22f230. What will be the new memory address if we increment this pointer by one?

0x22f234

Which of the following if missing would result in infinite recursion in case of recursive function?

Recursive call

Whenever we use a library function or a predefined object or macro, we need to use a ____.

header file



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Switch statement deals with _____ type of data.

Both Integer and Character



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Both compiler and _____ are used to translate program into machine language

code.

Interpreter

TWAIN stands for _____.

Technology Without An Interesting Name

The parameter passed to isdigit() function is _____.

a character variable

C++ views each file as a sequential stream of ____ _.

Bytes

Structure is a collection of _____ under a single name.

only variables

The default mode for writing into a file using ofstream object is ____ _.

out

The memory address of the first element of an array is called ____ _.

base address



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



We want to access array in random order which of the following approach is better?

Pointer



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



The _____ structure is a multiple-selection construct which makes the code more efficient and easy to read and understand.

switch

Which of the following is not a reserved word in C/C++? Sum

To access rand(), which library is required to be included in program? stdlib.h

What is the highest legal index for the following array? int arr[4]

3

Word processor is a type of a/an _____.
application software

Identify the correct option which is used for calling the function float area(int).
area(int num);



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



The _____ statement allows us to select from multiple choices based on a set of fixed values for a given expression.

switch

C is widely known as development language of _____ operating system.

Unix

To convert the value of one type into another type using built-in functions, we include header file.

stdlib.h

The keyword _____ is used to get some value back from a function.

return

The function seekg() takes _____ parameter(s).

2

The function write() takes _____ as parameter(s).

String and no. of bytes to be written

When the logical operator AND (&&) combines two expressions exp1 and exp2 then the result will be true only ____.

When both exp1 and exp2 are true



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Syntax of a union is identical to ____.

structure

In Flow Chart, flow of control is represented by ____.

Arrow

There can be _____ 'default' statement(s) in any switch structure.

2

The condition in loop should be a(n)____.

Arithmetic Expression

How many nested loops would be required to manipulate n-dimensional array?

$2n$

Which of the following is not an example of int data type?

-4

We should use_____ for clarity and to force the order of evaluation in an

expression.

parenthesis ()



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Which of the following is the starting index of an array in C++?

0

The statement $x += y$ can be interpreted as ____.

Adding the value of the x to the value of the y and storing the result in x

Given a 2D array of integers, what would be the correct way of assigning the value 5 to the element at second row and third column?

$m[1][2] = 5;$

Array is a data structure that stores ____.

Variables

A program statement that invokes a function is called ____.

function call

The compiler of C language is written in ____ language.

C

Which function is used to locate the first occurrence of a character in any string?

strlen()



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



To access the data members of structure, _____ is used.

Dot operator

In the following nested For Loop, which loop will run most number of times?

```
for( int i = 0; i < 5; i++)  
{  
  for(int k = 0; k < 5; k++)  
  {  
    . . . . .  
  }  
}
```

Depends upon the statements in the inner loop's body

Structure use _____ allocation.

Heap

_____ function give the position of the next character to be read from that file.

tellp()

What will be the size of the following character



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



```
array?char name[] = "Adeel";
```

5



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Function prototype is
written, Before call of that
function

Which one of the following languages has been used to write the
compiler of "C" language?

C

A hierarchy of classes which are used to deal with console and disk
files are called _ _.

Stream classes

_____ stops execution at the line that contains error(s) in the code.

Interpreter

C++ is a _____ language.

High level

How many elements are stored in the
following? `int matrix [4][5];`

20



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



_____ is a substitute of multiple if statement.

if. . .elseif statement



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



if

```
int sum = 54;
```

Then the value of the following

```
statement is sum = sum - 3;
```

51

What will be the correct syntax for declaration of the following statement? "ptr is a constant pointer to an integer"

```
const int *myptr;
```

_____ operator is used to pass the address of a variable in call by reference method.

&

_____ data type can operate on modulus operator.
int

Whenever some number is added in an array name, it will jump as many

_____ as the added

number.
rows



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Suppose that an integer type pointer contains a memory address 0x22f220. What will be the new memory address if we increment this pointer by one?

0x22f224



SUBSCRIBE

AR Lucky Bahi





_____ is the pointer which determines the position in a file from where the next read operation occurs.

put

what is the correct context to declare an array of 15 elements of type float? float array [14]

suppose we have a file with name "mylife.txt". what will be the correct

Syntax of file opening for input?

my file ("myfile.txt". ios::in)

which of the following will be the most appropriate data type to store the value 63.5 47?

Float

----- will explain the function of a program

Comments

these functions Seekg() and seekp() requires an argument of type-----

-

-- to let them how many bytes to move forward or

backward

all elements of an array must be of----- data type





Same

what will be the result of arithmetic expression $6 + 48 / 4 * 3$?





SUBSCRIBE

AR Lucky Bahi



42

----- allow us to have a memory location and use it as int or char interchangeably

none of the given

accessing a structure member the identifier to the left of the dot operator is the name of-----

structural variable

< and > both are----- operators

Arithmetic

what will be the output of the following code

```
segment? For (int = 2; i<10; i ++){
```

```
If ( i == 5 )
```

```
Continue;
```

```
cout<< i << “.”;
```

```
}
```

2,3,4,5,6,7,8,9

----- returns true if she is a digit or a letter and false otherwise



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Int isalnum (int c)



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



if a ----- find an error, it stop translating without generating any E executable code

Compiler

the ASCII code of null character is-----

000

if $X = 9$; then the expressions $x\% = 2$; will calculate the value of x as

-

1

the original value means unchanged in -----

Call by Value

which of the following is used to create an account stream?

Ofstream

how many times the following loop will

execute? $\text{Int } j = 3$;

While ($j > 0$)

{



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



```
Cout << " statements" << endl;
```

```
J - = 2;
```

```
}
```



SUBSCRIBE

AR Lucky Bahi





2

Use of word processor for writing the code of a program is not good because -----

It has less feature for writing code of a program

how many bytes and integer type pointer intptr will jump in memory if the statement below is executed?

Intptr + =

2;8

avoid loop may execute-----or more Times

0

raid stands for -----

redundant array of inexpensive dices

in a file is opened with iOS:: out mode, then-----

a new file is created

first step in designing a program

is Analysis

what will be the result of the





SUBSCRIBE

AR Lucky Bahi



expression $J = i++$



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



If initially $j = 0$ and i

$= 5$?

suppose we have `int y [10];`

to access the 4th element of the array be write-----

`Y [3];`

A-----structure specify that an action is to be repeated while some condition remains

trueControl

the most suitable data type for number 325.25 is-----

float

Which one of the following should be placed immediately either before or after the noun?

Modifiers of Nouns

Titles typically include both

a number and a description

For what purposes colons are

used? All of the above



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



The name of the array is a constant pointer which contains the memory address of the _ of the array.

first element

What will be the correct syntax for the following function call? float add(int &);

add(x);

In C/C++; by default arguments are passed by ___ to a function.

Value

< , <= , > , >= are called ___ operators.

Relational

char name [] = "Hello World" ; In the above statement, a memory of _____ characters will be

allocated 12

While developing a program; should we think about the reusability? Yes

C is widely known as development language of ___ operating system.

Unix



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Which of the following function call is “call by reference” for the following function prototype? `int add (int *); add(&x);`

If a function has not been declared before its definition, It is a None of these

While loop executes at least----
Zero time

A _____ is a precise sequence of steps to solve a particular problem

.

Program

In while loop the loop counter must be initialized,
Before entering the loop

```
int counter = 0 ;  
while(counter < 15)  
cout << counter <<  
“ ”; counter++;
```



SUBSCRIBE

AR Lucky Bahi





Infinite loop





SUBSCRIBE

AR Lucky Bahi



Why we use "cin"?

To read data from keyboard

Loops are _____ Structure

Repetition

1. **Special name which is substituted in code by its definition and as a result we get an expanded code is called**

Macro

2. **A=a+1, can be written as _____**

A+=1

3. **The compiler generates _____ automatically.**

Constructors

4. **The data members of the class are initialized _____**

At runtime

- **Explicitly write keyword private in the class definition**
- **Separate the interface and implementation**
- **The default constructor has no arguments**
- **Constructor has the same name as of class**



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



- **Initializing the data members in the definition of the class is a syntax error**

5. _____ **for parameters is also done for inline functions.**

Automatic type checking

6. **An instance of a class is called_____.**

Object

7. **With the use of dynamic allocation of memory, the system resources can be_____.**

Used efficiently

8. **When we include the header file in the angle brackets the compiler searches for it in**

Specific directory

9. _____ **is a special type of pointer we have to cast it before we use it.**

Void

10. **Multiplicative, additive and assignment operators are operators**

Binary

11. **The memory allocation functions return a chunk of memory with a pointer of type**

_____.

Void



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



12. Default constructor takes__.

No parameters

13. In a class we can have _____constructor(s).

Only one

14. Which one of the following is mandatory

preprocessor directive for c++?

#include <isotream?

15. Header files provide__so the program running on one operating system can runwithout an error on the other system

Accessibility

16. We should not use such variable names that are starting with

_because in C++ these are lots of internal constants and symbolic names that start with it.

Double underscore

17. Which of the following code segment represents a left shift operator?

Result= number<<1



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



18. Which of the following code segment represent a bitwise And operator?

$\&$

19. Which of the following code segment represent a bitwise OR operator?

$|$

$\wedge$

20. Which of the following code segment represent a NOT operator

$\sim$

21. C++ was developed by_____.

Bejame stroustrup

22. For converting a void type pointer ptr into integer

type, the correct syntax is: `int* ptr`

23. A pointer with value NULL is defined in the header files and_____.

Stdlib.h stddef.h

24. Constructor is a special function, called whenever we_.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Instantiate an object of a class

25. Constructor is itself a ___ of C++ and ____.

Function, can be overloaded

26. What is the other name of a variable?

Identifier

27. In shifting operations if zero is inserted at the left most bit, the negative number will become a ___ number.

Positive

28. A class is ____.

User defined Data type

29. Bugs can occur due to _.

Uninitialized data

30. The heap memory structure ____.

Constantly changes in size

31. How many bits from a byte?

8

32. The function calloc takes two arguments, first argument is the _____ and the second argument is the _.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Required space in terms of numbers, size of space

33. The main advantage of function overloading is that__.

The program becomes more readable

34. Marco are categorized

into_____type(S)Two

35. When we include the header file in the angle brackets the compiler searches for it in

_____.

Specific directory

36. Class can be defined as

A class includes both data members as well as functions to manipulate that data

37. _____operator

uses the

sign ^

Exclusive

OR



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



38. For console input and

output we use _____. conio.h header file

39. Header file provide __so the program running on one operating system can run without an error on the other system

Portability

40. Constructor has ____.

The same name as of class

41. The object code of our program is combined with the_.

Object code of the library functions

42. The malloc functions takes _argument(s)

Two

43. The function overloading requires ____.

The argument list to be different

44. Bugs can occur due to ____.

Uninitialized data

45. The name of the destructor is the same as that of a class proceeding with a _____.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



~sign

46. The main advantage of function overloading is that__.

The program becomes more reliable

47. Which function is used to delete the allocated memory space? Free

48. Symbolic constant PI

can be defined

as#define PI3,

14

49. Windows operating system may itself takes memory from__.

Heap

50. All the preprocessors directive

starts with_____.#

51. Which one of the following is used to

perform bit-wise OR operator I

52. Constructor is itself a__of C++ and____.

Funtion, can be overloaded



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



53. **RAID** stands for__.

Redundant array of
inexpensive devices

54. **Object code** is machine code but it is not ____ and ____.

Reloadable, executable

55. **Constructor** is a

special type of
function; Which
has no return
type

56. **#includ**

e

<iostrea

m>

#include

<conio.h

> Using

namesp

ace std;

Void display (int=1,

float=2,3, char='@');



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



```
Main()
```

```
{
```

```
Dis
```

```
pla
```

```
y();
```

```
Dis
```

```
pla
```

```
y(5
```

```
);
```

```
Dis
```

```
pla
```

```
y(6
```

```
,7,8
```

```
);
```

```
Get
```

```
ch(
```

```
);
```

```
}
```

```
Void display( int first float second char third)
```

```
{cout<<"intfirst=<<first cout <<second=<<second
```

```
cout<<third=<<third}
```

First=1, second=2,3, third=@first=5, second=2,3, third =@
first=6, second=7,8 third=@first=9, second=10,11 third=\$

57. Default constructor generated by _____ does ____ for us

Compiler, no initialization

58. #define

CIRCUMFERENCE(X)(2



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



***PI*R) is a Definition of a**

marco

59. Constructor is itself a _____ of C++ and ____.

Function, can be overloaded

60. We cannot use __pointer for storing and

reading data from it NULL

61. Which function is used to delete the allocated memory space?

Free()

62. The data members of the class are initialized ____.

At runtime

63. An instance of a class is called ____.

Object

64. Malloc function returns ____ to the _____ from the

available memory Void pointer, starting of the chunk of

memory allocated from the heap

65. The ____ is the increment operator in c++

++



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



66. The constructor contains.

No
return
type

67. For accessing data members we use __operator

Dot.

68. In a class we can have __constructor

Only one

69. Object code is machine code but it is not _____ and ____.

Reloadable, executable

70. Getche() is a __function and defined in header file.

Built in function, conio.h

71. In C++ a variable can be declared anywhere in the program, this will increase _____.

Reada
bility

72. The compiler use a name mangling technique to.

Generate a unique token that is assigned to each function

73. Destructor _____



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Takes no arguments and Can be overloaded

74. The default visibility for the data members of the class is__.

Private

75. Which of the following permits

function overloading in C++

Both type and arguments

76. Once we have defined a symbolic constant value using #define, that

**value_____duri
ngprogram execution.**

Cannot be changed

77. Encapsulation means __.

That the data of a class cannot be accessed from outside

78. The original value remains unchanged in __

Call by value

79. Programmer should be very careful about the memory management because it can

_____.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



cause problems of memory leakage and dangling pointers

80. All the preprocessors directive starts with_.

#

81. NULL has been defined in

header file.stdlib.h

82. Which one is the correct example of a unary operator

&

83. In which statement there can be default statement(s)

1

84. To access the data members of structure _ is used

Dot operator

85. The statement cout << yptr will show the

_____the



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



yptr points to Memory address

86. If an array has 50 elements. What is allowable range of subscript

0-49

$A=a^b;$

87. If $j=10$ and $x=++j$ then the value of x will be ____.

11

88. The string in the array is terminated by a__.

Null

89. In C++, what will be the highest index of the following array? `Int array{15}`

14

90. Which of the following is a correct way to assign the address of the first element of array to pointer? `Int data[10];`

`Int*ptr= data [0]`

91. For casting, we normally declare a pointer of type _____. We are going to use



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



92. $A = aIb$; can be

written as _____ $aI = b$;

93. The exclusive OR operator returns 1 if ____.

One inputs is 1 and other is zero

94. Sometimes after allocating memory we need additional space, for this purpose we use

_____.

Realloc function

95. An integer uses four bytes and the integer calculations occur in bytes.

4

96. Shifting the binary numbers is similar to

shifting the _____ numbers Decimal

97. _____ operator uses the sign ^

Exclusive OR

98. _____ operator uses the sign &

Bitwise AND operator

99. _____ operator uses the sign I



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Bit-wise OR operator

100. _____operator uses the sign ~

Not operator

101. _____operator uses the sign <<

Left shift operator

102. _____operator uses the sign >>

Right shift operator

103. What can be the resultant number when you AND two numbers 12 & bit-wise using & operator?

8

For console input and output we use_____?

???

$a = a + 1$; can be written as:

$a += 1$;

The compiler generates_____automatically

Constructors



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



The data members of the class are initialized_____.

At runtime

____For parameters is also done for inline functions

Automatic type checking

An instance of class is called:

Object



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



With the use of dynamic allocation of memory, the system resources can be

Use efficiently

When we include the header file in the angle brackets the compiler searches for it in

Specific directory

_____ is a special type of pointer we have to cast it before we use it.

Void

Multiplicative, Additive and assignment operators are _____ operators.

Binary

Special name which is substituted in code by its definition and as a result we get an expanded code is

Called Macro

For converting a void type pointer ptr into integer type, the correct syntax is

int" ptr

Header files provide _____ so the program running on one operating system can run without an error on the other system.



SUBSCRIBE

AR Lucky Bahi





???

A pointer with value NULL is defined in the header files and .





SUBSCRIBE

AR Lucky Bahi



stdlib.h stddef h

for parameters is also done for inline functions.

Automatic type checking

malloc function returns to the from the available memory

???

Constructor is a special function, called whenever we ?

Instantiate an object of a class

We should not use such variable names that are starting with _ because in C++, there are lots of internal constants and symbolic names that start with it

Double underscore

Constructor is itself a _____ of C++ and

Function, can be overloaded

What is the other name for a variable?

Identifier

< and > both are _____ operators.

Logical



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Find out the logical error in following lines of code. If ($x = 10$) cout “x is 10”;



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Assignment operator should not be used for Comparison

What will be the result of the expression $j = i++$; if initially $j = 0$ and $i = 5$?

5

Default mechanism of calling a function by passing it array is call by _____ and in case of passing variable is call by _____.

Reference, value

When the break statement is encountered in a loop's body, it transfers the control _____ from the current loop.

Outside

_____ statement is used to terminate the processing of a particular case and exit from switch structure.

Break

If we pass more than one arguments to a function then they are separated by _____.

Comma,

What will be the value of the variable output in the given piece of code?
 $\text{double output} = 0; \text{output} = (2 + 2) * 4 + 2 / (4 - 2);$

17



SUBSCRIBE

AR Lucky Bahi





Window operating system may itself takes memory from_____.

Heap





SUBSCRIBE

AR Lucky Bahi



Initializing the data member within the class_____.

Not an error

Constructor has_____.

The same name as of class

The compiler generates_____.

Constructor

What is the storage space of double data type?

8bytes

The dynamic allocation_____whereas static memory allocation uses_____

Heap, stack

Which one of is the correct example of a unary operator?

.

Array indexes start from_____.

0

C++ was developed by_____.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Bejame stroustrup

In **shifting** operations if zero is inserted at the left most bit, the negative number will become a _____ number.



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Positive

The compiler generates_____automatically.

Constructors

A class is____-

A member function

Bugs can occur due to_____.

Uninitiated data

The heap memory structure_____.

Constantly change in size

How many bits from a byte?

8

The function calloc takes two arguments, first argument is the _____and the second argument is the_____.

Required space in term of numbers, size of space

The main advantage of function overloading is that_____.

The program become more readable



SUBSCRIBE

AR Lucky Bahi





A pointer with value null is defined IN THE header files_____and_____.





SUBSCRIBE

AR Lucky Bahi



Stdlib.h, stddef.h

The increment operator in c++

++

The memory allocation functions return a chunk of memory with a pointer of type_____.

Void

The constructor contains_____.

No return types

Multiplication, additive and assignment operators are_____ operators.

Binary

For accessing data members we use _____ operators

Dot

In a class we can have_____ constructor(s).

Only one

Object code is machine code but it is not_____ and_____.

Relocatable, executable



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



With the use of dynamic allocation of memory the system resources can be_____.

Used efficiently



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



The main advantage of function overloading is that -----

The program becomes more readable

For accessing data members we use _____operator.

Dot .

Object code is machine code but it is not _____and_____.

Reloadable, executable

The memory allocation functions return a chunk of memory with a pointer type_____.

Void

The_____is the increment operator in c++.

++

The constructor contains_____.

No return type



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



A class is _____

A user defined data type

In a class we can have _____ constructor(s).

Many



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



When we include the header file in the angle brackets the compiler searches_____.

Specific directory

What is the other name of a variable?

Identifiers

An instance of a class is called _____

Object

_____is a special type of pointer we here to cast it before we use it.

Void

$A = a + 1$; can be written as

$A++$;

With the use of dynamic allocation memory, the system resources can be_____

Use efficiently

It shifting operations if zero is inserted at the left most bit , the negative number will become will become a_____number



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



Positive

What will be the output of following c++ code?

```
#include <isostream.h>
```

```
#define max 100
```



SUBSCRIBE

AR Lucky Bahi





SUBSCRIBE

AR Lucky Bahi



```
Main ()  
{  
#ifndef max  
cout<<"hellow;  
}
```

Error

We should not use such variable name that are starting with ____ because in c++ , there are lots of internal contents and symbolic names that start with it.

Double underscore

Header file provide _____ so the program running on one operating system can run without an error on the other system.

Accessibility

Bugs can occur due to _____

Uninitialized data

The data members of the class are initialized _____

At runtime

For converting a void type pointer ptr into integer type, the correct syntax is;

Int*ptr



SUBSCRIBE

AR Lucky Bahi





Macros are categorized into_____type(s)

Two





SUBSCRIBE

AR Lucky Bahi



Class can be defined as

A class includes both data members as well as functions to manipulate that data.

C++ was developed by _____

Bejame Stroustrup

_____ operator uses the sign $\wedge$.

Exclusive OR

For console input and output we use _____

stdiib.h header file

Header files provide _____ so the program running on one operating system can run without an error on the other system.

Accessibility

The function calloc takes two arguments, first argument is to _____ and the second argument is the _____

Required space in terms of numbers, size of space

Constructor has _____



SUBSCRIBE

AR Lucky Bahi





The same name of an class

Which of the following code segment represents a left shift operator?





SUBSCRIBE

AR Lucky Bahi



```
cout<<1;
```

The object code of our program is combined with the _____

object code of the library functions

The malloc function takes _____ argument(s)

Two

The memory allocation functions return a chunk of memory with a pointer of type _____

Void

_____ is a special type of pointer we have to cast it before we use it.

Void

The function overloading requires _____

the argument list to be different

Bugs can occur due to _____

Uninitialized data

Which of the following code segment represents left shift shifts operate?

```
Result = number << 1;
```



SUBSCRIBE

AR Lucky Bahi





The name of the destructor is the same as that of a class proceeding with a _____





SUBSCRIBE

AR Lucky Bahi



~ sign

The Compiler generates _____ automatically.

Constructors

Constructor is itself a _____ of C++ and _____

Function, can be overloaded

Constructor is a special function, called whenever we _____

Instantiate an object of a class

The heap memory structure _____

Constantly changes in size

A pointer with value null is defined in the header files _____ and _____

stdlib.h, stddef.h

_____ for parameters is also done for inline functions.

automatic type checking

How many bits form a type.

8



SUBSCRIBE

AR Lucky Bahi





Manipulate, Additive and assignment operators are_____operators.

Binary



Special name which is substituted in code by its definition and as a result we get an expanded code is called

Macro

For converting a void type pointer into integer type, the correct syntax is;

`int * ptr`

1. We use _____ to open a file or stream for extraction
in
2. Null character is represented by _____ in C++.
3. An object of _____ class can be created for saving the current position of any opened file before reading from the file.

Streampos

pg215

4. _____ Returns true if c is a digit or a letter and false otherwise.

int isalnum(int c)

5. We use _____ to open a file or stream for insertion.
out
6. Base address is the memory address of _____ element of an array.

1st

7. _____ allow us to have a memory location and use it as int or char interchangeably

union

8. To read command-line arguments, the main() function itself must be given _____ arguments.



SUBSCRIBE

AR Lucky Bahi



2

9. Individual characters in a string stored in an array can be accessed directly using array _____.

subscript

10. To manipulate n-dimensional array _____ nested loops are required.

n-1

1. A character is stored in the memory in _____

string

2. What will be the size of following array?

```
int arr[29];
```

29

3. An object of _____ class can be created for saving the current position of any opened file before reading from the file.

Streampos

pg215

4. We use _____ to open a file or stream for extraction.

in

5. We use _____ to open a file or stream for insertion.

out

6. _____ are conventional names of the command line parameters of the 'main()' function.

'argc' and 'argv'

7. In _____, we have different data members and all of these have their own memory space.

structures

8. How we declare an array of integer data whose size is 20 with array name "count".

```
int count[20];
```

9. A _____ is an array of characters that can store number of character specified.



SUBSCRIBE

AR Lucky Bahi



String

File. seekg (-10L, ios:cur)

backward direction

A function is a block of statements that can be defined once and used _____ in the program.

One time

Two times

Three times

As many times as user wants

What will be the output of the following while loop? `int counter = 0 ; while(counter < 15) cout << counter << " "; counter++;`

1 2 3 4

1 2 3 4 5

Compile time error

Infinite loop

We can access a global variable _____

From the functions only

From the loops only

From the main() function only

From anywhere in the program

A repetition statement specifies that an action is to be continued while some _____ remains true.

Condition



Control
Assignment
Operator

Loops are _____ Structure.

Decision

Sequential

Repetition

None of the given options

_____ operator is used to pass the address of a variable in call by reference method.

%

+

@

&

How many times the following do-while loop will execute? `int k = 10; do { cout << "Statements" << endl; k -= 2; } while(k>0);`

4

5

6

7

What is the output of the following code if the 3rd case is true `switch (var) { case 'a': cout<<"apple"<<endl; case 'b': cout<<"banana"<<endl; case 'm': cout<<"mango"<<endl; default: cout<<"any fruit"<<endl; }`

mango

mango any fruit

Apple



none of the above

By default, the starting index of an array in C++ is _____.

2

-1

0

1

A variable declared within a code block becomes _____ variable for that block

Static

Integer

Local

Global



SUBSCRIBE

AR Lucky Bahi



