

Question 1

Which of the following data dictionary view is used to find the Free space of tablespaces?

Table_FREE_SPACE

DA_FREE_SPACE

TB_FREE_SPACE

DBA_FREE_SPACE

Question 2

Which of the following data dictionary view is used to find used Data Size of Tablespaces?

DBA_DATA_FILES

DBA_SEGMENTS

V\$Tablespaces

DBA_TEMP_FILES

Question 3

Which of the following data dictionary view is used to display name and data file size in MB?

DBA_FILES

V\$Tablespaces

DBA_DATA_FILES

DBA_SEGMENTS

Question 4

A/an _____ is a set of extents allocated for a specific database object, such as a table.

Data file

Block

Control file

Segment

Question 5

Logical minimum storage unit is called_____.

Logical block

Database block

Data block

Control block

Question 6

An/a _____ is a set of logically contiguous data blocks allocated for storing a specific type of information.

Extent

Block

Control file

Data file

Question 7

An/a _____ is a logical storage structure whose size and structure are not known to the operating system.

Control file

Data file

Oracle block

Block file

Question 8

If _____ is not set, then the default data block size is operating system-specific.

BLOCK-SIZE

DB_BLOCK_SIZE

DATA_BLOCK_SIZE

BLOCK_SIZE

Question 9

Oracle Database manages the logical storage space in the data files of a database known as _____.

Control file

Oracle pages

Data file

Block file

Question 10

The _____ storage parameter is essential to how the database manages free space.

PFREE

PCTFREE

CTFREE

PTFREE

Question 11

The database can reuse space within an/a _____ block.

Index

Data

File

Control

Question 12

PCTFREE is important for preventing _____ and avoiding wasted space.

Data anomaly

Data redundancy

Row migration

Data Inconsistency

Question 13

An extent is always contained in one _____.

Data file

Data segment

Data block

Data memory

Question 14

By default, the database allocates an initial _____ for a data segment when the segment is created.

Data file

Data block

Memory space

Extent

Question 15

In Oracle Database 11g Release 2, you can also drop the segment using the _____package.

DB_SPACE_ADMIN

DBA_SPACE_ADMIN

DBMS_SPACE_ADMIN

DBMS_ADMIN

Question 16

_____are database objects, such as tables and indexes, that consume storage space.

Extent

Table space

Data block

Segments

Question 17

Collection of segments is called _____.

Data block

Data file

Data extent

Tablespace

Question 18

Collection of extents, may be from multiple data files is called _____.

Segments

Data block

Table

Table space

Question 19

A/an _____ is a logical representation of one or more tables.

Extent

Tablespace

Segments

View

Question 20

A/an _____ is a user-created object that can be shared by multiple users to generate integers.

Sequence

Table

Segment

Extent

Question 21

A/an _____ derives its data from the tables on which it is based.

Tablespace

View

Extent

Segments

Question 22

Concatenated index is an alternative name of _____?

None of these

Alter index

Composite index

Rebuild index

Question 23

Which option is true about the following code?

```
CREATE INDEX employees_ix ON  
employees (last_name, job_id, salary);
```

Composite index

Rebuild index

None of these

Alter index

Question 24

Which of the following is not a technique of data integrity?

Enforcing business rules without using code of a database application

Using stored procedures to completely control access to data

Enforcing business rules with triggered stored database procedures

Enforcing business rules in the code of a database application

Question 25

A constraint specified as part of the definition of a column or attribute is called an _____ specification.

Out-of-line

Outline

Null

Inline

Question 26

Which of the following is not a advantage of data integrity constraints?

Declarative ease

Centralized rules

Flexibility when loading data

Decentralized rules

Question 27

A _____ constraint requires that a column of a table contains no null values.

Not Null

Unique Key

Secondary Key

Foreign Key

Question 28

A _____ constraint requires that every value in a column or set of columns must be unique.

Unique Key

Primary Key

Foreign Key

Not Null

Question 29

_____ constraints require a database value to obey a specified condition.

Unique Key

Primary Key

Check

Foreign Key

Question 30

A view that derives its data from the tables on which it is based is called

_____.

Base Table

Store Procedure

Schema

Object

Question 31

_____ is a logical representation of a table or combination of tables.

Procedures

Table

View

Constraints

Question 32

A table that resides in the application database is called _____.

Base Table

Schema

Store Procedure

Object

Question 33

_____ are the basic unit of data storage in an Oracle Database.

Tables

Constraints

Store procedures

Sequences

Question 34

_____ constraint forces the column to contain a value in every row.

Not Null

Primary key

Unique key

Check

Question 35

_____ tables enable your data to be broken down into smaller, more manageable pieces.

Partitioned

Clustered

Centralized

None of them

Question 36

Which option is true about the following code? `FORALL ... INSERT /*+ APPEND VALUES */ ...`

Insert null values

Delete null values

None of them

Bulk data load

Question 37

Which option is true about the following code? CREATE GLOBAL TEMPORARY TABLE ... ON COMMIT DELETE ROWS;

Updating temporary table

None of them

Creating temporary table

Deleting temporary table

Question 38

Identify the correct syntax to drop the employee table from the database.

Drop employee table;

Table drop employee;

Employee table drop;

Drop table employee;

Question 39

The drop table statement is used when you want to:

Delete the column from the table

Delete the table structure along with data

Delete the record from the table

Delete a row from the table

Question 40

Which system privileges are required when you want to drop a table from the database?

None of these

Drop any table

Drop

Drop Table

Question 41

_____ is a data dictionary table containing information about dropped objects.

None of these

Garbage

Trash

Recycle bin

Question 42

Which of the following conditions is not true when you create an index in your own schema?

The table or cluster to be indexed is in your own schema.

You have CREATE ANY INDEX system privilege.

When a column is updated, all indexes that contain the column must be updated

You have INDEX privilege on the table to be indexed.

Question 43

Which option is true about the following code? `CREATE INDEX emp_ename ON emp(ename);`

Create index on employee name

Alter index of employee name

Update index of employee name

Delete index of employee name

Question 44

Which option is true about the following code? `ALTER INDEX emp_ename STORAGE (NEXT 40);`

Create index on employee name

Update index of employee name

Alter index of employee name

Delete index of employee name

Question 45

Which option is true about the following code? `Select Table_name From Dict Where Table_name like '%TAB%';`

Displaying Sequence for Table

Displaying synonyms for Table

Displaying Views for Table

Selecting Views for Table

Question 46

Which option is true about the following code? `select sum(bytes)/1024/1024 SizeMB from dba_segments where segment_name ='EMP';`

find size of table in TB

find size of table in MB

find size of table in KB

find size of table in GB

Question 47

How many types of Views to manage Tables related information in oracle database?

5

 3

4

2

Question 48

ALTER ANY INDEX is a _____ privilege.

Domain

 **System**

Organization

Complex

Question 49

Instead of making an index unusable or dropping it, you may make it _____

Visible

Initialize

Rebuild

Invisible

Question 50

Which option is true about the following code? ALTER INDEX emp_name REBUILD ONLINE;

Rebuild index

Create index

Update index

Delete index

Question 51

Which statement is used to permanently delete the table from recycle bin?

Remove

Drop

Purge

Delete

Question 52

Which command is used to restore the table from recycle bin?

Rename

Flashback

Purge

Delete

Question 53

When the recycle bin is _____ dropped tables and their dependent objects are placed in the recycle bin.

Enable

Full

Disable

Empty

Question 54

_____ statement is used to remove an index from database.

Flashback

Delete

Remove

Drop

Question 55

Which of the following is not a reason of dropping index?

The index has become invalid and must be dropped before being rebuilt.

If a table is dropped, all associated indexes are dropped automatically.

The index is no longer required.

Applications do not use the index to query the data.

Question 56

Which of the following is correct syntax for dropping employee name index from employee table?

DROP INDEX emp_ename;

INDEX DROP emp_ename;

ALTER INDEX emp_ename;

DROP emp_ename INDEX;

Question 57

_____ data dictionary view describes indexes on all tables accessible to the user.

USER

ALL

DBA

Question 58

_____ data dictionary view describes indexes on all tables in the database.

DBA

ALL

USER

Question 59

_____ data dictionary view is restricted to indexes owned by the user.

USER

DBA

ALL

Question 60

Which of following statement is true about choosing appropriate table for cluster?

Records from the tables are frequently queried together or joined.

Estimating the number of cluster keys that can fit in a clustered data block.

SIZE does not limit the space that can be used by a given cluster key.

You can use the estimated size of an individual cluster to better manage the disk space.

Question 61

_____ is the column, or group of columns, that the clustered tables have in common.

Cluster Column

Cluster Table

Cluster Key

Cluster Index

Question 62

A _____ is a schema object that contains data from one or more tables.

Cluster

Data blocks

Table

Tablespace

Question 63

You can alter an existing cluster to change which of the following settings?

None of these

The average amount of space is not required to store all the rows for a cluster key value (SIZE)

Physical attributes (INITRANS and storage characteristics)

There is no default degree of parallelism

Question 64

When we want to drop a table from the database, which clause should we use with the drop cluster statement?

Remove Tables

Excluding Tables

Update Tables

Including Tables

Question 65

Which command is used to drop cluster?

Delete

Drop

Flashback

Remove

Question 66

_____ data dictionary view describes all clusters in the database.

USER

None of these

DBA

ALL

Question 67

_____ data dictionary view describes all clusters accessible to the user.

ALL

None of these

DBA

USER

Question 68

_____ data dictionary view is restricted to clusters owned by the user.

ALL

DBA

None of these

USER

Question 69

The database physically stores the rows of a table in a hash cluster and retrieves them according to the results of a _____.

Hash Function

User-define Function

Built-in Function

None of these

Question 70

Identify the condition where hashing is useful.

Most queries on the table retrieve rows over a range of cluster key values.

You cannot afford to preallocate the space that the hash cluster will eventually need.

The table is not static, but instead is continually growing.

Most queries are equality queries on the cluster key

Question 71

Storing a table in a hash cluster is an optional way to improve the _____ of data retrieval.

Output

Achievement

Performance

Behavior

Question 72

Identify the correct statement of altering the cluster of employee department.

Emp_dep ALTER CLUSTER;

ALTER emp_dep CLUSTER;

None of these

ALTER CLUSTER emp_dep;

Question 73

You create a hash cluster using a CREATE CLUSTER statement, but you have to specify a _____ clause while creating the cluster.

HASH

HASHKEYS

TABLESPACE

HASHFUNCTION

Question 74

You can drop a hash cluster using the _____ statement.

Delete Cluster

Remove Cluster

Drop Cluster

Alter Cluster

Question 75

_____ data dictionary view describes all clusters (including hash clusters) in the database.

None of these

DBA

USER

ALL

Question 76

_____ show information about schema objects that are accessible to you at different level of privilege.

Tablespaces

Hash Function

Procedures

Data Dictionary Views

Question 77

A view derives its data from the tables on which it is based is called _____.

Relational Table

Temporary Table

Base Table

Permanent Table

Question 78

How many types of views are there in oracle database?

5

2(Oracle Database k 2 view hai logical aur physical. data dictory k 3 views hain)

3

4

Question 79

A _____ is a logical representation of a table or combination of tables.

Procedures

Tablespace

View

Sequence

Question 80

Which of the following is not a rule name for updating a join view in oracle?

Delete

Remove

Update

Insert

Question 81

“Any INSERT, UPDATE, or DELETE operation on a join view can modify only one underlying base table at a time” is the description of _____.

Delete Rule

General Rule

Insert Rule

Update Rule

Question 82

How many rules are there in oracle for updating a join view?

3

5

2

 4

Question 83

Which column is used to get the next value of the sequence?

NEXT

 NEXTVAL

NXTVL

NEXTVALUE

Question 84

Which of the following option is not available while creating sequence?

Minvalue

End

Start

Maxvalue

Question 85

_____ are database objects from which multiple users can generate unique integers.

Data Dictionary

Sequences

Function

Synonyms

Question 86

Identify the correct statement about where CURRVAL and NEXTVAL cannot be used?

The SELECT list of a SELECT statement

The SET clause of an UPDATE statement

VALUES clause of INSERT statements

A SELECT statement with a GROUP BY or ORDER BY clause

Question 87

Identify the incorrect statement about where CURRVAL and NEXTVAL cannot be used?

The SET clause of an UPDATE statement

A subquery

The condition of a CHECK constraint

The WHERE clause of a SELECT statement

Question 88

To drop a sequence in another schema, you must have the _____ system privilege.

DROP ANY CLUSTER

DROP ANY SEQUENCE

DROP CLUSTER

DROP SEQUENCE

Question 89

Which DDL command is required to create public synonyms?

CREATE PUBLIC SYNONYM

CREATE SYNONYM

DROP PUBLIC SYNONYM

DROP SYNONYM

Question 90

How many types of synonyms are there in oracle database?

4

2

3

1

Question 91

A _____ is an alias for a schema object.

Procedure

Function

Synonym

Cluster

Question 92

Which of the following command is used to drop the private synonyms?

DELETE PRIVATE SYNONYM

DROP SYNONYM

DROP PRIVATE SYNONYM

DROP PUBLIC SYNONYM

Question 93

You cannot specify a schema for the synonym if you have specified _____ in command.

Protected

None of these

Public

Private

Question 94

Which of the following command is used to drop the public synonyms?

DELETE SYNONYM

DROP PUBLIC SYNONYM

DELETE PUBLIC SYNONYM

DROP SYNONYM

Question 95

_____ data dictionary view is restricted to views accessible to the current user.

USER

None of these

ALL

DBA

Question 96

_____ data dictionary view describes all views in the database.

ALL

USER

None of these

DBA

Question 97

_____ data dictionary view is restricted to views owned by the current user.

None of these

ALL

USER

DBA

Question 98

PL/SQL is executed on _____ without any network overhead.

Client Side

Back end

Front end

Server side

Question 99

PL/SQL is a _____ structured programming.

Encapsulated

Inherited

Embedded

None of these

Question 100

PL/SQL can execute a number of queries in _____ block using single command.

Three

Four

One

Two

Question 101

PL/SQL is more powerful than pure_____.

Database

SQL

Python

C#

Question 102

A _____ statement allows us to execute a statement or group of statements multiple times.

None of these

Loop

Selection

If else

Question 103

A cursor is a _____ to this context area.

Pointer

Integer

Function

Variable

Question 104

In basic structure of PL/SQL, execution section end with _____ keyword.

END

EXCEPTIONS

BEGIN

DECLARE

Question 105

In basic structure of PL/SQL, exception section starts with _____ keyword.

END

DECLARE

BEGIN

EXCEPTIONS

Question 106

In basic structure of PL/SQL, execution section starts with _____ keyword.

END

DECLARE

BEGIN

EXCEPTIONS

Question 107

Which of the following is correct output for the following PL/SQL program?

```
DECLARE
```

```
    msg varchar2(40) := 'I love Oracle Programing' ;
```

```
BEGIN
```

```
    dbms_output.put_line(msg);
```

```
END;
```

```
/
```

```
Msg
```

```
I love Oracle Programing
```

```
'I love Oracle Programing';
```

```
(msg)
```

Question 108

Which of the following is correct syntax to print the output in PL/SQL?

db_output.put_line(t.table_name);

dbms_output.put_line(t.table_name);

dbms_output.put_(t.table_name);

dbms_output_line(t.table_name);

Question 109

Which of the following is correct syntax for assigning value 10 to a variable X?

X==10

X:=10

X=10

X=:10

Question 110

Which of the following program compile and executes on SQL prompt?

DECLARE EXCEPTION END; /

DECLARE BEGIN EXCEPTION END; /

DECLARE BEGIN EXCEPTION END /

DECLARE BEGIN EXCEPTION END; .

Question 111

Which of the following program run without compiling and execution on SQL prompt?

DECLARE EXCEPTION END; /

DECLARE BEGIN EXCEPTION END; /

DECLARE BEGIN EXCEPTION

DECLARE BEGIN EXCEPTION END .

Question 112

We can also compile Program using_____.

SQL Notepad

SQL Instance

SQL Developer

SQL Prompt

Question 113

The PLS_INTEGER datatype is specific to PL/SQL. It represents signed _____ bits int.

34

30

32

8

Question 114

Which of the following data type does not belong to scalar Data Types Families?

Character

Boolean

Number

Composite

Question 115

TableName.Column%TYPE is a _____ data type.

Scalar

Composite

Simple

Complex

Question 116

Which of the following is not a way to write IF condition in PL/SQL?

IF – ELSE – END IF

IF – ELSE – END

IF – END IF

IF – ELSIF – ELSE – END IF

Question 117

If v_sal is equal to 3000, what will be the final output for the following PL/SQL code? ...IF v_sal > 2000 Then total_sal := v_sal + 5000;...

5000

7000

3000

8000

Question 118

Which of the following is correct structure of IF THEN ELSIF Condition?

IF..THEN..ELSIF..ELSE..END IF;

IF..THEN..ELSE..END;

IF..THEN..ELSIF..ELSE..END;

IF..statements; THEN..

Question 119

Which of the following is correct Syntax of For LOOP?

FOR index IN lower_bound .. upper_bound ..END LOOP;

FOR index IN lower_bound .. upper_bound LOOP .. LOOP;

FOR index lower_bound .. upper_bound LOOP..END LOOP;

FOR index IN lower_bound .. upper_bound LOOP..END LOOP;

Question 120

A _____ statement allows us to execute a statement or group of statements multiple times.

Condition

Array

Procedure

Loop

Question 121

Which of the following is not a syntax for while loop in PL/SQL?

LOOP – EXIT WHEN – END LOOP

WHILE END LOOP

FOR – LOOP –END LOOP

WHILE – LOOP – END LOOP

Question 122

PL/SQL treats all errors that occur in an anonymous block, procedure, or function as _____.

Exclusion

Exceptions

Mistakes

Fault

Question 123

The code that you write to handle exceptions is called an/a _____.

Exception Handler

Exception Administrator

Exception code

Exception expert

Question 124

A _____ can have an exception-handling section, which can have one or more exception handlers.

Control block

PL/SQL block

Index block

Exception block

Question 125

In PL/SQL procedure, _____ keyword is not used.

ADD

DECLARE

DELETE

END

Question 126

Which of the following is not a parameter for the PL/SQL procedure?

IN

OUT IN

IN OUT

OUT

Question 127

_____ is a block with a name in PL/SQL.

Index

Control file

Exception

Procedure

Question 128

Which of the following is only parameter for the PL/SQL Function?

IN

OUT

IN OUT

OUT IN

Question 129

In PL/SQL function, _____ keyword is not used.

DELETE

END

DECLARE

ADD

Question 130

_____ returns one value only.

PL/SQL Procedure

PL/SQL Block

PL/SQL Control block

PL/SQL Function

Question 131

_____ can be called after compilation in some other function, procedure, block or package by assigning it to variable.

Table

Procedure

Index

Function

Question 132

_____ can be called after compilation in some other function, procedure, block or package.

Function

Table

Procedure

Index

Question 133

What will be the final output for the following PL/SQL code? (Factorial of 6)

Factorial num 6 is 720

720

Factorial is 720

Factorial 6 is 720

Question 134

Which of the following keyword is used to modify an existing PL/SQL function?

CHANGE

REPLACE

MODIFY

ALTER

Question 135

In PL/SQL function, the _____ keyword is used instead of the IS keyword for creating a standalone function.

WERE

AS

WAS

ARE

Question 136

A package body can have an _____ part whose statements initialize variables or perform other one-time setups for the whole package.

Declaration

Declare

Begin

Initialization

Question 137

A/an _____ includes variables, constants, cursors, exceptions, procedures, functions, and subprograms.

Procedures

Domain

Package

Index

Question 138

The package specification declares the _____ objects that are accessible from outside the package.

Null

Private

Local

Public

Question 139

A/an _____ is a named PL/SQL block stored in the Oracle Database and executed automatically when a triggering event takes place.

Control block

Event

Trigger

Index block

Question 140

The _____ keyword specifies that you are creating a new trigger.

CREATE

CAUSE

GENERATE

INITIATE

Question 141

The act of executing a trigger is also known as _____.

Firing a trigger

Initiate a trigger

Finding a trigger

Generate a trigger

Question 142

Which of the following is correct statement to disable a trigger in PL/SQL?

TRIGGER DISABLE;

TRIGGER trigger_name DISABLE;

ALTER TRIGGER trigger_name DISABLE;

ALTER TRIGGER DISABLE;

Question 143

Which of the following is not an attribute of Explicit Cursor?

%FOUND

%NOTFOUND

%CLOSE

%ISOPEN

Question 144

An explicit cursor is an _____ statement declared explicitly in the declaration section of the current block or a package specification.

INSERT

REPLACE

REPLY

SELECT

Question 145

_____ is mainly used with tables which return more than one row.

Index

Table

Cursor

Column

Question 146

Which option is true about the following Code?

```
CURSOR c_emp IS
```

```
SELECT empno, ename, job
```

```
FROM emp
```

```
WHERE deptno=20;
```

Cursor Retrieval

Cursor Deletion

Cursor Declaration

Cursor Updation

Question 147

We may use cursor with_____.

Parameters

Transition Graphs

Behavior

Pointers

Question 148

Which option is true about the following Code?

```
DECLARE
```

```
CURSOR c_emp (p_job IN EMP.job%TYPE) IS
```

```
SELECT *
```

```
FROM EMP WHERE job =p_job;
```

```
BEGIN
```

```
FOR r_amp IN c_emP('CLERK')
```

```
LOOP
```

```
DBMS _OUTPUT.PUT_LINE(r_emp.ename||'--'||r_emp.job);
```

```
END LOOP;
```

```
END:
```

 Cursor with Parameters

Cursor with Behavior

Cursor with Transition Graphs

Cursor with Pointers

Question 149

The lowest address corresponds to the _____ element and the highest address to the _____ element.

last, First

First, last

First, Second

Last, Second Last

Question 150

We must specify the _____ and the type of elements stored in the varray.

Number of arguments

Datatype

Type of arguments

Maximum size

Question 151

The key in Associative Array can be either an integer or a_____.

Double

String

Float

Boolean

Question 152

Dynamic SQL is a programming methodology for generating and running SQL statements at _____.

Run time

Compile time

None of these

Run and compile time

Question 153

Which of the following statement is not true about Dynamic SQL?

It is useful when writing programs that must run database definition language (DDL) statements.

It is useful when the number or data types of its input and output variables are known.

It is useful when writing general-purpose and flexible programs like ad hoc query systems.

It is useful when you know at compilation time the full text of a SQL statement.

Question 154

_____ is a programming methodology for generating and running SQL statements at run time.

Dynamic SQL

Light SQL

Static and Dynamic SQL

Static SQL

Question 155

Every running Oracle database is associated with at least _____ Oracle database instance.

Two

Five

One

Three

Question 156

The system global area is shared by the Oracle processes, which include server processes and background processes, running on a _____ computer.

Single

Various

Different

Question 157

A Database is a set of physical files on disk created by the _____ statement.

CREATE DATABASE

INSERT DATABASE

GENERATE DATABASE

ADD DATABASE

Question 158

In Oracle Real Application Clusters (Oracle RAC) configuration, A _____ relationship exists between the database and instances.

many-to-one

one-to-many

one-to-one

many-to-many

Question 159

In a Single-instance configuration, A _____ relationship exists between the database and an instance.

many-to-many

one-to-many

one-to-one

many-to-one

Question 160

We can start a database instance and mount (associate the instance with) one database, but not mount _____ databases simultaneously with the same instance.

Three

Five

Four

Two

Question 161

An instance begins when it is created with the _____ command and ends when it is terminated.

STARTUP

START

CREATE

BEGIN

Question 162

The system identifier is used by default to locate the_____ .

File directory

Program file

Parameter file

None of these

Question 163

The instance can mount a database only _____, close it only once, and open it only once.

Once

Twice

Question 164

The data contained in the data files is accessible to _____.

Unauthorized Users

None of these

Authorized Users

Question 165

In a typical use case, which command can be used to start an instance and then mount and open the database, making it available for users.

START

STARTUP

BEGIN

Question 166

A database _____ provides user access to a database.

Row

Table

Instance

Question 167

Temporary tablespaces created with the _____.

CREATE TEMPORARY TABLESPACE

INSERT TEMPORARY TABLESPACE

NEW TEMPORARY TABLESPACE

Question 168

_____ users do not have control over the current status of an Oracle database.

Normal

Privilege

Special

Question 169

_____ mode prevents users from starting new transactions but waits for all current transactions to complete before shutting down.

Immediate Shutdown

Shutdown Transactional

Restart

Question 170

Which of the following command is used to shut down the database, making it unavailable for users while you perform maintenance or other administrative tasks?

mySQL*MuI SHUTDOWN

SQL*Plus SHUTDOWN

All of these

Question 171

Active transactions are terminated and uncommitted changes are rolled back in _____.

Shutdown

Start

Immediate Shutdown

Question 172

Which of the following is not the goal of Oracle Database when using checkpoints :

Establish data consistency

Ensure that all committed data is written to disk during a consistent shutdown

Increase the time required for recovery in case of an instance or media failure

Question 173

Checkpoint is a mechanism in which all the previous logs are removed from the system and are stored permanently in the _____.

Cache

Buffer

Storage disk

Question 174

The checkpoint position acts as a _____ to the redo stream and is stored in the control file and in each data file header.

Heap

Pointer

Stack

Question 175

Which of the following is not a checkpoint situation when it occurs?

Offline redo log switch

Consistent database shutdown

ALTER DATABASE BEGIN BACKUP statement

Question 176

Shortest form of the Checkpoint Process is _____.

CKPT

CHPS

CKPS

Question 177

An incremental checkpoint is a type of _____ checkpoint.

Online

Subject

Offline

Thread

Question 178

At each switch of the redo log files _____ command will occur.

Update

Checkpoint

Alter

Question 179

Checkpoint command will run through _____.

DBA

User

sys user

User name

Question 180

Which option is true about the following statement? Alter system checkpoint;

Checkpoint Updating Command

Checkpoint Altering Command

Checkpoint Occurring Command

Question 181

When an instance of an ORACLE database fails then the changes made by transaction is written _____.

In redo log and data files

Only in redo log file

Only in control file

Question 182

Instance recovery ensures that the database is in a _____ state after an instance failure.

Consistent

Inconsistent

Question 183

Instance recovery occurs _____ when an administrator attempts to open a database that was previously shut down inconsistently.

Manually

Mechanically

Automatically

Question 184

A redo thread is marked open in the control file when a database instance _____ in read/write mode.

Closed

None of these

Opens

Question 185

A redo thread is marked _____ when the instance is shut down consistently.

Opens

Closed

None of these

Question 186

Whether instance recovery is required depends on the state of the _____ threads.

redo threads

undo

Question 187

ADR stand for _____.

None of these

Accelerated Data Recovery

Accelerated Recovery

Accelerated Database Recovery

Question 188

Which of the following does not represent a database restore process?

Copies all the data, log, and index pages from the backup media of a database to the database files.

Applies the transaction log in what is known as the recovery process.

Creates the database and transaction log files if they do not already exist.

Copies the data from the backup devices to the database file(s).

Question 189

A _____ in SQL Server is the process of restoring data from one or more backups and then recovering the database.

Undo Phase

Restore Scenario

Redo Phase

None of these

Question 190

Oracle Database can roll back _____ transactions simultaneously as needed.

Fewer

Multiple

None of these

Question 191

An alternate name of cache recovery is _____.

Rollback

None of these

Rolling forward

Question 192

The first phase of instance recovery is called _____.

Cache recovery

None of these

Redo file

Question 193

Oracle Database provides many initialization parameters to _____ its operation in diverse environments.

Grow

Optimize

Multiple

Question 194

Purpose of variable parameters is to _____ database performance.

Improve

Grow

None of these

Question 195

Which of the following is not a basic variable parameter characteristic?

Locations of the control files

Redo tablespace

Database name

Question 196

A server parameter file is a repository for initialization parameters that is managed by _____.

DBA

System user

Oracle Database

Database user

Question 197

_____ is a text file that contains a list of initialization parameters.

Server parameter file

Text initialization parameter file

Question 198

MEMORY_TARGET is an example of _____.

System-level parameters

Session level parameters

Question 199

Which of the following is the ADR root directory?

ADR dump

ADR base

None of these

Question 200

ADR is the abbreviation of?

Alternative Diagnostic Repository

Automatic Diagnostic Repository

Alternative Dispute Resolution

Question 201

Which of the following is not a goal of the advanced fault diagnosability infrastructure?

Increasing problem diagnostic and resolution time

Detecting problems proactively

Simplifying customer interaction with Oracle Support

Question 202

Which of the following is not a content of alert log file?

Non default initialization parameter used at startup

internal errors

Default initialization parameter used at startup

Question 203

___ is an XML file containing a chronological log of database messages and errors.

Alert log

Undo log

None of these

Question 204

_____ file constantly be monitored to detect unexpected messages and corruptions in database.

Redo log

Undo log

Alert log

Question 205

_____ is a special type of trace file.

Dump

None of these

Alert

Incident

Question 206

_____ files can be useful for tuning applications or instances.

Trace files

Log files

Redo log files

Question 207

A _____ is an administrative file that contain diagnostic data used to investigate problems.

Trace file

None of these

Log file

Question 208

Schema is a collection of _____.

Objects

Synonyms

Procedures

Question 209

The names of the users who are allowed to access a database are defined by the _____ .

User

Database administrator

None of these

Question 210

Which of the following option is not related to database security types and its issues?

Loss of integrity

Needs of Enterprises

Legal & Ethical Issues

Question 211

Which of the following attribute is used to specifies a temporary tablespace segment for the user?

default tablespace

Temporary tablespace

profile

Question 212

Which of the following attribute tells Oracle if the user can access his account or not?

default tablespace

unlock

account lock/unlock

Question 213

Which of the following SQL statement is used to display all the tablespace quotas from oracle database?

Select * from DBA_TS_QUOTAS;

Select * from DBA_QUOTAS;

Select * from TS_QUOTAS;

Question 214

Which of the following SQL statement is used to display all the profile from oracle database?

Select * from DBA_PROFILES ORDER BY PROFILE;

Select * DBA_PROFILES from ORDER BY PROFILE;

Select * from PROFILES;

Question 215

Which privileges is used to run a particular type of SQL statement, or the right to access an object that belongs to another user?

None of these

System Privileges

Object Privileges

User Privileges

Question 216

In Oracle, which string search is used to display the possible data dictionary views?

PRIV

DICT

Question 217

Which of the following command is used to give the privileges to users?

Grant

Delete

Revoke

Question 218

_____ privileges allow users to perform specific database operations.

None of these

Object

System

Question 219

_____ is a system defined privilege that control access to a specific object.

System Privilege

Object Privilege

User Privilege

Question 220

_____ are named groups of related privileges or rights.

System Privileges

Roles

User Privileges

Question 221

_____ extends the privileges of a user beyond those granted by the CONNECT role.

DBA

RESOURCE

CONNECT

Question 222

Which of the following options does not fall within the category of role benefits?

Dynamic privilege management

Easier privilege management

Resource Privileges

Question 223

Roles can be granted to _____ user.

Any

Special

Specific

Question 224

A role can be required a _____ to be enabled.

Username or password

Password

Question 225

_____ clause Indicates that verification is required when enabling the role.

IDENTIFIED

NOT IDENTIFIED

BY password

Question 226

_____ pre-define role is used to export the database in oracle.

IMP_FULL_DATABASE

EXP_FULL_DATABASE

Question 227

Which SQL statement is used to create role in oracle?

CREATE ROLE

DELETE ROLE

MODIFY ROLE

UPDATE ROLE

Question 228

_____ clause Indicates that a user must be authorized by an external service (such as the operating system or a third-party service) before enabling the role.

IDENTIFIED

NOT IDENTIFIED

EXTERNALLY

Question 229

Identify the correct syntax for altering role to the HR manager.

ALTER ROLE hr_manager NOT IDENTIFIED;

ALTER ROLE hr_manager NOT IDENTIFIED;

ALTER hr_manager ROLE NOT IDENTIFIED;

Question 230

_____ command is used to limit the default roles for a user.

ALTER USER

ALTER ROLE

DEFAULT ROLE

Question 231

_____ role modifies the authentication method.

ALTER

EXCEPT

CREATE

DEFAULT

Question 232

_____ clause Indicates that a user must be authorized to use the role by the enterprise directory service before the role is enabled with the SET ROLE statement, or at login.

NOT IDENTIFIED

GLOBALLY

EXTERNALLY

Question 233

_____ command enables and disables roles.

SET ROLE

MODIFY ROLE

UPDATE ROLE

CREATE ROLE

Question 234

_____ clause is used to create an application role.

Globally

USING

Delete

Question 235

_____ command is used to indicate which roles will be enabled for a user at login.

ALTER USER - DEFAULT ROLE

ALL OF THESE

MODIFY USER-DEFAULT ROLE

Question 236

Application roles can be enabled only by _____ PL/SQL packages.

Authorized

Unauthorized

Question 237

___ provide an additional level of security when enabling a role.

Passwords

PIN code

Username

Question 238

Which of the following SQL statement is used to revoke a role from a user?

Create

Revoke

All of these

Question 239

Which SQL statement is used to remove a role from the database?

DROP ROLE role;

REMOVE ROLE role;

ALTER ROLE role;

Question 240

Which of the following is correct SQL statement to obtain Information about roles?

Select table_name, comments from DICT where table_name like 'ROLE';

Select table_name, comments from DICT where table_name like '%ROLE%';

Select table_name from DICT where table_name like '%ROLE%';

Question 241

Which of the following is correct dictionary view to lists all roles that exist in the database, including secure application roles?

SESSION_PRIVS

DBA_ROLES

ROLE_TAB_PRIVS

Question 242

Which of the following is correct dictionary view to list all roles that are enabled for the current user?

DBA_ROLE_PRIVS

SESSION_ROLES

ROLE_TAB_PRIVS

Question 243

_____ is the process of transferring data from one storage system or computing environment to another.

Data Exchange

Data Transferring

Data migration

Question 244

Non integrated/distributed data can be integrated through_____.

Data Transferring

Data Exchange

Data migration

Question 245

A database's schema is like a _____ for how it is organized, controlling its logical architecture and structure.

Database

Blueprint

Question 246

_____ can be used to copy data from one table to another table within the same database.

Direct Load insert

indirect Load insert

SQL*Loader

Question 247

_____ loads data from external files into tables of an Oracle database.

Direct Loader insert

SQL*Loader

Indirect Load insert

Question 248

_____ speeds up the insert operation, bypassing the database buffer cache and writing data directly into the data files.

Direct Load insert

SQL*Loader

Indirect Load insert

Question 249

Each parallel execution server allocates a new temporary segment and inserts data into the _____ segment.

New

Private

Temporary

Question 250

The ALTER SESSION ENABLE PARALLEL DML command must be executed at the _____ of a transaction.

End

Half

Beginning

Question 251

The _____ is the level at which blocks have never been formatted to receive data.

Low-water mark

High-water mark

Question 252

_____ is a file that can be created, if necessary, to store all records that did not satisfy the selection criteria.

Discard file

Parameter file

Bad file

Question 253

_____ is used by the utility to write the records that are rejected during the load.

Discard file

Parameter file

Bad file

Log file

Question 254

_____ is created by SQL*Loader and contains a record of the load.

Log file

Bad file

Discard file

Question 255

The SQL*Loader control file is a text file that contains _____ instructions.

DCL

DDL

DLM

Question 256

The _____ keyword specifies the name of a data file containing data that you want to load.

ADD

INFILE

SELECT

Question 257

The _____ keyword is one of the options you can use when loading data into a table that is not empty.

APPEND

INSERT

ADD

Question 258

Which of the following is not a data file format?

Fixed-record format

String-record format

Variable-record format

Stream-record format

Question 259

A file is in _____ when records are not specified by size.

String-record format

Stream-record format

Variable-record format

Fixed-record format

Question 260

A file is in variable format when the length of each record in a _____ field is included at the beginning of each record in the data file.

Float

Character

Long

Int

Question 261

_____ can combine fixed number of physical records to form each logical record.

Indirect Load insert

Direct Loader insert

Direct Load insert

SQL*Loader

Question 262

_____ must be used if the number of physical records to be continued varies.

ADD

INSERT

CONTINUEIF

SELECT

Question 263

_____ is used when SQL*Loader should always add the same number of physical records to form one logical record.

CONCATENATE

SELECT

ADD

INSERT

Question 264

_____ generates redo entries just as any DML statement.

Indirect path load

Conventional path loading

Direct path load

Undirect path load

Question 265

Multiple SQL*Loader sessions improve the performance of a _____.

Indirect path load

Conventional path loading

Undirect path load

Direct path load

Question 266

Conventional path loads use SQL processing and database _____ for saving data.

INSERT

COMMITTS

ADD

CONCATENATE

Question 267

If row or record is rejected, SQL*Loader puts it in the _____.

Bad file

Parameter file

Discard file

Log file

Question 268

_____ file can only be used if it is enabled.

Bad file

Log file

Discard file

Parameter file

Question 269

Which of the following is not a content of log file?

Data File Information

Local Information

Header Information

Table Information

Question 270

Which of the following is correct SQL statement to select all the fields from a table?

SELECT * FROM table_name

SELECT * table_name;

SELECT * FROM table_name;

SELECT *;

Question 271

In oracle, Files can be _____ delaminated.

Hyphen

Star

Comma

Full stop

Question 272

In oracle, files can be in _____ format.

DOC

XML

CSS

HTML

Question 273

Data can be inserted from _____ into Oracle schema scott.

MS Access

MS Word

Question 274

Spool file contains _____ rows.

Dot-taged

XML-taged

Question 275

_____ are the foundation of any sound backup and recovery strategy.

Redo backups

Logfile backups

Logical backups

Physical backups

Question 276

Logical backups contain logical data (for example, tables or stored procedures) exported from a database with an Oracle export utility and stored in a

_____.

String file

Text file

Logical backups

Byte file

Question 277

_____ are a useful supplement to physical backups.

Backup logs

Logical backups

Redo logs

Physical files

Question 278

Any database file can be vulnerable to a _____.

Media failure

Logfile failure

Logical Failure

User Error

Question 279

A _____ is the failure of a read or write of a disk file required to run the database, due to a physical problem with the disk such as a head crash.

Media failure

Logfile failure

User Error

Logical Failure

Question 280

_____ occur when, either due to an error in application logic or a manual mis-step, data in your database is changed or deleted incorrectly.

Logfile failure

Media failure

Logical Failure

User Error

Question 281

Logical export backup generates necessary Structured Query Language (SQL) statements to obtain all table data that is written to a _____.

Binary file

Byte file

Text file

String file

Question 282

_____ logical export backups are recommended in case physical backups fail or the database machine becomes unavailable.

Constant

Periodic

Irregular

Repeating

Question 283

A logical export backup does not contain database instance-related information, such as the _____ so you can restore the same data on another database machine.

Data file

Redo file

Backup file

Physical disk location

Question 284

You can only recover the database up to the point when the last backup was made unless the database is running in _____ mode.

UNDOLOG

BACKUPLOG

REDOLOG

ARCHIVELOG

Question 285

If you make a cold backup in ARCHIVELOG mode, then do not backup

_____.

Transaction log

Log files

Redo log files

Back up log

Question 286

Offline or cold backups are performed when the database is completely

_____.

Shutdown

Sleep

Start

Restart

Question 287

An online backup or hot backup is also referred to as _____ backup.

ARCHIVE LOG

Redo backup

Cold backup

NON-ARCHIVE LOG

Question 288

An online backup can only be done when the database is running in _____ mode and the database is open.

ARCHIVELOG

NON ARCHIVELOG

SUB ARCHIVELOG

FULL ARCHIVELOG

Question 289

A _____ backup is taken when the database needs to run all the time.

Offline

Active

Hot

Cold

Question 290

A partial database backup includes a subset of the database: individual _____.

Tablespaces or data files

Transaction log and back up log

Redo log and log file

Log file or data files

Question 291

Tablespace backups, whether consistent or inconsistent, are valid only if the database is operating in _____ mode.

FULL ARCHIVELOG

NON ARCHIVELOG

SUB ARCHIVELOG

ARCHIVELOG

Question 292

During _____, before the oracle database is shutdown, all user sessions will be terminated immediately and uncommitted transactions will not be rolled back.

Shutdown abort

Terminate

Exit

Abort

Question 293

_____ recovery applies all redo changes contained in the archived and online logs to a backup.

Complete

Partial

Incomplete

Semi-full

Question 294

The target SCN can be specified using a date and time, in which case the operation is sometimes called _____.

Time-based recovery

Date-based recovery

Target-based recovery

SCN-based recovery

Question 295

_____ recovery, also called database point-in-time recovery, results in a noncurrent version of the database.

Noncurrent

Complete

Concurrent

Incomplete

Question 296

An/a _____ is an Oracle binary-format dump file that is typically located on disk or tape.

Redo file

Log file

Import file

Export file

Question 297

_____ can display the contents of an export file without actually performing an import.

Import Perform parameter

Import Demonstrate parameter

Import SHOW parameter

Import Display parameter

Question 298

Export _____ can only be read by the Oracle Import utility.

Dump files

Redo file

Log file

Import file

Question 299

When tables are manually created before data is imported, the _____ statement in the export dump file will fail because the table already exists.

CREATE TABLE

INSERT TABLE

MODIFY TABLE

IMPORT TABLE

Question 300

Import the objects from the transport tables to the target portal repository using _____.

Import Transport portlet Set

Import Set portlet Transport

Import Set portlet

Import Transport Set portlet

Question 301

Transport sets contain the _____ that you want to export to your target portal environment.

Redo objects

Log objects

Data objects

Portal objects

Question 302

Which of the following is not a component of Data Pump?

DBMS_DATAPUMP PL/SQL package

Impdp (Data Pump import utility)

Expdp (Data Pump export utility)

DBMS_DATA

Question 303

Which of the following is not a mode of Data Pump?

Entire database

File level

Schema level

Tablespace level

Question 304

_____ are backups in which the export utility (for example Exp) uses SQL to read database data and then export it into a binary file at the operating system level.

Logical backups

Cold backups

Physical backups

Hot backups

Question 305

A DBMS is _____ if at most one user can use the system at a time.

Single-user

Complex-user

Simple-user

Mutli-user

Question 306

A DBMS is _____ if many users can use the system concurrently.

Single-user

Simple-user

Complex-user

Mutli-user

Question 307

A/an _____ is a logical, atomic unit of work (block) that contains one or more SQL statements.

 **Transaction**

Redo log

Log file

Table

Question 308

A/an _____ is a logical, atomic unit of work (block) that contains one or more SQL statements.

SQL

 **Transaction**

Question 309

Transactions are _____ meaning that the operating system quickly switches CPU services among tasks.

Interlinked

Interleaved

Intermediate

Interconnected

Question 310

When a single system allows to execute more than one transaction at the same time, this process is called _____.

Concurrent execution

Immediate execution

Simultaneous execution

Multiple executions

Question 311

_____ problem is occurred when concurrent transactions are run in an uncontrolled manner?

Temporary

Concurrency

Unrepeatable

Lost Update

Question 312

_____ problem occurs when two transactions in database access the same data item and have their operations in an interleaved manner.

Temporary

Unrepeatable

Lost Update

Concurrency

Question 313

_____ problem arises when one transaction T1 modifies a database data item and then fails for some reason, but the updates are accessible by another transaction.

Dirty Write

Dirty read

Nonrepeatable read

Lost update

Question 314

In a dirty read problem, _____.

one transaction commits another transaction

one transaction reads both committed and uncommitted value of another transaction

one transaction reads an uncommitted value of another transaction

one transaction reads the committed value of another transaction

Question 315

If a transaction T1 reads the value of a data item twice and the data item is updated by another transaction T2 in between the two read operations, is referred to as a _____.

Dirty Write Problem

Lost update Problem

Nonrepeatable read Problem

Incorrect Summary Problem

Question 316

_____ is also known as an inconsistent retrieval problem.

Lost update

Incorrect Summary

Dirty Write

Nonrepeatable read

Question 317

When two or more users are issuing invoices, there is a chance of _____.

Data failure

Data lost

Data consistency

Data inconsistency

Question 318

Given figure states the example of _____ problem?

Transaction Issues

Data lost

Question 319

Which of the following is not a system failure problem?

System crash

Physical failures

Logical error

Disk failure

Question 320

_____ means that data used during the execution of a transaction cannot be used by a second transaction until the first one is completed.

Time stamping

Seperation

Atomicity

Isolation

Question 321

_____ problem occurs when system may crash before data is written back to disk.

Atomicity

Serialization

Question 322

Which of the following is not the use of log files?

All permanent changes to data are recorded

Need to either redo or undo everything that happened since last checkpoint

All permanent changes to data are not recorded

After crash, search log backwards until find last checkpoint

Question 323

_____ keeps track of all transaction operations that affect the values of database items.

Log

System

User

DBA

Question 324

Log is kept on _____.

None of these

Floppy

Disk

CD

Question 325

_____ transactions can be executed concurrently by interleaving their operations.

Fewer

Multiple

Some

Large

Question 326

Ordering of execution of operations from various transactions $T_1, T_2, \dots, T_n$ is called a _____.

Transaction

Schedule

Throughput

Output

Question 327

Which of the following is not a conflict condition for two operations?

at least one is a write item() operation

they access the same item AND

they belong to same transactions AND

they belong to different transactions AND

Question 328

_____ operations can creates inconsistency.

Conflict

None of these

Clash

Dispute

Question 329

Two schedules are called _____ if they produce the same final state of the database.

Result equivalent

None of these

Conflict equivalent

Conflict serializable

Question 330

A schedule S of n transactions is _____ if it is equivalent to some serial schedule of the same n transactions.

Serializable

Conflict

Non serial

Serial

Question 331

Two schedules are called _____ if they produce the same final state of the database.

Conflict serializable

Conflict serializable

None of these

Conflict equivalent

Question 332

A schedule S of n transactions is _____ if it is equivalent to some serial schedule of the same n transactions.

Conflict

Conflict serializable

Serial

Non serial

Question 333

Given below diagram states the example of _____?

Transaction

Conflict equivalent

Serial schedule

Conflict serializable

Question 334

To avoid the concurrent update problem when two or more users try to update/delete the same table in the database _____ technique will be used?

Database lock

Deadlock

Deadlock prevention

All of these

Question 335

In a database _____ is a situation in which two or more transactions are waiting for one another to give up locks.

Schedule

Transaction

Database lock

Deadlock

Question 336

When two sessions or users of database try to update or delete the same data in a table, then there will be a _____ problem.

Concurrent delete

None of these

Concurrent update

Concurrent insert

Question 337

_____ are used to create objects (structures) such as tables, sequences, views and PL/SQL programs.

Functions

Scripts

Statements

Procedures

Question 338

Given below diagram states the example of _____?

Alter Table with Storage

Alter Table

Alter Table with Move on Storage

Drop Table with Move on Storage

Question 339

Structure of schema objects can be populated using exported _____ file.

XML

DDL

DML

DMP

Question 340

Which SQL statement from the following is used to create a new tablespace?

CREATE UNDO TABLESPACE

CREATE REDO TABLESPACE

None of these

CREATE TABLESPACE

Question 341

Given below diagram states the example of _____?

Alter table for MCare_indx

Tablespace for Indexes

Create table for MCare_indx

Drop table for MCare_indx

Question 342

DML stand for?

Data Manipulated Language

Data Definition Language

Data Manipulation Language

None of these

Question 343

_____ statements are used to create database, schema, constraints, users, tables etc.

DDL

DMP

DML

XML

Question 344

Identify the correct statement about to creates the role for User1.

Create Role User1;

Create User1 Role;

Question 345

Identify the correct statement to drop the synonym for Employee.

Drop Employee Synonym;

Drop Synonym Employee;

Question 346

Identify the correct statement about to creates the synonym for User2.

Create User2 Synonym;

Create Synonym User2;