_____ has a "documentElement" property that is called root node.

Select the correct option

◉	XML document
○	XML
○	XML element
○	XML tag

What is correct statement to return all <title> elements using getElementsByTagName() method in XML document?

Select the correct option

○	xmlDoc.getElementsByTagName(<title>);
○	x.getElementsByTagName("title");
●	xmlDoc.getElementsByTagName("title");
○	x.getElementsByTagName(<title>);

If y = x.firstChild; represents first child node under element then while traversing nodes_____ is used to go to next same element.

Select the correct option

Reload

○	y = y.nextChild;
○	y = y++;
○	y = y.nextElement;
●	y = y.nextSibling;

Activa

Question # 1 of 2

To modify the text of XML file at runtime which property can be used?

Select the correct option

○	childNode
○	attributeValue
●	nodeValue
○	parentNode

The nodeValue property can be used to change the value of ____ node.

Select the correct option

◉	Text
○	Element
○	Parent
○	Attribute

"nodeValue" property specifies the _____ of a node.

Select the correct option

○	name
●	attribute
○	id
○	value

nodeValue is _____ for an element node.

Select the correct option

◉	0
○	2
○	1
○	undefined

What would be the length of child nodes of book element in the given code:

<book category = "java">
<title lang="eng"> Core Java Volume I – Fundamentals</title>
<author>Cay S. Horstmann </author>

Select the correct option

◉	4
○	2
○	1
○	3

Extracting the value of each element in XML document is called _____ the node tree.

Select the correct option

◉	traversing
○	sorting
○	conditioning
○	indexing

_____ through the node tree is called Traversing.

Select the correct option

○	indexing
○	sorting
◉	looping
○	conditioning

Given code loops through all child nodes of <book>, and displays their names and values. Which for loop synatx is correct fo traversing. x = xmlDoc.documentElement.childNodes;

```
for (_____) {
txt += x[i].nodeName + ": " + x[i].childNodes[0].nodeValue + "<br>";
}
```

Select the correct option

Reload Mat

○	i = 0; i < x.length ;i++
○	i = 1; i < x.length() ;i++
○	i = 0; i < x.length ;i+
○	i = 0; i < x.length() ;i++ ✓ Not Confirm

Activat
Go to Set

_____ character is illegal in XML element.

Select the correct option

- ( ) !
- ( ) [
- (•) <
- ( ) *

When an XML element is parsed, the_____ between the XML tags is also parsed.

Select the correct option

○	value
◉	text
○	element
○	attribute

_____ is interpreted by parser as start of a new element. So it will generate an error.

Select the correct option

- ○ !
- ○ <
- ○ >
- ○ &

CDATA is such type of data that should _____ by XML parser.

Select the correct option

○	commented
◉	not be parsed
○	parsed
○	skipped

XML elements can contain other elements and parser will _____ it into _____.

Select the correct option

○	parse, sub categories
○	combine, one element
○	break, sub-elements ✓
○	convert, comment

DOM has reduced complexity of dealing with multiple type of nodes by which method?

Select the correct option

○	removeChild()
○	removeNode()
○	removeElement()
○	removeAttribute()

Question # 2 of 5

If the sibling node is not an element node, it moves to the _____nodes until an element node is found.

Select the correct option

○	Last
○	First
◉	Next
○	Previous

The removeChild() method can also be used to remove the ____node.

Select the correct option

○	Text
○	Element
●	Parent
○	Attribute

To avoid navigation to empty text nodes, we use a function which checks the_____.

Select the correct option

●	Empty spaces
○	New line
○	Node type
○	Node elements

Function get_nextSibling(n) doesn't allow to get the property of _____.

Select the correct option

○	y.nodeType
○	n.firstChild
◉	y.nextSibling
○	node.nextSibling

If we want to get the child node of the first book _____ syntax is used.

Select the correct option

○	x = xmlDoc.getElementsByTagTitle("book")[1];
○	x = xmlDoc.getElementsByTagName("book")[1];
○	x = xmlDoc.getElementsByTagTitle("book")[0];
●	x = xmlDoc.getElementsByTagName("book")[0];

There is/are _____ parent node/nodes in a XML Doc.

Select the correct option

◉	1
○	2
○	3
○	0

_____ element is also called parentNode.

Select the correct option

○	Attribute
○	Name
◉	Root
○	Document

Accessing nodes in the node tree via the _____ between nodes is often called navigating nodes.

Select the correct option

○	similarity
○	differences
○	relationship ✓
○	alphabetical order

Node relationships are defined as _____ to the nodes in XML DOM.

Select the correct option

○	functions
○	attributes
●	properties
○	text

Which of the given browser will not consider empty white-spaces or new line as a text node?

Select the correct option

○	Mozilla Firefox
○	Google Chrome
●	Internet Explorer
○	Microsoft Edge

Function get_nextSibling(n) doesn't allow to get the property of _____.

Select the correct option

○	node.nextSibling
○	y.nodeType
◉	y.nextSibling
○	n.firstChild

Click to Save

To avoid navigation to empty text nodes, we use a function which checks the_____.

Select the correct option

- ○ Node elements
- ○ Empty spaces
- ◉ Node type
- ○ New line

The text value of an element node is stored in a _____.

Select the correct option

○	Parent Node
○	Element Node
○	Sibling
◉	Child Node

The nodeValue property is used to get the text value of a _____.

Select the correct option

○	Element
○	Attribute
○	Tag
●	Node

The childNodes property returns a list of an/a _____ child nodes.

Select the correct option

○	Value
◉	Element's
○	Siblings
○	Attributes

The _____ property returns the text value of a text node.

Select the correct option

◉	nodeType
○	nodeValue
○	childNodes
○	getElement

In DOM everything is _____.

Select the correct option

○	Element
○	Tag
●	Node
○	Tree

_____ is a named node map, that is similar to a node list.

Select the correct option

○	DOM Child List
○	DOM Element List
○	DOM Root List
◉	DOM Attribute List

_____ has a "documentElement" property that is called root node.

Select the correct option

- ○ XML tag
- ○ XML
- ◉ XML document
- ○ XML element

An element node has _____ property, that returns a list of attribute nodes.

Select the correct option

◉	attributes
○	value
○	text
○	element

The getAttributeNode() method returns an attribute _____.

Select the correct option

◉	Elements
○	Node
○	List
○	Value

Which type of nodes have text values?

Select the correct option

○	Siblings
◉	Attribute nodes
○	Child Nodes
○	Element Nodes

The getAttribute() method or the nodeValue property is used to get the value of an/a_____?

Select the correct option

○	Tag
○	Attribute
◉	Element
○	Node

The _____ for an element node is undefined.

Select the correct option

○	nodeId
○	nodeAttribute
●	nodeText
○	nodeValue

Given code is used to get the <title> element of _____ child node.

xmlDoc.getElementsByTagName("title")[0].childNodes[0].nodeValue = "new content"

Select the correct option

◉	First
○	Zero
○	Null
○	Last

The setAttribute() method is used to change an attribute_____.

Select the correct option

○	List
●	Value
○	Name
○	Property

The child node storing the text value of an element node is called?

Select the correct option

○	Attribute Node
◉	Child Node
○	Text Node
○	Element Node

If you want to change the value of an attribute, you have to change its_____.

Select the correct option

○	Node
○	property
◉	Text value
○	Elements

If you give the name of attribute which doesn't exist then _____.

Select the correct option

○	New attribute will not be created
○	Existing attribute is changed
○	Error is generated
○	New attribute is created

Which of the following node don't have text values?

Select the correct option

○	Child Node
○	Parent Node
○	Attribute Node
○	Element Node

The setAttribute () method changes the value of an(a)____.

Select the correct option

○	Tag
○	Element
○	Node ✓
○	Attribute

Which type of nodes have text values?

Select the correct option

●	Element Nodes
○	Siblings
○	Child Nodes
○	Attribute nodes

The nodeValue property can be used to change the value of a(an) ____?


Select the correct option

○	Element Node
○	Node
○	Child Node
○	Attribute Node

If you give the name of attribute which doesn't exist then _____.

Select the correct option

○	Existing attribute is changed
○	New attribute will not be created
○	New attribute is created
○	Error is generated



The getAttribute() method or the nodeValue property is used to get the value of an/a_____?

Select the correct option

○	Tag
○	Element
○	Node
○	Attribute

When you change the value property using nodeValue, it changes the value of the ____?

Select the correct option

◉	Attribute
○	Element
○	Text
○	Node

nodeValue property is the value of an(a) _____ node.

Select the correct option

○	Element
○	Text
○	Sibling
◉	Attribute

By ____ property of any attribute you can read and write the value.

Select the correct option

○	attributeValue
○	childNodes
○	parentNode
◉	nodeValue

nodeType is a _____ property.

Select the correct option

○	read only
○	write-only
◉	read and write
○	onlytext

If nodeType is 1 then node type is _____.

Select the correct option

◉	attribute
○	text
○	comment
○	element

If nodeType is 2 then node type is _____.

Select the correct option

○	text
◉	element
○	attribute
○	comment

If nodeType is 3 then node type is _____.

Select the correct option

◉	text
○	element
○	attribute
○	comment

If nodeType is 8 then node type is _____.

Select the correct option

○	comment
○	element
○	text
●	attribute

Which method removes a specified node?

Select the correct option

- (●) removeChild()
- ( ) removeNode()
- ( ) removeAttribute()
- ( ) removeElement()

When you remove a node, all its _____ nodes are also removed.

Select the correct option

○	Element
○	Text
○	Sibling
◉	Child

Which method removes a specified attribute?

Select the correct option

◉	removeAttribute()
○	removeChild()
○	removeNode()
○	removeElement()

To remove the self-node using removeChild() method we will move___ towards parent node.

Select the correct option

○	Downward
○	Backward
◉	Straight
○	Upward

_____ property is the possible way to remove the node to which you have navigated.

Select the correct option

◉	childNode
○	parentNode
○	attributeValue
○	nodeValue

_____ property of XML document is the _____ node.

Select the correct option

○	documentElement, type
○	element, type
○	documentElement, root
○	documentElement, child node

If the sibling node is not an element node, it moves to the _____nodes until an element node is found.

Select the correct option

○	First
○	Next
○	Last
○	Previous

If we want to name a node in XML document, which property of node should be used?

Select the correct option

○	name
○	node.name
○	nodeName
○	nameNode

Which of the given browser will not consider empty white-spaces or new line as a text node?

Select the correct option

- ○ Internet Explorer
- ○ Microsoft Edge
- ○ Google Chrome
- ○ Mozilla Firefox

Which property of node is the type of node?

Select the correct option

○	nodeType
○	typeNode
○	node.type
○	type

DOM has reduced complexity of dealing with multiple type of nodes by which method?

Select the correct option

○	removeAttribute()
○	removeNode()
○	removeElement()
○	removeChild()

The removeChild() method can also be used to remove the ____node.

Select the correct option

○	Element
○	Parent
○	Attribute
○	Text

Basic difference in text node and element node is that the text node contains_____.

Select the correct option

○	multiple child element
○	text data only
○	Attribute node
○	both text data and attribute node

y = y.nextSibling; is used to get the _____ .

Select the correct option

○	next same type of element
●	next child node of y
○	next element
○	next root element

Which of the following is the correct syntax to define the XML version?

Select the correct option

○	<?xml version="1.0" />
○	<?xml version="1.0"?>
○	<xml version="1.0" />
○	None of the given options

<!ELEMENT note (message*)>
The * sign in the example above declares that the child element "message" can occur _____ or _____ times inside the "note" element.

Select the correct option

- (●) zero or more
- ( ) two or more
- ( ) None of the given
- ( ) one or more

Ac
Go

XPath is

Select the correct option

- ○ not a W3C Standard
- ○ a W3C Standard
- ○ a Microsoft Standard
- ◉ not belong to any Standard

In XML single quote is represented by _____ symbol.

Select the correct option

○	&gt
○	&quot
○	&lt
◉	&apos

Which of the following provides extra information about XML elements.

Select the correct option

◉	Attributes
○	None of the given options
○	Entities
○	Tags

Which of the following encoding scheme is used to avoid character encoding problems?

Select the correct option

○	UTF-16
○	UTF-8
●	Both UTF-8 or UTF-16
○	None

In XML, some characters have a special meaning those are called _____.

Select the correct option

○	None of the given options
●	Entities
○	Symbols
○	Variables

An XML document is called a valid document if

Select the correct option

○	the document contains at-least one or more root element
○	each element must nest inside any enclosing element property
○	the document has root element
◉	the document has DTD associated with it & it complies with that DTD

The entity reference < represents _____ character.

Select the correct option

○	<=
○	=<
●	>
○	<