Question # 1 of 5

Which of the following does not belongs to DTD?

Select the correct option

○	PCDATA
○	Elements
○	Attributes
○	ACDATA ✓ Not confirm

Which of the following is the correct syntax of elements with children in DTD?

Select the correct option

○	<!ELEMENT element-name (child1,child2,...)> ✓
○	<#ELEMENT (child1,child2,...) element-name>
○	<?ELEMENT element-name (child1,child2,...)>
○	<!ELEMENT (child1,child2,...) element-name>

Question # 3 of 5

In XML, the correct syntax to declare an empty element is_____.

Select the correct option

○	
○	</br>
○	<br\>
○	<\br>

Question # 4 of 5

The attribute-type for Predefined Xml Value is _____.

Select the correct option

○	NMTOKEN
○	ID
○	xml: ✓
○	NOTATION

Question # 5 of 5

In DTD, CDATA means _____.

Select the correct option

○	Chained data
○	Collected data
○	Choice data
○	Character data



Question # 1 of 5

XML was designed to carry data - with focus on what data is.

Select the correct option

○	True 
○	False

HTML has Predefined tags.

Select the correct option

○	False
◉	True

Question # 3 of 5

Which of the following is not True about XML?

Select the correct option

○	It allows you to invent your own tags.
◉	XML is not portable.
○	XML is portable.
○	XML documents can easily be parsed.

XML tags are _____ like HTML tags.

Select the correct option

○	not flexible
●	not predefined
○	predefined
○	case insensitive

HTML is about to displaying information while XML is about to _____.

Select the correct option

○	carrying information
●	describing information
○	manipulating information
○	designing information

Which of the following sequence is correct while closing the given XML tags?

This text is bold and italic

Select the correct option

○	
○	
○	
●	

In XML, sub-elements are also called _____.

Select the correct option

○	child roots
○	sub-nodes
○	child-nodes
◉	child elements

Which of the following tag is considered to be the correct closing tag of XML tag <Message>?

Select the correct option

○	</message>
●	</Message>
○	<Message>
○	<message>

In XML, all elements _____ have a closing tag.

Select the correct option

○	may or may not
◉	must
○	must not
○	may

The terms parent, child, and sibling are used to describe the _____ among elements.

Select the correct option

- (●) relationships
- ( ) text content
- ( ) roots
- ( ) attributes

HTML has Predefined tags.

Select the correct option

○	False
●	True

XML tags must be properly nested.

Select the correct option

◉	True
○	False

Which of the following statement is correct about XML syntax?

Select the correct option

- (●) Attribute values must always appear in brackets 
- ( ) Attribute values always appear without quotation marks
- ( ) Attribute values must always appear in quotation marks 
- ( ) Attribute values always appear in uppercase letters

The Unicode Characters cites the character with standard _____, which shows the character's code point in hexadecimal.

Select the correct option

Reload Mo

- ○ Unicode "X+" notation
- ○ Unicode "V+" notation
- ○ Unicode "X+" notation
- ○ Unicode "U+" notation ✓

The purpose of a DTD is to define the _____ of an XML document.

Select the correct option

○	appropriate reference
◉	legal building blocks
○	document infrastructure
○	illegal reference

Which of the following statement is the correct linking of an external DTD?

Select the correct option

●	<!DOCTYPE note SYSTEM "note.dtd">
○	<!DOCTYPE to (#note)>
○	<!DOCTYPE note SYSTEM note body >
○	<!DOCTYPE note SYSTEM from>

A DTD can be declared _____.

Select the correct option

○	both b and c
◉	through a link to XML document
○	inline in your XML document
○	as an external reference





Question # 1 of 5

The following example shows incorrect syntax because _____.

....

Select the correct option

○	the attribute c is specified once
○	the attribute z is specified once
◉	the attribute b is specified twice
○	the tag a is closed incorrectly

XML declaration statement strictly needs to be the _____ of the XML document.

Select the correct option

○	either first or last statement
○	last statement
○	second last statement
●	first statement

XML tags must be properly nested.

Select the correct option

◉	True
○	False

XML Namespaces provide a method to avoid element _____.

Select the correct option

○	name applications
○	name conventions
◉	name conflicts
○	name tables

Question # 2 of 4

In an XML document, the invention of elements depends more likely on _____.

Select the correct option

○	Document tags
○	Document Author ✓
○	Document Other Elements
○	Document CSS

Name conflicts in XML can easily be avoided using a _____.

Select the correct option

○	name application
●	name prefix
○	name table
○	name convention

The declaration of XML must begin with "<?xml>", where "xml" is written in _____.

Select the correct option

○	camel-case
◉	lower-case
○	upper-case
○	either lower or upper case

XML provides a _____ way of describing, controlling, or allowing/disallowing particular types of document structure.

Select the correct option

Re

◉	standardized
○	expensive
○	complicated
○	simplified

Question # 2 of 4

XML is used to _____ data.

Select the correct option

○	transport
○	publish
○	format
○	display

Question # 3 of 4

XML documents can be converted into any other format _____.

Select the correct option

◉	with no loss of information.
○	but it becomes the generic application.
○	but the information is lost.
○	but the file and data is destroyed.

XML provides a _____ syntax for messaging systems for the exchange of information between applications.

Select the correct option

◉	common
○	unique
○	messy
○	complex

Question # 1 of 3

XML tree branches from the root to _____ elements.

Select the correct option

○	root
○	branch
○	child
○	sibling



Page 1 of 348 2763 words English (United States)

Siblings are _____.

Select the correct option

○	children at the branch level
○	children at the root level
●	children at the same level
○	children at the parent level

An XML tree starts at a _____ element.

Select the correct option

○	sibling
○	branch
◉	root
○	child

Which of the following statement is not true about XML?

Select the correct option

○	XML is expensive.
○	XML can't be pirated.
○	XML is free.
●	XML can't be hijacked.

HREF and href are considered _____ XML attributes.

Select the correct option

○	two incorrect
●	two same
○	two obsolete
○	two different

<author>J K. Rowling</author>

<year>2005</year>

<price>29.99</price>

</book>

Select the correct option

○	text
○	mix
○	element
◉	attribute

Which of the following XML Tree relationship can also be called brothers and sisters?

Select the correct option

○	roots
●	siblings
○	children
○	branches

Which of the following is the correct way to indicate an empty XML element?

Select the correct option

○	<element>blank</element>
○	<element>null</element>
○	<element>empty</element>
●	<element></element>

Which of the following cannot be used while naming an XML Element?

Select the correct option

◉	spaces Not Confirm
○	digits
○	letters
○	underscores

Which of the following statement is true about naming an XML element?

Select the correct option

○	Element names cannot contain underscores
○	Element names cannot start with the letters XML.
○	Element names can start with the letters XML. 
○	Element names cannot contain digits

Question # 4 of 5

Which of the following statement is true about naming an XML element?

Select the correct option

◉	Element names are case-sensitive
○	Element names cannot contain digits
○	Element names cannot contain underscores
○	Element names can contain spaces

An element with no content is said to be _____.

Select the correct option

○	original element
○	duplicate element
◉	empty element
○	spaced element

The element "<title>Harry Potter</title>" have _____ type of content.

Select the correct option

○	text
●	attribute
○	category
○	mix

Not confirm

There is/are _____ about when to use attributes or when to use elements in XML.

Select the correct option

○	three rules
○	one rule
●	no rules
○	two rules

Which of the following statement is true about writing XML attributes?

Select the correct option

○	Only a single quote can be used to write attribute values.
○	Only a double quote can be used to write attribute values.
◉	Either single or double quotes can be used to write attribute values.
○	No quote is needed while writing attribute value.

Not confirm

Which of the following statement is true about the XML attribute?

Select the correct option

○	attributes can have multiple values
◉	attributes can have tree structures
○	attributes are easily expandable
○	attributes cannot have multiple values

Not confirm

Attributes are designed to contain data related to a _____.

Select the correct option

○	specific text
○	specific image
◉	specific element
○	specific piece of code

<h:table> and **<f:table>** are examples of _____.

Select the correct option

○	name tables
○	name applications
○	name conventions
◉	name prefix

Name conflicts in XML can easily be avoided using a _____.

Select the correct option

○	name conventions
○	name tables
○	name applications
◉	name prefix

In the following code, **category="children"** is termed as _____ of element "book".

```
<book category="children">
 <title>Harry Potter</title>
 <author>J K. Rowling</author>
 <year>2005</year>
 <price>29.99</price>
 </book>
```

Select the correct option

- ○ attribute
- ○ mix
- element

Everything from the element's start tag to the element's end tag is called _____.

Select the correct option

○	an xml text
○	an xml attribute
○	a self closed attribute
◉	an xml element

The default encoding scheme for XML and HTML5 is _____.

Select the correct option

○	UTF-16
●	UTF-8
○	UTF-64
○	UTF-32

Character encoding is also called as _____.

Select the correct option

○	Character style
●	Character page
○	Character map
○	Character URL

UTF-8 uses one byte for basic _____.

Select the correct option

○	Mathematical characters
○	Arabic characters
●	Latin characters
○	Spanish characters

Which of the following is the safest encoding scheme and web standard to use?

Select the correct option

○	UTF-32
●	UTF-8
○	UTF-16
○	UTF-64

XML standard states that XML software must understand both _____.

Select the correct option

○	UTF-32 and UTF-64
○	UTF-16 and UTF-32
○	UTF-32 and UTF-8
◉	UTF-8 and UTF-16

When an XML document is opened in a browser then often a plus sign is used to _____ the elements.

Select the correct option

○	Destroy
○	Collapse
○	Hide
○	Expand

Which of the following is a valid prolog statement in XML document?

Select the correct option

○	<xml version="1.0" encoding="UTF-8"/>
○	<xml version="1.0" encoding="UTF-8">
●	<?xml version="1.0" encoding="UTF-8"/>
○	<?xml version="1.0" encoding="UTF-8"?>

XML documents do not carry information about how _____.

Select the correct option

○	Attributes will be defined
○	To display the data
○	To store the data
○	Tags will be defined

Raw XML files can be viewed in _____.

Select the correct option

○	Only in Chrome browser
●	All major browsers
○	Only in Firefox Brower
○	Only in Opera browser

Which of the following is the correct code to link "data.css" file with an XML document?

Select the correct option

○	<?xml-style type = "text/css" href= "data.css"?>
●	<?xml-stylesheet type = "text/css" href= "data.css"/>
○	<?xml-stylesheet type = "text/css" href= "data.css"?>
○	<xml-stylesheet type = "text/css" href= "data.css">

Which of the following is a valid XLS style sheet syntax?

Select the correct option

○	<xsl:stylesheet version="1.0" xmlns="http://www.w3.org/1999/XSL/Transform">
○	<xsl:stylesheet version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform">
○	<xsl version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform">
○	<stylesheet version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform">

Which of the following is best/recommended style sheet language for an XML document?

Select the correct option

●	XSLT
○	XLink
○	XPath
○	CSS

XPath is language for _____.

Select the correct option

○	Querying XML documents
◉	Formatting XML documents
○	Transforming XML documents
○	Navigating information in XML documents

XSLT uses _____ to find information in an XML document.

Select the correct option

○	XLink
○	XCode
◉	XPath
○	XInfo

XSLT stands for _____.

Select the correct option

◉	Extensible Style Sheet Language Transformation
○	X-Style Sheet Language Transformation
○	Extra Style Sheet Language Transformation
○	XML based Style Sheet Language Transformation

Which of the following is best/recommended style sheet language for an XML document?

Select the correct option

○	CSS
●	XSLT
○	XPath
○	XLink

When an XML document is opened in a browser then often a plus sign is used to _____ the elements.

Select the correct option

○	Hide
○	Destroy
◉	Expand
○	Collapse

In XPath expression "/bookstore/book[last()]" denotes:

Select the correct option

○	Selects the second last book element that is the child of the bookstore element
◉	Selects the last book element that is the child of the bookstore element
○	Selects the fourth last book element that is the child of the bookstore element
○	Selects the third last book element that is the child of the bookstore element

In XPath expression "/bookstore/book[position()<3]" denotes:

Select the correct option

○	Selects the second book element that is child of the bookstore element
●	Selects the first two book elements that are children of the bookstore element
○	Selects the third book element that is child of the bookstore element
○	Selects the first three book elements that are children of the bookstore element

Question # 3 of 5

XPath is not used in:

Select the correct option

◉	XAttribute
○	XLink
○	XPointer
○	XQuery

In XPath expression "//title[@lang]" denotes:

Select the correct option

●	Selects all the title elements that have an attribute named lang
○	Selects first two title elements that have an attribute named lang
○	Selects first title element that has an attribute named lang
○	Selects all the title elements that have an attribute named language

Without _____ knowledge you will not be able to create XSLT documents.

Select the correct option

○	XLX-FO
○	XQuery
○	XAttribute
◉	XPath

XSLT uses _____ to find information in an XML document.

Select the correct option

○	XLink
◉	XPath
○	XInfo
○	XCode

The _____ attribute specifies the URL to link.

Select the correct option

○	xlink:show
◉	xlink:href
○	xlink:url
○	xlink:type

xlink:show="new" is used for:

Select the correct option

○	To open link in a new browser
○	To open link in a new window
●	To show new link elements
○	To renew the link

Not confirm

Question # 3 of 5

XLink is used to create _____ in XML documents.

Select the correct option

○	Sub-Elements
○	Elements
○	Tags
●	Hyperlinks

To open "Google" search engine website in new window/tab with a link given in XML document which one of the following code will you use?

Select the correct option

Reload Ma

○	<searchengine xlink:type="simple" xlink:href="www.google.com.pk" xlink:show="blank">Google</institute>
○	<searchengine xlink:type="simple" xlink:href="www.google.com.pk" xlink:show="window">Google</institute>
○	<searchengine xlink:type="simple" xlink:href="www.google.com.pk" xlink:show="tab">Google</institute>
●	<searchengine xlink:type="simple" xlink:href="www.google.com.pk" xlink:show="new">Google</institute>

Which of the following is correct way to declare Xlink namespace?

Select the correct option

○	<bookstore xmlns:show="http://www.w3.org/1999/xlink">
●	<bookstore xmlns:href="http://www.w3.org/1999/xlink">
○	<bookstore xmlns:type="http://www.w3.org/1999/xlink">
○	<bookstore xmlns:xlink="http://www.w3.org/1999/xlink">

XML documents do not carry information about how _____.

Select the correct option

○	To store the data
○	Tags will be defined
○	To display the data
◉	Attributes will be defined

In XML file by setting the value of xlink:show attribute to _____, the linked resource should process inline within the page.

Select the correct option

Relo

○	new
●	embed
○	actuate
○	attach

The default value of xlink:show is _____.

Select the correct option

◉	New
○	Other
○	Replace
○	Embed

XPointer uses _____ expressions to navigate in the xml document.

Select the correct option

○	XPath
○	XQuery
○	XLink
◉	XSLT

In XML file by using _____ we can access remote locations as resources, instead of standalone pages.

Select the correct option

○	XPointer
○	XLink
○	XQuery
◉	XPath

HTML browsers are allowed to display _____ documents with errors.

Select the correct option

○	HTML
●	XSLT
○	DTD
○	XML

If an XML document is checked with XML validator and have no elements in it, then which of the following error will occur.

Select the correct option

○	Missing sub-child element
○	Missing child element
○	Missing root element
◉	Validator will not produce any error

The W3C XML specification states that a program should _____ processing an XML document if it finds an error.

lect the correct option

○	Start
○	Halt
○	Stop
◉	Slow down

A "Valid" XML document is not same as _____.

Select the correct option

◉	Well formed
○	Well Shaped
○	Well Designed
○	Well Structured

An XML document must have _____.

Select the correct option

○	Two elements
○	Three elements
◉	Root element
○	Child element

An XML document with correct syntax is called _____.

Select the correct option

◉	Well formed
○	Well Structured
○	Well Shaped
○	Valid XML document

Question # 4 of 9

XML tags are _____.

Select the correct option

○	All Lower Case
◉	Case Sensitive
○	Case Insensitive
○	All Upper Case

There are _____ different document type definitions that can be used with XML.

Select the correct option

○	Five
○	Two
○	Four
◉	Three

Not Confirm

The DTD starts with _____.

Select the correct option

●	<! DOCTYPE
○	<\ DOCTYPE
○	<# DOCTYPE
○	</ DOCTYPE

If the DTD is pointing to external path, it is called _____.

Select the correct option

○	Internal set
○	Internal subset
◉	External subset
○	DTD subset

A "Valid" XML document is a "Well Formed" XML document, which also confirms to the rules of a _____.

Select the correct option

○	XML
○	XLink
○	XSLT
●	DTD

DTD stands for _____.

Select the correct option

○	Document Type Distractor
○	Document Type Divider
○	Definition type Document
◉	Document Type Definition

An XML document validated against a DTD is _____.

Select the correct option

○	Well-formed only
○	Valid only
○	Well-formed and Invalid
◉	Well-formed and Valid

In _____, a doctype declaration can also be used to define special characters and character strings.

Select the correct option

- (●) DTD
- ( ) XLink
- ( ) XML
- ( ) XSLT

In DTD, an entity has ____ parts.

Select the correct option

◉	Three
○	One
○	Four
○	Two

Which of the following is not the part of DTD entity?

Select the correct option

◉	Entity name ✗
○	Ampersand (&)
○	Semicolon (;)
○	Hash (#) ✓

With _____, independent groups of people can agree on a standard for interchanging data.

Select the correct option

●	**DTD**
○	XSLT
○	XPointer
○	XML

Question # 5 of 5

PCDATA stands for_____.

Select the correct option

○	Parallel Character Data
○	Public Character Data
●	Parsed Character Data
○	Publishable Character Data

In DTD, CDATA means _____.

Select the correct option

○	Collected data
◉	Character data
○	Chained data
○	Choice data

Which of the following is the entity reference code for character "<"?

Select the correct option

○	$gt;
○	&lthen;
●	<
○	⁢

Which of the following does not belongs to DTD?


Select the correct option

◉	Attributes
○	PCDATA
○	Elements
○	ACDATA

Which of the following is the correct syntax to declare DTD elements?

Select the correct option

- ○ <!ELEMENT element-name category>
- ○ <$ELEMENT element-name category>
- ○ <#ELEMENT element-name category>
- ○ <?ELEMENT element-name category>



In DTD, the correct syntax to declare element with parsed character data is_____

Select the correct option

○	<!ELEMENT from (#PARSECDATA)>
◉	<!ELEMENT from (PCDATA)>
○	<!ELEMENT from (#PCDATA)>
○	<!ELEMENT from (#PCHARDATA)>

In XML, the correct syntax to declare an empty element is_____.

Select the correct option

○	
○	</br>
○	<\br>
◉	<br\>

In document type definition (DTD), the correct syntax to declare elements with "any" data is_____

Select the correct option

○	<!ELEMENT note ANYE>
○	<!ELEMENT note ANYELMNTS>
○	<!ELEMENT note ANYELMNT>
◉	<!ELEMENT note ANY>

In a DTD, elements are declared with an _____ declaration.

Select the correct option

○	Elements
●	Element
○	Elmnt
○	El

Which of the following is the correct syntax of elements with children in DTD?

Select the correct option

○	<!ELEMENT element-name (child1,child2,...)>
○	<?ELEMENT element-name (child1,child2,...)>
○	<!ELEMENT (child1,child2,...) element-name>
○	<#ELEMENT (child1,child2,...) element-name>

Elements with one or more children are declared with the _____ of the children elements inside parentheses.

Select the correct option

○	Property
○	Parent element
○	Id
○	Name

Which of the following is the correct option to declare zero or more occurrence of an element in DTD?

Select the correct option

○	<!ELEMENT element-name (child-name*2)>
◉	<!ELEMENT element-name (child-name*)>
○	<!ELEMENT element-name (child-name*1)>
○	<!ELEMENT element-name (child-name*0)>

Which of the following is the correct option to declare minimum one occurrence of an element in DTD?

Select the correct option

○	<!ELEMENT note (message+)>
○	<!ELEMENT note (message)*>
○	<!ELEMENT note (message1+)>
○	<!ELEMENT note (message+1)>

Which of the following is the correct option to declare only one occurrence of an element in DTD?

Select the correct option

○	<!ELEMENT element-name (child-name+)>
○	<!ELEMENT element-name (child-name+1)>
○	<!ELEMENT element-name (child-name)>
○	<!ELEMENT element-name (child-name)->

In DTD, the correct syntax to declare element with parsed character data is_____

Select the correct option

○	<!ELEMENT from (#PCDATA)>
◉	<!ELEMENT from (PCDATA)>
○	<!ELEMENT from (#PCHARDATA)>
○	<!ELEMENT from (#PARSECDATA)>

ATTLIST square width CDATA "0" is an example for_____.

Select the correct option

○	A #IMPLIED Value
○	A #REQUIRED Value
○	A Default Attribute Value ✓
○	xml-schema

The attribute-type (en1|en2|..) is _____.

Select the correct option

○	The value is a list of entities
○	The value is a predefined xml value
◉	The value is a list of other ids
○	The value must be one from an enumerated list

An attribute declaration: ATTLIST element-name attribute-name_____ attribute-value.

Select the correct option

○	attribute-type
○	attribute-tag
○	xml-schema
○	tag-color

The attribute-value #IMPLIED is a/an _____.

Select the correct option

○	disposable
○	ready-to-use
○	optional
○	volatile

The attribute-type for Predefined Xml Value is _____.

Select the correct option

○	NMTOKEN
○	xml: ✓
○	ID
○	NOTATION

The _____ are easily expandable for future changes.

Select the correct option

○	child elements
○	internal tags
○	external element
○	attributes

Attribute values are not easy to test against a _____.

Select the correct option

○	#REQUIRED Value
○	#IMPLIED Value
◉	DTD
○	list of entities

Data can be stored in _____ or in attributes.

Select the correct option

○	child elements
○	xml-schema
○	tag meta data
○	element name

Attributes cannot contain _____, while child elements can.

Select the correct option

○	NMTOKEN
○	ID
●	multiple values
○	NOTATION

The metadata (data about data) should be stored as_____.

Select the correct option

◉	attributes
○	child elements
○	predefined xml value
○	internal tags

DTD – Entity declaration can be _____.

Select the correct option

◉	internal and external declaration
○	multiple values declaration
○	NOTATION
○	NMTOKEN declaration

Entities are used to define_____ to special characters.

Select the correct option

○	xml-schema
○	child elements
○	shortcuts ✓
○	element name

An entity has three parts: an ampersand (&), an entity name, and _____.

Select the correct option

○	a semicolon (;) ✓
○	predefined URL
○	HTML tag
○	a child element

<!ENTITY entity-name SYSTEM "URI/URL"> is a/an _____.

Select the correct option

○	internal declaration
○	external declaration ✓
○	list of entities
○	#REQUIRED Value

The attribute-type (en1|en2|..) is _____.

Select the correct option

○	The value is a predefined xml value
●	The value must be one from an enumerated list
○	The value is a list of other ids
○	The value is a list of entities

DTD – Entity declaration can be _____.

Select the correct option

○	NMTOKEN declaration
○	multiple values declaration
◉	internal and external declaration
○	NOTATION

By using _____ you can convert data between different data types.

Select the correct option

○	XML elements
○	XML Schema
○	PHP server
○	HTML

Namespaces are supported by _____.

Select the correct option

○	XML DTDs
○	HTML tags
○	XML Schemas ✓
○	#REQUIRED Value

XML parser can also be used to parse the _____.

Select the correct option

○	external element
○	internal tag
○	HTML tags
○	Schema files

<xs:complexType>, here complex Type refers that the element has _____.

Select the correct option

○	predefined URL
○	HTML tags
○	no child elements
◉	child elements

The code is saved as _____ file on the web server, when XML database response is generated from the server.

Select the correct option

○	HTML
○	XML DTDs
○	ASP ✓ Not confirm
○	XML Schema

Question # 2 of 5

Different software programs can automatically read/write the XML file by using _____ at first.

Select the correct option

○	database connection
○	echo
○	predefined URL
◉	XML Schema/DTDs

To save the file "note.xml" on web server, you have to write the XML by using _____.

Select the correct option

○	Google Chrome
○	FireFox
◉	Notepad
○	MS Edge

While generating XML using PHP, the content type of the response header must be set to _____.

Select the correct option

◉	"text/xml"
○	"text/php"
○	".txt"
○	"xml/php"

By using _____ you can convert data between different data types.

Select the correct option

○	HTML
○	XML Schema
○	XML elements
◉	PHP server

DOM is a platform and _____ interface.

Select the correct option

○	Scripting dependent
○	Language-neutral ✓
○	Program oriented
○	Language dependent

The _____ is a standard model for any structured document .

Select the correct option

○	Standard DOM
○	DOM-Struct
○	Core DOM ✓
○	Doc DOM

HTML DOM defines the objects, properties and _____ of all HTML elements.

Select the correct option

○	Methods ✓
○	HTML tags
○	HTML child
○	XML DTDs

The DOM is separated into _____different parts.

Select the correct option

○	Four
○	Two
○	Three ✓
○	Five

DOM stands for _____.

Select the correct option

◉	Document Object Model
○	Data Object Model
○	Data Orientation Model
○	Document Orientation Method

By using _____ you can convert data between different data types.

Select the correct option

◉	PHP server
○	XML Schema
○	XML elements
○	HTML

The DOM says that the comments in the XML are _____.

Select the correct option

○	attributes
○	ignored
○	recorded as plain text
◉	comment nodes

In XML DOM tree, text nodes are placed at the _____ of tree.

Select the correct option

○	Highest level
○	Middle level
○	Lowest level ✓
○	Branch level

In XML DOM, tree starts from the _____.

Select the correct option

○	Child node
○	Tag element
◉	Root node
○	Sibling node

The XML DOM views an XML document as a _____.

Select the correct option

○	Schema elements
○	Script
○	Code statements
●	Node tree

The DOM says that the text in the XML elements are _____.

Select the correct option

○	Formatted text
◉	Text nodes
○	Plain text
○	Attribute text

The onreadystatechange event with value _____means "request finished and response is ready".

Select the correct option

○	5
○	12
○	8
○	4 ✓

The XMLHttpRequest Object is used to update a web page _____ the page.

Select the correct option

○	By restarting
○	Without reloading
○	By resetting
○	By reloading

The _____ event is triggered every time the readyState changes.

Select the correct option

○	new XMLHttpRequest();
○	onreadystatechange ✓
○	xhttp.onreadystatechange
○	xhttp.send();

The XMLHttpRequest Object is used to send data to a server _____.

Select the correct option

○	In the background
○	Every time server crashes
○	After session expiry
○	Before connection

During a server request, the readyState changes from _____.

Select the correct option

○	Down to live
○	11 and 12
○	0 to 4 ✓
○	5 to 8

PHP command _____ is used to show output of the code.

Select the correct option

○	parse.write
○	out.write
◉	echo
○	cout<<

Question # 1 of 5

send() function sends a _____ to the server for _____ method.

Select the correct option

○	request, GET 
○	response,GET
○	request, POST
○	response,POST

send(string) sends a _____ to the server for _____ method.

Select the correct option

○	response,GET
○	request string, GET
●	request string, POST
○	response,POST

Question # 3 of 5

For POST method _____ function sends a request string to server.

Select the correct option

○	send()
○	send(async)
○	send(url)
○	send(string) ✓

For security purposes, modern browsers try to load _____ and web page located on _____ server.

Select the correct option

○	xml file, different
○	url, different
◉	xml file, same
○	url, same

For GET method _____ function sends a request to server.

Select the correct option

○	send(async)
●	send(string)
○	send()
○	send(url)

In DOM, the correct way to check length of Node List under x element is _____ .

Select the correct option

○	length(x)
○	length("x")
○	x->length
○	x.length ✓

What is correct statement to return all <title> elements using getElementsByTagName() method in XML document?

Select the correct option

○	xmlDoc.getElementsByTagName(<title>);
○	x.getElementsByTagName(<title>);
○	xmlDoc.getElementsByTagName("title"); ✓
○	x.getElementsByTagName("title");

To get all elements with a specified tag name under a node, _____ syntax is used.

Select the correct option

○	tagname.getElementsByTagName("node");
○	node.getElementsByTagName(<tagname>);
○	tagname.getElementsByTagName(<node>);
○	node.getElementsByTagName("tagname"); ✓

A Node can be accessed by _____ method.

Select the correct option

○	getElementsByName()
○	getElementsByTagName() ✓
○	getElementsById()
○	getElementsByTagId()

An XML document must be loaded into an _____ before to access it.

Select the correct option

○	XML function
○	XML DOM object ✓
○	XML DOM class
○	XML object

Which property of XML document is the name of node?

Select the correct option

○	nameNode
○	nodeName ✓
○	node.name
○	name

_____ property of XML document is the _____ node.

Select the correct option

○	element, type
○	documentElement, type
○	documentElement, root ✓
○	documentElement, child node

Which property of node is the type of node?

Select the correct option

○	node.type
○	typeNode
○	nodeType ✓
○	type

If we want to name a node in XML document, which property of node should be used?

Select the correct option

- ○ nodeName
- ○ nameNode
- ○ name
- ○ node.name

_____ has a "documentElement" property that is called root node.

Select the correct option

○	XML
○	XML tag
○	XML element
●	XML document

Suppose you are checking the node types of child nodes under the root element. If a child node type is _____ , then it is an element node.

Select the correct option

Reload Mo

○	0
○	2
●	1
○	3

To get element node from an xml document, _____ condition will be used.

Select the correct option

○	x = xmlDoc.documentElement.childNodes; if (x[i].nodeType == 0)
○	x = xmlDoc.documentElement.childNodes; if (x[i].nodeType == 1)
○	x = xmlDoc.documentElement.childNodes; if (x[i].nodeElement == 1)
○	x = xmlDoc.documentElement.childNodes; if (x[i].nodeElement == 0)

Which syntax is correct to check the node is an element node?

Select the correct option

○	if (x[i].nodeType == "Element")
○	if (x[i].nodeType == 0)
○	if (x[i].nodeType == nodeElement)
○	if (x[i].nodeType == 1) ✓

If you want to check the node type is an element node, then _____ syntax for this purpose is correct.

Select the correct option

○	x = xmlDoc.documentElement.childNodes;
	for (i = 0; i <x.length; i++) {
	if (x[i].nodeType == 2) {
	.....
	}
	}

◉	x = xmlDoc.documentElement.childNodes;
	for (i = 0; i <x.length; i++) {
	if (x[i].nodeType == 1) {
	.....
	}
	}

○	x = xmlDoc.documentElement.childNodes;
	for (i = 0; i <x.length; i++) {
	if (x[i].nodeType == 3) {

If we want to get the child node of the first book _____ syntax is used.

Select the correct option

○	x = xmlDoc.getElementsByTagName("book")[1];
○	x = xmlDoc.getElementsByTagName("book")[0]; ✓
○	x = xmlDoc.getElementsByTagTitle("book")[0];
○	x = xmlDoc.getElementsByTagTitle("book")[1];

Question # 2 of 5

y = y.nextSibling; is used to get the _____ .

Select the correct option

○	next root element
○	next same type of element
○	next child node of y
○	next element

✓ Not confirm

If y = x.firstChild; represents first child node under element then while traversing nodes_____ is used to go to next same element.

Select the correct option

Reload Ma

○	y = y.nextSibling; ✓
○	y = y++;
○	y = y.nextElement;
○	y = y.nextChild;

What would be the length of child nodes of book element in the given code:

<book category = "java">
<title lang="eng"> Core Java Volume I – Fundamentals</title>
<author>Cay S. Horstmann </author>

Select the correct option

○	2
○	3
○	4 ✓ Not confirm
○	1

What would be returned through following line of code, x = xmlDoc.getElementByTagName("book")[0]; where xmlDoc is the root element.

Select the correct option

Reload M

○	only first book returned
○	only tag returned
○	all books returned
○	only first tag of book returned ✓ Not Confirm

Click to Save Answer & Move to N

_____ is the nodeName of text node.

Select the correct option

○	#nodeText
○	#textNode
○	nodeText
○	#text ✓

nodeName property of node is _____.

Select the correct option

○	write-only
◉	read-only
○	read and write
○	not read and not write

_____ is the nodeName of document node.

Select the correct option

○	#nodeDoc
○	nodeDoc
○	#docNode
◉	#document

Which property of an element is the same as tag name ?

Select the correct option

○	nodeValue
○	nodeAttribute
○	nodeType
○	nodeName ✓

What is the nodeName of an attribute node?

Select the correct option

○	Atribute Text
○	Attribute Value
◉	Attribute Tag
○	Attribute Name





nodeValue is _____ for a text node.

Select the correct option

○	1
●	text itself
○	undefined
○	0

nodeValue for_____ is text itself.

Select the correct option

○	node
○	root node
○	element node
◉	text node

"nodeValue" property specifies the _____ of a node.

Select the correct option

○	name
○	id
●	value
○	attribute

The _____ for an element node is undefined.

Select the correct option

○	nodeText
○	nodeAttribute
○	nodeId
◉	nodeValue

nodeValue is _____ for an element node.

Select the correct option

○	2
◉	undefined
○	1
○	0

If nodeType is 8 then node type is _____.

Select the correct option

○	attribute
●	comment
○	text
○	element

If nodeType is 1 then node type is _____.

Select the correct option

◉	element
○	text
○	attribute
○	comment

If nodeType is 3 then node type is _____.

Select the correct option

○	element
○	text 
○	comment
◉	attribute 

In given line of code, books.xml is loaded in xmlDoc and text node of first element node is reterived.

var x = xmlDoc.getElementsByTagName("title")[0].childNodes[0];

Choose correct option to change the value of text to "Hello World".

Select the correct option

Reloac

◉	x.nodeValue = "Hello World";
○	node.Text = "Hello World";
○	x.nodeText = "Hello World";
○	x.nodeId = "Hello World";

The _____ property of node list could be used to loop through all the elements in the list.

Select the correct option

○	length 
○	size
◉	count 
○	height

While using childNodes property a _____ object is returned.

Select the correct option

○	node
○	element
○	node list
◉	child





Node list object contains nodes in the list in _____ order as they are in xml.

Select the correct option

○	random
○	opposite
○	same
○	alphabetical

The _____ property of a node list is the number of nodes in the list.

Select the correct option

○	count
○	height
○	size
◉	length

Question # 5 of 5

If an element is added or deleted in the list, list is _____updated.

Select the correct option

◉	automatically
○	not
○	manually
○	randomly