

STREAM CAPTURE PRO-X5

Recording server
for audiovisual interrogations



PRODUCT DESCRIPTION

Server for recording and temporary storage of audiovisual interrogations with up to 5 camera views, data protection-compliant pause function, second-precise bookmark linking, and export function.

APPLICATION

- ✓ **Interrogation recording**
Audiovisual recording of witness and suspect interrogations for reliable documentation for police and judicial authorities.
- ✓ **Metadata capture**
Simultaneous recording of video, audio, and metadata (e.g., markers, measurements, observation data) for precise analysis and traceability.
- ✓ **Medical applications**
For use in healthcare, e.g., to record surgeries or training scenarios in medical training centers.
- ✓ **Training and education centers**
Multi-camera recording and analysis of practice or training situations - ideal for education, research, or quality assurance.

FEATURES

- Semi-passive cooling (low-noise)
- Operation via API /
Extron media control
- Up to 5 camera inputs (3G-SDI
or IP streams RTSP, UDP multicast)
- Create and save bookmarks
and markers
- Export one MP4 file per camera view
with digital security seal (HASH value)
incl. HTML-based multiview player for
external playback in a standard
browser and marker data
- Temporary storage of up to 24 hours
of camera recordings of all inputs
- Integrated SFPT server for data
transfer to long-term storage systems
- Optional connection
of transcription systems

STREAM CAPTURE PRO-X | STAND 2025-10

STREAM CAPTURE PRO-X5

HARDWARE SPECIFICATIONS

INPUT	TECHNISCHE DETAILS
Audio input	1 × 3.5 mm jack
Video inputs	5 × 3G-SDI
USB ports	4 × USB 3.2 Gen 2
OUTPUT	
Network connections	1 × 1 Gbit/s RJ45 1 × 2,5 Gbit/s RJ45
Audio/Video Output	Combined 3.5 mm jack (in/out) optional
HARDWARE	
Processor	Intel® Core™ i9-13900E
Working memory	32 GB DDR5
Operating system memory	265 GB M.2 SSD
Recording memory	2 × 4 TB SSD (2,5" SATA, RAID 1)
GENERAL	
Operating system	Linux Image
Dimensions / Weight	157 × 280 × 188 mm / 4,2 kg
Operating temperature	-25 °C ... +60 °C
Storage temperature	-40 °C ... +85 °C
Humidity	10 % ... 90 %, non-condensing
Mounting type	Wall mounting option
FEATURES	
Power supply	600 W AC/DC 24 V / 25 A with cable end terminals for terminal block
Power supply operating temperature	-20 °C ... +70 °C
Design / type	Robust industrial housing, temperature resistant
Operating environment	Designed for continuous operation in professional system environments

STREAM CAPTURE PRO-X | STAND 2025-10