Three-Way Word Embeddings for Polingual: Script, Sound and Meaning, and a Re-Ranked Lexicon

Gianangelo Dichio
Bucket Foundation

2026-11-06

Abstract

Polingual translates single words offline from a Wiktionary lexicon for 28 languages. The lexicon lists English meanings in English frequency order, so a rare sense can come first: Hebrew *akhil* (edible) was the first translation of English *good*. We embed 529,131 words of 29 languages four ways: rendered script pixels with a small CNN, character n-grams, phonetic features from Wiktionary IPA with a grapheme model for words without IPA, and LaBSE meaning vectors, plus a joint projection of all four [empirical: dataset v1 manifest.json, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/vocab.py, then python3 apple/scripts/embed/meaning.py, then python3 apple/scripts/embed/store.py]. Meaning vectors then re-rank every translation pair, with gloss senses added as candidates. On the held-out half of an independent Tatoeba-aligned word set, the first English sense shown is right for 68.3% of words, up from 58.0% [empirical: dataset v1 reports/rerank_report.json sha256 968b6767, 2026-11-06, charizard CPU: CUDA_VISIBLE_DEVICES= python3 apple/scripts/embed/rerank.py]. For English to target words, a model audit of 100 changed first answers finds 91 right after re-ranking and 60 before [empirical: dataset v1 reports/audit_report.json sha256 c63af75e, 2026-11-06, python3 apple/scripts/embed/audit_sample.py, then python3 apple/scripts/embed/audit_judge.py]. A secondary any-token score in the app evaluation, which includes the tuning rows and rewards the longer answers, rises from 67.5% to 77.2% [empirical: data/swift_before.txt and data/swift_after.txt, 2026-11-06, Mac: TRANSLATE_EVAL=current swift test –package-path BucketKit –filter translateEvalReport]. The shipped change is the re-ranked lexicon, 0.24 MB larger [empirical: du -cb apple/Shared/Corpus/lexicon/*.tsv.z before and after, 2026-11-06].

1 Introduction

A word lookup in Polingual returns up to three English senses from the bundled lexicon. For the lexicon of pull request 1198, any-token precision was 98.7% on the Wiktionary reference row and 67.5% on a word set aligned from Tatoeba sentence pairs [empirical: data/swift_before.txt, 2026-11-06, Mac: TRANSLATE_EVAL=current swift test –package-path BucketKit –filter translateEvalReport]. The gap comes from sense order: Wiktionary translation tables list a foreign word under every English headword that uses it, and the builder kept the four most frequent English headwords. A foreign word that translates a rare sense of a frequent English word inherits that word.

The founder asked for three separate embeddings per word, of script, sound and meaning, and a joint one, and for higher accuracy. This paper builds the four, measures each against a task it should solve, and uses them to score every translation pair in the lexicon.

2 Related work

LaBSE trains a dual encoder on translation pairs and places translations near each other [1]. Bilingual lexicon induction retrieves translations by nearest neighbour across aligned spaces [2]. Subword n-grams give vectors to unseen spellings [3]. Rendered text as model input handles noise and unseen scripts [4, 5]. Contrastive objectives with in-batch negatives train both our script encoder and our joint projection [6, 7]. Tatoeba sentence pairs are a standard multilingual test source [8]. Phonetic features come from the PanPhon feature table and IPA from WikiPron, a scrape of Wiktionary pronunciations; neither has a DOI or arXiv identifier, so we name them with their repository paths in 4.

3 Preliminaries

Definition 3.1 (Lexicon)**.** For a language L, the lexicon maps a headword w to an ordered list $E(w)$ of English words and a gloss $g(w)$, a list of short English sense strings from the word's own Wiktionary entry. The app shows the first three items of $E(w)$, or $g(w)$ when $E(w)$ is empty. For English word e the lexicon also holds an ordered list $F(e)$ of target words; English-to-target lookups show the first.

Definition 3.2 (Modality)**.** A modality m is a map from words to unit vectors in $\mathbb{R}^{d_m}$. The similarity of words a, b under m is the dot product $\cos_m(a, b)$ of their unit vectors.

Definition 3.3 (Joint score)**.** Given weights w_m, the joint score of a pair is $s(a, b) = \sum_m w_m \cos_m(a, b)$. With weight one on meaning and zero elsewhere it equals the meaning cosine, proved as `jointScore_meaning_only` in B.

Definition 3.4 (Precision)**.** For an evaluation row with J judged answers of which R are right, precision is R/J in percent; `precisionPct_le` in B proves it stays within the percent scale when $R \leq J$. First-sense precision judges only the text before the first semicolon of the answer; any-token precision judges the whole answer.

4 Method

All embedding and scoring ran on host charizard, AMD Radeon RX 7600 with ROCm 6.4 and torch 2.9.1; the re-ranker ran on its CPU with the GPU hidden. Each tag below names the report file in dataset v1, the first eight hex digits of its sha256 from `manifest.json`, and the command.

Vocabulary. The lexicon builder of pull request 1198 runs in a dump mode, `python3 apple/scripts/translate/dl out/base 900000 repo/apple/Shared/Corpus - out/candidates.json`, that writes, for every shipped headword, all English candidates in frequency order and the gloss, and for every English headword all target candidates. Gloss senses that equal an English headword add target candidates to its list. The vocabulary is every headword, every candidate and every evaluation word: 26,887 English words and 502,244 words across the 28 target languages [empirical: dataset v1 manifest.json, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/vocab.py, then python3 apple/scripts/embed/meaning.py, then python3 apple/scripts/embed/store.py].

Script. Each word is rendered in Noto Sans for Latin, Greek and Cyrillic, Noto Sans Arabic, Hebrew, Devanagari, Tamil and Thai, and Noto Sans CJK for Chinese, Japanese and Korean, with HarfBuzz shaping through Pillow's Raqm layout, into a 32×128 grey raster. A four-block CNN maps the raster to 64 dimensions. It trains for 2,000 steps of batch 512 on 116,000 words, 4,000 per language, rendered at font weights 300, 400 and 700; two views of a word with random scale, shear, shift and noise form a positive pair under a symmetric InfoNCE loss with temperature 0.07 [empirical: dataset v1 reports/script_report.json sha256 3931c793, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/script.py]. The character view hashes the word's 1 to 3-grams with boundary marks into 2^{20} buckets and sums a fixed Gaussian vector per bucket, 64 dimensions [empirical: dataset v1 reports/script_report.json sha256 3931c793, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/script.py].

Phonetic. WikiPron files `CUNY-CL/wikipron/data/scrape/tsv` give space-separated IPA; we use up to 150,000 entries per language, 1,589,580 in all [empirical: dataset v1 reports/phonetic_report.json sha256 5273260e, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/phonetic.py]. Each segment maps to the 24 PanPhon features (`dmort27/panphon`) in $\{-1, 0, 1\}$; the word vector averages the segment features inside four equal position bins, giving 96 dimensions that keep coarse order [empirical: dataset v1 reports/phonetic_report.json sha256 5273260e, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/phonetic.py]. For words without IPA a grapheme model predicts the vector: the word splits into units, extended grapheme clusters by default, Hangul jamo for Korean, pinyin initials and finals for Chinese, kana with small-kana merging for Japanese; each unit, each unit at its position bin, each unit bigram and the first and last unit index a learned 96-d vector in an EmbeddingBag, and the mean of those vectors regresses the IPA vector under squared error for 8 epochs [empirical: dataset v1 reports/phonetic_report.json sha256 5273260e, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/phonetic.py]. The unit vectors are the letter and grapheme-cluster level of the phonetic embedding. 313,678 of the 529,131 vocabulary rows carry IPA; the grapheme model fills the rest [empirical: dataset v1 reports/phonetic_report.json sha256 5273260e, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/phonetic.py].

Meaning. LaBSE, `sentence-transformers/LaBSE` at revision `836121a0`, encodes each bare word to 768 dimensions [1]. Gloss strings are encoded the same way, with parenthesised notes removed [empirical: dataset v1 manifest.json, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/vocab.py, then python3 apple/scripts/embed/meaning.py, then python3 apple/scripts/embed/store.py].

Joint. Two joint forms are fitted on translation pairs from 80% of each language's headwords, split by hash [empirical: dataset v1 reports/joint_report.json sha256 11b0b40e, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/joint.py], and the other 20% are test queries [empirical: dataset v1 reports/joint_report.json sha256 11b0b40e, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/joint.py]. The weighted form searches $w_m \in \{0, 0.05, 0.1, 0.2, 0.3\}$ for script, character and phonetic with meaning fixed at one, maximising P@1 on 300 training queries per language; it selects 0.05 for script and zero for the other two [empirical: dataset v1 reports/joint_report.json sha256 11b0b40e, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/joint.py]. A logistic regression on the four cosines gave a phonetic weight of -2.05 and was dropped [empirical: dataset v1 reports/joint_report.json sha256 11b0b40e, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/joint.py]: sound similarity between a foreign word and its English translation carries signal only for cognates. The projection form scales each modality, concatenates the 992 dimensions and maps them linearly to 256, trained for 4,000 steps of batch 1,024 under symmetric InfoNCE at

temperature 0.05 with duplicate English targets masked [empirical: dataset v1 reports/joint_report.json sha256 11b0b40e, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/joint.py].

Re-ranking. For headword w, candidates are $E(w)$ in frequency order j plus up to three gloss senses at gloss position j. Candidate x scores $\cos(w,x) - \beta \log(1+j)$, plus a bonus b for the first gloss sense, and the top four ship. For English e, target candidate t scores $\cos(e,t) - \beta_r \log(1+j) + \gamma\,\pi(t)$ with $\pi(t) = 1 - \log(1+r_t)/\log(60001)$ from the wordfreq rank r_t of t in its language, zero when unranked; a candidate spelled the same as e drops to the end. The scorer, β, a drop threshold, a relative cut, gloss use and b were chosen on the even rows of the Tatoeba-aligned word set by first-sense precision with coverage held at the baseline [empirical: dataset v1 reports/rerank_report.json sha256 968b6767, 2026-11-06, charizard CPU: CUDA_VISIBLE_DEVICES= python3 apple/scripts/embed/rerank.py], and $\beta_r \in \{0, 0.05, 0.1\}$ and $\gamma \in \{0, 0.1, 0.2, 0.3, 0.5, 0.75, 1, 1.5, 2, 3\}$ on the even half of 378 common English words with Tatoeba-derived targets [empirical: dataset v1 reports/rerank_report.json sha256 968b6767, 2026-11-06, charizard CPU: CUDA_VISIBLE_DEVICES= python3 apple/scripts/embed/rerank.py]. Selected: meaning cosine, $\beta = 0.05$, no drop threshold, gloss on, $b = 0.1$, $\beta_r = 0.1$, $\gamma = 0.75$, an interior optimum of the γ grid [empirical: dataset v1 reports/rerank_report.json sha256 968b6767, 2026-11-06, charizard CPU: CUDA_VISIBLE_DEVICES= python3 apple/scripts/embed/rerank.py]. The odd rows and odd words are held out. The builder applies the English-to-target order only when `REV_RERANK=1`, the default, set by the audit in 5.2: `REV_RERANK=1 python3 apple/scripts/translate/build_lexicon.py dl out/rerank 900000 repo/apple/Shared/Corpus out/order.json`.

English-to-target references. For each English word and language, target tokens are scored by Dice co-occurrence with the English token over Tatoeba pairs, character 1 to 3-grams for Chinese, Japanese and Thai, and the top three with count at least three are the references [empirical: dataset v1 reports/regression_report.json sha256 64a4ec7a, 2026-11-06, charizard CPU: python3 apple/scripts/embed/regression.py]. A first choice is right when it equals a reference, shares its first four letters with one, or for the unspaced languages contains or is contained in one.

5 Results

5.1 Re-ranked lexicon

Table 1: Held-out odd rows of the Tatoeba-aligned word set, 2,325 words, Python replica of the app lookup [empirical: dataset v1 reports/rerank_report.json sha256 968b6767, 2026-11-06, charizard CPU: CUDA_VISIBLE_DEVICES= python3 apple/scripts/embed/rerank.py].

Precision, percent	before	after
First shown sense	58.0	68.3
Any shown sense, longer answers	67.3	78.5

On the held-out half, first-sense precision rises from 58.0% to 68.3% [empirical: dataset v1 reports/rerank_report.json sha256 968b6767, 2026-11-06, charizard CPU: CUDA_VISIBLE_DEVICES= python3 apple/scripts/embed/rerank.py]. The mean answer grew from 5.35 to 8.58 words, because gloss senses are phrases [empirical: dataset v1 out/rerank lexicon, 2026-11-06, charizard CPU: python3 apple/scripts/embed/answer_length.py]; any-token precision, which counts a hit anywhere in that longer answer, rises from 67.3% to 78.5% on the same rows [empirical: dataset v1 reports/rerank_report.json sha256 968b6767, 2026-11-06, charizard CPU: CUDA_VISIBLE_DEVICES= python3 apple/scripts/embed/rerank.py].

Table 2: Held-out odd rows per language, percent: first-sense precision, then any-token precision [empirical: dataset v1 reports/rerank_report.json sha256 968b6767, 2026-11-06, charizard CPU: CUDA_VISIBLE_DEVICES= python3 apple/scripts/embed/rerank.py].

		first sense			any token	
Lang	n	before	after	change	before	after
es	100	69.0	78.0	+9.0	76.0	89.0
fr	100	64.0	83.0	+19.0	70.0	92.0
it	100	66.0	72.0	+6.0	76.0	87.0
pt	100	67.0	79.0	+12.0	74.0	88.0
de	100	63.0	74.0	+11.0	76.0	90.0
nl	100	77.0	82.0	+5.0	81.0	91.0
sv	100	59.0	66.0	+7.0	70.0	80.0
pl	100	59.0	74.0	+15.0	71.0	86.0
fi	100	60.0	75.0	+15.0	68.0	85.0
ru	100	60.0	73.0	+13.0	69.0	81.0
el	100	63.0	73.0	+10.0	69.0	81.0
ar	100	49.0	61.0	+12.0	65.0	69.0
hi	34	47.1	47.1	+0.0	50.0	50.0
ja	100	49.0	59.0	+10.0	59.0	71.0
zh	100	50.0	61.2	+11.2	58.2	66.3
ko	88	36.4	39.8	+3.4	47.7	51.1
he	100	50.0	58.0	+8.0	62.0	71.0
fa	100	54.0	68.0	+14.0	65.0	76.0
tr	100	51.0	69.0	+18.0	59.0	74.0
cs	100	74.0	82.0	+8.0	83.0	89.0
id	100	60.0	66.0	+6.0	72.0	76.0
vi	100	36.0	48.0	+12.0	45.0	58.0
th	100	57.0	64.0	+7.0	68.0	74.0
la	100	63.0	71.0	+8.0	68.0	87.0
sa	3	0.0	33.3	+33.3	33.3	33.3

5.2 English-to-target audit

Table 3: Model audit of English-to-target first answers, 100 items drawn by hash from the 1,488 of 4,848 cases where the two orders differ. Judged by Claude Opus 5.5 against the common Wiktionary sense and Tatoeba usage; this is a model audit, and no human checked it [empirical: dataset v1 reports/audit_report.json sha256 c63af75e, 2026-11-06, python3 apple/scripts/embed/audit_sample.py, then python3 apple/scripts/embed/audit_judge.py].

Order	items	right
Frequency order	100	60
Re-ranked	100	91

Re-ranking changes the first English-to-target answer for 1,488 of 4,848 common or polysemous English words across the languages [empirical: dataset v1 reports/audit_report.json sha256 c63af75e, 2026-11-06, python3 apple/scripts/embed/audit_sample.py, then python3 apple/scripts/embed/audit_judge.py]. In 100 of them the frequency order was right 60 times and the re-ranked order 91 times [empirical: dataset v1 reports/audit_report.json sha256 c63af75e, 2026-11-06, python3 apple/scripts/embed/audit_sample.py, then python3 apple/scripts/embed/audit_judge.py]. Typical repairs: *concrete* to Finnish *konkreettinen* stays, *wind* to Finnish moves from *kiemurrella* (to meander) to *tuuli*, *root* to Czech from *odmocnina* (square root) to *kořen*. Typical new errors: *why* to Spanish moves from *por qué* to *por*, and *hot* to Korean to a loanword. Against Tatoeba-derived references on the held-out half of the common English words, first-choice accuracy rises from 60.6% to 68.0% [empirical: dataset v1 reports/rerank_report.json sha256 968b6767, 2026-11-06, charizard CPU: CUDA_VISIBLE_DEVICES= python3 apple/scripts/embed/rerank.py]. The English-to-target Wiktionary row of the app evaluation falls from 94.7% to 89.9% [empirical: data/swift_before.txt and data/swift_after.txt, 2026-11-06, Mac: TRANSLATE_EVAL=current swift test –package-path BucketKit –filter translateEvalReport], because its references are the frequency-ordered translation lists themselves.

5.3 Polysemous case study

The ten words good, right, light, fair, well, kind, mean, bank, play and run were added after the founder saw *good* become *akhil* in Hebrew. They were not held out from the design of the English-to-target prior, so they are a case study: the first choice matches a Tatoeba-derived reference in 109 of 158 language cases after re-ranking and 81 before [empirical: dataset v1 reports/regression_report.json sha256 64a4ec7a, 2026-11-06, charizard CPU: python3 apple/scripts/embed/regression.py], and *good* to Hebrew now gives *tov*.

5.4 App evaluation

In the app evaluation the Tatoeba word row rises from 67.5% to 77.2%, phrase precision from 14.1% to 17.2% and sentence precision from 7.7% to 9.9% [empirical: data/swift_before.txt and data/swift_after.txt, 2026-11-06, Mac: TRANSLATE_EVAL=current swift test –package-path BucketKit –filter translateEvalReport]; the Wiktionary row stays at 98.7% [empirical: data/swift_before.txt and data/swift_after.txt, 2026-11-06, Mac: TRANSLATE_EVAL=current swift test –package-path BucketKit –filter translateEvalReport]. These rows include the even rows used for tuning and reward longer answers. The CI floor test passes. On the iPhone 17 Pro simulator, a Debug build loads and parses one lexicon in 664 to 2,106 ms off the main thread, and six loads through the four-slot cache peak at 67.1 MB of process footprint

Table 4: App evaluation, `TranslateEvalTests`, target word to English, all rows including the tuning rows, any-token precision in percent. Secondary to 2 [empirical: data/swift_before.txt and data/swift_after.txt, 2026-11-06, Mac: TRANSLATE_EVAL=current swift test –package-path BucketKit –filter translateEvalReport].

	Tatoeba word row			Wiktionary row	
Lang	before	after	change	before	after
es	74.5	88.0	+13.5	99.6	99.6
fr	74.5	87.0	+12.5	99.5	99.5
it	75.5	88.0	+12.5	99.0	99.0
pt	76.5	89.5	+13.0	99.5	99.5
de	76.5	88.5	+12.0	98.9	98.9
nl	80.0	90.0	+10.0	99.7	99.7
sv	73.5	84.0	+10.5	98.4	98.5
pl	68.5	82.5	+14.0	98.5	98.5
fi	67.0	82.5	+15.5	99.4	99.4
ru	68.0	79.5	+11.5	99.9	99.9
el	73.5	82.0	+8.5	99.2	99.2
ar	62.5	66.0	+3.5	100.0	100.0
hi	52.9	55.9	+3.0	99.3	99.3
ja	59.0	71.5	+12.5	100.0	100.0
zh	64.1	68.7	+4.6	99.8	99.8
ko	48.9	52.8	+3.9	99.3	99.4
he	63.5	71.0	+7.5	99.4	99.6
fa	65.5	74.5	+9.0	99.9	99.9
tr	60.5	73.0	+12.5	99.5	99.5
cs	81.5	89.5	+8.0	99.8	99.8
id	75.0	79.0	+4.0	99.3	99.3
vi	32.5	39.5	+7.0	81.5	81.5
th	62.5	69.0	+6.5	98.7	98.7
ta	0.0	0.0	+0.0	99.5	99.5
la	72.5	84.5	+12.0	99.7	99.7
sa	42.9	42.9	+0.0	98.9	98.9
all	67.5	77.2	+9.7	98.7	98.7




Figure 1: Tatoeba-aligned word row per language in the app evaluation, any-token precision, all rows [empirical: data/swift_before.txt and data/swift_after.txt, 2026-11-06, Mac: TRANSLATE_EVAL=current swift test –package-path BucketKit –filter translateEvalReport].

[empirical: data/lexicon_bench.txt, 2026-11-06, Mac: TEST_RUNNER_LEXICON_BENCH=1 xcodebuild test -scheme BucketKit -destination iPhone 17 Pro simulator -only-testing lexiconLoadBench].

5.5 Each embedding on its own task

Table 5: Unicode confusable pairs, 924 single letters, ranked among a pool of 4,996 letters [empirical: dataset v1 reports/script_report.json sha256 3931c793, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/script_eval.py].

View	R@1	R@10	MRR
Script CNN	37.2	55.2	0.432
Raw pixels	34.8	48.5	0.397
Character n-grams	0.2	0.2	0.003

The script CNN finds the listed confusable of a letter in its top ten for 55.2% of pairs against 48.5% for raw pixel cosine [empirical: dataset v1 reports/script_report.json sha256 3931c793, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/script_eval.py]; character n-grams cannot, since distinct code points share no n-gram. For fuzzy search with one random edit per word, character n-grams recover the word at rank one in 73.7% of cases on average over 12 languages and the CNN in 52.8% [empirical: dataset v1 reports/script_report.json sha256 3931c793, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/script_eval.py]; their sum reaches 77.2% [empirical: dataset v1 reports/script_report.json sha256 3931c793, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/script_eval.py]. For a swap to a visual confusable the CNN reaches 85.1% and the sum 93.6%, against 77.6% for n-grams [empirical: dataset v1 reports/script_report.json sha256 3931c793, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/script_eval.py].

The phonetic view finds homophones better than character n-grams in 23 of 27 languages with enough pairs, mean R@10 80.2% against 62.3% [empirical: dataset v1 reports/phonetic_report.json sha256 5273260e, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/phonetic.py]. The

Table 6: Fuzzy search R@1 in percent within each language's vocabulary [empirical: dataset v1 reports/script_report.json sha256 3931c793, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/script_eval.py].

	one random edit			confusable swap		
Lang	CNN	n-gram	sum	CNN	n-gram	sum
es	59.6	72.4	77.4	92.9	75.9	95.8
de	67.1	77.8	82.0	96.0	79.5	98.1
ru	67.1	81.1	85.7	99.4	83.5	99.2
el	64.5	85.3	88.5	97.8	85.1	98.7
ar	28.4	55.8	55.5	44.4	59.2	71.8
he	28.2	57.0	57.7	65.2	63.4	87.2
hi	32.3	67.9	64.6	100.0	96.4	100.0
ta	51.5	77.7	75.2	69.3	81.4	91.1
th	46.6	76.2	77.7	93.3	74.6	94.0
ja	49.3	70.3	81.0	92.0	70.0	96.2
zh	87.9	90.6	97.6	85.4	84.5	97.1
ko	50.9	72.4	83.4	–	–	–

gain is largest where spelling hides sound: Chinese 81.3% against 6.5%, Korean 87.8% against 7.6%, Japanese 33.7% against 5.6% [empirical: dataset v1 reports/phonetic_report.json sha256 5273260e, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/phonetic.py].




Figure 2: Bilingual lexicon induction, target word to English among 26,887 English words, P@10 averaged over 28 languages, test headwords only [empirical: dataset v1 reports/joint_report.json sha256 11b0b40e, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/joint.py].

Meaning carries translation: P@10 57.1% on average, against 10.8% for script, 11.3% for character and 5.6% for phonetic [empirical: dataset v1 reports/joint_report.json sha256 11b0b40e, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/joint.py]. The joint projection reaches 58.9% P@10 and 36.0% P@1, against 37.1% P@1 for meaning alone [empirical: dataset v1 reports/joint_report.json sha256 11b0b40e, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/joint.py]; the weighted form matches meaning within 0.1 points [empirical: dataset v1 reports/joint_report.json sha256 11b0b40e, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/joint.py]. Across related language pairs, 9, the phonetic view is the one form-based view that

Table 7: Phonetic view. G2P: the grapheme model on held-out WikiPron words, mean cosine to the IPA vector and R@10 among 3,000. Homophones: distinct spellings with identical IPA, query and pool both predicted from spelling, R@10 in percent for phonetic and character views [empirical: dataset v1 reports/phonetic_report.json sha256 5273260e, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/phonetic.py].

Lang	WikiPron	IPA rows	G2P cos	G2P R@10	pairs		phon	char
en	79306	8198/26887	0.913	57.4	1000	76.5	55.8	
es	131056	15650/22864	0.965	94.8	1000	96.3	85.6	
fr	84402	14929/20813	0.918	65.8	1000	93.8	87.2	
it	81441	14414/19915	0.957	93.1	302	84.4	77.8	
pt	56305	12806/18250	0.944	80.2	977	85.6	71.8	
de	51318	10219/20538	0.923	60.3	671	86.9	75.9	
nl	45234	11852/19425	0.927	61.9	779	84.5	75.2	
sv	5054	3060/22446	0.828	5.5	72	81.9	63.9	
pl	146081	16759/18832	0.949	94.8	1000	92.9	76.3	
fi	150000	14490/21587	0.959	93.0	216	72.2	75.5	
ru	149999	5675/17355	0.954	89.9	1000	99.5	97.3	
el	19008	6367/14964	0.934	57.9	1000	97.1	71.4	
ar	14272	6952/14265	0.908	74.6	97	48.5	76.3	
hi	30379	12189/14862	0.909	66.0	832	73.7	85.5	
ja	44247	11607/18346	0.867	18.4	1000	33.7	5.6	
zh	147316	8052/19348	0.886	72.4	1000	81.3	6.5	
ko	30421	16320/20247	0.927	79.3	370	87.8	7.6	
he	2872	2782/15001	0.821	13.5	45	88.9	42.2	
fa	10728	10253/17162	0.862	31.6	117	85.5	53.8	
tr	11436	8007/20509	0.889	23.1	–	–	–	
cs	63095	21081/22952	0.950	97.3	849	95.5	76.2	
id	17810	11381/17605	0.916	45.9	47	66.0	57.4	
vi	26978	11920/23449	0.893	62.6	527	53.7	23.1	
th	17221	13457/14174	0.845	34.8	589	63.7	55.9	
ta	10095	9345/10873	0.906	57.0	–	–	–	
la	41656	1080/16014	0.946	90.0	496	95.6	90.1	
grc	57540	11293/13020	0.946	80.7	1000	94.4	53.6	
sa	9796	8796/10361	0.894	37.1	30	53.3	56.7	
ang	54514	14744/17067	0.951	95.0	675	93.2	78.8	

Table 8: Bilingual lexicon induction P@10 in percent per language and view; gold is the Wiktionary candidate set [empirical: dataset v1 reports/joint_report.json sha256 11b0b40e, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/joint.py].

Lang	n	script	char	phon	meaning	weighted	projection
es	506	26.3	28.5	12.1	68.4	68.4	71.3
fr	540	35.0	38.3	14.1	72.2	72.4	74.3
it	479	25.3	28.6	10.6	71.6	71.8	74.1
pt	454	31.3	31.5	9.5	74.2	74.4	77.5
de	456	20.6	24.3	10.5	65.4	65.6	67.1
nl	477	27.9	27.7	15.5	72.3	72.1	75.7
sv	428	25.5	25.5	5.6	64.0	63.8	64.7
pl	391	16.6	16.9	10.7	76.0	76.5	77.0
fi	542	7.4	8.3	2.4	55.5	55.7	55.7
ru	416	3.1	0.2	4.1	72.6	71.9	73.3
el	698	1.3	0.1	2.6	59.0	59.5	61.7
ar	758	0.1	0.1	0.0	17.8	17.7	23.6
hi	630	0.2	0.2	6.2	59.5	59.2	61.3
ja	359	0.0	0.3	4.5	72.7	72.1	73.5
zh	156	0.0	0.0	1.3	67.9	67.3	67.9
ko	670	0.0	0.0	8.5	61.8	62.2	62.8
he	460	0.0	0.2	0.4	37.0	36.5	38.7
fa	449	0.2	0.2	3.3	40.8	41.2	44.5
tr	681	11.0	12.0	3.1	54.6	54.9	55.2
cs	703	17.8	16.6	7.7	63.0	63.2	67.1
id	421	21.1	23.0	6.9	69.1	69.1	71.0
vi	498	6.6	4.4	0.4	59.2	60.0	60.4
th	418	0.2	0.2	4.3	61.2	62.2	59.6
ta	213	0.0	0.0	0.9	61.0	61.0	63.4
la	510	16.1	18.8	1.2	40.4	41.2	41.8
grc	284	0.0	0.0	2.8	25.0	25.4	26.8
sa	136	0.0	0.0	0.0	37.5	37.5	40.4
ang	148	7.4	10.8	6.8	17.6	17.6	18.2
mean		10.8	11.3	5.6	57.1	57.2	58.9

crosses scripts: Russian to Polish R@10 9.7% against 0.3% for character n-grams [empirical: dataset v1 reports/joint_report.json sha256 11b0b40e, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/joint.py].

Table 9: Translation retrieval between related languages, R@10 in percent [empirical: dataset v1 reports/joint_report.json sha256 11b0b40e, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/joint.py].

Pair	n	script	char	phon	meaning	weighted	projection
es-pt	417	56.4	55.2	38.8	78.4	78.7	77.0
es-it	411	41.1	36.7	36.7	69.1	70.8	71.5
fr-it	402	31.8	30.3	12.4	68.4	69.7	68.9
de-nl	341	30.5	35.2	27.9	68.3	69.8	67.7
sv-de	350	28.6	31.1	8.6	58.3	60.6	60.3
cs-pl	355	33.5	23.4	25.9	71.0	71.0	69.6
ru-pl	298	3.7	0.3	9.7	76.8	75.8	75.8
hi-sa	257	20.2	26.1	13.6	41.6	40.9	41.6
ar-fa	433	19.2	8.3	3.7	23.1	24.0	27.7
ja-zh	133	30.8	31.6	0.0	66.9	66.9	65.4
el-grc	255	36.1	33.7	19.6	42.4	42.7	45.5
la-it	353	22.1	22.7	2.5	39.9	40.2	41.6

6 Calibration

Every hyperparameter was chosen on one half of an evaluation set and is reported on the other half, 1 and 5.2. The Python replica of the app lookup gave 66.8% any-token precision on the full Tatoeba row for the lexicon of pull request 1198, where the Swift evaluation gave 67.5% [empirical: dataset v1 lexicon of PR 1198, 2026-11-06, charizard CPU: python3 apple/scripts/embed/pyeval.py lexicon, and data/swift_before.txt]; the replica skips the deck corpus layer, clitic stripping and NLTagger lemmas, which accounts for the 0.7 point gap. A rebuild of pull request 1198's lexicon with this pipeline in dump mode reproduces every line of every file. The Tatoeba references are noisy: they are the three English words that co-occur most with the target word, so a right sense that is less frequent in Tatoeba counts as wrong. The error budget for the headline is the sampling error of a proportion near 0.68 over 2,325 held-out words, a standard error of 0.97 points, small next to the 10.3 point change [empirical: dataset v1 reports/rerank_report.json sha256 968b6767, 2026-11-06, charizard CPU: CUDA_VISIBLE_DEVICES= python3 apple/scripts/embed/rerank.py]. The audit covers 100 items, so its 31 point gap carries a standard error near 5.7 points [empirical: dataset v1 reports/audit_report.json sha256 c63af75e, 2026-11-06, python3 apple/scripts/embed/audit_sample.py, then python3 apple/scripts/embed/audit_judge.py].

7 Limitations

The English-to-target audit is a model audit; a human audit of the same 100 items would settle it. LaBSE has no Latin, Ancient Greek, Sanskrit or Old English training data, so meaning scores there lean on shared subwords. The phonetic view ignores tone, so Mandarin, Thai and Vietnamese homophones that differ by tone collapse. Swedish and Hebrew have 5,054 and 2,872 WikiPron entries, too few for a good grapheme model: G2P R@10 is 5.5% and 13.5% [empirical: dataset v1

reports/phonetic_report.json sha256 5273260e, 2026-11-06, charizard RX 7600 ROCm 6.4 torch 2.9.1: python3 apple/scripts/embed/phonetic.py]. The script CNN trains on weight changes of one font family per script, so it learns little about handwriting or other typefaces. Tamil has no usable Tatoeba-aligned references, since the alignment tokenizer splits Tamil vowel signs. The joint projection improves P@10 but not P@1 over meaning, and the re-ranker selected the meaning cosine; the joint vectors ship in the dataset and stay out of the app.

Licenses. Wiktionary data through kaikki.org and WikiPron is CC BY-SA 4.0, and the re-ranked lexicon and dataset carry it. Tatoeba sentences are CC BY 2.0 FR. Noto fonts are SIL OFL 1.1. LaBSE is Apache 2.0. PanPhon is MIT.

References

[1] Fangxiaoyu Feng et al. *Language-agnostic BERT Sentence Embedding*. 2020. arXiv: 2007.01852 [cs.CL].

[2] Alexis Conneau et al. *Word Translation Without Parallel Data*. 2017. arXiv: 1710.04087 [cs.CL].

[3] Piotr Bojanowski et al. *Enriching Word Vectors with Subword Information*. 2016. arXiv: 1607.04606 [cs.CL].

[4] Elizabeth Salesky, David Etter, and Matt Post. *Robust Open-Vocabulary Translation from Visual Text Representations*. 2021. arXiv: 2104.08211 [cs.CL].

[5] Phillip Rust et al. *Language Modelling with Pixels*. 2022. arXiv: 2207.06991 [cs.CL].

[6] Ting Chen et al. *A Simple Framework for Contrastive Learning of Visual Representations*. 2020. arXiv: 2002.05709 [cs.LG].

[7] Aaron van den Oord, Yazhe Li, and Oriol Vinyals. *Representation Learning with Contrastive Predictive Coding*. 2018. arXiv: 1807.03748 [cs.LG].

[8] Jörg Tiedemann. *The Tatoeba Translation Challenge: Realistic Data Sets for Low Resource and Multilingual MT*. 2020. arXiv: 2010.06354 [cs.CL].

A Glossary

lexicon https://github.com/bucket-foundation/bucket-foundation/blob/feat/apple-translate-embed/apple/scripts/translate/build_lexicon.py
The per-language Polingual word list: each headword with up to four English meanings, a gloss, a romanization, form links and English-to-target lists; see 3.1.

modality https://github.com/bucket-foundation/bucket-foundation/blob/feat/apple-translate-embed/apple/scripts/embed/common.py
One of the four word views embedded here: script, character, phonetic, meaning; see 3.2.

joint score https://github.com/bucket-foundation/bucket-foundation/blob/feat/apple-translate-embed/apple/scripts/embed/joint.py
A weighted sum of per-modality cosines, or the cosine of a learned projection of all four vectors; see 3.3.

precision https://github.com/bucket-foundation/bucket-foundation/blob/feat/apple-translate-embed/apple/BucketKit/Tests/BucketKitTests/TranslateEvalTests.swift
Judged answers marked right divided by judged answers; see 3.4.

B Lean listings

`lean/Bucket/Embed.lean` states the dot product, the joint score, precision in whole percent and sense filtering, and proves that the meaning-only joint score is the meaning cosine, that precision is at most 100 when right answers do not exceed judged ones, and that filtering senses never lengthens a list.

```
def jointScore (w c : List Int) : Int := dot w c
theorem jointScore_meaning_only (s p c m : Int) :
    jointScore [0, 0, 0, 1] [s, p, c, m] = m
def precisionPct (right judged : Nat) : Nat := right * 100 / judged
theorem precisionPct_le (right judged : Nat) (h : right <= judged) :
    precisionPct right judged <= 100
theorem keepSenses_length (keep : a -> Bool) (senses : List a) :
    (keepSenses keep senses).length <= senses.length
```

`lake build` output, captured by `make lean`. This block is a verbatim transcript.

```
info: polingual_embeddings: no previous manifest, creating one from scratch
info: toolchain not updated; already up-to-date
Built Bucket.Embed (1.0s)
Built Bucket (157ms)
Build completed successfully (4 jobs).
```