

计算物理作业 1

杨远青 22300190015

2024 年 9 月 14 日

1 题目 1：五次幂丢番图方程

1.1 题目描述

Find all integer solutions to the **Diophantine equation** $a^5 + b^5 + c^5 + d^5 = e^5$ within the range $[0, 200]$.

1.2 程序描述

1967 年, Lander 和 Parkin 使用 CDC 6600 计算机首次找到方程

$$a^5 + b^5 + c^5 + d^5 = e^5$$

的一个解, 即

$$27^5 + 84^5 + 110^5 + 133^5 = 144^5$$

这个解也推翻了欧拉的幂和猜想 (即至少需要 k 个 k 次幂才能表示另一 k 次幂的和, 且 $k \geq 2$)。相关参考资料可参见 [Diophantine Equation—5th Powers](#)。2004 年, J. Frye 使用分布式并行计算找到了第二个解:

$$55^5 + 3183^5 + 28969^5 + 85282^5 = 85359^5$$

题目要求我们找到所有满足 $0 \leq a \leq b \leq c \leq d < e \leq 200$ 的整数解

为了解决这个问题, 我们首先采用暴力搜索的方法, 遍历所有可能的 a, b, c, d, e 组合, 并逐一检查是否满足方程。在 `brute_force.f90` 中实现了这一方法, 其伪代码见算法 1。该程序的运行时间达到了 8.953 秒, 速度较为缓慢。

在网络上寻找更优解法时, 我偶然发现了一个专门讨论整数幂方程的论坛: [Euler Free](#)。该论坛提到可以通过数论优化的方法。注意到方程中的 x^5 是齐次的, 首先想到费马小定理:

$$a^p \equiv a \pmod{p}, \quad \text{where } p \text{ is a prime number.}$$

基于此, 在搜索时可以将步长扩大到 5。然而, 进一步查阅 Lander 和 Parkin 的论文后, 未能找到有效的进一步启发。在 Rosetta Code 网站上, 我发现了 C 语言中使用的 [Mod30 Trick](#), 这让我意识到可以进一步扩展费马小定理的应用范围。即我们可以证明:

$$a^5 \equiv a \pmod{30}$$

这意味着在搜索时可以将步长扩展到 30。具体而言，对于 $n = 2, 3, 5$ ，我们可以分别讨论奇偶性和模数的同余关系：- 对于 $n = 2$ ，由于奇偶性，显然有 $a^5 \equiv a \pmod{2}$ 。

- 对于 $n = 3$ ：- 若 $\gcd(a, 3) = 1$ ，则 $a^2 \equiv 1 \pmod{3}$ ，因此

$$a^5 = a \cdot (a^2)^2 \equiv a \cdot 1^2 \equiv a \pmod{3}$$

- 若 $3 \mid a$ ，则 $a \equiv 0 \pmod{3}$ ，因此 $a^5 \equiv 0 \pmod{3}$ 。- 对于 $n = 5$ ：- 若 $\gcd(a, 5) = 1$ ，则 $a^4 \equiv 1 \pmod{5}$ ，因此

$$a^5 = a \cdot a^4 \equiv a \cdot 1 \equiv a \pmod{5}$$

- 若 $5 \mid a$ ，则 $a \equiv 0 \pmod{5}$ ，因此 $a^5 \equiv 0 \pmod{5}$ 。

根据中国剩余定理，我们得出： $a^5 \equiv a \pmod{30}$

利用这个技巧，我们得到了算法 2，经测试，其 Fortran 实现的运行时间缩短至 0.797 秒。此外，通过反向查找，即从 e 开始，结合 mod30 技巧，我们进一步优化了算法，得到了算法 3，运行时间进一步缩短至 0.438 秒。

尽管运行时间有所改善，但 mod30 技巧只是常数级别的优化，不能显著加快找到第二个非平凡解的速度。为了进一步降低算法的复杂度，我们尝试将暴力搜索的时间复杂度从 $\mathcal{O}(N^5)$ 降低至 $\mathcal{O}(N^3)$ 。最自然的想法是使用哈希表和分治法。遗憾的是，Fortran 对哈希表的支持较为有限，通常需要依赖外部库，而我对其实现原理尚不完全理解。

因此，我决定使用 Python 进行对比研究，并通过哈希法和多线程进一步优化搜索过程。

1.3 伪代码

Algorithm 1: Brute-force solution to the Diophantine equation

Input: N : Integer (the upper bound, $N = 200$)

Output: *solutions*: List of tuples (a, b, c, d, e) where $0 \leq a \leq b \leq c \leq d < e \leq N$

```

1 for  $a \leftarrow 0$  to  $N$  do
2   for  $b \leftarrow a$  to  $N$  do
3     for  $c \leftarrow b$  to  $N$  do
4       for  $d \leftarrow c$  to  $N$  do
5         for  $e \leftarrow d + 1$  to  $N$  do
6           if  $a^5 + b^5 + c^5 + d^5 = e^5$  then
7             |  $solutions.append((a, b, c, d, e))$ ;           // Store the solution tuple
8           end
9         end
10      end
11    end
12  end
13 end
14 return solutions

```

Algorithm 2: Mod30 trick for solving the Diophantine equation

Input: N : Integer (the upper bound, $N = 200$)

Output: *solutions*: List of tuples (a, b, c, d, e)
where $1 \leq a \leq b \leq c \leq d < e \leq N$

```

1 for  $a \leftarrow 1$  to  $N$  do
2   for  $b \leftarrow a$  to  $N$  do
3     for  $c \leftarrow b$  to  $N$  do
4       for  $d \leftarrow c$  to  $N$  do
5          $r\_left \leftarrow \text{mod}(a + b + c + d, 30)$  ;
          // Compute remainder for  $e$ 
6          $e\_start \leftarrow$ 
           $d + ((r\_left - d) \bmod 30)$  ;
          // Ensure  $e \geq d$  and
           $a + b + c + d \equiv e \pmod{30}$ 
7         for  $e \leftarrow e\_start$  to  $N$  do
8           if  $(e - e\_start) \bmod 30 = 0$ 
9             then
10              // Increase the step
               size to 30
11              if  $a^5 + b^5 + c^5 + d^5 = e^5$ 
12                then
13                   $solutions.append((a, b, c, d, e))$ 
14                end
15              end
16            end
17          end
18        end
19      end
20    end
21  end
22 end
23 return solutions

```

Algorithm 3: Reverse Mod30 trick for solving the Diophantine equation

Input: N : Integer (the upper bound, $N = 200$)

Output: *solutions*: List of tuples (a, b, c, d, e)
where $1 \leq a \leq b \leq c \leq d < e \leq N$

```

1 for  $e \leftarrow N$  to 1 do
2   for  $d \leftarrow e$  to 1 do
3     for  $c \leftarrow d$  to 1 do
4       for  $b \leftarrow c$  to 1 do
5          $a\_min \leftarrow (e - d - c - b) \bmod 30$  ;
          // Compute minimal  $a$  using
          modular arithmetic
6         if  $a\_min \leq 0$  then
7            $a\_min \leftarrow a\_min + 30$  ;
          // Adjust  $a\_min$  to fit
          within the modulus
8         end
9         for  $a \leftarrow a\_min$  to  $b$  do
10          if  $(a - a\_min) \bmod 30 = 0$ 
11            then
12              if  $a^5 + b^5 + c^5 + d^5 = e^5$ 
13                then
14                   $solutions.append((a, b, c, d, e))$ 
15                end
16              end
17            end
18          end
19        end
20      end
21    end
22  end
23 end
24 return solutions

```

Algorithm 4: Brute-force solution using a single hash

Input: *limit*: Upper bound

Output: *solution*: Tuple (a, b, c, d, e) or None

```
1 pow_5  $\leftarrow [n^5 \text{ for } n \text{ in } [0, \textit{limit}]]$  ; // List of  $n^5$  values
2 pow5_to_n  $\leftarrow \{n^5 : n \text{ for } n \text{ in } [0, \textit{limit}]\}$  ; // Dictionary mapping  $n^5$  to  $n$ 
3 for  $a \leftarrow 1$  to limit do
4   for  $b \leftarrow a$  to limit do
5     for  $c \leftarrow b$  to limit do
6       for  $d \leftarrow c$  to limit do
7          $\textit{pow\_5\_sum} \leftarrow \textit{pow\_5}[a] + \textit{pow\_5}[b] + \textit{pow\_5}[c] + \textit{pow\_5}[d]$  if  $\textit{pow\_5\_sum}$  in pow5_to_n
8           then
9              $e \leftarrow \textit{pow5\_to\_n}[\textit{pow\_5\_sum}]$  return  $(a, b, c, d, e)$ 
10          end
11        end
12      end
13 end
14 return None
```

Algorithm 5: Parallel brute-force solution using double hash

Input: *limit*: Upper bound

Output: *solution*: Tuple (a, b, c, d, e) or None

```
1 power_5  $\leftarrow \{i^5 : i \text{ in } [1, \textit{limit}]\}$  ; // Dictionary of fifth powers
2 sum2  $\leftarrow \{\}$  ; // Dictionary to store sums of two fifth powers
3 for  $i \leftarrow 1$  to limit // Parallelized computation do
4    $a5 \leftarrow i^5$  for  $j \leftarrow i$  to limit do
5      $\textit{sum2}[a5 + j^5] \leftarrow (i, j)$ 
6   end
7 end
8  $sk \leftarrow$  sorted keys of sum2 foreach  $p$  in sorted(power_5.keys()) do
9   foreach  $s$  in sk do
10    if  $p \leq s$  then
11      break ; // Exit the loop early if no further solutions are possible
12    end
13    if  $p - s$  in sum2 then
14      return  $(\textit{power\_5}[p], \textit{sum2}[s], \textit{sum2}[p - s])$ 
15    end
16  end
17 end
18 return None
```

1.4 输入输出示例

<pre>PS D:\BaiduSyncdisk\Work\Courses\Junior Fall\CompPhys> & 'c:\Users\Gilbert\.vscode\extensions\ms-vscode.cpptools-1.22.3-win32-x64\debugAdapters\bin\WindowsDebugLauncher.exe' '--stdin=Microsoft-MIEngine-In-hdl1jd4j.jls' '--stdout=Microsoft-MIEngine-Out-4psoirjy.ock' '--stderr=Microsoft-MIEngine-Error-vnkasmm.jxs' '--pid=Microsoft-MIEngine-Pid-bexkdd1.fq4' --dbgExe=c:\Strawberry\c\bin\gdb.exe' --interpreter=mi' Solution:27^5+84^5+110^5+133^5=144^5 Elapsed time for brute_force: 8.95312500000 00000 seconds</pre>	<pre>PS D:\BaiduSyncdisk\Work\Courses\Junior Fall\CompPhys> & 'c:\Users\Gilbert\.vscode\extensions\ms-vscode.cpptools-1.22.3-win32-x64\debugAdapters\bin\WindowsDebugLauncher.exe' '--stdin=Microsoft-MIEngine-In-2px200w.i0j' '--stdout=Microsoft-MIEngine-Out-5br4udb3.in4' '--stderr=Microsoft-MIEngine-Error-as1iztba.vij' '--pid=Microsoft-MIEngine-Pid-ikcnqoq3.ft1' --dbgExe=c:\Strawberry\c\bin\gdb.exe' --interpreter=mi' Solution:27^5+84^5+110^5+133^5=144^5 Elapsed time for mod30_trick: 0.796875000000 00000 seconds</pre>	<pre>PS D:\BaiduSyncdisk\Work\Courses\Junior Fall\CompPhys> & 'c:\Users\Gilbert\.vscode\extensions\ms-vscode.cpptools-1.22.3-win32-x64\debugAdapters\bin\WindowsDebugLauncher.exe' '--stdin=Microsoft-MIEngine-In-s4ikkeas.i1p' '--stdout=Microsoft-MIEngine-Out-zbwvqsm.3ng' '--stderr=Microsoft-MIEngine-Error-j4b1q4o4.x5n' '--pid=Microsoft-MIEngine-Pid-0ncw1xye.hsz' --dbgExe=c:\Strawberry\c\bin\gdb.exe' --interpreter=mi' Solution:27^5+84^5+110^5+133^5=144^5 Elapsed time for mod30_trick_reverse: 0.4375 00000000000000 seconds</pre>
---	---	--

图 1: 程序运行结果

<pre>PS D:\BaiduSyncdisk\Work\Courses\Junior Fall\CompPhys> & C:/ProgramData/anaconda3/python.exe "d:/BaiduSyncdisk/Work/Courses/Junior Fall/CompPhys/repo/Week 1/Codes/brute_force.py" Solution: 27^5 + 84^5 + 110^5 + 133^5 = 144^5 Total time: 3.929487 seconds</pre>	<pre>PS D:\BaiduSyncdisk\Work\Courses\Junior Fall\CompPhys> & C:/ProgramData/anaconda3/python.exe "d:/BaiduSyncdisk/Work/Courses/Junior Fall/CompPhys/repo/Week 1/Codes/hash_quick.py" Solution: 27^5 + 84^5 + 110^5 + 133^5 = 144^5 Total time: 0.055831 seconds</pre>
---	--

图 2: 程序运行结果