DAY 2 -

1. `<h1>` to `<h6>` (Headings):

   - These tags are used to define headings of different levels, with `<h1>` being the highest and most important level, and `<h6>` the lowest.

   - Headings provide structure and hierarchy to your content, with `<h1>` typically used for the main title of a page or section, and `<h2>` to `<h6>` for subsections and subheadings.

2. `<p>` (Paragraph):

   - The `<p>` tag is used to define paragraphs of text.

   - It separates blocks of text, making it easier to structure and format content.

3. `<b>` (Bold):

   - The `<b>` tag is used to apply bold formatting to text.

   - It makes the enclosed text visually stand out.

4. `<i>` (Italic):

   - The `<i>` tag is used to apply italic formatting to text.

   - It is often used for emphasizing or styling text differently.

5. `<sup>` (Superscript) and `<sub>` (Subscript):

   - `<sup>` is used for superscript text (raised above the baseline), commonly used for mathematical notations like exponents.

   - `<sub>` is used for subscript text (lowered below the baseline), often used in chemical formulas and footnotes.

6. `<br>` (Line Break):

   - The `<br>` tag is a self-closing tag used to insert a line break within text or between elements.

   - It creates a new line without starting a new paragraph.

7. `<hr>` (Horizontal Rule):

   - The `<hr>` tag inserts a thematic horizontal line or rule to visually separate content sections.

- It is often used to break up content or add visual dividers.

8. `<strong>` (Strong):

   - The `<strong>` tag is used to indicate strong importance or emphasis on text.

   - It typically renders text as bold, but its primary purpose is semantic, indicating importance rather than visual styling.

9. `<em>` (Emphasis):

   - The `<em>` tag is used to emphasize or give importance to text.

   - It typically renders text as italic, but like `<strong>`, it focuses on semantic meaning.

10. `<q>` (Quote) and `<blockquote>` (Block Quote):

   - `<q>` is used for inline quotations, enclosing a short, inline quote within double quotation marks.

   - `<blockquote>` is used for longer block quotes, often with indentation for readability.

11. `<abbr>` (Abbreviation) and `<cite>` (Citation):

   - `<abbr>` is used to mark up abbreviations or acronyms, providing the full expansion as an attribute.

   - `<cite>` is used to reference the title of a creative work (e.g., a book or movie) or a citation source.

12. `<dfn>` (Definition):

   - The `<dfn>` tag is used to define the term or phrase it encloses.

   - It is helpful for marking up glossary or dictionary entries.

13. `<del>` (Delete) and `<ins>` (Insert):

   - `<del>` is used to indicate deleted or removed text. It typically renders text with a strike-through.

   - `<ins>` is used to indicate inserted or added text. It often renders text as underlined.